

### Compilers & Assemblers

- When you hit "compile" or "run" (e.g. in your Java IDE), many actions take place "behind the scenes"
- You are usually only aware of the work that the parser does



3

**Development Process** 

- 1. Write program in high-level language
- 2. Compile program into assembly
- 3. Assemble program into objects
- 4. Link multiple objects programs into one executable
- 5. Load executable into memory
- 6. Execute it

4


6

# From Abstract to Machine

### Compiler

- Convert programs from high-level languages (such as C or C++) into assembly language
- Some create machine-code directly...
- *Interpreters*, however...
  - · never compile code
  - · Instead, they run parts of their own program

5




Assembler

- Converts assembly into the binary representation used by the processor
- Often the result is an object file
  - · usually not executable yet
  - contains computer instructions and information on how to "link" into other executable units
  - file may include: relocation data, unresolved labels, debugging data

Parameter Park Code CD-28

8



Linkers

- Often, parts of a program are created <u>separately</u>
- Happens more often than you think – almost always
- Different parts of a program are called *objects*
- A *linker* joins them into a single file

9 Sacramento State - Cook - CSc

10

### What a Linker Does

- Connects labels (identifiers) used in one object - to the object that defines it
- So, one object can call another object
- A linker will show an error if there are label conflicts or missing labels

Sacramento State - Cook - CSc 35

Linking your program


- UNIX header is defined by crt1.o and crti.o
- They are supplied behind the scenes, so you don't need to worry about them


UNIX Header


Main


cramento State - Gook - CSc 35

11 12












15 1





17 18



Assembly Language

- Assembly allows you to write machine language programs using easy-to-read text
- Assembly programs is based on a <u>specific</u> processor architecture





24 5

20

### **Assembly Benefits**

19

- 1. Consistent way of writing instructions
- 2. Automatically counts bytes and allocates buffers
- 3. Labels are used to keep track of <u>addresses</u> which prevents common machine-language mistakes

Fall 2024 Sacramento State - Cook - CSc 25

1. Consistent Instructions

- Assembly combines related machine instructions into a single notation (and name) called a mnemonic
- For example, the following machine-language actions are different, but related:
  - register → memory
  - register → register
  - constant → register

2N Sacramento State - Cook -

21 22

### 2. Count and Allocate Buffers

- Assembly automatically counts bytes and allocates buffers
- Miscounts (when done by hand) can be very problematic – and can lead to hard to find errors




Sacramento State - Cook - CSc 35

3. Labels & Addresses

- Assembly uses *labels* to store addresses
- Used to keep track of locations in your programs
  - data
  - subroutines (functions)
  - · ...and much more

Sacramento State - Cook - CSc 35



23 24

### Battle of the Syntax

- The basic concept of assembly's notation and syntax hasn't changed
- However, there are two major competing notations
- They are just different enough to make it confusing for students and programmers (who are used to the other notation)

25

Battle of the Syntax AT&T Syntax • dominate on UNIX / Linux systems · registers prefixed by %, values with \$ · receiving register is last Intel Syntax · actually created by Microsoft · dominate on DOS / Windows systems · neither registers or values have a prefix

· receiving register is first

26

# AT&T Example # Just a simple add mov value, %rdx #rdx = value add %rbx, %rax #rax += rbx


Intel Example # Just a simple add #rdx = value add rax, rbx #rax += rbx


27 28




**Assembly Programs** Assembly programs are divided into two sections data section allocate the bytes to store your constants, variables, etc... text section contains the instructions that will make up your program

29 30













33 34







35 36









39 40

Basics UNIX

UNIX was developed at AT&T's Bell Labs in 1969

Design goals:
operating system for mainframes
stable and powerful
but not exactly easy to use — GUI hadn't been invented yet

There are versions of UNIX with a nice graphical user interface
 A good example is all the various versions of Linux
 However, all you need is a command line interface

41 42

### Command Line Interface

- Command line interface is text-only
- But, you can perform all the same functions you can with a graphical user interface
- This is how computer scientists have traditionally used computers

>gcc hello.c a.out hello.c >a.out Hello world!

Command Line Interface • Each command starts with a name followed by zero or more arguments Using these, you have the same abilities that you do in Windows/Mac name argument1 argument2 ...

44 43

## 1s Command Short for List Lists all the files in the current directory It has arguments that control how the list will look Notation: · directory names have a slash suffix · programs have an asterisk suffix

1s Command a.out\* csc35/ html/ mail/ test.asm

45 46

```
11 Command

    Short for List Long

  This command is a shortcut
  notation for 1s -1
• Besides the filename, its size,
  access rights, etc... are
  displayed
```

11 Command 1 cookd othcsc 4650 Sep 10 17:44 a.out\* 2 cookd othcsc 4096 Sep 5 17:49 csc35/ drwxrwxrwx 10 cookd othcsc 4096 Sep 6 11:04 html/ 4096 Jun 20 17:58 mail/ 74 Sep 10 17:44 test.asm


47 48



nano Application
 Nano will open and edit the filename provided
 If the file doesn't exist, it will create it

nano filename
TA SER
Description:

49 50



The -o specifies the next name listed is the output file
 So, the second is the output file (object)
 The third is your input (assembly)

51 52

```
    Be very careful – anything after –o will be destroyed
    There is no "undo" in UNIX!
    Check the two extensions for "o" then "asm"


as –o lab.o lab.asm
```

as Command

> 1s
| lab.asm

> as -o lab.o lab.asm

> 1s
| lab.asm | lab.o



1d Command ■ The -o specifies the next name is the output The second is the output file (executable) The third is your input objects (1 or more) ld -o a.out csc35.o lab.o

56


```
1d Command


    Be very careful – if you list your input file (an

  object) first, it will be destroyed
• I will provide the "csc35.o" file
 ld -o a.out csc35.o lab.o
```


1d Command lab.o csc35.o > 1d -o a.out lab.o csc35.o lab.o csc35.o a.out\*


57 58





60










63





65 66

```
rm Command

> 1s
a.out* html/ mail/ test.asm
> rm a.out
> 1s
html/ mail/ test.asm
```