

Modern Responsive Slider Source Code

Complete HTML5, CSS3, and JavaScript Implementation for GitHub Upload

Executable Source Code (index.html)

index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Modern Responsive Slider</title>
  <style>
    * {
      box-sizing: border-box;
      margin: 0;
      padding: 0;
    }

    body {
      font-family: Arial, sans-serif;
      background-color: #0f172a;
      display: flex;
      justify-content: center;
      align-items: center;
      min-height: 100vh;
    }

    /* Slider Wrapper */
    .slider-container {
      position: relative;
      width: 90%;
      max-width: 800px;
      height: 400px;
      overflow: hidden;
      border-radius: 12px;
      box-shadow: 0 10px 25px rgba(0, 0, 0, 0.5);
    }

    .slides {
      display: flex;
      width: 100%;
      height: 100%;
      transition: transform 0.5s ease-in-out;
    }

    .slide {
      min-width: 100%;
      height: 100%;
      position: relative;
    }
```

```
.slide img {
  width: 100%;
  height: 100%;
  object-fit: cover;
}

.caption {
  position: absolute;
  bottom: 20px;
  left: 20px;
  color: #fff;
  background: rgba(0, 0, 0, 0.6);
  padding: 10px 18px;
  border-radius: 6px;
  font-size: 1.1rem;
}

/* Navigation Buttons */
.btn {
  position: absolute;
  top: 50%;
  transform: translateY(-50%);
  background: rgba(255, 255, 255, 0.7);
  border: none;
  color: #333;
  font-size: 24px;
  padding: 12px 16px;
  cursor: pointer;
  border-radius: 50%;
  transition: background 0.3s;
}

.btn:hover {
  background: rgba(255, 255, 255, 1);
}

.prev { left: 15px; }
.next { right: 15px; }

/* Indicator Dots */
.dots-container {
  position: absolute;
  bottom: 15px;
  width: 100%;
  display: flex;
  justify-content: center;
  gap: 8px;
}

.dot {
  width: 12px;
  height: 12px;
  background: rgba(255, 255, 255, 0.5);
  border-radius: 50%;
  cursor: pointer;
  transition: background 0.3s;
}
```

```

    .dot.active {
      background: #3b82f6;
    }
  </style>
</head>
<body>

<div class="slider-container">
  <div class="slides" id="slides">
    <div class="slide">
      
      <div class="caption">Slide 1: Front-End Design</div>
    </div>
    <div class="slide">
      
      <div class="caption">Slide 2: Python Integration</div>
    </div>
    <div class="slide">
      
      <div class="caption">Slide 3: Java Development</div>
    </div>
  </div>

  <!-- Navigation Buttons -->
  <button class="btn prev" onclick="moveSlide(-1)">&#10094;</button>
  <button class="btn next" onclick="moveSlide(1)">&#10095;</button>

  <!-- Indicators -->
  <div class="dots-container">
    <span class="dot active" onclick="currentSlide(0)"></span>
    <span class="dot" onclick="currentSlide(1)"></span>
    <span class="dot" onclick="currentSlide(2)"></span>
  </div>
</div>

<script>
  let currentIndex = 0;
  const slides = document.getElementById('slides');
  const dots = document.querySelectorAll('.dot');
  const totalSlides = dots.length;

  function updateSlider() {
    slides.style.transform = `translateX(-${currentIndex * 100}%)`;
    dots.forEach((dot, index) => {
      dot.classList.toggle('active', index === currentIndex);
    });
  }

  function moveSlide(direction) {
    currentIndex = (currentIndex + direction + totalSlides) % totalSlides;
    updateSlider();
  }

  function currentSlide(index) {
    currentIndex = index;
    updateSlider();
  }

```

```
// Auto Slide Every 4 Seconds
setInterval(() => {
  moveSlide(1);
}, 4000);
</script>

</body>
</html>
```