

Project Development Phase

Model Performance Test

Date	10 February 2025
Team ID	SWTID-2026-2051
Project Name	Script-Controlled ACL – Restrict Record Access Based on Field Value
Maximum Marks	

Model Performance Testing:

Project team shall fill the following information in model performance testing template.

S.No.	Parameter	Values	Screenshot
1.	Model Summary	Script-controlled Access Control Lists (ACLs) on the custom ServiceNow table Institution Details (u_institution_details). Access is restricted by user role and by the value of the Branch field. Users and roles: Test user EEE User with custom roles bb1 (read), bb2 (create), bb3 (write), bb4 (delete). Table fields: Student Roll Number (auto number), Student Name (reference: User), Faculty Name (reference: User), Branch (choice: ECE, EEE, CSE), Email, Phone Number, Description. READ ACL: Requires bb1; data condition Branch is EEE plus an advanced script. Only EEE records are visible to bb1 users; admins keep full access. CREATE ACL: Requires bb2; enables the New button. WRITE ACL: Requires bb3; allows editing records. DELETE ACL: Requires bb4; allows deleting records.	<i>READ ACL page showing the Data Condition (Branch is EEE) and the script; table columns screenshot.</i>
2.	Accuracy (test accuracy)	Training Accuracy (configuration/setup): 100% – all 4 roles, the table and 4 ACLs created correctly. Validation Accuracy (role-based access verification): 100% – all scenarios matched	<i>Three verification screens: EEE-only list, empty list, admin full list.</i>

S.No.	Parameter	Values	Screenshot
		expected behavior. Validation scenarios: • A user with bb1 sees only EEE records (2 of 6). • A user without the role sees no records ("No records to display"). • An admin sees all 6 records, regardless of branch. • bb1 and bb2 users see EEE records plus the New button. • bb1, bb2 and bb3 users can edit records (Description updated to "ACL Is Executed"). • bb1 through bb4 users can view, create, edit and delete EEE records.	
3.	Fine Tuning Result (if done)	The READ ACL script was refined from a basic role check to a layered check: • Admin users get full access (gs.hasRole('admin')). • bb1 users get access, with the Branch is EEE data condition limiting them to EEE records. • Everyone else is denied (return false). Validation Accuracy: 100% – EEE-only access for bb1, no access for users without the role, and full access for admins.	<i>Final ACL script and the delete confirmation screen.</i>