

User Acceptance Testing (UAT) Template

Date	
Team ID	SWTID-2026-2051
Project Name	Script-Controlled ACL - Restrict Record Access Based on Field Value
Maximum Marks	

Project Overview:

Project Name: Script-Controlled ACL - Restrict Record Access Based on Field Value

Project Description: A ServiceNow lab that restricts access to records of a custom table (Institution Details) using roles and script-controlled Access Control Lists. Only users with the required role can read, create, edit or delete records, and READ access is limited to records where Branch is EEE. Admins keep full access.

Project Version: 1.0

Testing Period: [Start Date] to [End Date]

Testing Scope:

- Features: user and role creation, custom table creation, and READ, CREATE, WRITE and DELETE ACLs on u_institution_details.
- Requirements: bb1 users see only EEE records; users without the role see nothing; admins see all records; bb2 enables New; bb3 enables editing; bb4 enables deleting.

Testing Environment:

URL/Location: [Your ServiceNow instance URL]

Credentials (if required): Admin account (security_admin elevated) and EEE User, accessed through impersonation. [Add passwords only if required]

Test Cases:

Test Case ID	Test Scenario	Test Steps	Expected Result	Actual Result	Pass/Fail
TC-001	Create test user and custom roles	1. Open User Administration > Users, create EEE User. 2. Open Roles, create bb1, bb2, bb3, bb4. 3. Assign all roles to EEE User.	User and 4 roles are created and assigned	User and roles created and assigned	Pass
TC-002	Create Institution Details table and sample records	1. Open System Definition > Tables, create u_institution_details. 2. Add the 7 fields. 3. Create records for ECE, EEE and CSE.	Table is saved; 6 records exist with mixed Branch values	Table and 6 records created	Pass
TC-003	READ ACL: user with bb1 role	1. Create READ ACL (advanced, role bb1, Branch is EEE). 2. Impersonate EEE User. 3. Open u_institution_details.list.	Only EEE records are shown	2 of 6 records shown, both EEE	Pass
TC-004	READ ACL (negative): user without the role	1. Impersonate a user without bb1. 2. Open the list.	No records are shown	"No records to display"	Pass
TC-005	READ ACL: admin access	1. Impersonate Admin. 2. Open the list.	All records are shown regardless of Branch	All 6 records shown	Pass
TC-006	CREATE ACL: user with bb1 and bb2	1. Create CREATE ACL (role bb2). 2. Impersonate EEE User. 3. Open the list.	New button is visible	New button shown	Pass

Test Case ID	Test Scenario	Test Steps	Expected Result	Actual Result	Pass/Fail
TC-007	CREATE ACL (negative): user without bb2	1. Impersonate a user with bb1 only. 2. Open the list.	New button is not visible	Not recorded in the lab	Pending
TC-008	WRITE ACL: user with bb1, bb2 and bb3	1. Create WRITE ACL (role bb3). 2. Double-click Description on an EEE record. 3. Enter text and save.	Field is editable and the value saves	Description saved as "ACL Is Executed"	Pass
TC-009	WRITE ACL (negative): user without bb3	1. Impersonate a user without bb3. 2. Try to edit Description.	Field is read-only	Not recorded in the lab	Pending
TC-010	DELETE ACL: user with bb1 to bb4	1. Create DELETE ACL (role bb4). 2. Select an EEE record. 3. Actions > Delete, confirm.	Delete option is available and the record is removed after confirmation	Delete option and confirmation dialog shown	Pass
TC-011	DELETE ACL (negative): user without bb4	1. Impersonate a user without bb4. 2. Select a record and open Actions.	Delete option is not available	Not recorded in the lab	Pending

Bug Tracking:

Bug ID	Bug Description	Steps to reproduce	Severity	Status	Additional feedback
BG-001	Branch field type in the table columns screenshot is String, but the instructions say Choice (ECE, EEE, CSE).	1. Open table columns for u_institution_details. 2. Check the Branch type.	Low	Open	Change the type to Choice so only valid branches can be entered.
BG-002	READ ACL script in the instructions includes an admin check, but the script in the screenshot only checks bb1.	1. Open the READ ACL. 2. Compare the Script field with the instructions.	Low	Open	Admin still sees all records because Admin overrides is selected. Align the script and instructions.

Sign-off:

Tester Name:	
Date:	
Signature:	

Notes:

- Ensure that all test cases cover both positive and negative scenarios.
- Encourage testers to provide detailed feedback, including any suggestions for improvement.
- Bug tracking should include details such as severity, status, and steps to reproduce.
- Obtain sign-off from both the project manager and product owner before proceeding with deployment.