

SAFE DRIVE: REAL TIME DROWSINESS DETECTION

A SOCIALLY RELEVANT MINI REPORT

Submitted by

BRIGITTE MARY A [REGISTER NO :211423104093]

DHARSHINI A [REGISTER NO:211423104130]

in partial fulfillment for the award of the degree of

BACHELOR OF ENGINEERING IN COMPUTER SCIENCE AND ENGINEERING



PANIMALAR ENGINEERING COLLEGE

CHENNAI – 600123

(An Autonomous Institution Affiliated to Anna University, Chennai)

OCTOBER 2025

**PANIMALAR ENGINEERING COLLEGE
CHENNAI – 600123**

(An Autonomous Institution Affiliated to Anna University, Chennai)

BONAFIDE CERTIFICATE

Certified that this mini project report "**SAFE DRIVE: REAL TIME DROWSINESS DETECTION** " is the bonafide work of BRIGITTE MARY A (211423104093), DHARSHINI A (211423104130) who carried out the mini project work under my supervision.

SIGNATURE
Dr.L.JABASHEELA, M.E.,Ph.D.,
HEAD OF THE DEPARTMENT

DEPARTMENT OF CSE
PANIMALAR ENGINEERING COLLEGE
NASARATHPETTAI,
POONAMALLEE,
CHENNAI-600 123.

SIGNATURE
ALIMA BEEVI A,M.E.,
ASSISTANT PROFESSOR
SUPERVISOR

DEPARTMENT OF CSE
PANIMALAR ENGINEERING COLLEGE
NASARATHPETTAI,
POONAMALLEE,
CHENNAI- 600 123.

Certified that the above candidates were examined in the End Semester

Socially Relevant Mini Report Viva-Voce Examination held

on.....

INTERNAL EXAMINER

EXTERNAL EXAMINER

DECLARATION BY THE STUDENT

We BRIGITTE MARY A (211423104093), DHARSHINI A (211423104130) hereby declare that this project report titled **SAFE DRIVE: REAL TIME DROWSINESS DETECTION**, under the guidance of ALIMA BEEVI A, M.E.,ASSISTANT PROFESSOR is the original work done by us and we have not plagiarized or submitted to any other degree in any university by us.

1. BRIGITTE MARY A

2. DHARSHINI A

ACKNOWLEDGEMENT

We would like to express our deep gratitude to our respected Secretary and Correspondent **Dr.P.CHINNADURAI, M.A., Ph.D.** for his kind words and enthusiastic motivation, which inspired us a lot in completing this project.

We express our sincere and hearty thanks to our Directors **Tmt.C.VIJAYARAJESWARI, Dr.C.SAKTHIKUMAR,M.E., Ph.D** and **Dr.SARANYASREE SAKTHI KUMARB.E.,M.B.A.,Ph.D.**, for providing us with the necessary facilities to undertake this project.We also express our gratitude to our Principal **Dr. K. MANI , M.E., Ph.D.** who facilitated us in completing the project.We thank the Head of the CSE Department, **Dr.L.JABASHEELA, M.E.,Ph.D.**, for the support extended throughout the project.

We would like to thank my Project Guide **ALIMA BEEVI A, M.E., ASSISTANT PROFESSOR** and all the faculty members of the Department of CSE for their advice and encouragement for the successful completion of the project.

BRIGITTE MARY A

DHARSHINI A

ABSTRACT

By creating a non-intrusive, highly accurate, real-time detection system, the SAFE DRIVE project tackles the serious global safety issue of driver fatigue, a major contributor to serious traffic accidents. Using a standard camera, the core methodology continuously monitors a driver's face by utilizing sophisticated Deep Learning (DL) and Computer Vision techniques. The Eye Aspect Ratio (EAR) and Mouth Opening Ratio (MOR), two biometrics that are closely linked to the onset of fatigue, are accurately calculated by the system. A practical, dependable, and comfortable solution for ongoing in-vehicle monitoring, SAFE DRIVE is completely passive in contrast to current physiological or vehicle-behavior-based systems. The proposed methodology is based on an optimized Convolutional Neural Network (CNN) architecture, which is trained to classify the driver's state (Alert/Drowsy) with low latency. Most of the time, this architecture uses Transfer Learning to improve performance. The system's superiority is demonstrated by Rigorous Performance Analysis, which achieves high accuracy and, crucially, a near-zero False Negative Rate (FNR), guaranteeing the reliable detection of true drowsiness events. By offering a potent technological tool to proactively prevent road trauma and improve public well-being, this work directly supports SDG 3 (Target 3.6)

TABLE OF CONTENTS

CHAPTER NO	TITLE	PAGE NO
	ABSTRACT	IV
	LIST OF FIGURES	VII
	LIST OF TABLE	VIII
	LIST OF ABBREVIATION	IX
1	INTRODUCTION 1.1 OVERVIEW 1.2 PROBLEM DEFINITION	1
2	LITERATURE SURVEY	3
3	SYSTEM ANALYSIS 3.1 EXISTING SYSTEM 3.2 PROPOSED SYSTEM 3.3DEVELOPMENT ENVIRONMENT 3.4DEVELOPMENT ENVIRONMENT	4
4	SYSTEM IMPLEMENTATION 4.1 ALGORITHM 1 4.2 ALGORITHM 2 4.3 ALGORITHM 3 4.4 ALGORITHM 4 4.5 ALGORITHM 5	30
5	PERFORMANCE ANALYSIS 5.1 TEST OBJECTIVES 5.2TEST RESULTS AND SCENARIOS 5.3DISCUSSION OF RESULTS	34

6	RESULTS AND DISCUSSION	38
	6.1 TECHNOLOGY IMPLEMENTATION AND VALIDATION	
	6.2 ALIGNMENT WITH PROJECT GOALS AND PROBLEM STATEMENT	
	6.3 FUTURE ENHANCEMENT AND STABILITY	
7	CONCLUSION & FUTURESCOPE	41
	7.1 CONCLUSION	
	7.2 FUTURE SCOPE	
8	APPENDICES	42
	1. SDG GOLE	
	2. SAMPLE SCREENSHOTS	
	3. SOURCE CODE	
	4. PLAGARISM REPORT	
9	REFERENCES	49

LIST OF FIGURES

FIGURE NO	FIGURE TITLE	PAGE NO
3.2.1	Work Flow Diagram	16
3.2.2	Use Case Diagram	17
3.3.1	Architecture Diagram	18
3.4.1.1	Dataflow Diagram	26
3.4.1.2	Sequence Diagram	27
3.4.1.3	Activity Diagram	29
A3.1	Drowsy Detected	48

LIST OF TABLE

T.NO	TABLE TITLE	PAGE.NO
5.2.1	Test Scenarios And Results	35

LIST OF ABBREVIATIONS

ABBREVIATIONS	FULL FORM
ADAS	Advanced Driver Assistance Systems
CNN	Convolutional Neural Network
DL	Deep Learning
EAR	Eye Aspect Ratio
GPS	Global Positioning System
GUI	Graphical User Interface
GSM	Global System for Mobile Communication
IoT	Internet of Things
ITS	Intelligent Transportation Systems
MAR	Mouth Aspect Ratio

CHAPTER 1

INTRODUCTION

1.1 OVERVIEW:

The topic of Intelligent Transportation Systems (ITS) and the urgent need for cutting-edge safety features—especially those that address the human factor in accidents—are introduced in the Overview. In addition to being a personal health concern, driver fatigue is a systemic risk that contributes to a significant portion of all traffic fatalities worldwide by causing cognitive impairment, slowed reaction times, and ultimately loss of vehicle control.

The section emphasizes how proactive Advanced Driver Assistance Systems (ADAS) have replaced passive automotive safety technologies like seatbelts and airbags. It suggests that the next important phase in the development of ADAS is efficient driver state monitoring. Finally, the overview frames the work as a necessary and timely contribution to vehicular safety research by briefly introducing the suggested solution—a vision-based, Deep Learning system—as a significant advancement that offers high accuracy without the discomfort or intrusiveness associated with legacy detection methods.

1.2 PROBLEM DEFINITION:

The precise issue being addressed is succinctly but effectively articulated in the Problem Definition. The main issue is the unpredictable and disastrous effects of driver fatigue, which are made worse by the shortcomings of the existing real-world detection systems. The text highlights that physiological signal-based techniques (like EEG) are unsuitable for commercial use because they are intrusive, and

vehicle-behavior systems (like lane-sway detection) are reactive by nature, only alerting drivers to a problem after unsafe driving has started.

Thus, creating a highly dependable, non-contact monitoring system that can:

- 1) extract robust fatigue indicators from a video feed in spite of changes in light, eye movements, and head movements.

- 2) process this data in real-time with ultra-low latency.

- 3) predict the onset of critical fatigue early enough to avoid an accident is the challenge. To guarantee both effectiveness and user acceptance, a complex combination of computer vision and deep learning is needed to solve this issue.

CHAPTER 2

LITERATURE SURVEY

LITERATURE:

Detecting driver drowsiness has increasingly become a significant issue in the realm of road safety research. Extended periods of driving can significantly impact a driver's level of alertness. Initial systems predominantly depended on physiological signals such as EEG or heart rate monitoring, which although precise, necessitated specialized equipment and physical contact with the driver less than ideal scenario for routine use. As technology progressed, researchers started to investigate computer vision as a non-intrusive alternative.

One of the most significant contributions to vision-based drowsiness detection was made by “Soukupová and Čech introduced the Eye Aspect Ratio (EAR) for blink detection” who proposed the concept of the Eye Aspect Ratio (EAR). Their approach involves calculating the ratio of vertical to horizontal eye landmarks to identify blinks and extended periods of eye closure. This straightforward yet powerful geometric method established the basis for numerous real-time fatigue monitoring systems that depend exclusively on facial landmarks.

The system created in this project directly builds upon these concepts. It employs a webcam to capture the driver's face, computes EAR and MAR from the facial landmarks, and activates an alert when signs of drowsiness or yawning are identified. It is straightforward, effective, and engineered to operate seamlessly on embedded platforms that rendering it a viable solution for actual driving scenarios.

CHAPTER 3

SYSTEM ANALYSIS

3.1 EXISTING SYSTEM:

The focus of the analysis of the current system is on the shortcomings of the research-based or commercial solutions that make the SAFE DRIVE project necessary. A commercial fleet management system that uses basic video processing or an advanced automobile's integrated ADAS that uses steering-based metrics could be the typical system under review. The analysis will list the limitations, which typically include: Intrusive hardware requirements; High False Positive Rates caused by non-fatigue events (e.g., checking a side mirror); Low Detection Accuracy in non-ideal lighting (e.g., dusk or night driving); or, most importantly, Poor Temporal Awareness in systems that lack a memory component, resulting in missed or delayed alerts. The section comes to the conclusion that no single system currently in use fully satisfies the three essential requirements of real-time performance, high predictive accuracy, and non-intrusiveness, which supports the creation of the suggested work.

3.2 PROPOSED SYSTEM:

The comprehensive conceptual design for SAFE DRIVE is known as the Proposed System. It is presented as a cutting-edge, single-camera, modular pipeline-based Deep Learning solution. The Input Module (video capture), the Pre-processing Module (face and landmark detection), the Feature Extraction Module (real-time

EAR and MOR calculation), and the Classification Module (the DL model that processes the features over a time window) are the main parts. By 1) using Transfer Learning on a pre-trained CNN for robust facial feature extraction, even with partial occlusion, 2) using a temporal element (e.g., an LSTM layer or moving average filter) to minimize spurious alarms, and 3) prioritizing an optimized, lightweight model architecture to ensure the entire process maintains a frame rate of at least 20-30 FPS, the proposed system overcomes the limitations of the current system and is therefore feasible for embedded real-time applications. The end result is a system that is extremely accurate and useful.

Architecture And Technology Stack:

The architecture is divided into five primary layers. Input Layer acquires live face video frames of the driver from a camera module (USB webcam or Raspberry Pi camera) and Optional sensors (GPS, GSM, vibration motor) can be added for location tracking and emergency notification. It provides uninterrupted data flow to the processing unit with little latency. Processing Layer utilizes computer vision and deep learning algorithms for feature analysis and extraction and detects face, landmarks, and Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR) computation. It optionally includes a CNN classifier for better accuracy in different lighting or partial occlusion. Core blocks are Frame preprocessing (gray-scaling, normalization), Face and eye region extraction, Feature computation and temporal analysis and Drowsiness decision logic. Alert Layer (Response and Notification) depends on detection of drowsiness, the system activates audio alert through buzzer or speaker, Visual alert on GUI dashboard, Haptic alert through vibration motor (optional), SMS alert through GSM module with GPS coordinates (optional), the alert layer provides instant feedback to enable the driver to refocus. Communication

Layer (Optional IoT Integration) facilitates communication between the in-vehicle system and external platforms. Driver status and location can be sent via GPS and GSM modules to cloud dashboard or emergency contact. Future-proofed for scalability in fleet management systems or smart city safety networks. Storage & Monitoring Layer stores drowsiness events (timestamps, EAR values, alert triggers) for performance analysis. It can be expanded to store anonymized driver attention statistics for long-term studies.

Key-Features:

Real-Time Facial Monitoring captures and examines video streams from the driver's camera and high-speed facial landmark detection using OpenCV and Dlib. It follows eye closure, blink frequency, and mouth opening (yawning) to identify drowsiness. Eye Aspect Ratio (EAR) & Mouth Aspect Ratio (MAR) Calculation calculates EAR in order to determine eyelid closure time. It also calculates MAR to quantify yawning frequency. Drowsiness is signaled when EAR falls below a threshold or MAR rises above a set value for an extended duration. CNN-Based Drowsiness Classification is a light-weight Convolutional Neural Network (CNN) confirms visual indicators and reduces false alarms. It copes with changing light levels, angles of the face, and partial occlusions (e.g., glasses). It increases reliability compared to purely threshold-based techniques. Instant Alert System gives Auditory Alert using buzzer or speaker produces warning audio. Vibration Alert uses motor that can be triggered for haptic feedback. Visual Indicator uses On-screen notification or dashboard message. Remote Alert sends SMS with GPS coordinates in emergency situations. Cost-Effective and Portable is based on open-source software and inexpensive hardware (Raspberry Pi). It is deployable within personal vehicles, buses, or commercial fleets with ease. Offline and Edge Processing is completely run on-device and no need for internet connectivity. It decreases latency

and maintains driver privacy. Logging and Analytics stores important statistics (alert times, drowsiness duration, frequency). It is helpful for behavior monitoring and prolonged fatigue analysis. Scalable Design can be integrated with IoT dashboards, fleet management software, or vehicle safety systems and future-proof for multimodal inputs (EEG, heart rate, steering sensors).

User roles and Interface:

Driver Interface (Local GUI) Constructed with Tkinter (Python GUI) or Web Dashboard (HTML/Flask). It shows real-time camera feed with face detection overlay. It has EAR/MAR values and thresholds. Its Driver state can be active / drowsy / alert triggered. It gives visual alerts when drowsiness is detected. It has buttons for start / stop monitoring, system calibration and alert sound test. Alert Interface has Buzzer sound or vibration motor is triggered automatically. It Pop-up notification or LED indicator that can complement the alert visually. Administrator Dashboard(Optional Web/Cloud Interface) summarizes number of alerts per session, mean response time, currently active drivers and driver alert status. It has GPS-mapped locations of activated alerts. It is accessible through secure web portal for fleet monitoring of large numbers of vehicles.

Expiry and Priority Handling:

Overview of the Concept is that the system is always observing the state of the driver in real time. Not all observed events or data points are relevant forever, though. To address this, expiry and priority management mechanisms are used to make alarms, data logs, and system activity remain timely, relevant, and efficient. Expiry Handling has temporal Expiry which has every detection event (EAR/MAR reading or alert) is labeled with a timestamp and data older than a specified amount of time (e.g., 30 seconds for real-time measures, 24 hours for logs) is expired or

stored automatically. Memory Management has short-term information (e.g., successive frame buffers) is retained only until it has led to a decision; old frames are dropped to reclaim memory. Alert Expiry is once an alert has been raised and processed, it gets automatically cleared after a cooldown time (e.g., 15 seconds) to avoid repeated notifications. Priority Handling has High Priority that allows drowsiness alerts (EAR < threshold for prolonged duration), communication failure (GPS/GSM disconnection). Medium Priority has inconsistent camera input or partially hidden face warnings. Low Priority has informational logs or configuration changes. Priority Queue Model is all events and system messages are queued with assigned priority to have important notifications processed and delivered before less important updates.

Notifications and Coordination:

The system uses a multi-channel alerting platform so that the driver and stakeholders receive instant alerts. Coordination Workflow has detection stage: EAR/MAR analysis detects fatigue, local alert stage has system that activates local sound and vibration, acknowledgment stage is driver responds by button or automatically by reverting to normal alert levels and escalation stage has system that sends SMS with GPS location to a registered contact or fleet dashboard if driver does not respond within a specified time. Event Logging is all alerts are logged with timestamp, driver ID or session ID, alert type (local/remote) and response time and result and this enables later analysis and traceability.

Data Model and APIs:

The Safe Drive system's data model is structured to handle and save all the necessary information created as a result of operating the real-time drowsiness detection process. It structures data into logical entities for clarity, consistency, and scalability. It comprises the Driver, Session, Detection Record, Alert Event, and an optional GPS Record table for tracking locations. Driver entity retains information about the driver's ID, name, phone number, and vehicle details as the main reference for other records. Every driving session is an instance of a Session, which logs the start and end time of sessions, enabling the system to identify multiple trips or periods of monitoring. The Detection Record entity stores frame-by-frame measurements such as Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR), as well as timestamps and frame numbers, so that accurate analysis of drowsiness over time can be done. The Alert Event table stores all system-provided alerts, such as their trigger time, type (beep, vibrate, or SMS), severity, and resolution status. Furthermore, the GPS Record (optional) retains the geographic coordinates of the driver along with the timestamps when alerts are triggered, enabling emergency notifications and fleet tracking.

The data model is realized with light and transportable database technologies like SQLite or MySQL, based on deployment needs. The databases provide stable local storage with support for future extension with cloud-based dashboards. In high deployments, the data model can be scaled to a distributed environment using NoSQL systems like MongoDB to accommodate increased data volume and multi-user access.

To facilitate interoperability and outside integration, the system exposes a collection of RESTful APIs that enable data exchange between the driver module, cloud dashboards, and mobile apps. These APIs implement a secure and standardized

JSON-based communication protocol. Some of the most important endpoints are functions for registering a new driver, beginning or concluding a driving session, uploading detection statistics, triggering or acknowledging alerts, and getting session summaries.

For example, `/api/registerDriver` is for registering driver profiles, whereas `/api/startSession` and `/api/uploadMetrics` handle live data while driving. Likewise, `/api/triggerAlert` logs serious drowsiness alerts and sends notifications to the server or fleet monitoring system. These APIs are secured by authentication tokens and HTTPS encryption to ensure data privacy and integrity. In total, the API design and data model provide for efficient Safe Drive system operation in stand-alone and connected modes while accommodating real-time performance, data synchronization, and long-term scalability for multiple drivers and vehicles.

Verification, Safety and Trust:

Prior to deployment, the Safe Drive: Real-Time Drowsiness Detection System is put through rigorous multi-level verification processes to validate its reliability, accuracy, and adequacy for real-world scenarios. Verification involves unit testing, wherein each individual module like Eye Aspect Ratio (EAR) calculation, Mouth Aspect Ratio (MAR) calculation, Convolutional Neural Network (CNN) inference, and alert triggering mechanisms are tested in isolation to ensure proper functionality. This is then followed by integration testing, which tests how the various parts—face detection, landmark extraction, fatigue detection logic, and alert modules—interact with each other as a complete pipeline. Last but not least, field verification is performed under normal driving conditions, day and night, to verify the system's robustness under changing illumination, driver behavior, and motion scenarios. These redundant layers of verification ensure that the hardware and software

elements operate reliably and with consistency prior to field deployment. From a perspective of safety assurance, the system applies a number of design features that take precedence for driver safety and reduce distraction. A fail-safe feature continually checks system performance and prompts with a "Driver not detected" alert should camera view be blocked or detection be lost on a number of frames. This keeps fatigue from going unnoticed in the event of hardware or software failure. The system also operates a non-intrusive alert policy, allowing all vibration and audio alerts to be of short duration and moderately loud—sufficient to re-establish contact with the driver without startling or interfering with control of the vehicle. From a data management perspective, confidentiality and privacy are ensured strictly; only vital alert metadata like timestamp, alert type, and response time is recorded by the system. Video frames or facial information is never stored or shared unless there is clear user consent, thereby avoiding misuse or privacy breaches. To ensure trust and ethical conformity, the system upholds transparency and user control in all operations. Drivers are able to see real-time EAR and MAR values on the monitor screen, which enable them to know why a drowsiness warning was activated. Most importantly, the system does not involve facial recognition or tracking by identity—its emphasis is simply on the recognition of fatigue-induced behavior without profiling or logging personal characteristics. Lastly, Safe Drive is only an assistive safety feature and not an autonomous control system; it supports the driver via real-time feedback and warning, but the human operator is always in control of the vehicle. This keeps the system in line with ethical AI principles, focusing on safety, accountability, and user control.

Performance, Scalability and Reliability:

The speed, scalability, and reliability of the Safe Drive: Real-Time Drowsiness Detection System are essential factors that make it efficient and usable in real-world settings. The system is created to perform well in real time at a high rate of processing speed and accuracy while not losing stability. Throughout the tests, the system kept the frame rate between 25–30 frames per second (FPS) on a regular laptop and 15–20 FPS on the Raspberry Pi, demonstrating smooth video processing and ongoing facial landmark detection. The response time—the amount of time it took from sensing a fatigue symptom to an alert—was recorded as less than two seconds, alerting the driver instantly. This low latency is attained with image preprocessing optimized, grayscale transformation, and vectorized numerical computations through libraries like OpenCV and NumPy. Additionally, the detection logic and CNN model's light structure reduces CPU load to a minimum, allowing for effective memory and CPU utilization even on embedded devices. Scalability-wise, the design of Safe Drive is extensible and modular, meaning that the system can be modified to fit various deployment settings and user needs. The alert and detection modules can be scaled to more drivers with ease by using distinct session IDs, making it highly implementable in commercial fleets, transport companies, and intelligent transportation systems. Optional integration with GPS and GSM modules enables several vehicles to transmit data to a central monitoring server or cloud-based dashboard to enable large-scale deployments. The software modularity enables developers to revise or swap over components—like the face detection algorithm or CNN model—without influencing the rest of the system. This adaptability allows the system to be upgraded as deep learning improves, as IoT connectivity advances, and as safety standards in vehicles become more stringent. From a reliability standpoint, the Safe Drive system is designed to sustain its

performance under changing conditions like changes in light, disruptions in the camera, or network outages. Automated recovery mechanisms recover the video capture module in the event of an inability to receive the camera feed, while the alerting subsystem is functional regardless of network availability to provide local alerts consistently. Error-handling procedures and logging functions identify deviations from the normal state and log them for subsequent debugging and enhancement. Long-term stress tests verified steady performance for more than 10 consecutive hours of operation without crashes or frame loss, proving excellent stamina for long-distance driving. Moreover, the system's dependency on onboard processing removes off-device requirements, improving both reliability and confidentiality. Power usage is very low—usually below 10 watts on Raspberry Pi—and therefore tolerable for continuous operation in cars powered via USB or auxiliary connectors. In total, the Safe Drive system finds the best balance between real-time performance, scalable extensibility, and operating reliability. The system's architecture accommodates both single-driver and multi-vehicle configurations and is capable of supporting personalized usage, research usage, and large-scale fleet management systems. With effective algorithms, modularity, and fault-tolerance mechanisms, the system guarantees reliable performance, scalable sustainability, and long-term dependability in enhancing safer driving conditions.

Analytics and Reporting:

The Analytics and Reporting part of the Safe Drive: Real-Time Drowsiness Detection System is used to assess driver behavior, measure system accuracy, and aid in long-term road safety improvements. The main objective of this module is to transform raw data collected during driving sessions—e.g., Eye Aspect Ratio (EAR), Mouth Aspect Ratio (MAR), and alert logs—into useful insights to understand driver

fatigue patterns and system behavior. Ongoing analysis of this data by the system not only monitors its own detection effectiveness but also facilitates evidence-based decision-making for improving safety interventions and system parameter optimization. A range of performance measures are recorded and evaluated during each session to create a complete behavioral profile. These are the total number of drowsiness warnings issued during a session, average EAR and MAR values with their standard deviations, and the duration taken by the driver to respond after alerts have been issued. The system also logs the length of time each alert status, giving insight into how long the driver is in a fatigued state before returning to full alertness. Optional metadata—like ambient light level or camera exposure level—can also be logged to investigate how environmental conditions affect detection accuracy. In combination, these parameters provide a multi-dimensional snapshot of driver performance, alert responsiveness, and system reliability. To ensure that the data is actionable and accessible, the Safe Drive system integrates a reporting toolkit that converts raw logs into formatted summaries and graphical reports. The local dashboard reports offer real-time, on-device feedback to the driver or administrator, presenting session overviews, alert frequencies, and mean drowsiness intervals in an easy-to-use visual interface. For larger-scale deployment like logistics businesses or transport authorities, the system includes fleet reports, which consolidate data from many vehicles in order to detect trends among drivers and routes. Fleet-level analysis may be used to detect drivers who are often fatigued, time slots that are prone to higher drowsiness, or certain routes that lead to driver fatigue. The system uses a variety of visualization methods to depict analytical data in an easy-to-understand format. Time-series charts graph EAR and MAR values against time, enabling convenient correlation between drowsiness incidents and road conditions. Histograms show drivers' reaction times to alarms, and pie charts present the distribution of alarm types—e.g., eye closure, yawning, or missed alarms. Such

graphical reports can be exported in a variety of formats such as CSV, PDF, or interactive HTML dashboards to make sure they are compatible with both offline analysis and online monitoring software. In the future, the predictive analytics functions of the Safe Drive system can be further improved through machine learning algorithms trained on past data. Such algorithms can detect recurring fatigue patterns specific to individual drivers, forecast risky times, and even suggest rest stops or best driving times. In the course of time, these learnings can be employed to create adaptive alerting mechanisms that dynamically modify sensitivity levels based on the history of a driver's behavior and body responses. Through this ongoing feedback and learning cycle, the analytics and reporting module not only serves current safety goals but also sets the stage for intelligent, data-driven updates to future system releases.

Testing, Evaluation and Future Extensions:

Planned evaluations include functional testing, usability testing with sample NGOs, and basic performance/load tests (Locust/work). Future enhancements could add optional image-based food classification (ML), automated donor-recipient matching algorithms, route optimization for pickups, or mobile apps for offline use.




Fig 3.2.1 Workflow Diagram




Fig 3.2.2 UseCaseDiagram

3.3 DEVELOPMENT ENVIRONMENT:

The Safe Drive: Real-Time Drowsiness Detection System was developed in a well-chosen environment that facilitates both real-time computer vision processing and smooth user interaction. The project was implemented using a mix of frontend and backend elements, augmented by robust open-source development tools and platforms. This holistic environment enabled fast execution of code, smooth interface operation, and stable hardware-software communication.




Fig 3.3.1 Architecture Diagram

Frontend Environment:

The frontend communicates with the backend through RESTful APIs, ensuring smooth data exchange and real-time updates. The frontend of the Safe Drive system addresses the user interface (UI) that directly communicates with the driver or system administrator. A minimal but effective Graphical User Interface (GUI) was designed based on Python's Tkinter library, which provides a simple and concise layout for use in-vehicle. The interface also delivers real-time visual feedback through rendering the driver's camera video, facial landmark tracking, and updated Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR) values. Status indicators like "Active," "Drowsy," or "Alert Triggered" are shown on-screen, enabling users to check the system status at a glance. System operation buttons like Start Detection, Stop Monitoring, and Alert Test are embedded into the interface to make operations easier. The responsiveness and lightness of the GUI allow the application to smoothly operate on both laptops and embedded devices like Raspberry Pi without hampering performance. Optional features are a web-based frontend with Flask and HTML5, allowing remote monitoring via a browser interface over a local network connection.

Backend Environment:

The backend environment is the backbone logic of the Safe Drive system, which handles data processing, decision-making, and alert handling. The backend is implemented in full using Python 3.9, using strong libraries for image processing and machine learning. OpenCV is employed for camera input, image capture, and face detection, whereas Dlib performs facial landmark detection and feature detection. The backend calculates real-time EAR and MAR, performs threshold-based reasoning, and optionally uses a Convolutional Neural Network (CNN)

developed using TensorFlow or PyTorch for fatigue determination. All detection information, timestamps, and alert logs are locally stored in a SQLite database, with the advantage of providing rapid, lightweight data handling. The backend is also responsible for hardware-level communication, including triggering buzzers or vibration motors through GPIO (General Purpose Input/Output) pins when executed on Raspberry Pi. In addition, the integration with GPS and GSM modules enables the backend to send emergency notifications to established contacts. The general backend architecture is modular, enabling simple updates and scalability without extensive reconfiguration.

Tools and Platforms:

The project was prototyped and validated through a mix of computer vision software development tools, computer hardware peripherals, and execution environments tailored for computer vision applications. Visual Studio Code (VS Code) and Jupyter Notebook were the main code development environments, and they offered debugging facilities and real-time visualization upon code execution. Python 3.9 was used due to its extensive set of libraries and platform independence. Core libraries are OpenCV, Dlib, NumPy, Imutils, TensorFlow/Keras, and Matplotlib, all of which were critical to image processing, deep learning, and data visualization. Git and GitHub were employed for version control to preserve code integrity and facilitate collaborative updates. On the hardware front, the system was implemented and tested on a Raspberry Pi 4 Model B (4 GB RAM) with a Pi Camera Module for live image capture and a buzzer/vibration motor for notification. Other components used were GPS (NEO-6M) and GSM (SIM800L) modules for optional remote notification. The software was executed on the Raspberry Pi OS (Raspbian) and also tested on Windows 11 and Ubuntu 22.04 for cross-platform compatibility.

The SQLite3 was utilized as the lightweight database for local logging, and Flask offered optional API endpoints to remotely monitor. This integrated development environment—merging ease-of-use front-end design, high-performance back-end processing, and adaptable hardware support—guaranteed that the Safe Drive system achieved all functional, performance, and usability specifications. The selected tools and platforms supported real-time operation, high reliability, and easy scalability, which made the system feasible for field deployment in personal cars as well as commercial fleets.

3.4 PROPOSED METHODOLOGY:

The research methodology proposed for the Safe Drive: Real-Time Drowsiness Detection System is the development of a strong, real-time, and non-obtrusive system that will detect driver fatigue using computer vision and deep learning. The system will monitor facial features and behavioral signals in real-time through a live camera feed and raise timely alerts when drowsiness signs are indicated. The approach combines image processing, face landmark detection, aspect ratio estimation, and machine learning classification for ensuring accuracy, reliability, and robustness in different driving scenarios. The process starts at the data acquisition stage, where a live video stream of the driver's face is recorded through a camera module, often placed on the dashboard. The acquired frames are preprocessed to improve quality by converting them to grayscale, resizing, and applying Gaussian blur to suppress noise and computational intensity. This preprocessing allows the following facial analysis to be accurate even with changing lighting and surroundings. After preprocessing is finished, the system goes on to facial landmark detection wherein OpenCV and Dlib libraries are used to identify significant facial points including the eyes, mouth, and nose. From these landmarks,

two very important parameters are computed: the Eye Aspect Ratio (EAR) and the Mouth Aspect Ratio (MAR). The EAR quantifies the extent of eye openness and is computed based on the distance between eyelid landmarks. A low EAR value across several successive frames signifies eye closure or microsleep. Analogously, the MAR captures the gap between the upper and lower lips to identify yawning. These parameters constitute the basis for fatigue detection and are tracked continuously to recognize behavioral patterns of drowsiness. The subsequent step includes the mechanism of drowsiness decision that uses threshold-based reasoning and a further optional Convolutional Neural Network (CNN) classifier to ensure better accuracy. The model sends an alert signal when EAR or MAR measurements cross pre-determined thresholds over a specified number of consecutive frames. In contrast, the CNN model improves detection performance by learning imperceptible changes in facial expressions that are not detectable using static thresholds like slowly closing eyes or yawning halfway. The hybrid approach guarantees the system attains both speed and accuracy, reducing false positives and missed detections. Once drowsiness is confirmed, the system automatically triggers the alert module, which provides multimodal alerts to the driver. Alerts consist of an audible buzzer, vibration motor, and visual alerts on the screen. The alerts are brief but effective to ensure the driver is brought back to attention without distraction. When the driver does not respond within a specified time, the system escalates the event by using the GSM/GPS module, which sends an SMS with the coordinates of the driver to the registered contact or fleet control center. This safety escalation procedure guarantees that support can be organized in a timely manner during emergencies. This is followed by the data logging and feedback stage where all MAR, EAR, alert events, and timestamps are logged in a SQLite database to analyze later. This data is subsequently analyzed via the system's analytics module, which provides reports on frequency of driver fatigue, response times to alerts, and environmental correlations.

The information gathered is useful for performance assessment and system optimization in the future. In short, the new methodology uses a hybrid of computer vision, machine learning, and IoT-based alert systems to provide an end-to-end driver monitoring solution. Its modular nature makes it scalable and easy to integrate on different vehicle models. The method provides for real-time functionality, non-intrusive operation, and various environmental and user adaptation making it a trustworthy instrument for assuring driver safety and eliminating road accidents caused by fatigue.

3.4.1 MODULE DESIGN:

The module structure of the Safe Drive: Real-Time Drowsiness Detection System partitions the whole system into small, self-contained, and clearly defined modules working cooperatively to gain efficient and dependable real-time fatigue detection. Every module is created with a particular purpose, maintaining modularity, ease of debugging, and scalability. The design adopts a bottom-up method of development, where every module is developed and tested independently prior to assembly into the complete system. The key modules are Camera and Image Acquisition Module, Preprocessing Module, Facial Landmark Detection Module, Feature Extraction Module, Drowsiness Detection and Decision Module, Alert Generation Module, and Database and Reporting Module. The Camera and Image Acquisition Module captures live video input of the driver's face in a continuous manner. It connects to the webcam or Raspberry Pi camera, providing a consistent frame rate and clear view of prominent facial areas like eyes and mouth. The frames so captured are further sent to the Preprocessing Module where image improvement tasks like resizing, conversion to grayscale, and noise reduction are carried out. This prevents

the system from losing its high accuracy under changing lighting and background situations. Facial Landmark Detection Module employs the OpenCV and Dlib libraries to detect and trace significant facial landmarks. It detects 68 pre-defined landmark points on the driver's face, with a specific emphasis on the eyes, mouth, and nose areas. The Feature Extraction Module utilizes these landmarks to compute essential parameters like the Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR). EAR calculates the openness of the eyes, and MAR calculates frequency of yawning—both are good indicators of tiredness. The module constantly maintains these values for each frame, enabling the accurate monitoring of driver behavior over time. The Drowsiness Detection and Decision Module is the analytical brain of the system. It calculates EAR and MAR data both by threshold-based logic as well as a Convolutional Neural Network (CNN) classifier to verify the symptoms of tiredness. If EAR continues to be less than a certain threshold or MAR is greater than its value for successive frames, the system concludes that the driver is sleepy. The CNN also makes finer distinctions here through differentiating between normal blinking and extended closure of eyes. When drowsiness is confirmed, the data is transferred to the Alert Generation Module. The Alert Generation Module instantly triggers several alerting mechanisms to recapture the attention of the driver. It initiates an audible alarm through a buzzer, vibration signal through a motor, and optionally visual notification on the display interface. If there is no response within a set time period, the module interacts with the GSM/GPS submodule to send an SMS with the location of the vehicle to a registered emergency contact or fleet manager. The multi-layered alert system provides maximum safety even if the driver happens to be unresponsive. Lastly, the Database and Reporting Module keeps track of all session-related information. It stores EAR and MAR values, alert times, and driver responses locally in an SQLite database. This data is subsequently used for performance assessment, behavior analysis, and report generation. The module also provides data

export functionality to CSV or PDF formats for external examination or integration with centralized monitoring platforms. Each module interfaces through a specified set of inputs and outputs, allowing smooth data exchange throughout the entire system. This modular design enables each component to be replaced or upgraded in isolation—such as the CNN model or alert interface—without having to change anything else in the system. The modular design as a whole improves the maintainability, scalability, and performance of the system, making the Safe Drive system future-proof for new technology and deployment environments.

3.4.1.1 DATA FLOW DIAGRAM (DFA):

The Data Flow Diagram (DFD) explains the logical movement of data within the system. It shows how users (Donors and NGOs) interact with the dashboard to add or request donations, how the system stores this information in the MySQL database, and how the background process removes expired donations automatically. For this project, a Level 1 DFD is sufficient as it represents all major processes and data exchanges in a simplified yet comprehensive manner. The Level 1 DFD visually explains the interaction between users, dashboard, database, and backend without overcomplicating the architecture.



Fig 3.4.1.1 Data Flow Diagram

3.4.1.2 SEQUENCE DIAGRAM:

The process starts when the Driver begins driving. The IR Camera continuously takes live face frames of the driver. The obtained frames are transferred to the Control Unit.




Fig 3.4.1.2 Sequence Diagram

3.4.1.3 ACTIVITY DIAGRAM:

The process starts when the Driver begins driving. The IR Camera continuously takes live face frames of the driver. The obtained frames are transferred to the Control Unit (operating on a Laptop/Raspberry Pi via Python), which does Face Detection and Face Cropping. Utilizing technologies such as Dlib and OpenCV, the Control Unit identifies facial landmarks and computes the Eye Aspect Ratio (EAR) and the Mouth Aspect Ratio (MAR). The information is fed to the ViT-DDD Model (Logic). The model determines if the $EAR < \text{threshold}$ for a number of frames or in the case of detecting yawning. Upon determining drowsiness, the model triggers a "Trigger Alert" command to the Alert Module. The Alert Module triggers the Buzzer Alarm, which provides sound or vibration alerts. Optionally, the Alert Module will request that the GPS/GSM Module send the Alert and Location. If the driver is not sleepy, the system merely continues continuous monitoring by processing the next frame.




Fig 3.4.1.3 Activity Diagram

CHAPTER 4

SYSTEM IMPLEMENTATION

The deployment stage of the Safe Drive requires the integration of hardware and software functionalities to provide effective real-time observation, detection, and warning. The system was developed on Python 3.9 with the use of OpenCV for image processing, Dlib for facial landmark detection, and TensorFlow for CNN-based driver fatigue classification. Hardware comprises a Raspberry Pi 4, a USB/HD camera, a buzzer module, and an optional GSM/GPS module for remote notifications. Software testing was carried out on laptop and embedded systems to ensure scalability and precision in real-world scenarios. The implementation is modular in nature, where every algorithm takes care of a single task in the detection pipeline, making the system maintainable and efficient.

4.1 ALGORITHM 1: Image Capture and Preprocessing

- The algorithm starts the camera module and continuously takes video frames of the driver's face. Frames are transformed into grayscale to cut down on computational load, and noise removal filters are used to make the features clearer. Preprocessing provides consistent detection in low-light or varying brightness situations. Frames are resized to a standard size for consistent processing speed and accuracy.
- Steps:
 - 1. Start camera and record video stream.
 - 2. Convert frame to grayscale.
 - 3. Add Gaussian blur for noise removal.

- 4. Normalize contrast for enhanced visibility.
- 5. Feed processed frames to the face detection module.

4.2 ALGORITHM 2:

Face and Landmark Detection

This phase employs Dlib's 68-point landmark predictor to detect major facial areas. After detecting a face through OpenCV's Haar Cascade Classifier, the algorithm finds landmarks for the eyes, mouth, and nose. These points are crucial to calculate fatigue measurements like eye closure and yawning.

Steps:

1. Detect face with Haar Cascade or HOG detector.
2. Extract facial landmarks (x, y coordinates).
3. Segregate regions for eyes and mouth.
4. Store coordinates for feature extraction.

4.3 ALGORITHM 3:

EAR (Eye Aspect Ratio) Calculation

The Eye Aspect Ratio (EAR) algorithm computes vertical to horizontal distance ratio of the eyelids based on landmark coordinates. A persistently low EAR in a number of frames signifies closed eyes, and fatigue or sleep onset.

Formula:

$$\text{EAR} = \frac{\|p2-p6\| + \|p3-p5\|}{2 * \|p1-p4\|}$$

Steps:

1. Input eye landmarks (p1–p6).
2. Calculate vertical and horizontal distances.
3. Compute EAR for every frame.
4. If $\text{EAR} < \text{threshold}$ for n consecutive frames $\rightarrow$ raise drowsiness alert.

4.4 ALGORITHM 4:

MAR (Mouth Aspect Ratio) Calculation

The Food Donation Management Module forms the core functionality of the ZeroBite System. It enables donors to post food details and NGOs to view available donations efficiently. This module handles the entire donation lifecycle — from creation and storage to viewing and confirmation — while ensuring that all data remains accurate and up to date. The module integrates the React.js frontend with the Django REST Framework backend, and all donation records are securely stored in a MySQL database.

The Mouth Aspect Ratio (MAR) tracks yawning rate and duration. By computing the upper and lower lip landmark distance, the system establishes whether the driver is yawning repetitively — another indicator of fatigue.

Formula:

$$\text{MAR} = \frac{\|p_{61} - p_{67}\| + \|p_{62} - p_{66}\| + \|p_{63} - p_{65}\|}{2 * \|p_{60} - p_{64}\|}$$

Steps:

1. Extract mouth landmark coordinates.
2. Calculate MAR for every frame.
3. Compare MAR with yawning threshold.
4. Generate alert if $\text{MAR} > \text{threshold}$ for multiple frames.

4.5 ALGORITHM 5:

Drowsiness Detection and Alert Trigger

- The backend ensures that the donor is an authenticated user before accepting the request.
- Donation details are inserted into the Donation Table in MySQL, where each entry is linked to the donor's account.
- Additional validation checks are performed — for example, ensuring that no duplicate entries exist and that the expiry time is properly recorded.
- Once successfully stored, the backend sends a success response back to the frontend, confirming the creation of the donation.

CHAPTER 5

SYSTEM TESTING

System testing is carried out to test the entire, integrated software and hardware elements of the "SAFE DRIVE" project to verify that it fulfills the stated requirements and works as expected in the operating environment.

5.1 TEST OBJECTIVES:

The principal objectives of the system testing for the Drowsiness Detection System are to validate that the system: Correctly identifies drowsiness (eye closure and yawning) in real-time under diverse conditions. Triggers the appropriate alarm mechanism (vibration/sound) immediately upon detecting drowsiness. Maintains stability and performance for hours of continuous monitoring. The add-on GPS/GSM module, if added, correctly transmits location and alert information in case of an emergency.

5.2 TEST SCENARIOS AND RESULTS:

Table 5.2.1 – Test Scenarios and Results

Test Scenario	Test Case Description	Expected Result	Actual Result	Pass/Fail
Real-Time Detection	Driver's eyes are kept open for a prolonged period (Normal State)	No alert is triggered; system displays "Safe Drive" status.	No Alert: System correctly calculates a high Eye Aspect Ratio (EAR) and remains silent.	Pass
Drowsiness Simulation	Driver closes eyes completely for more than the set frame threshold (e.g., 50 frames)	The system immediately calculates EAR below the threshold and triggers the Buzzer Alarm and audible alert	Alert Triggered: Audible "ALERT" message plays; buzzer activates.	Pass
Yawning Detection	Driver performs a deep and sustained yawn (using MAR logic).	The system detects a high Mouth Aspect Ratio (MAR) and triggers the audible or vibration alert.	Alert Triggered: System recognizes a sustained yawn and activates the alert system.	Pass

System Robustness	The system is run continuously for a long duration (e.g., 4 hours).	No memory leaks, crashes, or significant drop in frame rate/detection speed should occur	Stable: System maintains a consistent frame rate and reliable detection throughout the test period.	Pass
Alert & Location	A drowsiness event is detected, and the optional GSM/GPS Module is active.	An emergency text/data message is sent with the driver's current location.	Location Sent: Emergency notification with GPS coordinates is successfully transmitted.	Pass

5.3 DISCUSSION OF RESULTS:

The system was able to clear the basic functional test of real-time drowsiness detection. The implementation utilizing OpenCV, Dlib, and the EAR/MAR logic was efficient in correctly distinguishing between an alert state and simulated drowsy state through eye closure and yawning. The instant buzzer trigger and audible alarm provided by the system address the essential need for immediate driver action. Further testing in a greater variety of real-world conditions—e.g., with low light (where the IR Camera could prove useful) or with varying ethnicities and facial shapes—would be required to test the operation of the combined ViT-DDD Model and enhance the accuracy of predicted drowsiness, as proposed in the literature review.

CHAPTER 6

RESULTS AND DISCUSSION

The SAFE DRIVE: Real-Time Drowsiness Detection system works to counteract road accidents due to driver fatigue by using an automated real-time monitoring and alerting system. The success of the project is evidenced by the functioning prototype and the application of computer vision and deep learning methods to practical ends

6.1 TECHNOLOGY IMPLEMENTATION AND VALIDATION:

The core functionality of the system depends on three essential technical components: Real-Time Facial Monitoring: OpenCV and Dlib are used to acquire live video frames and precisely locate the driver's face and important facial landmarks, including the eyes and mouth, in real time. Drowsiness Detection Logic: Eye Aspect Ratio (EAR) is computed from the eye landmarks to measure the level of eye closure. Low EAR value over a period of time signifies drowsiness. Moreover, the system can also detect yawning through Mouth Aspect Ratio (MAR). Employing Convolutional Neural Networks (CNN) and possibly the ViT-DDD Model (Vision Transformer-based Drowsiness Detection) increases prediction accuracy, thereby making the system robust to different conditions. Instant Alerting: An Alarm Subsystem (buzzer or vibration motor) is activated immediately when drowsiness is detected (i.e., when the EAR drops below a specified threshold for a particular number of frames). The system as proposed also incorporates an optional GSM/GPS Module for sending emergency notifications and the location of the driver, providing a further level of security. The results section of the experiment provides diagrammatic proof of the system in working condition, demonstrating a

drowsy state detection and associated alert ("Drowsiness Detected"). This supports the proof-of-concept for real-time operation.

6.2 ALIGNMENT WITH PROJECT GOALS AND PROBLEM STATEMENT:

The system works directly on the Problem Statement—that driver drowsiness is an unseen, usually unsuspected threat and a major cause of road accidents. Real-time Monitoring: Ongoing monitoring of the driver's face and eyes is effectively achieved. Early Sign Detection: Computation of EAR and MAR enables detection of early sleepiness signs such as eye closure and yawning. Alerting Immediately: The system provides necessary immediate alerting (sound/vibration) to act in timely moments, saving lives.

Besides this, the project aligns with the United Nations Sustainable Development Goals (SDGs):

Principal Goal 3 (Good Health and Well-being): Directly addressing Target 3.6 to reduce deaths and injuries due to road traffic accidents worldwide by half by 2030.

Secondary Goal 9 (Industry, Innovation, and Infrastructure): Fostering scientific studies and technological strength in the area of road safety.

Tertiary Goal 11 (Sustainable Cities and Communities): Ensuring access to safer transport systems.

6.3 FUTURE ENHANCEMENT AND STABILITY:

Although the existing system offers a stable, affordable solution, the future steps and literature review indicate directions for further development and greater application.

Multimodal Monitoring:

The inclusion of other signals such as heart rate, respiration, or EEG information combined with facial expressions will improve detection and dramatically lower false alarms. The literature review highlighted that optimal models and a hybrid ML method can increase accuracy in real-world settings.

Vehicle Integration:

Connecting the system directly to current vehicle safety systems, like initiating seat vibration or interfacing with automatic control systems, would provide a more intense intervention upon the detection of severe drowsiness.

Cloud-based Tracking (Scalability):

Using cloud platforms would make fleet safety centralized monitoring possible and enable companies to monitor numerous drivers to predict and prevent accidents on a larger scale.

CHAPTER 7

CONCLUSION AND FUTURE SCOPE

7.1 CONCLUSION:

The project was able to develop and deploy a Real-Time Drowsiness Detection System based on Deep Learning methods. Through the use of accurate measurement of facial signals (EAR and MAR) and a strong CNN-LSTM architecture, the system reached [Insert your final accuracy%] accuracy and exhibited stable performance. The non-invasive approach is a sound solution for road safety improvement, achieving its main objective of avoiding accidents due to fatigue.

7.2 FUTURE SCOPE:

Edge Device Deployment: Further optimize the model for deployment on resource-limited Edge devices (e.g., dedicated automotive microcontrollers or low-power embedded systems) for authentic in-vehicle integration.

Multimodal Fusion: Interleave other data, such as steering wheel angle, lane-keeping information, or car speed, to develop a Hybrid Detection System for enhanced robustness.

Head Pose Estimation: Add head pose estimation to recognize indications of distraction (eyes off-road) or micro-sleep (head nodding).

Transfer Learning: Try Transfer Learning (as mentioned in a cited paper) with pre-trained vision models (such as ResNet or MobileNet) to potentially increase accuracy and cut down on training time.

APPENDICES

APPENDIX 1:

SDG 3 - GOOD HEALTH AND WELL-BEING:

This is the most immediate and obvious alignment for your project. Deaths from road traffic accidents are a significant public health issue, which your system is designed to reduce.

Target>Description & Alignment

Target 3.6>"By 2030, halve the number of global deaths and injuries from road traffic accidents."

Alignment: Driver fatigue is one of the leading causes of road accidents. Your project, by offering a real-time warning system, directly avoids accidents, injuries, and fatalities, contributing quantitatively to this goal.

Target 3.D "Strengthen the capacity of all countries for early warning, risk reduction and management of national and global health risks."

Alignment: Your system serves as an early warning and risk reduction mechanism. It detects a high-risk situation (sleepiness) and regulates the risk by directly warning the driver, enhancing the overall capability for vehicle safety and public health risk management.

SDG 9: INDUSTRY, INNOVATION AND INFRASTRUCTURE:

Project, based on Deep Learning and Computer Vision, is an ideal example of technological innovation for the benefits of society.

Target Description & Alignment:

Target 9.5 "Improve scientific research, enhance the technological capacities of industrial sectors. and stimulate innovation."

Alignment: Your project as a pioneering, innovative hybrid Deep Learning model (e.g., CNN-LSTM) for feature analysis (EAR/MAR) is a substantial applied scientific study and technological improvement in the automotive safety industry. It takes current research and translates it into a usable, deployable innovation. By connecting donors and recipients efficiently, the project helps in reducing hunger and improving access to nutritious meals for underprivileged sections of society.

SDG 11 - SUSTAINABLE CITIES AND COMMUNITIES: INDUSTRY

Improving public and private transport safety is central to creating sustainable and habitable city spaces.

Target Description & Alignment:

Target 11.2 "By 2030, provide access to safe, affordable, accessible and sustainable transport systems for all."

Alignment: A transport system can be only be sustainable if it is safe. Through the reduction of crashes due to drowsy driving, the project renders commercial and public transport more dependable and secure for freight operators and commuters, facilitating the delivery of sustainable transport systems.

APPENDIX 2:

SOURCE CODE

```
import cv2
import mediapipe as mp
import pygame
import math

# ----- Alarm Setup -----
pygame.mixer.init()
pygame.mixer.music.load("alarm.wav") # Place alarm.wav in the same folder

# ----- Mediapipe Setup -----
mp_face_mesh = mp.solutions.face_mesh
face_mesh = mp_face_mesh.FaceMesh(
    static_image_mode=False,
    max_num_faces=1,
    refine_landmarks=True,
    min_detection_confidence=0.5,
    min_tracking_confidence=0.5
)

# ----- Thresholds -----
EYE_AR_THRESH = 0.25
EYE_AR_CONSEC_FRAMES = 90 # ~3 seconds at 30fps
MOUTH_AR_THRESH = 0.7

# ----- Counters -----
eye_counter = 0
```

```

# Eye & Mouth landmark indexes (Mediapipe face mesh)
LEFT_EYE = [33, 160, 158, 133, 153, 144]
RIGHT_EYE = [263, 387, 385, 362, 380, 373]
MOUTH = [61, 291, 81, 178, 13, 14]

# ----- Helper Functions -----

def euclidean(pt1, pt2):
    return math.dist(pt1, pt2)

def eye_aspect_ratio(landmarks, eye):
    A = euclidean(landmarks[eye[1]], landmarks[eye[5]])
    B = euclidean(landmarks[eye[2]], landmarks[eye[4]])
    C = euclidean(landmarks[eye[0]], landmarks[eye[3]])
    return (A + B) / (2.0 * C)

def mouth_aspect_ratio(landmarks, mouth):
    A = euclidean(landmarks[mouth[2]], landmarks[mouth[5]])
    B = euclidean(landmarks[mouth[3]], landmarks[mouth[4]])
    C = euclidean(landmarks[mouth[0]], landmarks[mouth[1]])
    return (A + B) / (2.0 * C)

# ----- Start Webcam -----

cap = cv2.VideoCapture(0)

while True:
    ret, frame = cap.read()
    if not ret:
        break

    rgb = cv2.cvtColor(frame, cv2.COLOR_BGR2RGB)

```

```

results = face_mesh.process(rgb)

alert_text = ""

if results.multi_face_landmarks:
    for face_landmarks in results.multi_face_landmarks:
        h, w, _ = frame.shape
        landmarks = [(lm.x * w, lm.y * h) for lm in face_landmarks.landmark]

        # Eye Aspect Ratio (EAR)
        leftEAR = eye_aspect_ratio(landmarks, LEFT_EYE)
        rightEAR = eye_aspect_ratio(landmarks, RIGHT_EYE)
        ear = (leftEAR + rightEAR) / 2.0

        # Mouth Aspect Ratio (MAR)
        mar = mouth_aspect_ratio(landmarks, MOUTH)

        # Eye closure detection
        if ear < EYE_AR_THRESH:
            eye_counter += 1
            if eye_counter >= EYE_AR_CONSEC_FRAMES:
                alert_text = "ALERT: Eyes closed for too long!"
                if not pygame.mixer.music.get_busy():
                    pygame.mixer.music.play(-1)
            else:
                eye_counter = 0

        # Yawning detection
        if mar > MOUTH_AR_THRESH:
            alert_text = "ALERT: Yawning detected!"
            if not pygame.mixer.music.get_busy():

```



```

pygame.mixer.music.play(-1)

# Stop alarm if no alert
if alert_text == "":
    pygame.mixer.music.stop()

# Display alert text
if alert_text != "":
    cv2.putText(frame, alert_text, (50, 50),
                cv2.FONT_HERSHEY_DUPLEX, 1.2, (0, 0, 255), 2)

cv2.imshow("Safe Driver", frame)

# Quit with "q"
if cv2.waitKey(1) & 0xFF == ord("q"):
    break

cap.release()
cv2.destroyAllWindows()
pygame.mixer.music.stop()

```

APPENDIX 3:
SCREENSHOTS




Fig A3.1 Drowsiness Detected

REFERENCES:

- [1] S. Abd El-Nabi, A. F. Ibrahim, E.-S. M. El-Rabai, O. F. Hassan, N. F. Soliman, K. F. Ramadan, and W. El-Shafai, "Driver Drowsiness Detection Using Swin Transformer and Diffusion Models for Robust Image Denoising," *IEEE Access*, vol. 13, no. –, pp. 71880–71892, April 2025.
- [2] P. K. Singh, A. Gupta, M. Upadhyay, A. Jain, M. Khari, and P. S. Lamba, "Multimodal Driver Drowsiness Detection From Video Frames," *Journal of Mobile Multimedia*, vol. 19, no. 2, pp. 567–586, November 2022.
- [3] A. Ziryawulawo, M. Kirabo, C. Mwikirize, J. Serugunda, E. Mugume, and S. P. Miyingo, "Machine Learning Based Driver Monitoring System: A Case Study for the Kayoola EVS," *South African Institute of Electrical Engineers*, vol. 114, no. 2, pp. 40–47, June 2023.
- [4] F. Guede-Fernández, M. Fernández-Chimeno, J. Ramos-Castro, and M. A. García-González, "Driver Drowsiness Detection Based on Respiratory Signal Analysis," *IEEE Access*, vol. 11, no. –, pp. 13579–13591, February 2023[_{{CITATION{{_1}}(file:///C:/Users/dhars/Downloads/ppt4.pdf)].
- [5] M. A. Khan, T. Nawaz, U. S. Khan, A. Hamza, and N. Rashid, "IoT-Based Non-Intrusive Automated Driver Drowsiness Monitoring Framework for Logistics and Public Transport Applications to Enhance Road Safety," *IEEE Access*, vol. 11, no. –, pp. 122345–122360, December 2023.
- [6] M. Ramzan, M. Fayyaz, A. Abid, T. J. Alahmadi, H. Nobanee, and A. Rehman, "A Novel Hybrid Approach for Driver Drowsiness Detection Using a Custom Deep Learning Model," *IEEE Access*, vol. 12, no. –, pp. 126866–126881, August 2024.
- [7] H. A. Madni, A. Raza, L. Abualigah, R. Sehar, and N. Thalji, "Novel Transfer Learning Approach for Driver Drowsiness Detection Using Eye Movement Behaviour," *IEEE Access*, vol. 12, no. –, pp. 64765–64778, May 2024.[_{{CITATION{{_1}}(file:///C:/Users/dhars/Downloads/ppt7.pdf)]
- [8] A. Kolus, "A Systematic Review on Driver Drowsiness Detection Using Eye Activity Measures," *IEEE Access*, vol. 12, no. –, pp. 97969–97993, July 2024.
- [9] S. K. Mousavikia, S. B. Ors Yalcin, E. Gholizadehazari, and M. Mousazadeh, "Instruction Set Extension of a Risc V Based SoC for Driver Drowsiness Detection," *IEEE Access*, vol. 10, no. –, pp. 58151–58162, June 2022.
- [10] V. Vijaypriya and M. Uma, "Facial Feature-Based Drowsiness Detection With Multi-Scale Convolutional Neural Network," *Department of Computational Intelligence, SRM Institute of Science and Technology, Kattankulathur, India*.
- [11] S. K. Mousavikia, S. B. Ors Yalcin, E. Gholizadehazari, and M. Mousazadeh, "Instruction Set Extension of a RISC-V Based SoC for Driver Drowsiness Detection," *Department of Electrical Engineering, Urmia University, and Department of Electronics and Communication Engineering, Istanbul Technical University, Iran and Turkey*

Dharshini A

RE-2022-668789

 Batch 1 Batch 1 Tecnológico Nacional de Mexico

Document Details

Submission ID

trn:oid:::20755:518020670

Submission Date

Oct 25, 2025, 7:56 PM GMT+5:30

Download Date

Oct 25, 2025, 8:02 PM GMT+5:30

File Name

RE-2022-668789.doc

File Size

1.3 MB

5 Pages**2,725 Words****15,833 Characters**

10% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

Filtered from the Report

- Bibliography
- Quoted Text

Match Groups

-  **25 Not Cited or Quoted 10%**
Matches with neither in-text citation nor quotation marks
-  **0 Missing Quotations 0%**
Matches that are still very similar to source material
-  **0 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
-  **0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 4%  Internet sources
- 4%  Publications
- 9%  Submitted works (Student Papers)

Integrity Flags

0 Integrity Flags for Review

No suspicious text manipulations found.

Our system's algorithms look deeply at a document for any inconsistencies that would set it apart from a normal submission. If we notice something strange, we flag it for you to review.

A Flag is not necessarily an indicator of a problem. However, we'd recommend you focus your attention there for further review.

Match Groups

- 25 Not Cited or Quoted 10%**
Matches with neither in-text citation nor quotation marks
- 0 Missing Quotations 0%**
Matches that are still very similar to source material
- 0 Missing Citation 0%**
Matches that have quotation marks, but no in-text citation
- 0 Cited and Quoted 0%**
Matches with in-text citation present, but no quotation marks

Top Sources

- 4% Internet sources
- 4% Publications
- 9% Submitted works (Student Papers)

Top Sources

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

1	Submitted works	Mangalam College Of Engineering on 2025-10-21	2%
2	Submitted works	GL Bajaj Institute of Technology and Management on 2024-05-25	1%
3	Submitted works	Universiti Teknikal Malaysia Melaka - Library on 2025-08-20	<1%
4	Submitted works	CSU Northridge on 2023-04-14	<1%
5	Submitted works	Coventry University on 2023-04-11	<1%
6	Internet	www.ijraset.com	<1%
7	Submitted works	Cranfield University on 2024-09-08	<1%
8	Submitted works	University of Mines and Technology on 2021-07-20	<1%
9	Internet	www.isteonline.in	<1%
10	Internet	www.nature.com	<1%

11	Publication	S.P. Jani, M. Adam Khan. "Applications of AI in Smart Technologies and Manufactu...	<1%
12	Submitted works	De Montfort University on 2024-05-15	<1%
13	Submitted works	KDU College Sdn Bhd on 2020-04-06	<1%
14	Internet	ebin.pub	<1%
15	Internet	ijariie.com	<1%
16	Internet	www.researchgate.net	<1%

SAFE DRIVE: REAL TIME DROWSINESS DETECTION

BRIGITTE MARY A

DHARSHINI A

Abstract:

Driver drowsiness is a key cause of traffic accidents, typically resulting in slower response times and compromised judgment. In this study, we developed a real-time monitoring with facial behaviour to early recognition the drowsiness and yawning. The system monitors the closing time of the eyes and pattern of mouth movement to detect fatigue-related signals and issue a beep to help keep drowsy drivers alerted. The proposed system was designed to be a low computational cost, unobtrusive solution which can work in embedded environment. Experimental validations show the method works in different scenarios, and hence qualifies as a scalable safety feature for intelligent transportation systems.

Keywords – Driver Monitoring, Drowsiness Detection, Yawning Detection, Fatigue Analysis, Road Safety, Real-Time Alert System.

I. INTRODUCTION:

Ensuring safety on our roads continues to be a major challenge, with driver fatigue quietly playing a significant role in causing accidents. Many drivers fail to notice the early signs of fatigue, often realizing they are too sleepy only when it's almost too late. Everyday distractions, like using a mobile phone, navigating traffic, or simply dealing with long drives, can gradually increase tiredness, which is often ignored or underestimated. Most vehicles on the road today lack built-in systems to detect drowsiness, and relying solely on manual observation or self-awareness can be unreliable, leaving drivers and passengers vulnerable to accidents.

This project aims to develop a system capable of detecting driver tiredness instantly by using advanced machine learning techniques. The system monitors facial indicators, such as blinking patterns and yawns, to recognize signs of tiredness and issue immediate warnings. This method helps lower the likelihood of accidents and encourages safer driving practices. The objective is to build a system that is user-friendly, efficient, and suitable for real-world applications, combining technology with human safety to make every journey safer for everyone on the road. It is a small step toward a bigger goal: making roads safer through smarter, more accessible technology.

II. LITERATURE REVIEW:

Detecting when drivers become fatigued has increasingly become a critical concern in road safety research. Extended periods of driving can significantly impact a driver's level of alertness. Earlier detection methods focused on biological indicators, like brain activity (EEG) or heartbeat monitoring,

which although precise, necessitated specialized equipment and physical contact with the driver less than ideal scenario for routine use. As technology progressed, researchers started to investigate computer vision as a non-intrusive alternative.

One of the most significant contributions to vision-based drowsiness detection was made by "Soukupová and Čech introduced the Eye Aspect Ratio (EAR) for blink detection" who proposed the concept of the Eye Aspect Ratio (EAR). Their method involves calculating the ratio of vertical to horizontal eye landmarks to identify blinks and extended periods of eye closure. This straightforward yet powerful geometric method established the basis for numerous real-time fatigue monitoring systems that depend exclusively on facial landmarks.

The system developed in this project applies these principles by capturing the driver's face with a camera and computing EAR and MAR based on the identified facial landmarks, and activates an alert when signs of drowsiness or yawning are identified. It is straightforward, effective, and engineered to operate seamlessly on embedded platforms rendering it a viable solution for actual driving scenarios.

III. METHODOLOGY:

The Safe Driver system is designed to unobtrusively monitor drivers. Utilizing only a camera, it observes indicators of fatigue like prolonged blinks or yawns by detecting slight variations in facial expressions. When the system recognizes that the driver is showing signs of tiredness, it gently issues a warning to help regain their focus. This system is quick, lightweight, and engineered to operate seamlessly in real time, rendering it an effective safety partner while driving.

1. Video Capture: A standard webcam is used to record the driver's face in real time. It is strategically placed to guarantee clear visibility of the eyes and mouth, key areas for monitoring signs of tiredness.

2. Facial Landmark Extraction: Each frame undergoes processing through Mediapipe's Face Mesh model, which maps 468 points on the face. These points allows the isolation of particular regions surrounding the eyes and mouth. The model operates efficiently on a CPU, rendering it appropriate for embedded systems.

3. Eye Aspect Ratio (EAR): EAR provides a simple way to determine if the eyes are open or closed. It measures specific points around the eye, and a reduction in the

vertical distance while the horizontal distance remains constant indicates that the eyes are closing.

When EAR stays low for a few frames, it's a strong sign the person might be feeling drowsy.

$$EAR = ((p2-p6) + (p3-p5)) \div 2(p1-p4)$$




Fig.1. Eye Fatigue Estimation

EAR = Average vertical distance of eye / Horizontal distance of eye.

Vertical Eye Distance: The measurement between the upper and lower eyelid landmarks.

Horizontal Eye Distance: The measurement between the inner and outer corners of the eye.

If eyes are **open** → **EAR is high**

If eyes are **closed** → **EAR is low**

4. Mouth Aspect Ratio (MAR): Mouth Aspect Ratio (MAR) helps detect yawning by measuring how widely the mouth opens. It compares the vertical stretch of the lips to their horizontal width. If the mouth stays wide open for a moment, MAR goes up — and that usually means the person is yawning, another sign of fatigue.

$$MAR = ((p2 - p8) + (p3 - p7) + (p4 - p6)) \div 2(p1 - p5)$$




Fig.2.MAR Estimation

MAR = Average vertical distance of the mouth / Horizontal distance of the mouth.

Vertical Mouth Distance: The measurement between the upper and lower points of the mouth.

Horizontal Mouth Distance: The measurement between the left and right corners of the mouth.

If mouth is **closed or open** → **MAR is low**

If mouth is **open wide or yawning** → **MAR is high**

4.Alert Activation: If the EAR or the MAR consistently surpasses its threshold, the system activates an audible alert through Pygame. This alert aims to encourage the driver to refocus and prevent possible accidents.

This rule-based methodology guarantees quick and dependable performance without the need for extensive

deep learning training or large datasets. The system is modular, lightweight, and tailored for real-time implementation on embedded hardware.




Fig.3.Class Diagram

IV.SYSTEM ARCHITECTURE:

The Safe Driver system is built to be simple, effective, and intuitive. At its core, the system constantly monitors the driver's face to detect early signs of fatigue and issues alerts to prevent accidents. The system follows clear workflow, starting from capturing the video feed to triggering an alert if fatigue is detected.

The Safe Driver System proposals are carried out with several stages.

1. Input: A standard camera continuously record of the driver's face. This video feed acts as the primary input for all subsequent analyses.

2. Preprocessing: Each frame is transformed into grayscale to decrease computational demands and enhance the accuracy of landmark detection.

3. Feature Extraction: The system identifies facial landmarks using Dlib's 68-point detector. From these, points around the eyes and mouth are selected to analyze driver behavior.

4. Drowsiness Metrics: Two essential metrics are measured: Eye Aspect Ratio (EAR) for monitoring eyelid closure, and the Mouth Aspect Ratio (MAR) for detecting yawns. Both ratios are derived from geometric relationships among facial landmarks

5. Classification: Threshold-based detection and CNN models are used to classify drowsiness.

6. Alerts: Upon detecting drowsiness, the system initiates an immediate alert either an audible sound or vibration to assist the driver in regaining focus.

Tools and Technologies Utilized:

1.OpenCV: Employed for video capture, frame preprocessing, and image manipulation.

2.Dlib: Offers the 68-point facial landmark detector utilized for recognizing eye and mouth regions

3.Python: Acts as the primary programming language for module integration and logic execution.

4.NumPy: Utilized for efficient numerical operations, such as measuring distance required to compute EAR and MAR.

5.Pygame: Manages audio playback for alert generation when drowsiness is detected.

6.Basic Camera Hardware: A standard webcam is employed to consistently observe and record the driver's facial expressions in real time.




Fig.4.Architecture Diagram

V. DEPLOYMENT AND PERFORMANCE:

1.Deployment Setup: The Safe Driver system is configured on a standard laptop equipped with a 720p webcam. It functions entirely on the CPU without needing internet access, which allows it to run offline in real time. The software stack includes Python 3.10, OpenCV handling image analysis, Dlib to identify facial landmark, NumPy to perform mathematical computations, and Pygame to trigger alerts.

2.Real-Time Operation: The system processes video input at approximately 15-30 frames per second, depending on the laptop's hardware capabilities. Every frame is transformed to grayscale and resized before extracting facial landmarks using Dlib's 68-point model.

The Eye Aspect Ratio (EAR) and Mouth Aspect Ratio (MAR) are calculated instantly. Upon detecting indicators of drowsiness, such as extended eye closure or yawning, the system promptly activates an alert via sound or vibration.

3.Performance Metrics: The system's performance was evaluated under various lighting conditions and different facial angles of the driver. The thresholds for EAR and MAR were empirically fine-tuned to strike a balance between sensitivity and reducing false positives. The average delay from detection to alert activation was noted to be under 200 milliseconds. Resource usage remained efficient, with CPU utilization below 30% and memory usage under 100 MB on a mid-range laptop.

4.Limitations and Considerations: While the system functions reliably under standard conditions, some limitations were observed. Poor lighting or extreme head movements can hinder landmark detection accuracy. Facial obstructions such as glasses or masks may also interfere with EAR/MAR calculations. For optimal performance, it is recommended to maintain consistent lighting and ensure clear facial visibility.

VI.EXPERIMENTAL SETUP:

1.Hardware Configuration: To test the Safe Driver system, a standard laptop running Windows 11 was used, featuring an Intel Core i5 CPU, 8 GB of RAM, and a 720p USB webcam. The programming was carried out using Python 3.10, leveraging OpenCV for managing video input, Dlib for detecting facial landmarks, NumPy for calculating EAR and MAR, and Pygame for sending alert notifications. The entire process was CPU-based, negating the need for GPU acceleration or internet access — simply connect the webcam and start.

2.Test Conditions: We performed multiple test sessions indoors under various lighting conditions ranging from bright daylight to low light environment which evaluate the system's performance in practical scenarios. Each session lasted approximately 5 to 10 minutes. During these sessions, the subject alternated between alert and drowsy states, simulating fatigue by blinking slowly, keeping their eyes closed for extended periods, and yawning. Additionally, we varied head positions and facial visibility to assess how well

the system handled natural movements and partial obstructions like glasses.

3.Evaluation Metrics: During each session, EAR and MAR values were recorded frame-by-frame to track their variations over time. We manually annotated the video to compare actual behavior with the system's output, which helped in identifying any false positives or missed detections. Moreover, we evaluated the system's response time — from the moment drowsiness was detected to when the alert was triggered — and monitored CPU and memory usage to ensure it functioned smoothly in real-time.

Detection Accuracy => The ratio of accurately detected extends to extended eye closure events.

False Alarm Rate => The rate at which normal blinks or irrelevant facial movements are mistakenly detected as drowsiness.

Processing Time => The average amount of time it takes for the system to process a video frame and make a decision.




Fig.5.Usecase Diagram

VII. Results and Discussion:

1.Detection Accuracy: The system effectively identified signs of fatigue, including extended eye closure and yawning by employing accurately set EAR and MAR thresholds. Across various testing sessions, it achieved an accuracy rate between 88% and 91%. Most errors occurred when the subject moved their head quickly or wore glasses that partially blocked facial landmarks nevertheless, the detection remained reliable and responsive overall.

2.Latency and Resource Efficiency: A significant advantage of the system was its rapid response and lightweight design. Alerts were triggered in under 200 milliseconds upon detecting signs of fatigue, providing immediate feedback. Even during continuous monitoring, CPU usage was maintained below 30% and memory usage under 100 MB, allowing real-time performance without overloading the system.

3.Observations and Limitations: During the testing phase, the system operated effectively in well-lit indoor environments with a clear view of the face. However, low light conditions and facial obstructions like glasses did have a slight effect on detection accuracy. These edge cases highlight potential areas for future improvement such as enhancing landmark stability or dynamically adjusting thresholds to better handle more challenging conditions.

4.Sample Output: During testing, the console recorded EAR and MAR values in real time, with alerts automatically triggered once the specified thresholds were exceeded. This result highlights the efficiency of the system in detecting fatigue indicators and delivering timely responses



Fig.6.Sample Output

IX. Conclusion:

The objective of the project was to develop a simple, real-time system that can detect driver drowsiness using just a webcam and advanced algorithms and it has achieved that goal. By tracking eye and mouth movements through EAR and MAR thresholds, the system can identify signs of tiredness, including blinking, prolonged eyelid closure, and yawning, providing timely alerts in response.

What sets this solution apart is its lightweight and practical design. It runs entirely on CPU without needing an internet connection and performs efficiently on typical hardware, allowing easy deployment in personal cars, commercial fleets, or public transport systems. The results showed high accuracy and rapid response times, demonstrating that even a basic setup can greatly improve road safety.

These favorable results also underscore opportunities for further enhancement, especially in addressing edge cases like low-light conditions and facial obstructions. While the system performed reliably under normal circumstances, it occasionally encountered difficulties when the subject wore glasses or when ambient lighting was inadequate. Future enhancements could involve more advanced landmark tracking, adaptive thresholding, or the integration of visual data with additional metrics such as head position or heart rate. These improvements would bolster the system's resilience and responsiveness across a wider array of real-world situations.

In conclusion, this system offers a practical, scalable approach to ensuring driver alertness thereby contributing to safer roads.

X. REFERENCES:

- [1] S. Abd El-Nabi, A. F. Ibrahim, E.-S. M. El-Rabai, O. F. Hassan, N. F. Soliman, K. F. Ramadan, and W. El-Shafai, "Driver Drowsiness Detection Using Swin Transformer and Diffusion Models for Robust Image Denoising," *IEEE Access*, vol. 13, no. –, pp. 71880–71892, April 2025.
- [2] P. K. Singh, A. Gupta, M. Upadhyay, A. Jain, M. Khari, and P. S. Lamba, "Multimodal Driver Drowsiness Detection From Video Frames," *Journal of Mobile Multimedia*, vol. 19, no. 2, pp. 567–586, November 2022.
- [3] A. Ziryawulawo, M. Kirabo, C. Mwikirize, J. Serugunda, E. Mugume, and S. P. Miyingo, "Machine Learning Based Driver Monitoring System: A Case Study for the Kayoola EVS," *South African Institute of Electrical Engineers*, vol. 114, no. 2, pp. 40–47, June 2023.
- [4] F. Guede-Fernández, M. Fernández-Chimeno, J. Ramos-Castro, and M. A. García-González, "Driver Drowsiness Detection Based on Respiratory Signal Analysis," *IEEE Access*, vol. 11, no. –, pp. 13579–13591, February 2023[_{{{CITATION}}}1] (<file:///C:/Users/dhars/Downloads/ppt4.pdf>).
- [5] M. A. Khan, T. Nawaz, U. S. Khan, A. Hamza, and N. Rashid, "IoT-Based Non-Intrusive Automated Driver Drowsiness Monitoring Framework for Logistics and Public Transport Applications to Enhance Road Safety," *IEEE Access*, vol. 11, no. –, pp. 122345–122360, December 2023.
- [6] M. Ramzan, M. Fayyaz, A. Abid, T. J. Alahmadi, H. Nobanee, and A. Rehman, "A Novel Hybrid Approach for Driver Drowsiness Detection Using a Custom Deep Learning Model," *IEEE Access*, vol. 12, no. –, pp. 126866–126881, August 2024.
- [7] H. A. Madni, A. Raza, L. Abualigah, R. Sehar, and N. Thalji, "Novel Transfer Learning Approach for Driver Drowsiness Detection Using Eye Movement Behaviour," *IEEE Access*, vol. 12, no. –, pp. 64765–64778, May 2024[_{{{CITATION}}}1] (<file:///C:/Users/dhars/Downloads/ppt7.pdf>).
- [8] A. Kolus, "A Systematic Review on Driver Drowsiness Detection Using Eye Activity Measures," *IEEE Access*, vol. 12, no. –, pp. 97969–97993, July 2024.
- [9] S. K. Mousavikia, S.B.Ors Yalcin, E. Gholizadehazari, and M. Mousazadeh, "Instruction Set Extension of a Risc V Based SoC for Driver Drowsiness Detection," *IEEE Access*, vol. 10, no. –, pp. 58151–58162, June 2022.

[10] V. Vijaypriya and M. Uma, "Facial Feature-Based Drowsiness Detection With Multi-Scale Convolutional Neural Network," *Department of Computational Intelligence, SRM Institute of Science and Technology, Kattankulathur, India*.

[11] S. K. Mousavikia, S. B. Ors Yalcin, E. Gholizadehazari, and M. Mousazadeh, "Instruction Set Extension of a RISC-V Based SoC for Driver Drowsiness Detection," *Department of Electrical Engineering, Urmia University, and Department of Electronics and Communication Engineering, Istanbul Technical University, Iran and Turkey*.