Project Documentation

Implement Client Script & UI Policy (Incident)

Team ID: SWTID-2026-5858

Team Leader : Dharshini.P

Email ID : dharshinipakkiri14@gmail.com

NM ID: 6AEB01A0A359A078D1146F78934319A4

Team Member : Dharshini.A

Email ID : dharshiniashok4006@gmail.com

NM ID: 82FC8BCDDADC303A2FD4B97EB5B2A704

Team Member : Joseya Arockiya Mary.U

Email ID : joseyaarockiyamary06@gmail.com

NM ID: 422BAC145F749C499C54D16FACC71C0A

Team Member : Santhiya.V

Email ID : iswaryaveeraragavan2005@gmail.com

NM ID: 98F16B0E2AE1CBA9A9C4C7F6F025421F

Implement Client Script & UI Policy (Incident)

Problem Statement

Incident records often require consistent and accurate data entry to ensure effective triage, routing, and resolution. However, relying solely on user awareness and manual checks can lead to incomplete, inconsistent, or incorrect data being submitted. This can impact reporting accuracy, SLA compliance, and overall service quality. To address this challenge, there is a need to enforce conditional field behavior and validation directly at the user interface level. Implementing standardized UI Policies and Client Scripts helps control field visibility, mandatory status, and save-time validation, ensuring that Incident records meet defined business rules before they are submitted.

Objective

The objective of the Implement Client Script & UI Policy (Incident) project is to demonstrate how ServiceNow client-side controls can be used to enforce data integrity on Incident records. This implementation showcases how UI Policies and Client Scripts can dynamically make fields mandatory, auto-populate values, control field behavior, and prevent record submission when required conditions are not met. The solution ensures that Incidents are created with complete and valid information, improving data quality and consistency across the platform.

Skills

Incident Management
UI Policy
UI Policy Actions
Client Scripts
Form Validation

Task 1: Create UI Policy on Incident

Activity 1: Create UI Policy

1. Log in to the **ServiceNow instance** with administrative or configuration access.

2. Navigate to:
   System UI → UI Policies

3. Click **New** to create a new UI Policy record.

4. Fill in the following details:

   - **Name**: High Impact Control
     This name clearly represents the purpose of the policy, which is to apply additional controls when an Incident has a high impact.

   - **Table**: Incident
     Specifies that the UI Policy applies to Incident records.

   - **Active**: true
     Enables the UI Policy so it is enforced on the Incident form.

5. Configure the **Conditions** section as follows:

   - **Field**: Impact

   - **Operator**: is


   - **Value**: 1 – High


6. This condition ensures the UI Policy is triggered only when the Incident impact is set to High.
7. And Ui policy action Assignment group
8. Check mandatory


9. Set **Reverse if false** to **true**.
   This ensures that when the condition is not met, any field changes applied by the policy are automatically reverted.

10. Review the configuration to ensure accuracy.

11. Click **Submit** to save the UI Policy.


servicenow
All
Favorites
History
Workspaces
Admin
UI Policies
Search
UI Policies
Order
New
Short description
Table
Conditions
Reverse if false
On load
Updated
Order
System Mobile
Mobile UI
Mobile UI Policies
Service Catalog
Catalog Administration
Catalog UI Policies
System Diagnostics
Session Debug
Debug UI Policies
Disable UI Policies Debug
System UI
UI Policies
MID Server
MID Security Policy
System Web Services
SOAP Security Policies


servicenow
All
Favorites
History
Workspaces
Admin
UI Policy - High Impact Control
Search
UI Policy
High Impact Control
View: Advanced
Update
Delete
Table
Incident [incident]
Application
Global
Active
Short description
High Impact Control
Order
100
When to Apply
Script
Conditions
Add Filter Condition
Add OR Clause
Impact
is
1 - High
AND
OR
Global
On load
Reverse if false
Inherit



Task 2: Create UI Policy Action – Urgency

Activity 1: Configure the Urgency Field

1. **Open the UI Policy Actions**
   Go to the **High Impact Control** UI Policy you created earlier. Scroll down to the **UI Policy Actions** related list. This is where you define the specific behavior of fields when the policy conditions are met.

2. **Create a New Action**
   Click **New** to create a UI Policy Action. This lets you configure how individual fields behave when the UI Policy is triggered.

3. **Fill in the Action Details**

   - **Field name:** Urgency
     Select the **Urgency** field on the Incident form. This is the field you want to control.


   - **Read-only:** true
     Check this option to make the Urgency field read-only whenever the UI Policy condition is met (Impact = High). Users will be able to see the field but cannot change its value.

- **Visible:** Leave this field as is (do not change).
  By leaving it unchanged, the field will remain visible on the form, but its behavior will be controlled by the Read-only setting.

4. **Submit the Action**
   Click **Submit** to save the UI Policy Action. The action is now linked to the High Impact Control UI Policy and will automatically apply to the Urgency field when an Incident has High Impact.

5. **Optional Verification**
   To test the action:

   - Open an Incident record.
   - Set the **Impact** field to **High**.
   - Check that the **Urgency** field becomes read-only.
   - Change Impact to a different value to confirm that the field reverts back if needed.



Task 3: Create onChange Client Script

Activity 1: Create Client Script

1. **Navigate to Client Scripts:**
   Go to System UI → Client Scripts.
2. **Click New** to create a new Client Script.
3. **Fill in the details:**
   - **Name:** Auto set urgency for high impact – clearly shows the purpose.
   - **Table:** Incident – the script runs only on Incident records.
   - **Type:** onChange – executes when a field value changes.
   - **Field name:** Impact – triggers the script when Impact is updated.
   - **Active:** true – ensures the script runs immediately.
4. **Paste the script** in the script editor section.
5. **Click Submit** to save the Client Script.
6. **Verify:** Open an Incident record and change the Impact field to **High**. The Urgency field should update automatically


Script:


```
function onChange(control, oldValue, newValue, isLoading) {
  if (isLoading || newValue == '') {
    return;
  }

  if (newValue == '1') {
    g_form.setValue('urgency', '1');
    g_form.addInfoMessage('Urgency set to High for High impact incident.');
  }
```

}

5. Click **Submit**.





Task 4: Create onSubmit Client Script (Save Validation)

Activity 1: Create Client Script

1. **Navigate to Client Scripts:**
   Go to System UI → Client Scripts in your ServiceNow instance.

2. **Click New** to create a new Client Script.

3. **Fill in the details:**

   - **Name:** Prevent save if Assigned To missing – clearly indicates that the script prevents saving if the field is empty.
   - **Table:** Incident – applies the script only to Incident records.
   - **Type:** onSubmit – executes when the user tries to save the record.
   - **Active:** true – ensures the script is enforced immediately.

4. **Paste the script** into the script editor section. This script should check if the **Assigned To** field is empty and prevent the record from saving if it is.

5. **Click Submit** to save the Client Script.

6. **Verify:** Try saving an Incident without filling the **Assigned To** field. The script should prevent the save and display a warning.


7. Paste the script:

```
function onSubmit() {
  if (g_form.getValue('impact') == '1' &&
    g_form.getValue('assigned_to') == '') {

    g_form.showErrorBox(
      'assigned_to',
      'Assigned To is mandatory for High impact incidents.'
    );
```

```
        return false;
    }
    return true;
}
```

8. Click **Submit**.



Task 5: Create onCellEdit Client Script

Activity 1: Create Client Script

1. **Navigate to Client Scripts:**
   Go to System UI → Client Scripts in your ServiceNow instance.

2. **Click New** to create a new Client Script.

3. **Fill in the details:**

- **Name:** Prevent state change via list edit – clearly indicates that the script prevents users from changing the State field directly in a list.
- **Table:** Incident – applies the script only to Incident records.
- **Type:** onCellEdit – runs whenever a field is edited directly in a list view.
- **Field name:** State – the script will monitor changes to the State field.
- **Active:** true – ensures the script is enforced immediately.

4. **Paste the script** into the script editor section. The script should prevent unauthorized changes to the State field when editing from the list view.
5. **Click Submit** to save the Client Script.
6. **Verify:** Open an Incident list and try to change the State field directly in the list. The script should block the change as intended.

7. In the Script field, paste the following code:

```
function onCellEdit(sysIDs, table, oldValues, newValue, callback) {

  alert('State cannot be updated using list editing. Please open the Incident.');

  callback(false);
}
```

8. Click **Submit**.



Task 6: Testing the Configuration

Activity 1: Test Mandatory Enforcement

1. **Navigate to Incident:**
   Go to Incident → Create New to open a new Incident form.


2. **Set the Impact Field:**
   Select **High** for the **Impact** field. This will trigger the UI Policy and Client Script behaviors you configured earlier.


3. **Leave Assigned To Empty:**
   Do not fill in the **Assigned To** field. This will test the onSubmit Client Script that prevents saving if Assigned To is missing.

4. **Click Submit:**
   Attempt to save the Incident record.

5. **Verify the Result:**

- The Incident should **not be saved** because Assigned To is required when Impact is High.
- An **error message** should appear, indicating that the Assigned To field cannot be empty.
- Confirm that all UI Policy actions, such as read-only fields or automated urgency updates, are working as expected.






Activity 2: Test Successful Save

1. **Fill the Assigned To Field:**
   Open the Incident form and select a user in the **Assigned To** field. This ensures the onSubmit Client Script condition is satisfied.

2. **Click Submit:**
   Attempt to save the Incident record.

3. **Verify the Result:**

   - The Incident should be **saved successfully** without any errors.
   - Confirm that all other configured behaviors, such as:
     - **Urgency auto-setting** (from the onChange Client Script)
     - **Read-only fields** (from the UI Policy Action)
     - **State restrictions** (from the onCellEdit Client Script) are functioning as expected



Activity 3: Reverse Condition Test

1. **Open an Existing Incident:**
   Go to Incident → Open and select an Incident where **Impact** is currently set to **High**.


2. **Change Impact:**
   Update the **Impact** field from **High** to **Medium**. This will test the **Reverse if false** functionality of your UI Policy and the behavior of your Client Scripts.

3. **Verify the Field Behavior:**

   - **Assigned To** should no longer be mandatory.

   - **Urgency** should now be editable, meaning the read-only UI Policy action is reversed.

4. **Save the Record:**
   Click **Submit** to save the changes. The record should save successfully without errors, confirming that the reverse condition works as intended.



Activity 4: Test List Edit Blocking


1. **Navigate to the Incident List:**
   Go to Incident → All to view all Incident records in a list view.

2. **Attempt a List Edit:**

   - Locate any Incident in the list.
   - **Double-click the State field** to try editing it directly from the list.

3. **Verify the Behavior:**

   - An **alert message** should appear, indicating that direct changes to the State field are not allowed.
   - The **State value should remain unchanged**, confirming that the onCellEdit Client Script is working correctly.



Activity 5: Test Form-Based Update


1. **Open the Incident Record:**
   Navigate to the same Incident record you used in previous tests.


2. **Change the State:**
   On the **Incident form**, update the **State** field to a new value. This tests that changes via the form (not the list) are allowed.

3. **Click Update:**
   Save the record by clicking **Update**.

4. **Verify the Result:**

   - The **State change should be saved successfully**.
   - Confirm that other fields, such as **Assigned To** and **Urgency**, still follow the configured UI Policy and Client Script rules.





Conclusion

The Implement Client Script & UI Policy (Incident) micro project effectively demonstrates how **UI Policies** and **Client Scripts** can work together to enforce dynamic field behavior, automate updates, and prevent incorrect data submission on Incident forms. By using onChange, onSubmit, and onCellEdit scripts alongside UI Policy actions, the project ensures fields like **Assigned To** and **Urgency** respond appropriately to changes in **Impact**, maintaining clean and

consistent data. This solution not only enforces mandatory fields and controls user interactions but also remains lightweight, efficient, and easy to implement, making it ideal for short-duration micro projects while showcasing practical best practices for improving form usability and data integrity in ServiceNow.