User Acceptance Testing (UAT) Template

Date	7 October 2026
Team ID	
Project Name	Script-Controlled ACL – Restrict Record Access Based on Field Value
Maximum Marks	

Project Overview:

Project Name: Script-Controlled ACL – Restrict Record Access Based on Field Value

Project Description: A script-controlled ACL on ServiceNow that restricts record access based on a field value (e.g., Sensitivity = Confidential) and the logged-in user.

Project Version: 1.0

Testing Period: 26 Oct 2026 to 31 Oct 2026 (planned, Sprint-3)

Testing Scope:

Features: record-level ACL with script, field-value check, access for assigned users and privileged roles, list view and report restriction, write operation, Script Include, impersonation testing.

User stories to be tested: USN-1 to USN-11 (see the Project Planning Template).

Testing Environment:

URL/Location: ServiceNow Personal Developer Instance (add the instance URL)

Credentials (if required): Test users created for UAT (do not write passwords in this document)

Test Cases:

Test Case ID	Test Scenario	Test Steps	Expected Result	Actual Result	Pass/Fail
TC-001	Create the record-level ACL with script	Step 1: Open System Security > Access Control (ACL) Step 2: Create a record ACL with the script for the table Step 3: Save and check that it is active	ACL is saved and active		
TC-002	Script checks the Sensitivity field value	Step 1: Open a Public record Step 2: Open a Confidential record Step 3: Compare the access result	Script returns true / false based on the field value		
TC-003	Authorised user opens a Confidential record	Step 1: Impersonate the assigned user Step 2: Open the Confidential record assigned to the user	Record opens; user can view and edit		
TC-004	Unauthorised user cannot open a Confidential	Step 1: Impersonate a non-assigned user Step 2: Open the Confidential	Record is hidden / access is denied		

Test Case ID	Test Scenario	Test Steps	Expected Result	Actual Result	Pass/Fail
	record	record			
TC-005	Empty field value is denied by default	Step 1: Create a record with an empty Sensitivity value Step 2: Open it as a non-privileged user	Access is denied		
TC-006	Allowed records appear in the list view	Step 1: Impersonate a user Step 2: Open the table list	Only allowed records are listed		
TC-007	Reports show only allowed records	Step 1: Impersonate a user Step 2: Run a report on the table	Restricted records are not in the report		
TC-008	ACL applies to the write operation	Step 1: Assigned user edits a Confidential record Step 2: Non-assigned user tries to edit it	Assigned user can save; other user cannot		
TC-009	ACL calls the Script Include	Step 1: Open the ACL script Step 2: Check the Script Include call and test the record access	Script Include runs and returns the correct result		
TC-010	Test users and test records are created	Step 1: Create test users and roles Step 2: Create records with different Sensitivity values	Test data is available for all scenarios		
TC-011	Impersonation test of different users	Step 1: Impersonate each test user Step 2: Open Public and Confidential records	Result matches the expected access for each user		
TC-012	Script review for audit	Step 1: Open the ACL script Step 2: Check comments and logic with the security officer	Script is documented and readable		

Bug Tracking:

Bug ID	Bug Description	Steps to reproduce	Severity	Status	Additional feedback
BG-001			[Low/ Medium/ High]	[Open/In Progress/Closed]	
BG-002					

No bugs are recorded yet. Fill this table during UAT.

Sign-off:

Tester Name:

Date:

Signature:

Notes:

- Ensure that all test cases cover both positive and negative scenarios.
- Encourage testers to provide detailed feedback, including any suggestions for improvement.
- Bug tracking should include details such as severity, status, and steps to reproduce.
- Obtain sign-off from both the project manager and product owner before proceeding with deployment.