Problem-Solution fit canvas 2.0

Purpose / Vision: Script-Controlled ACL – Restrict Record Access Based on Field Value

Define CS, fit into CC

1. CUSTOMER SEGMENT(S) — CS

- ServiceNow administrators and security / compliance officers who protect sensitive records (e.g., incidents marked Confidential)
- End users (ITIL users, assigned users, callers) who work with those records

6. CUSTOMER CONSTRAINTS — CC

- Role-based ACLs cannot compare a field value
- Limited admin time and scripting skills
- Script must not slow down list / form loading
- Change must be safe on a live instance (valid users must not be blocked)

5. AVAILABLE SOLUTIONS — AS

- Role-only ACLs (everyone with the role sees the record)
- Business Rules / Query Rules as workarounds
- Extra roles or groups per department

Pros: simple. Cons: too many roles, hard to audit, easy to miss a case.

Explore AS, differentiate

Focus on J&P, tap into BE, understand RC

2. JOBS-TO-BE-DONE / PROBLEMS — J&P

- Make record access depend on a field value (e.g., Sensitivity = Confidential)
- Allow only the assigned user, caller or privileged roles
- Prove who can see which record during audits

9. PROBLEM ROOT CAUSE — RC

- Standard role checks apply to everyone holding the role and cannot compare the record's field value with the logged-in user
- Organisations now need record-level privacy and audit compliance

7. BEHAVIOUR — BE

- Admins create extra roles and groups
- Add Business Rules and manual checks
- Test by impersonating users
- Users raise tickets when they cannot see a record they need

Focus on J&P, tap into BE, understand RC

Identify strong TR & EM

3. TRIGGERS — TR

- A confidential record is seen by an unauthorised user
- A data-leak incident or audit finding
- A new compliance rule for sensitive data

4. EMOTIONS: BEFORE / AFTER — EM

Before: worried, insecure, frustrated with many roles
After: confident, in control, relieved that access is enforced automatically

10. YOUR SOLUTION — SL

A script-controlled ACL: the ACL script checks the record's field value (e.g., Sensitivity) and the logged-in user (gs.hasRole(), assigned_to, caller) and returns answer = true / false. The logic sits in a reusable Script Include and is verified by impersonating authorised and unauthorised users.

8. CHANNELS of BEHAVIOUR — CH

8.1 ONLINE
ServiceNow instance: list view, form view, reports, Service Portal; ServiceNow ACL documentation and community

8.2 OFFLINE — CH

Team and security review meetings; audit discussions and access-matrix documents shared with stakeholders

Extract online & offline CH of BE

Problem-Solution fit canvas by Daria Nepriakhina / Amaltama.com – licensed under CC BY-NC-ND 4.0

Filled for: Script-Controlled ACL – Restrict Record Access Based on Field Value