Customer Journey Map

Script-Controlled ACL – Restrict Record Access Based on Field Value

Persona: ServiceNow Administrator / Security Officer | Scenario: Identifying, creating, testing and maintaining a script-controlled ACL for a table

	Identify	**Design**	**Build**	**Test**	**Maintain**
Stage question	How does the admin find that role-only access is not enough?	How is the access rule planned?	How is the ACL created?	How is the rule verified?	What happens after go-live?
Steps	Notice that all ITIL users can open Confidential records Review the ACL documentation	Select the table and the field (e.g., Sensitivity) Decide who may access (assigned user, caller, privileged role)	Create a record-level ACL with a script Add the logic to a Script Include	Impersonate authorised and unauthorised users Check list, form and reports	Update the rule when field values or roles change Review the script during audits
Interactions	ServiceNow instance ServiceNow ACL documentation	Team discussion Requirement documents	Studio / System Security > ACL Script editor	User impersonation Test records	System logs Audit reports
Goals & motivations	Protect sensitive records from unauthorised users.	Have one clear and simple rule.	Make access depend on the field value.	Be sure nobody gets access by mistake.	Keep the rule correct and easy to maintain.
Positive moments	Problem is clearly understood.	A simple rule that the whole team agrees on.	The script returns the correct true / false result.	Unauthorised users cannot see the record.	The same pattern can be reused for other tables.
Negative moments	Sensitive records are already visible to many users.	Unsure about edge cases (empty field value).	A script error can block valid users.	Many test users and cases to check.	Rule can break when roles or field values change.
Areas of opportunity	Add awareness about field-based access control.	Document the access matrix before coding.	Use a Script Include and code comments.	Create a reusable test-case checklist.	Schedule periodic ACL reviews.