

ContosoShield™ Exterior Acrylic Latex Paint

Finish: Satin **Intended Use:** Exterior siding, trim, masonry primed surfaces **Base:** Deep Base



Color palette (sample) - Coastal Teal

Coastal Teal
#25BABA
Finish options vary

Contoso Blue
#2B8D96
Finish options vary

Flat Grey
#B2BEC3
Finish options vary

Deep Navy
#1B2A41
Finish options vary

Warm Sand
#D9C7A1
Finish options vary

Forest Green
#0B8466
Finish options vary

Product Details

SKU	CTSO-PAINT-EXT-SAT-1G-DB
UPC	0 12345 10001 1 (sample)
Color	Coastal Teal
Low VOC	< 50 g/L (sample)
Coverage	350–400 sq ft per gallon (single coat)
Dry Time	Touch: 1 hr • Recoat: 4 hr • Full cure: 30 days
Sheen	Satin (20–35 @ 60°)
Recommended Coats	2 coats over properly prepared/primed surface
Cleanup	Soap & water
Warranty	10-year limited (sample)

Product Summary

Premium, low-VOC exterior acrylic latex coating engineered for color retention and weather resistance. Satin finish balances washability with subtle sheen.

Technical Data

Property	Value	Notes
Resin Type	100% Acrylic	Coating binder
Solids by Volume	38% (sample)	Affects film build
Solids by Weight	52% (sample)	Affects hide/viscosity
Viscosity (KU)	95–105 KU	Application ready
Recommended DFT/WFT	2.0 mil / 5.2 mil	Per coat
Storage	50–90°F (10–32°C)	Protect from freezing/heat
Shelf Life	24 months (unopened)	Unopened container

Application & Surface Prep (Sample)

Surface prep: Remove chalking, dirt, mildew, and loose coatings. Repair defects and spot-prime bare areas.
Application: Brush, roll, or spray; back-roll sprayed surfaces. **Conditions:** Apply 50–90°F; no rain expected for 24 hours.

Safety & Handling (Sample)

Use in well-ventilated areas. Avoid breathing spray mist. Wear protective eyewear and gloves. Keep out of reach of children. For real products, refer to SDS.

Disclaimer: This PDF is a synthetic sample generated for review and demonstration purposes only. All product values are illustrative and not intended for real-world use.