

ContosoGuard™ Premium Primer-Sealer

Finish: Flat **Intended Use:** Interior/exterior primer for drywall, wood, masonry **Base:** White



Color palette (sample) - White

Bright White
#FFFFFF
Finish options vary

Primer Grey
#D0D3D4
Finish options vary

Stone
#CACFD2
Finish options vary

Warm Sand
#D9C7A1
Finish options vary

Charcoal
#2E4053
Finish options vary

Teal
#25BABA
Finish options vary

Product Details

SKU	CTSO-PRIMER-PS-1G-WH
UPC	0 12345 10003 5 (sample)
Color	White
Low VOC	< 50 g/L (sample)
Coverage	300–400 sq ft per gallon
Dry Time	Recoat: 1–2 hr
Sheen	Flat
Recommended Coats	1 coat primer; spot-prime as needed
Cleanup	Soap & water
Warranty	1-year limited (sample)

Product Summary

High-adhesion primer-sealer that evens porosity and improves topcoat uniformity. Helps block mild stains and promotes consistent sheen.

Technical Data

Property	Value	Notes
Resin Type	Acrylic	Coating binder
Solids by Volume	35% (sample)	Affects film build
Solids by Weight	50% (sample)	Affects hide/viscosity
Viscosity (KU)	90–100 KU	Application ready
Recommended DFT/WFT	1.5 mil / 4.3 mil	Per coat
Storage	50–90°F (10–32°C)	Protect from freezing/heat
Shelf Life	18 months (unopened)	Unopened container

Application & Surface Prep (Sample)

Surface prep: Clean and dry; remove loose material. **Application:** Brush/roll/spray. **Topcoat:** Apply paint after primer is dry to touch.

Safety & Handling (Sample)

Use ventilation when spraying. Avoid breathing mist. If irritation occurs, discontinue use and rinse exposed skin.

Disclaimer: This PDF is a synthetic sample generated for review and demonstration purposes only. All product values are illustrative and not intended for real-world use.