

ContosoTrim™ Waterborne Urethane Enamel

Finish: Semi-Gloss **Intended Use:** Interior trim, doors, cabinets **Base:** Tint Base



Color palette (sample) - Deep Navy

Deep Navy
#1B2A41
Finish options vary

Coastal Teal
#25BABA
Finish options vary

Steel
#7F8C8D
Finish options vary

Fog
#D5DBDB
Finish options vary

Pearl
#F8F9F9
Finish options vary

Slate
#566573
Finish options vary

Product Details

SKU	CTSO-ENAMEL-WU-SG-1Q-TB
UPC	0 12345 10004 2 (sample)
Color	Deep Navy
Low VOC	< 80 g/L (sample)
Coverage	90–110 sq ft per quart
Dry Time	Touch: 1 hr • Recoat: 4 hr
Sheen	Semi-gloss (55–70 @ 60°)
Recommended Coats	2 coats for durability
Cleanup	Soap & water (before cure)
Warranty	7-year limited (sample)

Product Summary

Hard, smooth semi-gloss enamel formulated for trim and cabinet surfaces. Resists scuffs and cleans easily after full cure.

Technical Data

Property	Value	Notes
Resin Type	Waterborne Urethane	Coating binder
Solids by Volume	32% (sample)	Affects film build
Solids by Weight	45% (sample)	Affects hide/viscosity
Viscosity (KU)	85–95 KU	Application ready
Recommended DFT/WFT	1.5 mil / 4.7 mil	Per coat
Storage	50–90°F (10–32°C)	Protect from freezing/heat
Shelf Life	24 months (unopened)	Unopened container

Application & Surface Prep (Sample)

Surface prep: Degloss and clean. **Application:** Fine-finish roller or high-quality brush. **Drying:** Allow extended cure time before heavy use.

Safety & Handling (Sample)

Avoid eye contact. Wear gloves when sanding cured films. Use ventilation during application.

Disclaimer: This PDF is a synthetic sample generated for review and demonstration purposes only. All product values are illustrative and not intended for real-world use.