

# ContosoDeck™ Exterior Wood Stain + Seal

**Finish:** Low Sheen    **Intended Use:** Exterior decks, fences, outdoor furniture    **Base:** Ready Mixed



Color palette (sample) - Warm Sand

**Warm Sand**  
#D9C7A1  
Finish options vary

**Cedar**  
#A04000  
Finish options vary

**Walnut**  
#6E2C00  
Finish options vary

**Driftwood**  
#B7950B  
Finish options vary

**Stone**  
#CACFD2  
Finish options vary

**Forest**  
#0B8466  
Finish options vary

## Product Details

|                   |                                                  |
|-------------------|--------------------------------------------------|
| SKU               | CTSO-STAIN-EX-WD-LS-1G                           |
| UPC               | 0 12345 10005 9 (sample)                         |
| Color             | Warm Sand                                        |
| Low VOC           | < 100 g/L (sample)                               |
| Coverage          | 150–250 sq ft per gallon (porous wood dependent) |
| Dry Time          | Dry: 2–4 hr • Recoat: 24 hr                      |
| Sheen             | Low sheen                                        |
| Recommended Coats | 1–2 coats depending on porosity                  |
| Cleanup           | Soap & water                                     |
| Warranty          | 3-year limited (sample)                          |

## Product Summary

Penetrating exterior wood stain with added water repellency. Enhances grain while providing UV and moisture resistance.

# Technical Data

| Property            | Value                | Notes                      |
|---------------------|----------------------|----------------------------|
| Resin Type          | Acrylic              | Coating binder             |
| Solids by Volume    | 28% (sample)         | Affects film build         |
| Solids by Weight    | 40% (sample)         | Affects hide/viscosity     |
| Viscosity (KU)      | 60–80 KU             | Application ready          |
| Recommended DFT/WFT | 1.0 mil / 3.5 mil    | Per coat                   |
| Storage             | 50–90°F (10–32°C)    | Protect from freezing/heat |
| Shelf Life          | 18 months (unopened) | Unopened container         |

## Application & Surface Prep (Sample)

**Surface prep:** Clean, dry wood; remove mildew. **Application:** Brush or pad; back-brush for even penetration. **Weather:** Avoid direct hot sun and rain for 24 hours.

## Safety & Handling (Sample)

Use ventilation. Avoid ingestion. Keep container closed when not in use.

*Disclaimer:* This PDF is a synthetic sample generated for review and demonstration purposes only. All product values are illustrative and not intended for real-world use.