

ContosoFloor™ Garage & Concrete Coating

Finish: Satin **Intended Use:** Garages, basements, concrete floors **Base:** Tint Base



Color palette (sample) - Steel Grey

Steel Grey
#7F8C8D
Finish options vary

Graphite
#2C3E50
Finish options vary

Silver
#B2BEC3
Finish options vary

White
#FFFFFF
Finish options vary

Teal
#25BABA
Finish options vary

Navy
#1B2A41
Finish options vary

Product Details

SKU	CTSO-FLOOR-GC-SAT-1G
UPC	0 12345 10006 6 (sample)
Color	Steel Grey
Low VOC	< 50 g/L (sample)
Coverage	250–350 sq ft per gallon
Dry Time	Walk-on: 24 hr • Vehicle: 7 days
Sheen	Satin
Recommended Coats	2 coats recommended
Cleanup	Soap & water (uncured)
Warranty	2-year limited (sample)

Product Summary

Durable coating for interior concrete floors with improved abrasion resistance. Designed for light-to-moderate traffic environments.

Technical Data

Property	Value	Notes
Resin Type	Acrylic	Coating binder
Solids by Volume	45% (sample)	Affects film build
Solids by Weight	60% (sample)	Affects hide/viscosity
Viscosity (KU)	95–110 KU	Application ready
Recommended DFT/WFT	3.0 mil / 6.6 mil	Per coat
Storage	50–90°F (10–32°C)	Protect from freezing/heat
Shelf Life	24 months (unopened)	Unopened container

Application & Surface Prep (Sample)

Surface prep: Etch or mechanically profile concrete; rinse and dry. **Application:** Roll with 3/8" nap. **Cure:** Allow full cure before heavy loads.

Safety & Handling (Sample)

Use ventilation and avoid breathing mist. Keep away from food and beverages.

Disclaimer: This PDF is a synthetic sample generated for review and demonstration purposes only. All product values are illustrative and not intended for real-world use.