

ContosoPro™ High-Build Exterior Masonry Coating

Finish: Low Sheen **Intended Use:** Exterior masonry, stucco, concrete block **Base:** Tint Base



Color palette (sample) - Terracotta Red

Terracotta Red
#C0392B
Finish options vary

Clay
#AF601A
Finish options vary

Sand
#D9C7A1
Finish options vary

Stone
#CACFD2
Finish options vary

Olive
#7D6608
Finish options vary

Charcoal
#2E4053
Finish options vary

Product Details

SKU	CTSO-MASN-EXT-HB-LS-5G
UPC	0 12345 10010 3 (sample)
Color	Terracotta Red
Low VOC	< 50 g/L (sample)
Coverage	100–150 sq ft per gallon (high-build)
Dry Time	Recoat: 8 hr • Full cure: 14 days
Sheen	Low sheen
Recommended Coats	2 coats recommended
Cleanup	Soap & water
Warranty	12-year limited (sample)

Product Summary

High-build exterior coating designed to bridge minor hairline cracks and provide long-term protection on masonry substrates.

Technical Data

Property	Value	Notes
Resin Type	Acrylic	Coating binder
Solids by Volume	55% (sample)	Affects film build
Solids by Weight	70% (sample)	Affects hide/viscosity
Viscosity (KU)	115–125 KU	Application ready
Recommended DFT/WFT	8.0 mil / 14.5 mil	Per coat
Storage	50–90°F (10–32°C)	Protect from freezing/heat
Shelf Life	18 months (unopened)	Unopened container

Application & Surface Prep (Sample)

Surface prep: Remove efflorescence and loose material; prime as needed. **Application:** Heavy-nap roller or spray. **Tip:** Maintain recommended film build.

Safety & Handling (Sample)

Use ventilation during spray application. Avoid breathing mist. Wear eye protection.

Disclaimer: This PDF is a synthetic sample generated for review and demonstration purposes only. All product values are illustrative and not intended for real-world use.