

ContosoShield™ Exterior Acrylic Latex Paint

Finish: Satin **Intended Use:** Exterior siding, trim, masonry primed surfaces **Base:** Deep Base



Coastal Teal
#25BABA
Finish: Satin

Contoso Blue
#2B8D96
Finish: Satin

Flat Grey
#B2BEC3
Finish: Satin

Deep Navy
#1B2A41
Finish: Satin

Warm Sand
#D9C7A1
Finish: Satin

Forest Green
#0B8466
Finish: Satin

Custom Product Metadata

SKU	CTSO-PAINT-EXT-SAT-1G-DB
UPC	0 12345 67890 5 (sample)
Color Family	Teal/Blue (tintable)
Low VOC	< 50 g/L (sample)
Coverage	350–400 sq ft per gallon (single coat)
Dry Time	Touch: 1 hr • Recoat: 4 hr • Full cure: 30 days
Sheen	Satin (20–35 @ 60°)
Recommended Coats	2 coats over properly prepared/primed surface
Cleanup	Soap & water
Warranty	10-year limited (sample)

Product Summary

ContosoShield™ is a premium, low-VOC, exterior acrylic latex coating engineered for durable color retention and weather resistance. The satin finish balances washability with a subtle sheen suitable for siding and trim. This sample sheet demonstrates how you can package a product description, imagery, and structured metadata into a single PDF artifact for downstream indexing and retrieval.

Technical Data

Property	Value	Notes
Resin Type	100% Acrylic	For exterior durability
Solids by Volume	38% (sample)	Affects coverage and film build
Solids by Weight	52% (sample)	Affects viscosity and hide
Viscosity (KU)	95–105 KU	Application ready
Recommended DFT/WFT	2.0 mil / 5.2 mil	Per coat
Flash Point	Non-flammable (waterborne)	Typical for latex paints
Storage	50–90°F (10–32°C)	Protect from freezing
Shelf Life	24 months (unopened)	When stored per guidance

Application & Surface Prep (Sample)

Surface prep: Remove chalking, dirt, mildew, and loose coatings. Repair defects and spot-prime bare areas.
Application: Brush, roll, or spray. Back-roll sprayed surfaces for uniform film build. **Conditions:** Apply between 50–90°F and when no rain is expected for 24 hours.

Packaging & Ordering

Pack Size	Item Code	Case Pack
1 Gal	CTSO-PAINT-EXT-SAT-1G-DB	4 units / case
5 Gal	CTSO-PAINT-EXT-SAT-5G-DB	1 unit / pail

Safety, Compliance & Indexing Fields

Safety: Use in well-ventilated areas. Avoid breathing spray mist. Wear protective eyewear and gloves. Keep out of reach of children. In case of eye contact, flush with water for 15 minutes and seek medical advice.

Regulatory (Sample): Low-VOC formulation. Complies with common architectural coating VOC limits (example only). For a real product, attach or reference the SDS and local regulatory statements.

Custom Index Fields (for Search / AI Enrichment)

metadata.company	Contoso Paint Co.
metadata.category	Exterior Paint
metadata.subcategory	Acrylic Latex
metadata.finish	Satin
metadata.color	Coastal Teal (Tintable)
metadata.sku	CTSO-PAINT-EXT-SAT-1G-DB
metadata.voc_g_per_l	50
metadata.coverage_sqft_per_gal	350-400
metadata.keywords	exterior, acrylic, satin, low VOC, weather resistant, washable
metadata.images	contoso_paint_product_can.png; contoso_paint_color_swatches.png

Disclaimer: This PDF is a synthetic sample generated for review and demonstration purposes only. All product values are illustrative and not intended for real-world use.