

# Practical: 9

**AIM: Define a ring topology of ten nodes for a dynamic network where the routing adjusts to a link failure.**



**Ganpat  
University**

॥ विद्यया समाजोत्कर्षः ॥

**Department of Computer  
Engineering/Information Technology**

**U.V. Patel  
College of  
Engineering**

## Practical: 9

---

```
set ns [new Simulator]
$ns rtproto DV
set nf [open p9out.nam w]
$ns namtrace-all $nf

proc finish {} {
    global ns nf
    $ns flush-trace
    close $nf
    exec nam p9out.nam
    exit 0
}

for {set i 0} {$i<10} {incr i} {
    set n($i) [$ns node]
}

for {set i 0} {$i<10} {incr i} {
    $ns duplex-link $n($i) $n([expr ($i+1)%10]) 1Mb 10ms DropTail
}

set udp0 [new Agent/UDP]
$ns attach-agent $n(0) $udp0

set cbr0 [new Application/Traffic/CBR]
$cbr0 attach-agent $udp0

set null0 [new Agent/Null]
$ns attach-agent $n(7) $null0

$ns connect $udp0 $null0

$ns rtmodel-at 1.0 down $n(9) $n(8)
$ns rtmodel-at 2.0 up $n(9) $n(8)


$ns at 0.5 "$cbr0 start"
$ns at 4.5 "$cbr0 stop"

$ns at 4.0 "finish"
$ns run
```

## Practical: 9

### Output:

Here packet is transfer from node 0 to node 7.



Link is fail between node 8 and node 9.

