


Program 12

Aim: To construct a VLAN and make the PC's communicate among a VLAN.

Topology , Procedure and Observation:



Procedures

1. Create topology as above.
2. choose 1841 router.
3. In switch, go to config tab & select VLAN Database
 - Give VLAN num (2) , name(bms) . say Add.
 - Select ~~Port~~ eth6/1 and make it trunk.
 - Fa2/1 → VLAN → select 2 bms
 - Fa3/1
4. In config tab of router select VLAN Database enter the number and name of the vlan created
5. Go to config in CLI of router:

```
interface Fa 0/0.1
encapsulation dot1 q 2
ip address 192.168.2.1 255.255.255.0
no shut
exit
```

Observation:

- VLAN trunking allowed switch to forward frames from different VLANs over a single link called trunk.
- When pinged the message is successfully sent.

Output:

PC1:

PC> ping 192.168.2.2

Pinging 192.168.2.2 with 32 bytes of data:

Reply from 192.168.2.2: bytes=32 time=0ms TTL=127

11 ——— 11


11 ——— 11

11 ——— 11

ping statistics for 192.168.2.2:

Packets: sent=4, received=4, lost=0 (0% loss)

Screen Shots:



Command Prompt

```
Packet Tracer PC Command Line 1.0
PC>ping 192.168.2.2

Pinging 192.168.2.2 with 32 bytes of data:

Request timed out.
Reply from 192.168.2.2: bytes=32 time=0ms TTL=127
Reply from 192.168.2.2: bytes=32 time=0ms TTL=127
Reply from 192.168.2.2: bytes=32 time=4ms TTL=127

Ping statistics for 192.168.2.2:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 4ms, Average = 1ms

PC>ping 192.168.2.2

Pinging 192.168.2.2 with 32 bytes of data:

Reply from 192.168.2.2: bytes=32 time=0ms TTL=127
Reply from 192.168.2.2: bytes=32 time=0ms TTL=127
Reply from 192.168.2.2: bytes=32 time=2ms TTL=127
Reply from 192.168.2.2: bytes=32 time=0ms TTL=127

Ping statistics for 192.168.2.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 2ms, Average = 0ms

PC>ping 192.168.2.3

Pinging 192.168.2.3 with 32 bytes of data:

Request timed out.
Reply from 192.168.2.3: bytes=32 time=3ms TTL=127
Reply from 192.168.2.3: bytes=32 time=2ms TTL=127
Reply from 192.168.2.3: bytes=32 time=1ms TTL=127

Ping statistics for 192.168.2.3:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
Approximate round trip times in milli-seconds:
    Minimum = 1ms, Maximum = 3ms, Average = 2ms

PC>ping 192.168.2.3

Pinging 192.168.2.3 with 32 bytes of data:

Reply from 192.168.2.3: bytes=32 time=0ms TTL=127
Reply from 192.168.2.3: bytes=32 time=0ms TTL=127
Reply from 192.168.2.3: bytes=32 time=2ms TTL=127
Reply from 192.168.2.3: bytes=32 time=0ms TTL=127

Ping statistics for 192.168.2.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
    Minimum = 0ms, Maximum = 2ms, Average = 0ms

PC>|
```