

Social network Graph Link Prediction - Facebook Challenge

In [0]:

```
#Importing Libraries
# please do go through this python notebook:
import warnings
warnings.filterwarnings("ignore")

import csv
import pandas as pd#pandas to create small dataframes
import datetime #Convert to unix time
import time #Convert to unix time
# if numpy is not installed already : pip3 install numpy
import numpy as np#Do arithmetic operations on arrays
# matplotlib: used to plot graphs
import matplotlib
import matplotlib.pyplot as plt
import seaborn as sns#Plots
from matplotlib import rcParams#Size of plots
from sklearn.cluster import MiniBatchKMeans, KMeans#Clustering
import math
import pickle
import os
# to install xgboost: pip3 install xgboost
import xgboost as xgb

import warnings
import networkx as nx
import pdb
import pickle
from pandas import HDFStore, DataFrame
from pandas import read_hdf
from scipy.sparse.linalg import svds, eigs
import gc
from tqdm import tqdm
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import f1_score
```

In [0]:

```
#reading
from pandas import read_hdf
df_final_train = read_hdf('data/fea_sample/storage_sample_stage4.h5', 'train_df', mode='r')
df_final_test = read_hdf('data/fea_sample/storage_sample_stage4.h5', 'test_df', mode='r')
```

In [0]:

```
df_final_train.columns
```

Out[0]:

```
Index(['source_node', 'destination_node', 'indicator_link',
      'jaccard_followers', 'jaccard_followees', 'cosine_followers',
      'cosine_followees', 'num_followers_s', 'num_followees_s',
      'num_followees_d', 'inter_followers', 'inter_followees', 'adar_index',
      'follows_back', 'same_comp', 'shortest_path', 'weight_in', 'weight_out',
      'weight_f1', 'weight_f2', 'weight_f3', 'weight_f4', 'page_rank_s',
      'page_rank_d', 'katz_s', 'katz_d', 'hubs_s', 'hubs_d', 'authorities_s',
      'authorities_d', 'svd_u_s_1', 'svd_u_s_2', 'svd_u_s_3', 'svd_u_s_4',
      'svd_u_s_5', 'svd_u_s_6', 'svd_u_d_1', 'svd_u_d_2', 'svd_u_d_3',
      'svd_u_d_4', 'svd_u_d_5', 'svd_u_d_6', 'svd_v_s_1', 'svd_v_s_2',
      'svd_v_s_3', 'svd_v_s_4', 'svd_v_s_5', 'svd_v_s_6', 'svd_v_d_1',
      'svd_v_d_2', 'svd_v_d_3', 'svd_v_d_4', 'svd_v_d_5', 'svd_v_d_6'],
      dtype='object')
```

In [0]:

```
y_train = df_final_train.indicator_link
```

```
y_test = df_final_test.indicator_link
```

```
In [0]:
```

```
df_final_train.drop(['source_node', 'destination_node', 'indicator_link'], axis=1, inplace=True)  
df_final_test.drop(['source_node', 'destination_node', 'indicator_link'], axis=1, inplace=True)
```


```
In [0]:
```

```
estimators = [10,50,100,250,450]  
train_scores = []  
test_scores = []  
for i in estimators:  
    clf = RandomForestClassifier(bootstrap=True, class_weight=None, criterion='gini',  
                                max_depth=5, max_features='auto', max_leaf_nodes=None,  
                                min_impurity_decrease=0.0, min_impurity_split=None,  
                                min_samples_leaf=52, min_samples_split=120,  
                                min_weight_fraction_leaf=0.0, n_estimators=i, n_jobs=-1, random_state=25, verbose=0, warm_start=False)  
    clf.fit(df_final_train, y_train)  
    train_sc = f1_score(y_train, clf.predict(df_final_train))  
    test_sc = f1_score(y_test, clf.predict(df_final_test))  
    test_scores.append(test_sc)  
    train_scores.append(train_sc)  
    print('Estimators = ', i, 'Train Score', train_sc, 'test Score', test_sc)  
plt.plot(estimators, train_scores, label='Train Score')  
plt.plot(estimators, test_scores, label='Test Score')  
plt.xlabel('Estimators')  
plt.ylabel('Score')  
plt.title('Estimators vs score at depth of 5')
```

```
Estimators = 10 Train Score 0.9063252121775113 test Score 0.8745605278006858  
Estimators = 50 Train Score 0.9205725512208812 test Score 0.9125653355634538  
Estimators = 100 Train Score 0.9238690848446947 test Score 0.9141199714153599  
Estimators = 250 Train Score 0.9239789348046863 test Score 0.9188007232664732  
Estimators = 450 Train Score 0.9237190618658074 test Score 0.9161507685828595
```

```
Out[0]:
```

```
Text(0.5,1,'Estimators vs score at depth of 5')
```



```
In [0]:
```

```
depths = [3,9,11,15,20,35,50,70,130]  
train_scores = []  
test_scores = []  
for i in depths:  
    clf = RandomForestClassifier(bootstrap=True, class_weight=None, criterion='gini',  
                                max_depth=i, max_features='auto', max_leaf_nodes=None,  
                                min_impurity_decrease=0.0, min_impurity_split=None,  
                                min_samples_leaf=52, min_samples_split=120,  
                                min_weight_fraction_leaf=0.0, n_estimators=115, n_jobs=-1, random_state=25, verbose=0, warm_start=False)  
    clf.fit(df_final_train, y_train)  
    train_sc = f1_score(y_train, clf.predict(df_final_train))  
    test_sc = f1_score(y_test, clf.predict(df_final_test))  
    train_scores.append(train_sc)  
    test_scores.append(test_sc)
```

```


test_scores.append(test_sc)
train_scores.append(train_sc)
print('depth = ',i, 'Train Score',train_sc, 'test Score',test_sc)
plt.plot(depths,train_scores,label='Train Score')
plt.plot(depths,test_scores,label='Test Score')
plt.xlabel('Depth')
plt.ylabel('Score')
plt.title('Depth vs score at depth of 5 at estimators = 115')
plt.show()

```

```

depth = 3 Train Score 0.8916120853581238 test Score 0.8687934859875491
depth = 9 Train Score 0.9572226298198419 test Score 0.9222953031452904
depth = 11 Train Score 0.9623451340902863 test Score 0.9252318758281279
depth = 15 Train Score 0.9634267621927706 test Score 0.9231288356496615
depth = 20 Train Score 0.9631629153051491 test Score 0.9235051024711141
depth = 35 Train Score 0.9634333127085721 test Score 0.9235601652753184
depth = 50 Train Score 0.9634333127085721 test Score 0.9235601652753184
depth = 70 Train Score 0.9634333127085721 test Score 0.9235601652753184
depth = 130 Train Score 0.9634333127085721 test Score 0.9235601652753184

```



In [0]:

```

from sklearn.metrics import f1_score
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import f1_score
from sklearn.model_selection import RandomizedSearchCV
from scipy.stats import randint as sp_randint
from scipy.stats import uniform

param_dist = {"n_estimators":sp_randint(105,125),
              "max_depth": sp_randint(10,15),
              "min_samples_split": sp_randint(110,190),
              "min_samples_leaf": sp_randint(25,65)}

clf = RandomForestClassifier(random_state=25,n_jobs=-1)

rf_random = RandomizedSearchCV(clf, param_distributions=param_dist,
                               n_iter=5,cv=10,scoring='f1',random_state=25)

rf_random.fit(df_final_train,y_train)
print('mean test scores',rf_random.cv_results_['mean_test_score'])
print('mean train scores',rf_random.cv_results_['mean_train_score'])

```

```

mean test scores [0.96225043 0.96215493 0.96057081 0.96194015 0.96330005]
mean train scores [0.96294922 0.96266735 0.96115674 0.96263457 0.96430539]

```

In [0]:

```
print(rf_random.best_estimator_)
```

```

RandomForestClassifier(bootstrap=True, class_weight=None, criterion='gini',
                        max_depth=14, max_features='auto', max_leaf_nodes=None,
                        min_impurity_decrease=0.0, min_impurity_split=None,
                        min_samples_leaf=28, min_samples_split=111,
                        min_weight_fraction_leaf=0.0, n_estimators=121, n_jobs=-1,
                        oob_score=False, random_state=25, verbose=0, warm_start=False)

```

In [0]:

```
clf = RandomForestClassifier(bootstrap=True, class_weight=None, criterion='gini',
                             max_depth=14, max_features='auto', max_leaf_nodes=None,
                             min_impurity_decrease=0.0, min_impurity_split=None,
                             min_samples_leaf=28, min_samples_split=111,
                             min_weight_fraction_leaf=0.0, n_estimators=121, n_jobs=-1,
                             oob_score=False, random_state=25, verbose=0, warm_start=False)
```

In [0]:

```
clf.fit(df_final_train,y_train)
y_train_pred = clf.predict(df_final_train)
y_test_pred = clf.predict(df_final_test)
```

In [0]:

```
from sklearn.metrics import f1_score
print('Train f1 score',f1_score(y_train,y_train_pred))
print('Test f1 score',f1_score(y_test,y_test_pred))
```

Train f1 score 0.9652533106548414
Test f1 score 0.9241678239279553

In [0]:

```
from sklearn.metrics import confusion_matrix
def plot_confusion_matrix(test_y, predict_y):
    C = confusion_matrix(test_y, predict_y)

    A = ((C.T) / (C.sum(axis=1))).T)

    B = (C/C.sum(axis=0))
    plt.figure(figsize=(20,4))

    labels = [0,1]
    # representing A in heatmap format
    cmap=sns.light_palette("blue")
    plt.subplot(1, 3, 1)
    sns.heatmap(C, annot=True, cmap=cmap, fmt=".3f", xticklabels=labels, yticklabels=labels)
    plt.xlabel('Predicted Class')
    plt.ylabel('Original Class')
    plt.title("Confusion matrix")

    plt.subplot(1, 3, 2)
    sns.heatmap(B, annot=True, cmap=cmap, fmt=".3f", xticklabels=labels, yticklabels=labels)
    plt.xlabel('Predicted Class')
    plt.ylabel('Original Class')
    plt.title("Precision matrix")

    plt.subplot(1, 3, 3)
    # representing B in heatmap format
    sns.heatmap(A, annot=True, cmap=cmap, fmt=".3f", xticklabels=labels, yticklabels=labels)
    plt.xlabel('Predicted Class')
    plt.ylabel('Original Class')
    plt.title("Recall matrix")


    plt.show()
```

In [0]:


```
print('Train confusion_matrix')
plot_confusion_matrix(y_train,y_train_pred)
print('Test confusion_matrix')
plot_confusion_matrix(y_test,y_test_pred)
```

Train confusion_matrix






Test confusion_matrix



In [0]:

```
from sklearn.metrics import roc_curve, auc
fpr, tpr, ths = roc_curve(y_test, y_test_pred)
auc_sc = auc(fpr, tpr)
plt.plot(fpr, tpr, color='navy', label='ROC curve (area = %0.2f)' % auc_sc)
plt.xlabel('False Positive Rate')
plt.ylabel('True Positive Rate')
plt.title('Receiver operating characteristic with test data')
plt.legend()
plt.show()
```



In [0]:

```
features = df_final_train.columns
importances = clf.feature_importances_
indices = (np.argsort(importances))[-25:]
plt.figure(figsize=(10,12))
plt.title('Feature Importances')
plt.barh(range(len(indices)), importances[indices], color='r', align='center')
plt.yticks(range(len(indices)), [features[i] for i in indices])
plt.xlabel('Relative Importance')
plt.show()
```

