

DonorsChoose

DonorsChoose.org receives hundreds of thousands of project proposals each year for classroom projects in need of funding. Right now, a large number of volunteers is needed to manually screen each submission before it's approved to be posted on the DonorsChoose.org website.

Next year, DonorsChoose.org expects to receive close to 500,000 project proposals. As a result, there are three main problems they need to solve:

- How to scale current manual processes and resources to screen 500,000 projects so that they can be posted as quickly and as efficiently as possible
- How to increase the consistency of project vetting across different volunteers to improve the experience for teachers
- How to focus volunteer time on the applications that need the most assistance

The goal of the competition is to predict whether or not a DonorsChoose.org project proposal submitted by a teacher will be approved, using the text of project descriptions as well as additional metadata about the project, teacher, and school. DonorsChoose.org can then use this information to identify projects most likely to need further review before approval.

About the DonorsChoose Data Set

The `train.csv` data set provided by DonorsChoose contains the following features:

Feature	Description
<code>project_id</code>	A unique identifier for the proposed project. Example: p036502
<code>project_title</code>	Title of the project. Examples: <ul style="list-style-type: none">• Art Will Make You Happy!• First Grade Fun
<code>project_grade_category</code>	Grade level of students for which the project is targeted. One of the following enumerated values: <ul style="list-style-type: none">• Grades PreK-2• Grades 3-5• Grades 6-8• Grades 9-12
<code>project_subject_categories</code>	One or more (comma-separated) subject categories for the project from the following enumerated list of values: <ul style="list-style-type: none">• Applied Learning• Care & Hunger• Health & Sports• History & Civics• Literacy & Language• Math & Science• Music & The Arts• Special Needs• Warmth Examples: <ul style="list-style-type: none">• Music & The Arts• Literacy & Language, Math & Science
<code>school_state</code>	State where school is located (Two-letter U.S. postal code). Example: WY
<code>project_subject_subcategories</code>	One or more (comma-separated) subject subcategories for the project. Examples: <ul style="list-style-type: none">• Literacy

Feature	Description
<code>project_resource_summary</code>	An explanation of the resources needed for the project. Example: <ul style="list-style-type: none"> My students need hands on literacy materials to manage sensory needs!
<code>project_essay_1</code>	First application essay*
<code>project_essay_2</code>	Second application essay*
<code>project_essay_3</code>	Third application essay*
<code>project_essay_4</code>	Fourth application essay*
<code>project_submitted_datetime</code>	Datetime when project application was submitted. Example: 2016-04-28 12:43:56.245
<code>teacher_id</code>	A unique identifier for the teacher of the proposed project. Example: bdf8baa8fedef6bfeec7ae4ff1c15c56
<code>teacher_prefix</code>	Teacher's title. One of the following enumerated values: <ul style="list-style-type: none"> nan Dr. Mr. Mrs. Ms. Teacher.
<code>teacher_number_of_previously_posted_projects</code>	Number of project applications previously submitted by the same teacher. Example: 2

* See the section **Notes on the Essay Data** for more details about these features.

Additionally, the `resources.csv` data set provides more data about the resources required for each project. Each line in this file represents a resource required by a project:

Feature	Description
<code>id</code>	A <code>project_id</code> value from the <code>train.csv</code> file. Example: p036502
<code>description</code>	Description of the resource. Example: Tenor Saxophone Reeds, Box of 25
<code>quantity</code>	Quantity of the resource required. Example: 3
<code>price</code>	Price of the resource required. Example: 9.95

Note: Many projects require multiple resources. The `id` value corresponds to a `project_id` in `train.csv`, so you use it as a key to retrieve all resources needed for a project:

The data set contains the following label (the value you will attempt to predict):

Label	Description
<code>project_is_approved</code>	A binary flag indicating whether DonorsChoose approved the project. A value of 0 indicates the project was not approved, and a value of 1 indicates the project was approved.

Notes on the Essay Data

Prior to May 17, 2016, the prompts for the essays were as follows:

- `__project_essay_1__` "Introduce us to your classroom"
- `__project_essay_2__` "Tell us more about your students"
- `__project_essay_3__` "Describe how your students will use the materials you're requesting"
- `__project_essay_3__` "Close by sharing why your project will make a difference"

Starting on May 17, 2016, the number of essays was reduced from 4 to 2, and the prompts for the first 2 essays were changed to the following:

- `__project_essay_1__` "Describe your students: What makes your students special? Specific details about their background, your neighborhood, and your school are all helpful"

your neighborhood, and your school are all helpful.

- `__project_essay_2__` "About your project: How will these materials make a difference in your students' learning and improve their school lives?"

For all projects with `project_submitted_datetime` of 2016-05-17 and later, the values of `project_essay_3` and `project_essay_4` will be NaN.

In [158]:

```
%matplotlib inline
import warnings
warnings.filterwarnings("ignore")

import sqlite3
import pandas as pd
import numpy as np
import nltk
import string
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.feature_extraction.text import TfidfTransformer
from sklearn.feature_extraction.text import TfidfVectorizer

from sklearn.feature_extraction.text import CountVectorizer
from sklearn.metrics import confusion_matrix
from sklearn import metrics
from sklearn.metrics import roc_curve, auc
from nltk.stem.porter import PorterStemmer

import re
# Tutorial about Python regular expressions: https://pymotw.com/2/re/
import string
from nltk.corpus import stopwords
from nltk.stem import PorterStemmer
from nltk.stem.wordnet import WordNetLemmatizer

from gensim.models import Word2Vec
from gensim.models import KeyedVectors
import pickle

from tqdm import tqdm
import os

from plotly import plotly
import plotly.offline as offline
import plotly.graph_objs as go
offline.init_notebook_mode()
from collections import Counter
```

1.1 Reading Data

In [159]:

```
project_data = pd.read_csv('train_data.csv')
resource_data = pd.read_csv('resources.csv')
```

In [160]:

```
print("Number of data points in train data", project_data.shape)
print('-'*50)
print("The attributes of data :", project_data.columns.values)
```

Number of data points in train data (109248, 17)

```
-----
The attributes of data : ['Unnamed: 0' 'id' 'teacher_id' 'teacher_prefix' 'school_state'
 'project_submitted_datetime' 'project_grade_category'
 'project_subject_categories' 'project_subject_subcategories'
 'project_title' 'project_essay_1' 'project_essay_2' 'project_essay_3'
 'project_essay_4' 'project_resource_summary'
 'teacher_number_of_previously_posted_projects' 'project_is_approved']
```

In [161]:

```
print("Number of data points in train data", resource_data.shape)
print(resource_data.columns.values)
resource_data.head(2)
```

Number of data points in train data (1541272, 4)
['id' 'description' 'quantity' 'price']

Out[161]:

	id	description	quantity	price
0	p233245	LC652 - Lakeshore Double-Space Mobile Drying Rack	1	149.00
1	p069063	Bouncy Bands for Desks (Blue support pipes)	3	14.95

In [162]:

```
y = project_data['project_is_approved'].values
project_data.drop(['project_is_approved'], axis=1, inplace=True)
project_data.head(1)
```

Out[162]:

	Unnamed: 0	id	teacher_id	teacher_prefix	school_state	project_submitted_datetime	project_is_approved
0	160221	p253737	c90749f5d961ff158d4b4d1e7dc665fc	Mrs.	IN	2016-12-05 13:43:57	Grade

In [163]:

```
price_data = resource_data.groupby('id').agg({'price': 'sum', 'quantity': 'sum'}).reset_index()
project_data = pd.merge(project_data, price_data, on='id', how='left')
project_data.head(5)
```

Out[163]:

	Unnamed: 0	id	teacher_id	teacher_prefix	school_state	project_submitted_datetime	project_is_approved
0	160221	p253737	c90749f5d961ff158d4b4d1e7dc665fc	Mrs.	IN	2016-12-05 13:43:57	Grade
1	140945	p258326	897464ce9ddc600bced1151f324dd63a	Mr.	FL	2016-10-25 09:22:10	Grade
2	21895	p182444	3465aaf82da834c0582ebd0ef8040ca0	Ms.	AZ	2016-08-31 12:03:56	Grade
3	45	p246581	f3cb9bffbba169bef1a77b243e620b60	Mrs.	KY	2016-10-06 21:16:17	Grade

	Unnamed: 0	id	teacher_id	teacher_prefix	school_state	project_submitted_datetime	pro
4	172407	p104768	be1f7507a41f8479dc06f047086a39ec	Mrs.	TX	2016-07-11 01:10:09	Gra

In [164]:

```
X=project_data
X.head(5)
```

Out[164]:

	Unnamed: 0	id	teacher_id	teacher_prefix	school_state	project_submitted_datetime	pro
0	160221	p253737	c90749f5d961ff158d4b4d1e7dc665fc	Mrs.	IN	2016-12-05 13:43:57	Gra
1	140945	p258326	897464ce9ddc600bcd1151f324dd63a	Mr.	FL	2016-10-25 09:22:10	Gra
2	21895	p182444	3465aaf82da834c0582ebd0ef8040ca0	Ms.	AZ	2016-08-31 12:03:56	Gra
3	45	p246581	f3cb9bffbb1a169bef1a77b243e620b60	Mrs.	KY	2016-10-06 21:16:17	Gra
4	172407	p104768	be1f7507a41f8479dc06f047086a39ec	Mrs.	TX	2016-07-11 01:10:09	Gra

1.2 preprocessing of project_subject_categories

In [165]:

```
categories = list(X['project_subject_categories'].values)
# remove special characters from list of strings python:
https://stackoverflow.com/a/47301924/4084039

# https://www.geeksforgeeks.org/removing-stop-words-nltk-python/
# https://stackoverflow.com/questions/23669024/how-to-strip-a-specific-word-from-a-string
# https://stackoverflow.com/questions/8270092/remove-all-whitespace-in-a-string-in-python
cat_list = []
for i in categories:
    temp = ""
    # consider we have text like this "Math & Science, Warmth, Care & Hunger"
    for j in i.split(','): # it will split it in three parts ["Math & Science", "Warmth", "Care & Hunger"]
        if 'The' in j.split(): # this will split each of the category based on space "Math & Science" => "Math", "&", "Science"
            j=j.replace('The','') # if we have the words "The" we are going to replace it with '' (i.e removing 'The')
            j = j.replace(' ', '') # we are placing all the ' ' (space) with '' (empty) ex: "Math & Science" => "Math&Science"
            temp+=j.strip()+" " # " abc ".strip() will return "abc", remove the trailing spaces
            temp = temp.replace('&','_') # we are replacing the & value into
        cat_list.append(temp.strip())

X['clean_categories'] = cat_list
```

```
X.drop(['project_subject_categories'], axis=1, inplace=True)

from collections import Counter
my_counter = Counter()
for word in project_data['clean_categories'].values:
    my_counter.update(word.split())

cat_dict = dict(my_counter)
sorted_cat_dict = dict(sorted(cat_dict.items(), key=lambda kv: kv[1]))
```

1.3 preprocessing of project_subject_subcategories

In [166]:

```
sub_catogories = list(X['project_subject_subcategories'].values)
# remove special characters from list of strings python:
https://stackoverflow.com/a/47301924/4084039

# https://www.geeksforgeeks.org/removing-stop-words-nltk-python/
# https://stackoverflow.com/questions/23669024/how-to-strip-a-specific-word-from-a-string
# https://stackoverflow.com/questions/8270092/remove-all-whitespace-in-a-string-in-python

sub_cat_list = []
for i in sub_catogories:
    temp = ""
    # consider we have text like this "Math & Science, Warmth, Care & Hunger"
    for j in i.split(','): # it will split it in three parts ["Math & Science", "Warmth", "Care & Hunger"]
        if 'The' in j.split(): # this will split each of the category based on space "Math & Science" => "Math", "&", "Science"
            j=j.replace('The','') # if we have the words "The" we are going to replace it with '' (i.e removing 'The')
            j = j.replace(' ', '') # we are placing all the ' ' (space) with '' (empty) ex: "Math & Science" => "Math&Science"
            temp +=j.strip()+" #" abc ".strip() will return "abc", remove the trailing spaces
            temp = temp.replace('&','_')
        sub_cat_list.append(temp.strip())

X['clean_subcategories'] = sub_cat_list
X.drop(['project_subject_subcategories'], axis=1, inplace=True)

# count of all the words in corpus python: https://stackoverflow.com/a/22898595/4084039
my_counter = Counter()
for word in X['clean_subcategories'].values:
    my_counter.update(word.split())

sub_cat_dict = dict(my_counter)
sorted_sub_cat_dict = dict(sorted(sub_cat_dict.items(), key=lambda kv: kv[1]))
```

1.3 Text preprocessing

In [167]:

```
# merge two column text dataframe:
X["essay"] = X["project_essay_1"].map(str) + \
             X["project_essay_2"].map(str) + \
             X["project_essay_3"].map(str) + \
             X["project_essay_4"].map(str)
```

In [168]:

```
X.head(2)
```

Out[168]:

Unnamed: 0	id	teacher_id	teacher_prefix	school_state	project_submitted_datetime	pro

	Unnamed: 0	id	teacher_id	teacher_prefix	school_state	project_submitted_datetime	pro
0	160221	p253737	c90749f5d961ff158d4b4d1e7dc665fc	Mrs.	IN	2016-12-05 13:43:57	Gra
1	140945	p258326	897464ce9ddc600bcd1151f324dd63a	Mr.	FL	2016-10-25 09:22:10	Gra

In [169]:

```
# printing some random reviews
print(X['essay'].values[0])
print("="*50)
print(X['essay'].values[150])
print("="*50)
print(X['essay'].values[1000])
print("="*50)
print(X['essay'].values[20000])
print("="*50)
```

My students are English learners that are working on English as their second or third languages. We are a melting pot of refugees, immigrants, and native-born Americans bringing the gift of language to our school. \r\n\r\n We have over 24 languages represented in our English Learner program with students at every level of mastery. We also have over 40 countries represented with the families within our school. Each student brings a wealth of knowledge and experiences to us that open our eyes to new cultures, beliefs, and respect.\"The limits of your language are the limits of your world.\"-Ludwig Wittgenstein Our English learner's have a strong support system at home that begs for more resources. Many times our parents are learning to read and speak English alongside of their children. Sometimes this creates barriers for parents to be able to help their child learn phonetics, letter recognition, and other reading skills.\r\n\r\nBy providing these dvd's and players, students are able to continue their mastery of the English language even if no one at home is able to assist. All families with students within the Level 1 proficiency status, will be offered to be a part of this program. These educational videos will be specially chosen by the English Learner Teacher and will be sent home regularly to watch. The videos are to help the child develop early reading skills.\r\n\r\nParents that do not have access to a dvd player will have the opportunity to check out a dvd player to use for the year. The plan is to use these videos and educational dvd's for the years to come for other EL students.\r\nnnnnnn

=====

The 51 fifth grade students that will cycle through my classroom this year all love learning, at least most of the time. At our school, 97.3% of the students receive free or reduced price lunch. Of the 560 students, 97.3% are minority students. \r\nThe school has a vibrant community that loves to get together and celebrate. Around Halloween there is a whole school parade to show off the beautiful costumes that students wear. On Cinco de Mayo we put on a big festival with crafts made by the students, dances, and games. At the end of the year the school hosts a carnival to celebrate the hard work put in during the school year, with a dunk tank being the most popular activity. My students will use these five brightly colored Hokki stools in place of regular, stationary, 4-legged chairs. As I will only have a total of ten in the classroom and not enough for each student to have an individual one, they will be used in a variety of ways. During independent reading time they will be used as special chairs students will each use on occasion. I will utilize them in place of chairs at my small group tables during math and reading times. The rest of the day they will be used by the students who need the highest amount of movement in their life in order to stay focused on school.\r\n\r\nWhenever asked what the classroom is missing, my students always say more Hokki Stools. They can't get their fill of the 5 stools we already have. When the students are sitting in group with me on the Hokki Stools, they are always moving, but at the same time doing their work. Anytime the students get to pick where they can sit, the Hokki Stools are the first to be taken. There are always students who head over to the kidney table to get one of the stools who are disappointed as there are not enough of them. \r\n\r\nWe ask a lot of students to sit for 7 hours a day. The Hokki stools will be a compromise that allow my students to do desk work and move at the same time. These stools will help students to meet their 60 minutes a day of movement by allowing them to activate their core muscles for balance while they sit. For many of my students, these chairs will take away the barrier that exists in schools for a child who can't sit still.nnnnn

=====

How do you remember your days of school? Was it in a sterile environment with plain walls, rows of desks, and a teacher in front of the room? A typical day in our room is nothing like that. I work hard to create a warm inviting themed room for my students look forward to coming to each day.\r\n\r\nMv class is made up of 28 wonderfully unique boys and girls of mixed races in

Arkansas.\r\nThey attend a Title I school, which means there is a high enough percentage of free and reduced-price lunch to qualify. Our school is an \"open classroom\" concept, which is very unique as there are no walls separating the classrooms. These 9 and 10 year-old students are very eager learners; they are like sponges, absorbing all the information and experiences and keep on wanting more. With these resources such as the comfy red throw pillows and the whimsical nautical hanging decor and the blue fish nets, I will be able to help create the mood in our classroom setting to be one of a themed nautical environment. Creating a classroom environment is very important in the success in each and every child's education. The nautical photo props will be used with each child as they step foot into our classroom for the first time on Meet the Teacher evening. I'll take pictures of each child with them, have them developed, and then hung in our classroom ready for their first day of 4th grade. This kind gesture will set the tone before even the first day of school! The nautical thank you cards will be used throughout the year by the students as they create thank you cards to their team groups.\r\n\r\nYour generous donations will help me to help make our classroom a fun, inviting, learning environment from day one.\r\n\r\nIt costs a lot of money out of my own pocket on resources to get our classroom ready. Please consider helping with this project to make our new school year a very successful one. Thank you!nannan

My kindergarten students have varied disabilities ranging from speech and language delays, cognitive delays, gross/fine motor delays, to autism. They are eager beavers and always strive to work their hardest working past their limitations. \r\n\r\nThe materials we have are the ones I seek out for my students. I teach in a Title I school where most of the students receive free or reduced price lunch. Despite their disabilities and limitations, my students love coming to school and come eager to learn and explore. Have you ever felt like you had ants in your pants and you needed to groove and move as you were in a meeting? This is how my kids feel all the time. They want to be able to move as they learn or so they say. Wobble chairs are the answer and I love them because they develop their core, which enhances gross motor and in turn fine motor skills. \r\nThey also want to learn through games, my kids don't want to sit and do worksheets. They want to learn to count by jumping and playing. Physical engagement is the key to our success. The number toss and color and shape mats can make that happen. My students will forget they are doing work and just have the fun a 6 year old deserves.nannan

In [170]:

```
# https://stackoverflow.com/a/47091490/4084039
import re

def decontracted(phrase):
    # specific
    phrase = re.sub(r"won't", "will not", phrase)
    phrase = re.sub(r"can't", "can not", phrase)

    # general
    phrase = re.sub(r"n't", " not", phrase)
    phrase = re.sub(r"'re", " are", phrase)
    phrase = re.sub(r"'s", " is", phrase)
    phrase = re.sub(r"'d", " would", phrase)
    phrase = re.sub(r"'ll", " will", phrase)
    phrase = re.sub(r"\t", " not", phrase)
    phrase = re.sub(r"'ve", " have", phrase)
    phrase = re.sub(r"'m", " am", phrase)
    return phrase
```

In [171]:

```
sent = decontracted(X['essay'].values[20000])
print(sent)
print("="*50)
```

My kindergarten students have varied disabilities ranging from speech and language delays, cognitive delays, gross/fine motor delays, to autism. They are eager beavers and always strive to work their hardest working past their limitations. \r\n\r\nThe materials we have are the ones I seek out for my students. I teach in a Title I school where most of the students receive free or reduced price lunch. Despite their disabilities and limitations, my students love coming to school and come eager to learn and explore. Have you ever felt like you had ants in your pants and you needed to groove and move as you were in a meeting? This is how my kids feel all the time. They want to be able to move as they learn or so they say. Wobble chairs are the answer and I love them because they develop their core, which enhances gross motor and in turn fine motor skills. \r\nThey also want to learn through games, my kids do not want to sit and do worksheets. They want to learn to count by jumping and playing. Physical engagement is the key to our success. The number toss and color and shape mats can make that happen. My students will forget they are doing work and just have the fun a 6 year old deserves.nannan

In [172]:

```
# \r \n \t remove from string python: http://texthandler.com/info/remove-line-breaks-python/
sent = sent.replace('\\r', ' ')
sent = sent.replace('\\n', ' ')
sent = sent.replace('\\t', ' ')
print(sent)
```

My kindergarten students have varied disabilities ranging from speech and language delays, cognitive delays, gross/fine motor delays, to autism. They are eager beavers and always strive to work their hardest working past their limitations. The materials we have are the ones I seek out for my students. I teach in a Title I school where most of the students receive free or reduced price lunch. Despite their disabilities and limitations, my students love coming to school and come eager to learn and explore. Have you ever felt like you had ants in your pants and you needed to groove and move as you were in a meeting? This is how my kids feel all the time. The want to be able to move as they learn or so they say. Wobble chairs are the answer and I love them because they develop their core, which enhances gross motor and in turn fine motor skills. They also want to learn through games, my kids do not want to sit and do worksheets. They want to learn to count by jumping and playing. Physical engagement is the key to our success. The number toss and color and shape mats can make that happen. My students will forget they are doing work and just have the fun a 6 year old deserves. nan

In [173]:

```
# remove spacial character: https://stackoverflow.com/a/5843547/4084039
sent = re.sub('[^A-Za-z0-9]+', ' ', sent)
print(sent)
```

My kindergarten students have varied disabilities ranging from speech and language delays cognitive delays gross fine motor delays to autism They are eager beavers and always strive to work their hardest working past their limitations The materials we have are the ones I seek out for my students I teach in a Title I school where most of the students receive free or reduced price lunch Despite their disabilities and limitations my students love coming to school and come eager to learn and explore Have you ever felt like you had ants in your pants and you needed to groove and move as you were in a meeting This is how my kids feel all the time The want to be able to move as they learn or so they say Wobble chairs are the answer and I love them because they develop their core which enhances gross motor and in turn fine motor skills They also want to learn through games my kids do not want to sit and do worksheets They want to learn to count by jumping and playing Physical engagement is the key to our success The number toss and color and shape mats can make that happen My students will forget they are doing work and just have the fun a 6 year old deserves nan

In [174]:

```
# https://gist.github.com/sebleier/554280
# we are removing the words from the stop words list: 'no', 'nor', 'not'
stopwords= ['i', 'me', 'my', 'myself', 'we', 'our', 'ours', 'ourselves', 'you', "you're", "you've", \
            'you'll', "you'd", 'your', 'yours', 'yourself', 'yourselves', 'he', 'him', 'his', \
            'himself', \
            'she', "she's", 'her', 'hers', 'herself', 'it', "it's", 'its', 'itself', 'they', 'them', \
            'their', \
            'theirs', 'themselves', 'what', 'which', 'who', 'whom', 'this', 'that', "that'll", \
            'these', 'those', \
            'am', 'is', 'are', 'was', 'were', 'be', 'been', 'being', 'have', 'has', 'had', 'having', \
            'do', 'does', \
            'did', 'doing', 'a', 'an', 'the', 'and', 'but', 'if', 'or', 'because', 'as', 'until', \
            'while', 'of', \
            'at', 'by', 'for', 'with', 'about', 'against', 'between', 'into', 'through', 'during', \
            'before', 'after', \
            'above', 'below', 'to', 'from', 'up', 'down', 'in', 'out', 'on', 'off', 'over', 'under', \
            'again', 'further', \
            'then', 'once', 'here', 'there', 'when', 'where', 'why', 'how', 'all', 'any', 'both', 'each', \
            'few', 'more', \
            'most', 'other', 'some', 'such', 'only', 'own', 'same', 'so', 'than', 'too', 'very', \
            's', 't', 'can', 'will', 'just', 'don', "don't", 'should', "should've", 'now', 'd', 'll', \
            'm', 'o', 're', \
            've', 'y', 'ain', 'aren', "aren't", 'couldn', "couldn't", 'didn', "didn't", 'doesn', "doesn't", 'hadn', \
            'hadn't', 'hasn', "hasn't", 'haven', "haven't", 'isn', "isn't", 'ma', 'mightn', \
            'mightn't', 'mustn', \
            'mustn't', 'needn', "needn't", 'shan', "shan't", 'shouldn', "shouldn't", 'wasn', \
            "wasn't", 'weren', "weren't", \
```

```
'won', 'won't', 'wouldn', 'wouldn't']
```

In [175]:

```
# Combining all the above stundents
from tqdm import tqdm
preprocessed_essays = []
# tqdm is for printing the status bar
for sentence in tqdm(X['essay'].values):
    sent = decontracted(sentence)
    sent = sent.replace('\\r', ' ')
    sent = sent.replace('\\\"', ' ')
    sent = sent.replace('\\n', ' ')
    sent = re.sub('[^A-Za-z0-9]+', ' ', sent)
    # https://gist.github.com/sebleier/554280
    sent = ' '.join(e for e in sent.split() if e not in stopwords)
    preprocessed_essays.append(sent.lower().strip())
```

```
100%|████████████████████████████████████████████████████████████████████████████████| 109248/109248
[00:57<00:00, 1900.56it/s]
```

In [176]:

```
# after preprocesing
preprocessed_essays[20000]
```

Out[176]:

'my kindergarten students varied disabilities ranging speech language delays cognitive delays gross fine motor delays autism they eager beavers always strive work hardest working past limitations the materials ones i seek students i teach title i school students receive free reduced price lunch despite disabilities limitations students love coming school come eager learn explore have ever felt like ants pants needed groove move meeting this kids feel time the want able move learn say wobble chairs answer i love develop core enhances gross motor turn fine motor skills they also want learn games kids not want sit worksheets they want learn count jumping playing physical engagement key success the number toss color shape mats make happen my students forget work fun 6 year old de serves nannan'

1.4 Preprocessing of `project_title`

In [177]:

```
# Displaying first two datasets
X.head(2)
```

Out[177]:

	Unnamed: 0	id	teacher_id	teacher_prefix	school_state	project_submitted_datetime	project_title
0	160221	p253737	c90749f5d961ff158d4b4d1e7dc665fc	Mrs.	IN	2016-12-05 13:43:57	Grade 1 Math
1	140945	p258326	897464ce9ddc600bcd1151f324dd63a	Mr.	FL	2016-10-25 09:22:10	Grade 1 Math

In [178]:

```
# printing some random project titles.
print(X['project_title'].values[0])
print("="*50)
print(X['project_title'].values[150])
print("="*50)
print(X['project_title'].values[1000])
print("="*50)
```

```
Educational Support for English Learners at Home
=====
More Movement with Hokki Stools
=====
Sailing Into a Super 4th Grade Year
=====
```

In [179]:

```
# https://stackoverflow.com/a/47091490/4084039
import re

def decontracted(phrase):
    # specific
    phrase = re.sub(r"won't", "will not", phrase)    #re represents regular expression
    phrase = re.sub(r"can't", "can not", phrase)    #sub represents substate

    # general
    phrase = re.sub(r"n't", " not", phrase)
    phrase = re.sub(r"\ 're", " are", phrase)
    phrase = re.sub(r"\ 's", " is", phrase)
    phrase = re.sub(r"\ 'd", " would", phrase)
    phrase = re.sub(r"\ 'll", " will", phrase)
    phrase = re.sub(r"\ 't", " not", phrase)
    phrase = re.sub(r"\ 've", " have", phrase)
    phrase = re.sub(r"\ 'm", " am", phrase)
    return phrase
```

In [180]:

```
sent = decontracted(X['project_title'].values[20000])
print(sent)
print("="*50)
```

```
We Need To Move It While We Input It!
=====
```

In [181]:

```
# \r \n \t remove from string python: http://texthandler.com/info/remove-line-breaks-python/
sent = sent.replace('\r', ' ')
sent = sent.replace('\n', ' ')
sent = sent.replace('\t', ' ')
print(sent)
```

```
We Need To Move It While We Input It!
```

In [182]:

```
#remove spacial character and converting to lowercase: https://stackoverflow.com/a/5843547/4084039
sent = re.sub('[^A-Za-z0-9]+', ' ', sent).lower()
print(sent)
```

```
we need to move it while we input it
```

In [183]:

```
# https://gist.github.com/sebleier/554280
# we are removing the words from the stop words list: 'no', 'nor', 'not'
stopwords= ['i', 'me', 'my', 'myself', 'we', 'our', 'ours', 'ourselves', 'you', "you're", "you've",
\
```

```
'you'll', 'you'd', 'your', 'yours', 'yourself', 'yourselves', 'he', 'him', 'his',
'himself', \
'she', 'she's', 'her', 'hers', 'herself', 'it', 'it's', 'its', 'itself', 'they', 'them',
'their', \
'theirs', 'themselves', 'what', 'which', 'who', 'whom', 'this', 'that', 'that'll',
'these', 'those', \
'am', 'is', 'are', 'was', 'were', 'be', 'been', 'being', 'have', 'has', 'had', 'having',
'do', 'does', \
'did', 'doing', 'a', 'an', 'the', 'and', 'but', 'if', 'or', 'because', 'as', 'until', '
while', 'of', \
'at', 'by', 'for', 'with', 'about', 'against', 'between', 'into', 'through', 'during',
'before', 'after', \
'above', 'below', 'to', 'from', 'up', 'down', 'in', 'out', 'on', 'off', 'over', 'under'
, 'again', 'further', \
'then', 'once', 'here', 'there', 'when', 'where', 'why', 'how', 'all', 'any', 'both', 'e
ach', 'few', 'more', \
'most', 'other', 'some', 'such', 'only', 'own', 'same', 'so', 'than', 'too', 'very', \
's', 't', 'can', 'will', 'just', 'don', 'don't', 'should', 'should've', 'now', 'd', 'll'
, 'm', 'o', 're', \
've', 'y', 'ain', 'aren', 'aren't', 'couldn', 'couldn't', 'didn', 'didn't', 'doesn', 'do
esn't', 'hadn', \
'hadn't', 'hasn', 'hasn't', 'haven', 'haven't', 'isn', 'isn't', 'ma', 'mightn',
'mightn't', 'mustn', \
'mustn't', 'needn', 'needn't', 'shan', 'shan't', 'shouldn', 'shouldn't', 'wasn',
'wasn't', 'weren', 'weren't', \
'won', 'won't', 'wouldn', 'wouldn't']
```

In [184]:

```
sent = ' '.join(e for e in sent.split() if e not in stopwords)
print(sent)
```

need move input

In [185]:

```
# Combining all the above statemennts
from tqdm import tqdm
preprocessed_project_titles = []
# tqdm is for printing the status bar
for sentence in tqdm(X['project_title'].values):
    sent = decontracted(sentence)
    sent = sent.replace('\\r', ' ')
    sent = sent.replace('\\\"', ' ')
    sent = sent.replace('\\n', ' ')
    sent = re.sub('[^A-Za-z0-9]+', ' ', sent).lower()
    # https://gist.github.com/sebleier/554280
    sent = ' '.join(e for e in sent.split() if e not in stopwords)
    preprocessed_project_titles.append(sent.lower().strip())
```

```
100%|████████████████████████████████████████████████████████████████████████████████| 109248/109248
[00:02<00:00, 45274.84it/s]
```

In [186]:

```
# after preprocesing
preprocessed_project_titles[20000]
```

Out[186]:

'need move input'

2. Splitting Data

Splitting data into Train and cross validation(or test): Stratified Sampling

In [187]:

```
# train test split
from sklearn.model_selection import train_test_split
```

```

from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.33, stratify=y)
X_train, X_cv, y_train, y_cv = train_test_split(X_train, y_train, test_size=0.33, stratify=y_train)

```

1.5 Preparing data for models

In [31]:

```
X.columns
```

Out[31]:

```

Index(['Unnamed: 0', 'id', 'teacher_id', 'teacher_prefix', 'school_state',
      'project_submitted_datetime', 'project_grade_category', 'project_title',
      'project_essay_1', 'project_essay_2', 'project_essay_3',
      'project_essay_4', 'project_resource_summary',
      'teacher_number_of_previously_posted_projects', 'price', 'quantity',
      'clean_categories', 'clean_subcategories', 'essay'],
      dtype='object')

```

we are going to consider

- school_state : categorical data
- clean_categories : categorical data
- clean_subcategories : categorical data
- project_grade_category : categorical data
- teacher_prefix : categorical data
- project_title : text data
- text : text data
- project_resource_summary: text data (optinal)
- quantity : numerical (optinal)
- teacher_number_of_previously_posted_projects : numerical
- price : numerical

1.5.1 Vectorizing Categorical data

- <https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/handling-categorical-and-numerical-features/>

In [32]:

```

vectorizer = CountVectorizer()
vectorizer.fit(X_train['school_state'].values) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_state_ohe = vectorizer.transform(X_train['school_state'].values)
X_cv_state_ohe = vectorizer.transform(X_cv['school_state'].values)
X_test_state_ohe = vectorizer.transform(X_test['school_state'].values)

print("After vectorizations")
print(X_train_state_ohe.shape, y_train.shape)
print(X_cv_state_ohe.shape, y_cv.shape)
print(X_test_state_ohe.shape, y_test.shape)
print(vectorizer.get_feature_names())
print("="*100)

```

```

After vectorizations
(49041, 51) (49041,)
(24155, 51) (24155,)
(36052, 51) (36052,)
['ak', 'al', 'ar', 'az', 'ca', 'co', 'ct', 'dc', 'de', 'fl', 'ga', 'hi', 'ia', 'id', 'il', 'in', 'k
s', 'ky', 'la', 'ma', 'md', 'me', 'mi', 'mn', 'mo', 'ms', 'mt', 'nc', 'nd', 'ne', 'nh', 'nj', 'nm',
'nv', 'ny', 'oh', 'ok', 'or', 'pa', 'ri', 'sc', 'sd', 'tn', 'tx', 'ut', 'va', 'vt', 'wa', 'wi', 'wv
', 'wy']
=====

```

In [33]:

```
X_train['teacher_prefix'].fillna(value='Teacher',inplace=True)
X_cv['teacher_prefix'].fillna(value='Teacher',inplace=True)
X_test['teacher_prefix'].fillna(value='Teacher',inplace=True)
vectorizer = CountVectorizer()
vectorizer.fit(X_train['teacher_prefix'].values) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_teacher_ohe = vectorizer.transform(X_train['teacher_prefix'].values)
X_cv_teacher_ohe = vectorizer.transform(X_cv['teacher_prefix'].values)
X_test_teacher_ohe = vectorizer.transform(X_test['teacher_prefix'].values)

print("After vectorizations")
print(X_train_teacher_ohe.shape, y_train.shape)
print(X_cv_teacher_ohe.shape, y_cv.shape)
print(X_test_teacher_ohe.shape, y_test.shape)
print(vectorizer.get_feature_names())
print("="*100)
```

```
After vectorizations
(49041, 5) (49041,)
(24155, 5) (24155,)
(36052, 5) (36052,)
['dr', 'mr', 'mrs', 'ms', 'teacher']
=====
```

In [34]:

```
vectorizer = CountVectorizer()
vectorizer.fit(X_train['project_grade_category'].values) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_grade_ohe = vectorizer.transform(X_train['project_grade_category'].values)
X_cv_grade_ohe = vectorizer.transform(X_cv['project_grade_category'].values)
X_test_grade_ohe = vectorizer.transform(X_test['project_grade_category'].values)

print("After vectorizations")
print(X_train_grade_ohe.shape, y_train.shape)
print(X_cv_grade_ohe.shape, y_cv.shape)
print(X_test_grade_ohe.shape, y_test.shape)
print(vectorizer.get_feature_names())
print("="*100)
```

```
After vectorizations
(49041, 3) (49041,)
(24155, 3) (24155,)
(36052, 3) (36052,)
['12', 'grades', 'prek']
=====
```

In [35]:

```
vectorizer = CountVectorizer()
vectorizer.fit(X_train['clean_categories'].values) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_category_ohe = vectorizer.transform(X_train['clean_categories'].values)
X_cv_category_ohe = vectorizer.transform(X_cv['clean_categories'].values)
X_test_category_ohe = vectorizer.transform(X_test['clean_categories'].values)

print("After vectorizations")
print(X_train_category_ohe.shape, y_train.shape)
print(X_cv_category_ohe.shape, y_cv.shape)
print(X_test_category_ohe.shape, y_test.shape)
print(vectorizer.get_feature_names())
print("="*100)
```

```
After vectorizations
(49041, 9) (49041,)
```

```
(24155, 9) (24155,)
(36052, 9) (36052,)
['appliedlearning', 'care_hunger', 'health_sports', 'history_civics', 'literacy_language',
'math_science', 'music_arts', 'specialneeds', 'warmth']
=====
```

In [36]:

```
vectorizer = CountVectorizer()
vectorizer.fit(X_train['clean_subcategories'].values) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_subcategory_ohe = vectorizer.transform(X_train['clean_subcategories'].values)
X_cv_subcategory_ohe = vectorizer.transform(X_cv['clean_subcategories'].values)
X_test_subcategory_ohe = vectorizer.transform(X_test['clean_subcategories'].values)

print("After vectorizations")
print(X_train_subcategory_ohe.shape, y_train.shape)
print(X_cv_subcategory_ohe.shape, y_cv.shape)
print(X_test_subcategory_ohe.shape, y_test.shape)
print(vectorizer.get_feature_names())
print("="*100)
```

```
After vectorizations
(49041, 30) (49041,)
(24155, 30) (24155,)
(36052, 30) (36052,)
['appliedsciences', 'care_hunger', 'charactereducation', 'civics_government',
'college_careerprep', 'communityservice', 'earlydevelopment', 'economics', 'environmentalscience',
'esl', 'extracurricular', 'financialliteracy', 'foreignlanguages', 'gym_fitness',
'health_lifescience', 'health_wellness', 'history_geography', 'literacy', 'literature_writing', 'm
athematics', 'music', 'nutritioneducation', 'other', 'parentinvolvement', 'performingarts', 'socia
lsciences', 'specialneeds', 'teamsports', 'visualarts', 'warmth']
=====
```

1.5.2 Vectorizing Text data

1.5.2.1 Bag of words

In [118]:

```
print(X_train.shape, y_train.shape)
print(X_cv.shape, y_cv.shape)
print(X_test.shape, y_test.shape)

print("="*100)

from sklearn.feature_extraction.text import CountVectorizer
vectorizer_essay = CountVectorizer(min_df=10, ngram_range=(1,4), max_features=15000)
vectorizer_essay.fit(X_train['essay'].values) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_essay_bow = vectorizer_essay.transform(X_train['essay'].values)
X_cv_essay_bow = vectorizer_essay.transform(X_cv['essay'].values)
X_test_essay_bow = vectorizer_essay.transform(X_test['essay'].values)

print("After vectorizations")
print(X_train_essay_bow.shape, y_train.shape)
print(X_cv_essay_bow.shape, y_cv.shape)
print(X_test_essay_bow.shape, y_test.shape)
print("="*100)
```

```
(49041, 19) (49041,)
(24155, 19) (24155,)
(36052, 19) (36052,)
=====
```

After vectorizations

```
(49041, 15000) (49041,)
(24155, 15000) (24155,)
(36052, 15000) (36052,)
=====
```

In [121]:

```
print(X_train.shape, y_train.shape)
print(X_cv.shape, y_cv.shape)
print(X_test.shape, y_test.shape)

print("="*100)

from sklearn.feature_extraction.text import CountVectorizer
vectorizer_title = CountVectorizer(min_df=10,ngram_range=(1,4),max_features=5000)
vectorizer_title.fit(X_train['project_title'].values) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_title_bow = vectorizer_title.transform(X_train['project_title'].values)
X_cv_title_bow = vectorizer_title.transform(X_cv['project_title'].values)
X_test_title_bow = vectorizer_title.transform(X_test['project_title'].values)

print("After vectorizations")
print(X_train_title_bow.shape, y_train.shape)
print(X_cv_title_bow.shape, y_cv.shape)
print(X_test_title_bow.shape, y_test.shape)
print("="*100)
```

```
(49041, 19) (49041,)
(24155, 19) (24155,)
(36052, 19) (36052,)
=====
```

After vectorizations

```
(49041, 5000) (49041,)
(24155, 5000) (24155,)
(36052, 5000) (36052,)
=====
```

1.5.2.2 TFIDF vectorizer

In [188]:

```
print(X_train.shape, y_train.shape)
print(X_cv.shape, y_cv.shape)
print(X_test.shape, y_test.shape)

print("="*100)

from sklearn.feature_extraction.text import TfidfVectorizer
vectorizer_essay = TfidfVectorizer(min_df=10,ngram_range=(1,4),max_features=15000)
vectorizer_essay.fit(X_train['essay'].values) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_essay_tfidf = vectorizer_essay.transform(X_train['essay'].values)
X_cv_essay_tfidf = vectorizer_essay.transform(X_cv['essay'].values)
X_test_essay_tfidf = vectorizer_essay.transform(X_test['essay'].values)

print("After vectorizations")
print(X_train_essay_tfidf.shape, y_train.shape)
print(X_cv_essay_tfidf.shape, y_cv.shape)
print(X_test_essay_tfidf.shape, y_test.shape)
print("="*100)
```

```
(49041, 19) (49041,)
(24155, 19) (24155,)
(36052, 19) (36052,)
=====
```

After vectorizations


```
(49041, 15000) (49041,)
(24155, 15000) (24155,)
(36052, 15000) (36052,)
=====
```

In [138]:

```
print(X_train.shape, y_train.shape)
print(X_cv.shape, y_cv.shape)
print(X_test.shape, y_test.shape)

print("="*100)

from sklearn.feature_extraction.text import TfidfVectorizer
vectorizer_title = TfidfVectorizer(min_df=10, ngram_range=(1,4), max_features=5000)
vectorizer_title.fit(X_train['project_title'].values) # fit has to happen only on train data

# we use the fitted CountVectorizer to convert the text to vector
X_train_title_tfidf = vectorizer_title.transform(X_train['project_title'].values)
X_cv_title_tfidf = vectorizer_title.transform(X_cv['project_title'].values)
X_test_title_tfidf = vectorizer_title.transform(X_test['project_title'].values)

print("After vectorizations")
print(X_train_title_tfidf.shape, y_train.shape)
print(X_cv_title_tfidf.shape, y_cv.shape)
print(X_test_title_tfidf.shape, y_test.shape)
print("="*100)
```

```
(49041, 19) (49041,)
(24155, 19) (24155,)
(36052, 19) (36052,)
=====
```

```
After vectorizations
(49041, 5000) (49041,)
(24155, 5000) (24155,)
(36052, 5000) (36052,)
=====
```

1.5.3 Vectorizing Numerical features

In [122]:

```
from sklearn.preprocessing import Normalizer
normalizer = Normalizer()
# normalizer.fit(X_train['price'].values)
# this will rise an error Expected 2D array, got 1D array instead:
# array=[105.22 215.96 96.01 ... 368.98 80.53 709.67].
# Reshape your data either using
# array.reshape(-1, 1) if your data has a single feature
# array.reshape(1, -1) if it contains a single sample.
normalizer.fit(X_train['price'].values.reshape(-1,1))

X_train_price_norm = normalizer.transform(X_train['price'].values.reshape(-1,1))
X_cv_price_norm = normalizer.transform(X_cv['price'].values.reshape(-1,1))
X_test_price_norm = normalizer.transform(X_test['price'].values.reshape(-1,1))

print("After vectorizations")
print(X_train_price_norm.shape, y_train.shape)
print(X_cv_price_norm.shape, y_cv.shape)
print(X_test_price_norm.shape, y_test.shape)
print("="*100)
```

```
After vectorizations
(49041, 1) (49041,)
(24155, 1) (24155,)
(36052, 1) (36052,)
=====
```

In [123]:

```
from sklearn.preprocessing import Normalizer
normalizer = Normalizer()
# normalizer.fit(X_train['price'].values)
# this will rise an error Expected 2D array, got 1D array instead:
# array=[105.22 215.96 96.01 ... 368.98 80.53 709.67].
# Reshape your data either using
# array.reshape(-1, 1) if your data has a single feature
# array.reshape(1, -1) if it contains a single sample.
normalizer.fit(X_train['teacher_number_of_previously_posted_projects'].values.reshape(-1,1))

X_train_teacher_norm = normalizer.transform(X_train['teacher_number_of_previously_posted_projects'].values.reshape(-1,1))
X_cv_teacher_norm = normalizer.transform(X_cv['teacher_number_of_previously_posted_projects'].values.reshape(-1,1))
X_test_teacher_norm = normalizer.transform(X_test['teacher_number_of_previously_posted_projects'].values.reshape(-1,1))

print("After vectorizations")
print(X_train_teacher_norm.shape, y_train.shape)
print(X_cv_teacher_norm.shape, y_cv.shape)
print(X_test_teacher_norm.shape, y_test.shape)
print("=="*100)
```

After vectorizations

```
(49041, 1) (49041,)
(24155, 1) (24155,)
(36052, 1) (36052,)
```

In [124]:

```
from sklearn.preprocessing import Normalizer
normalizer = Normalizer()
# normalizer.fit(X_train['price'].values)
# this will rise an error Expected 2D array, got 1D array instead:
# array=[105.22 215.96 96.01 ... 368.98 80.53 709.67].
# Reshape your data either using
# array.reshape(-1, 1) if your data has a single feature
# array.reshape(1, -1) if it contains a single sample.
normalizer.fit(X_train['quantity'].values.reshape(-1,1))

X_train_quantity_norm = normalizer.transform(X_train['quantity'].values.reshape(-1,1))
X_cv_quantity_norm = normalizer.transform(X_cv['quantity'].values.reshape(-1,1))
X_test_quantity_norm = normalizer.transform(X_test['quantity'].values.reshape(-1,1))

print("After vectorizations")
print(X_train_quantity_norm.shape, y_train.shape)
print(X_cv_quantity_norm.shape, y_cv.shape)
print(X_test_quantity_norm.shape, y_test.shape)
print("=="*100)
```

After vectorizations

```
(49041, 1) (49041,)
(24155, 1) (24155,)
(36052, 1) (36052,)
```

1.5.4 Merging all the above features

- we need to merge all the numerical vectors i.e catogorical, text, numerical vectors

Merging features for BOW

In [125]:

```
# merge two sparse matrices: https://stackoverflow.com/a/19710648/4084039
from scipy.sparse import hstack
X_tr = hstack((X_train_essay_bow,X_train_title_bow, X_train_state_ohc, X_train_teacher_ohc,
X_train_grade_ohc,X_train_category_ohc,X_train_subcategory_ohc,X_train_price_norm,X_train_teacher_norm,X_train_quantity_norm)).tocsr()
X_cr = hstack((X_cv_essay_bow,X_cv_title_bow, X_cv_state_ohc, X_cv_teacher_ohc, X_cv_grade_ohc,X_cv_category_ohc,X_cv_subcategory_ohc,X_cv_price_norm,X_cv_teacher_norm,X_cv_quantity_norm)).tocsr()
X_te = hstack((X_test_essay_bow, X_test_title_bow,X_test_state_ohc, X_test_teacher_ohc, X_test_grade_ohc,X_test_category_ohc,X_test_subcategory_ohc,X_test_quantity_norm,X_test_teacher_norm,X_test_quantity_norm)).tocsr()

print("Final Data matrix")
print(X_tr.shape, y_train.shape)
print(X_cr.shape, y_cv.shape)
print(X_te.shape, y_test.shape)
print("="*100)
```

```
Final Data matrix
(49041, 20101) (49041,)
(24155, 20101) (24155,)
(36052, 20101) (36052,)
=====
```

Merging features for TFIDF

In [139]:

```
# merge two sparse matrices: https://stackoverflow.com/a/19710648/4084039
from scipy.sparse import hstack
X2_tr = hstack((X_train_essay_tfidf,X_train_title_tfidf, X_train_state_ohc, X_train_teacher_ohc, X_train_grade_ohc,X_train_category_ohc,X_train_subcategory_ohc,X_train_price_norm,X_train_teacher_norm,X_train_quantity_norm)).tocsr()
X2_cr = hstack((X_cv_essay_tfidf,X_cv_title_tfidf, X_cv_state_ohc, X_cv_teacher_ohc, X_cv_grade_ohc,X_cv_category_ohc,X_cv_subcategory_ohc,X_cv_price_norm,X_cv_teacher_norm,X_cv_quantity_norm)).tocsr()
X2_te = hstack((X_test_essay_tfidf, X_test_title_tfidf,X_test_state_ohc, X_test_teacher_ohc, X_test_grade_ohc,X_test_category_ohc,X_test_subcategory_ohc,X_test_quantity_norm,X_test_teacher_norm,X_test_quantity_norm)).tocsr()

print("Final Data matrix")
print(X2_tr.shape, y_train.shape)
print(X2_cr.shape, y_cv.shape)
print(X2_te.shape, y_test.shape)
print("="*100)
```

```
Final Data matrix
(49041, 20101) (49041,)
(24155, 20101) (24155,)
(36052, 20101) (36052,)
=====
```

2. Naive Bayes

2.4.1 Applying Naive Bayes on BOW, SET 1

In [92]:

```
# https://scikit-learn.org/stable/modules/generated/sklearn.model_selection.GridSearchCV.html
from sklearn.model_selection import GridSearchCV
from sklearn.naive_bayes import MultinomialNB

naive = MultinomialNB()
parameters = {'alpha':[10**-4,10**-3,10**-2,10**-1,10**0,10**1,10**2,10**3,10**4]}
clf = GridSearchCV(naive, parameters, cv=2, scoring='roc_auc')
clf.fit(X_tr, y_train)

train_auc= clf.cv_results_['mean_train_score']
test_auc= clf.cv_results_['mean_test_score']
```

```

train_auc_std= clf.cv_results_['std_train_score']
cv_auc = clf.cv_results_['mean_test_score']
cv_auc_std= clf.cv_results_['std_test_score']


plt.plot(parameters['alpha'], train_auc, label='Train AUC')
# this code is copied from here: https://stackoverflow.com/a/48803361/4084039
plt.gca().fill_between(parameters['alpha'],train_auc - train_auc_std,train_auc +
train_auc_std,alpha=0.2,color='darkblue')

plt.plot(parameters['alpha'], cv_auc, label='CV AUC')
# this code is copied from here: https://stackoverflow.com/a/48803361/4084039
plt.gca().fill_between(parameters['alpha'],cv_auc - cv_auc_std,cv_auc + cv_auc_std,alpha=0.2,color=
'darkorange')

plt.scatter(parameters['alpha'], train_auc, label='Train AUC points')
plt.scatter(parameters['alpha'], cv_auc, label='CV AUC points')
plt.xscale("log")

plt.legend()
plt.xlabel("K: hyperparameter")
plt.ylabel("AUC")
plt.title("ERROR PLOTS")
plt.grid()
plt.show()

```



- The best value of alpha obtained from the plot is 1.

In [127]:

```

#calculating the best score
clf.best_score_

```

Out[127]:

```
0.6934215020857804
```

In [128]:

```

#calculating the best alpha parameter value
clf.best_params_

```

Out[128]:

```
{'alpha': 1}
```

In [129]:

```
best_alpha=1
```

In [130]:

```

def batch_predict(clf, data):
    # roc_auc_score(y_true, y_score) the 2nd parameter should be probability estimates of the posi
    tive class

```

```

# not the predicted outputs

y_data_pred = []
tr_loop = data.shape[0] - data.shape[0]%1000
# consider you X_tr shape is 49041, then your cr_loop will be 49041 - 49041%1000 = 49000
# in this for loop we will iterate until the last 1000 multiplier
for i in range(0, tr_loop, 1000):
    y_data_pred.extend(clf.predict_proba(data[i:i+1000])[:,1])
# we will be predicting for the last data points
y_data_pred.extend(clf.predict_proba(data[tr_loop:])[:,1])

return y_data_pred

```

In [131]:

```

# we are writing our own function for predict, with defined threshold
# we will pick a threshold that will give the least fpr
def predict(proba, threshold, fpr, tpr):

    t = threshold[np.argmax(fpr*(1-tpr))]

    # (tpr*(1-fpr)) will be maximum if your fpr is very low and tpr is very high

    print("the maximum value of tpr*(1-fpr)", max(tpr*(1-fpr)), "for threshold", np.round(t,3))
    predictions = []
    for i in proba:
        if i>=t:
            predictions.append(1)
        else:
            predictions.append(0)
    return predictions

```

In [98]:

```

# https://scikit-learn.org/stable/modules/generated/sklearn.metrics.roc_curve.html#sklearn.metrics.roc_curve
from sklearn.metrics import roc_curve, auc
import matplotlib.pyplot as plt
from sklearn.naive_bayes import MultinomialNB
from sklearn.metrics import roc_auc_score


clf = MultinomialNB(alpha=best_alpha)
clf.fit(X_tr, y_train)
# roc_auc_score(y_true, y_score) the 2nd parameter should be probability estimates of the positive class
# not the predicted outputs


y_train_pred = batch_predict(clf, X_tr)
y_test_pred = batch_predict(clf, X_te)

train_fpr, train_tpr, tr_thresholds = roc_curve(y_train, y_train_pred)
test_fpr, test_tpr, te_thresholds = roc_curve(y_test, y_test_pred)

plt.plot(train_fpr, train_tpr, label="train AUC =" + str(auc(train_fpr, train_tpr)))
plt.plot(test_fpr, test_tpr, label="test AUC =" + str(auc(test_fpr, test_tpr)))
plt.legend()
plt.xlabel("Alpha: hyperparameter")
plt.ylabel("AUC")
plt.title("ERROR PLOTS")
plt.grid()
plt.show()

```





- Train AUC is 0.9490
- Test AUC is 0.6798 represent the prediction level on the test dataset. In other words if a data point is provided the probability of classifying it correctly after the training has been done is 67.98 %.

In [133]:

```
print("="*100)
from sklearn.metrics import confusion_matrix
import seaborn as sns
class_label = ["negative", "positive"]


# Reference: https://seaborn.pydata.org/generated/seaborn.heatmap.html
# https://stackoverflow.com/questions/37790429/seaborn-heatmap-using-pandas-dataframe

print("Train confusion matrix")
cm=confusion_matrix(y_train, predict(y_train_pred, tr_thresholds, train_fpr, train_fpr))
df= pd.DataFrame(cm, index = class_label, columns = class_label)
sns.heatmap(df, annot = True, fmt = "d")
plt.title("Confusion Matrix")
plt.xlabel("Predicted Label")
plt.ylabel("True Label")
plt.show()


print("Test confusion matrix")


cm=confusion_matrix(y_test, predict(y_test_pred, tr_thresholds, test_fpr, test_fpr))
df = pd.DataFrame(cm, index = class_label, columns = class_label)
sns.heatmap(df, annot = True, fmt = "d")
plt.title("Confusion Matrix")
plt.xlabel("Predicted Label")
plt.ylabel("True Label")
plt.show()
```

Train confusion matrix
the maximum value of $tpr \cdot (1-fpr)$ 0.25 for threshold 0.008



Test confusion matrix
the maximum value of $tpr \cdot (1-fpr)$ 0.24999999161092998 for threshold 0.593





2.4.1.1 Top 10 important features of positive class from SET 1

In [119]:

```
# Ref:https://stackoverflow.com/questions/50526898/how-to-get-feature-importance-in-naive-bayes
# getting important features by using get_feature_names()
imp_features=vectorizer_essay.get_feature_names()
pos_features=sorted(zip(clf.feature_log_prob_[1],imp_features),reverse=True)[:10]
for log_var,text in pos_features:
    print(log_var,text)
```

```
-6.216113836868047 used to create
-8.03739184136639 my students qualify
-8.186801328423197 these new
-8.235385388378962 books for
-8.242091108187365 books have
-8.353117576165637 comprised of
-8.377828371765322 school year we
-8.51131782499003 perform
-8.555409118274403 talent
-8.663320683673781 first graders are
```

2.4.1.2 Top 10 important features of negative class from SET 1

In [120]:

```
# Ref:https://stackoverflow.com/questions/50526898/how-to-get-feature-importance-in-naive-bayes
# getting important features by using get_feature_names()
imp_features=vectorizer_essay.get_feature_names()
neg_features=sorted(zip(clf.feature_log_prob_[0],imp_features),reverse=True)[:10]
for log_var,text in neg_features:
    print(log_var,text)
```

```
-6.211348534978423 used to create
-7.998546892013838 my students qualify
-8.19518226882036 these new
-8.317197296111281 books for
-8.325340659244624 books have
-8.36866074343822 comprised of
-8.491727532063301 school year we
-8.50686607891722 talent
-8.584352732396876 in age
-8.683358213231251 perform
```

2.4.2 Applying Naive Bayes on TFIDF, SET 2

In [108]:

```
# https://scikit-learn.org/stable/modules/generated/sklearn.model_selection.GridSearchCV.html
from sklearn.model_selection import GridSearchCV

neigh = MultinomialNB()
parameters = {'alpha':[10**-4,10**-3,10**-2,10**-1,10**0,10**1,10**2,10**3,10**4]}
clf = GridSearchCV(neigh, parameters, cv=2, scoring='roc_auc')
clf.fit(X2_tr, y_train)

train_auc= clf.cv_results_['mean_train_score']
train_auc_std= clf.cv_results_['std_train_score']
cv_auc = clf.cv_results_['mean_test_score']
cv_auc_std= clf.cv_results_['std_test_score']


plt.plot(parameters['alpha'], train_auc, label='Train AUC')
```

```
plt.plot(parameters['alpha'], train_auc, label='Train AUC')
# this code is copied from here: https://stackoverflow.com/a/48803361/4084039
plt.gca().fill_between(parameters['alpha'], train_auc - train_auc_std, train_auc +
train_auc_std, alpha=0.2, color='darkblue')

plt.plot(parameters['alpha'], cv_auc, label='CV AUC')
# this code is copied from here: https://stackoverflow.com/a/48803361/4084039
plt.gca().fill_between(parameters['alpha'], cv_auc - cv_auc_std, cv_auc + cv_auc_std, alpha=0.2, color=
'darkorange')

plt.scatter(parameters['alpha'], train_auc, label='Train AUC points')
plt.scatter(parameters['alpha'], cv_auc, label='CV AUC points')
plt.xscale("log")

plt.legend()
plt.xlabel("K: hyperparameter")
plt.ylabel("AUC")
plt.title("ERROR PLOTS")
plt.grid()
plt.show()
```



- The best value of alpha obtained from the plot is 1.

In [109]:

```
# calculating the best score
clf.best_score_
```

Out[109]:

```
0.661698494669202
```

In [110]:

```
#calculating the best alpha parameter value
clf.best_params_
```

Out[110]:

```
{'alpha': 0.01}
```

In [142]:

```
best_alpha=0.01
```

In [143]:

```
def batch_predict(clf, data):
    # roc_auc_score(y_true, y_score) the 2nd parameter should be probability estimates of the posi
    tive class
    # not the predicted outputs

    y_data_pred = []
    tr_loop = data.shape[0] - data.shape[0]%1000
    # consider you X tr shape is 48041 then your for loop will be 48041 - 48041%1000 = 48000
```



```

# consider you X_train shape is 49041, then your cl_loop will be 49041 - 49041*1000 = 49000
# in this for loop we will iterate until the last 1000 multiplier
for i in range(0, tr_loop, 1000):
    y_data_pred.extend(clf.predict_proba(data[i:i+1000])[:,1])
# we will be predicting for the last data points
y_data_pred.extend(clf.predict_proba(data[tr_loop:])[:,1])

return y_data_pred

```

In [144]:

```

# we are writing our own function for predict, with defined threshold
# we will pick a threshold that will give the least fpr
def predict(proba, threshold, fpr, tpr):

    t = threshold[np.argmax(fpr*(1-tpr))]

    # (tpr*(1-fpr)) will be maximum if your fpr is very low and tpr is very high

    print("the maximum value of tpr*(1-fpr)", max(tpr*(1-fpr)), "for threshold", np.round(t,3))
    predictions = []
    for i in proba:
        if i>=t:
            predictions.append(1)
        else:
            predictions.append(0)
    return predictions

```

In [114]:

```

# https://scikit-learn.org/stable/modules/generated/sklearn.metrics.roc_curve.html#sklearn.metrics.roc_curve
from sklearn.metrics import roc_curve, auc
import matplotlib.pyplot as plt
from sklearn.naive_bayes import MultinomialNB
from sklearn.metrics import roc_auc_score


clf = MultinomialNB(alpha=best_alpha)
clf.fit(X2_tr, y_train)
# roc_auc_score(y_true, y_score) the 2nd parameter should be probability estimates of the positive class
# not the predicted outputs

y_train_pred = batch_predict(clf, X2_tr)
y_test_pred = batch_predict(clf, X2_te)

train_fpr, train_tpr, tr_thresholds = roc_curve(y_train, y_train_pred)
test_fpr, test_tpr, te_thresholds = roc_curve(y_test, y_test_pred)

plt.plot(train_fpr, train_tpr, label="train AUC =" + str(auc(train_fpr, train_tpr)))
plt.plot(test_fpr, test_tpr, label="test AUC =" + str(auc(test_fpr, test_tpr)))
plt.legend()
plt.xlabel("Alpha: hyperparameter")
plt.ylabel("AUC")
plt.title("ERROR PLOTS")
plt.grid()
plt.show()

```



- Train AUC is 0.9740.
- Test AUC is 0.6781 represent the prediction level on the test dataset. In other words if a data point is provided the probability of classifying it correctly after the training has been done is 67.81 %.

In [146]:

```
print("="*100)
from sklearn.metrics import confusion_matrix
import seaborn as sns
class_label = ["negative", "positive"]


# Reference: https://seaborn.pydata.org/generated/seaborn.heatmap.html
# https://stackoverflow.com/questions/37790429/seaborn-heatmap-using-pandas-dataframe

print("Train confusion matrix")
cm=confusion_matrix(y_train, predict(y_train_pred, tr_thresholds, train_fpr, train_fpr))
df= pd.DataFrame(cm, index = class_label, columns = class_label)
sns.heatmap(df, annot = True, fmt = "d")
plt.title("Confusiion Matrix")
plt.xlabel("Predicted Label")
plt.ylabel("True Label")
plt.show()


print("Test confusion matrix")

cm=confusion_matrix(y_test, predict(y_test_pred, tr_thresholds, test_fpr, test_fpr))
df = pd.DataFrame(cm, index = class_label, columns = class_label)
sns.heatmap(df, annot = True, fmt = "d")
plt.title("Confusiion Matrix")
plt.xlabel("Predicted Label")
plt.ylabel("True Label")
plt.show()
```

Train confusion matrix
the maximum value of $tpr*(1-fpr)$ 0.25 for threshold 0.729



Test confusion matrix
the maximum value of $tpr*(1-fpr)$ 0.24999999161092998 for threshold 0.805





2.4.2.1 Top 10 important features of positive class from SET 2

In [189]:

```
# Ref:https://stackoverflow.com/questions/50526898/how-to-get-feature-importance-in-naive-bayes
# getting important features by using get_feature_names()
imp_features=vectorizer_essay.get_feature_names()
pos_features=sorted(zip(clf.feature_log_prob_[1],imp_features),reverse=True)[:10]
for log_var,text in pos_features:
    print(log_var,text)
```

```
-5.394624139642957 title school which means
-5.55452837742811 ancient
-5.643328821538889 that with
-5.838294496074951 student who
-6.109876155775069 obstacles
-6.19746541114854 improve the
-6.262457842405584 musicians
-6.430743462328809 apps to
-6.43704634690946 they
-6.509349004291267 wiggly
```

2.4.2.2 Top 10 important features of negative class from SET 2

In [190]:

```
# Ref:https://stackoverflow.com/questions/50526898/how-to-get-feature-importance-in-naive-bayes
# getting important features by using get_feature_names()
imp_features=vectorizer_essay.get_feature_names()
neg_features=sorted(zip(clf.feature_log_prob_[0],imp_features),reverse=True)[:10]
for log_var,text in neg_features:
    print(log_var,text)
```

```
-5.401247223611035 title school which means
-5.553463305854071 ancient
-5.676090066620301 that with
-5.868233780751327 student who
-6.115781225191968 obstacles
-6.18712951734553 improve the
-6.293796801566286 musicians
-6.429516338825206 they
-6.430254907486976 apps to
-6.555620986726958 the year and
```

3. Conclusions

In [195]:

```
# Please compare all your models using Prettytable library
# Reference: http://zetcode.com/python/prettytable/
from prettytable import PrettyTable

x = PrettyTable()
x.field_names = ["Vectorizer", "Model", "Alpha Hyper Parameter", "AUC"]
x.add_row(["BOW", "Brute", 1.0,0.6798 ])
x.add_row(["TFIDF", "Brute", 0.01,0.6781 ])
print(x)
```

Vectorizer	Model	Alpha Hyper Parameter	AUC
BOW	Brute	1.0	0.6798
TFIDF	Brute	0.01	0.6781

- Naive Bayes works good at text classification like spam filtering, review polarity etc.
- In Naive Bayes the best value of Hyperparameter 'Alpha' for this case lies between 0.01 to 1 according to the observations made with BOW,TFIDF.
- Naive Bayes with BOW,TFIDF have almost the same AUC and give almost same results .
- Thus from the observations made, Naive Bayes is a good classifying model for predicting the project is approved or not in this case as it gives prediction rate between 65-70%.