Login Validation API – Technical Documentation

1. Overview

The **Login Validation API** provides secure access to user authentication and login validation service under the Panchayat Darpan ecosystem. The API is designed for authorized system-to-system integration and uses encrypted request and response payloads to ensure data confidentiality.

---

2. API Environment

Environment	Endpoint
Production	`https://api.mppanchayatdarpan.gov.in/api/Authentication/JalRekha/LoginValidate`

---

3. HTTP Method

`POST`

---

4. Authentication & Security

The API uses **header-based authentication** along with **payload encryption**.

4.1 Request Headers

Header Name	Description	Mandatory
`ClientCode`	Unique client identifier issued by the department	Yes
`APIKey`	Secret API key mapped to the client	Yes

> **Note:** ClientCode and APIKey will be shared securely and separately.

---

5. Request Body

- Content-Type: `form-data`
- All request parameters must be **AES encrypted** using the shared encryption key.

5.1 Request Parameters

Parameter	Type	Description	Mandatory
`UserName`	String	Encrypted Username	Yes
`Password`	String	Encrypted Password	Yes

---

6. Encryption & Decryption

All request and response payloads are encrypted using **AES encryption (128-bit)**.

- Algorithm: AES
- Mode: CBC
- Padding: PKCS7
- IV: 16 bytes (initialized as zero array)

The consumer must encrypt the request payload and decrypt the response payload using the shared encryption key.

---

7. API Responses

7.1 General Response Structure (Decrypted)

```json
{
  "Status": "00",
  "Rows": {},
  "Message": "SUCCESS"
}
```

7.2 Success Response

- HTTP Status: **200 OK**

```json
{
  "Status": "00",
  "Rows": [<data>],
  "Message": "SUCCESS"
}
```

7.3 No Data Response

- HTTP Status: **200 OK**

```json
{
  "Status": "03",
  "Rows": [],
  "Message": "NO DATA"
}
```

7.4 Error Response

- HTTP Status: **200 OK**

```json
{
  "Status": "03",
  "Rows": [],
  "Message": "ERROR"
}
```

---

8. Authorization Error Responses

8.1 Invalid Client Code

- HTTP Status: **401 Unauthorized**

```json
{
  "Status": "401",
  "Message": "Invalid Client Code."
}
```

8.2 Invalid API Key

- HTTP Status: **401 Unauthorized**

```json
{
  "Status": "401",
  "Message": "Invalid Secret Key."
}
```

8.3 Missing Client Code

- HTTP Status: **401 Unauthorized**

```json
{
  "Status": "401",
  "Message": "Client Code not provided"
}
```

8.4 Missing API Key

- HTTP Status: **401 Unauthorized**

```json
{
  "Status": "401",
```

```
  "Message": "API Key not provided"
}
```

---

9. Sample Response

9.1 Encrypted

1BE5b0Wqivn8xWhVJm+2FwTFpKWnM57118CcxwdYGrmbCK0nSpxIWOXWVix3OH3S2mbgR5MEWFDMkDE
Tlj0uzg1Afw67qXPSRIDi3/u5Cw5xZ1bUVqDYCmg0rc0WXGcdygnSypA2h1BLti7Q9RndO2X6Uk+cN2keXcrtEQ
DVAKA8yNFuZLi1vUbZO4CuO6Bha58tUufhJAN+imSouFUGA0MtAGTGCU7StTKiryqscBy6RjisxyMmoFOwu12
eRboU/rw/cM6DLaEmcQtmZmbQFWDzSSOxl4Xy8yo51UI3e9+nwocJCrAwZOKQiux96bAtFmr9rmJd7A9zhm
OaldUv3+wUEKHmHKezScz5OVhzdRfiarhyPNJM41hqRKdOEL2cy7x5dr3tiyjrwN/nKlgghliZ+sL/2ZWQlr/1XafR
xEVi7wZrq78pcH1dfp53pX0EG9n8pECX5RSXMx0ma1piaocOWGernces2C+URQdUk9KsI7n45OFxtP5IGk4+Z
P4zRxvfBxAqeGHXv3j8qq9PudT9GhVb/Kvuine7/OFCCEzGC8Iw4B9yz4ZgbBRLutCBQScZ1oUWvVH0S/zI6HM
SLtSFuSpYW6dpRjRvg7asLprK7yc3H03pY38fW4W3yZwp5Z4qwZIM8OvBH1QVZN/TXavSzHXk6orNKh7PGh2
E3ROm1+jKj7rHUgsJ15mJsU6w1vjoiXWNCbzBHD3IryE1aNGjnc5jmPLNfePBX7/KQgnTnLgUUEhSnU4I1uGx4
4qU9Gl0S6opaOxuFhNZIltwR9uhByyb3yfvcVTLdrRp2/oq4yFDi2o6OIUEcBLgTRBPAFsgYWhUYYWvyi4W+cm
M1wvDcsOchCdQ2IiKuF5axSIqx055WneuhgzGMrxzam7vPVWICPk8TpR1gYV5VlaHK50rgR9YgKQ6rwEDUz43
AQs=

9.2 Decrypted

{

 "Status": "00",
 "Rows": [
  {
   "OfficeName": "ZILA PANCHAYAT, CHHATARPUR",
   "DisplayName": "Zila Panchayat CHHATARPUR",
   "MobileNo": "9425881118",
   "UserID": "3063576",
   "DistrictID": 357,
   "DistrictName": "CHHATARPUR",
   "BlockID": 0,
   "BlockName": "Jilla Panchayat, CHHATARPUR",
   "UserName": "PD ZP 37857",
   "UserType": "ZilaPanchayat",
   "LoginToken":
"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJVc2VySUQiOiIzMDYzNTc2IiwiVXNlck5hbWUiOiJQRCBaUCAzNzg
1NyIsIlVzZXJUeXBlIjoiWmlsYVBhbmNoYXlhdCIsImV4cCI6MTc3MDk3OTgxMywiaXNzIjoiaHR0cHM6Ly9sb2N
hbGhvc3Q6NzE1OSIsImF1ZCI6Imh0dHBzOi8vbG9jYWxob3N0OjcxNTkifQ.PaxGMQ5i1ibZOCpRMm_WBDW
OAv-zpfiLWTZzUrf8dIU",
   "TokenExpiresAt": "13-02-2026 16:20:13",
   "TokenIssuedAt": "13-02-2026 15:20:13"
  }

```
],
"Message": "SUCCESS"
}
```

```
{
  "Status": "00",
  "Rows": [
    {
      "OfficeName": "ZILA PANCHAYAT, CHHATARPUR",
      "DisplayName": "Zila Panchayat CHHATARPUR",
      "MobileNo": "9425881118",
      "UserID": "3063576",
      "DistrictID": 357,
      "DistrictName": "CHHATARPUR",
      "BlockID": 0,
      "BlockName": "Jilla Panchayat, CHHATARPUR",
      "UserName": "PD ZP 37857",
      "UserType": "ZilaPanchayat",
      "LoginToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9
        .eyJVc2VySUQiOiIzMDYzNTc2IiwiVXNlck5hbWUiOiJQRCBaUCAzNzg1NyIsIlVzZXJUeXB
        lIjoiWmlsYVBhbmNoYXlhdCIsImV4cCI6MTc3MDk3OTgxMywiaXNzIjoiaHR0cHM6Ly9sb2N
        hbGhvc3Q6NzE1OSIsImF1ZCI6Imh0dHBzOi8vbG9jYWxob3N0OjcxNTkifQ
        .PaxGMQ5i1ibZOCpRMm_WBDWOAv-zpfiLWTZzUrf8dIU",
      "TokenExpiresAt": "13-02-2026 16:20:13",
      "TokenIssuedAt": "13-02-2026 15:20:13"
    }
  ],
  "Message": "SUCCESS"
}
```

10. Technical Notes

- All integrations must strictly adhere to encryption standards.
- API access is restricted to whitelisted IPs (if configured).
- Excessive or unauthorized requests may lead to key revocation.

11. Support

For API onboarding, key generation, or technical support, please contact the Panchayat Darpan technical team through official communication channels.

Document Version: 1.0 **Last Updated:** 12-May-2026

Encryption & Decryption (C#)

```
using System.IO;
using System.Text;
using System.Security.Cryptography;
```

```
public string Encrypt(string plainText,string encKey)
 {
    try
    {
       byte[] iv = new byte[16];
       byte[] array;

       using (Aes aes = Aes.Create())
       {
          aes.Key = Encoding.UTF8.GetBytes(encKey);
          aes.IV = iv;

          ICryptoTransform encryptor = aes.CreateEncryptor(aes.Key, aes.IV);

          using (MemoryStream memoryStream = new MemoryStream())
          {
             using (CryptoStream cryptoStream = new CryptoStream((Stream)memoryStream,
encryptor, CryptoStreamMode.Write))
             {
                using (StreamWriter streamWriter = new StreamWriter((Stream)cryptoStream))
                {
                   streamWriter.Write(plainText);
                }

                array = memoryStream.ToArray();
             }
          }
       }
       return Convert.ToBase64String(array);
    }
    catch (Exception ex)
    {
       throw new InvalidCastException("Unable to encrypt. Invalid Plain text Data. Error: " +
ex.Message);
    }

 }
```

```
 public string Decrypt(string cipherText, string encKey)
 {
```

```
    try
    {
       byte[] iv = new byte[16];
       byte[] buffer = Convert.FromBase64String(cipherText);

       using (Aes aes = Aes.Create())
       {
          aes.Key = Encoding.UTF8.GetBytes(encKey);
          aes.IV = iv;
          ICryptoTransform decryptor = aes.CreateDecryptor(aes.Key, aes.IV);

          using (MemoryStream memoryStream = new MemoryStream(buffer))
          {
             using (CryptoStream cryptoStream = new CryptoStream((Stream)memoryStream,
decryptor, CryptoStreamMode.Read))
             {
                using (StreamReader streamReader = new StreamReader((Stream)cryptoStream))
                {
                   return streamReader.ReadToEnd();
                }
             }
          }
       }
    }
    catch (Exception ex )
    {
       throw new InvalidCastException("Unable to Decrypt. Invalid Cipher Text. Error: " +
ex.Message);
    }
 }
```