

```
In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
```

```
In [2]: df=pd.read_csv(r"C:\Users\Admin\Downloads\10_USA_Housing.csv")
df
```

Out[2]:

	Avg. Area Income	Avg. Area House Age	Avg. Area Number of Rooms	Avg. Area Number of Bedrooms	Area Population	Price	Address
0	79545.458574	5.682861	7.009188	4.09	23086.800503	1.059034e+06	208 Michael Ferr 674\nLaurabur 3
1	79248.642455	6.002900	6.730821	3.09	40173.072174	1.505891e+06	188 Johnson \ Suite 079\r Kathleen,
2	61287.067179	5.865890	8.512727	5.13	36882.159400	1.058988e+06	9127 Eliz Stravenue\nDaniel WI 06
3	63345.240046	7.188236	5.586729	3.26	34310.242831	1.260617e+06	USS Barnett\nFP 4
4	59982.197226	5.040555	7.839388	4.23	26354.109472	6.309435e+05	USNS Raymond\nAE C
...	
4995	60567.944140	7.830362	6.137356	3.46	22837.361035	1.060194e+06	USNS Williams\nAP 30153-
4996	78491.275435	6.999135	6.576763	4.02	25616.115489	1.482618e+06	PSC 9258 8489\nAPO AA 4:
4997	63390.686886	7.250591	4.805081	2.13	33266.145490	1.030730e+06	4215 Tracy G. Suite 076\nJoshua VA
4998	68001.331235	5.534388	7.130144	5.44	42625.620156	1.198657e+06	USS Wallace\nFP 7
4999	65510.581804	5.992305	6.792336	4.07	46501.283803	1.298950e+06	37778 George R Apt. 509\nEast N

5000 rows × 7 columns

In [3]:

df.head()

Out[3]:

	Avg. Area Income	Avg. Area House Age	Avg. Area Number of Rooms	Avg. Area Number of Bedrooms	Area Population	Price	Address
0	79545.458574	5.682861	7.009188	4.09	23086.800503	1.059034e+06	208 Michael Ferry Ap 674\nLaurabury, N 3701
1	79248.642455	6.002900	6.730821	3.09	40173.072174	1.505891e+06	188 Johnson View Suite 079\nLak Kathleen, CA
2	61287.067179	5.865890	8.512727	5.13	36882.159400	1.058988e+06	9127 Elizabe Stravenue\nDanieltow WI 06482
3	63345.240046	7.188236	5.586729	3.26	34310.242831	1.260617e+06	USS Barnett\nFPO A 4482
4	59982.197226	5.040555	7.839388	4.23	26354.109472	6.309435e+05	USNS Raymond\nFP AE 093E

In [4]:

df.info()

```
<class 'pandas.core.frame.DataFrame'>  
RangeIndex: 5000 entries, 0 to 4999  
Data columns (total 7 columns):  
#   Column                                Non-Null Count  Dtype  
---  -  
0   Avg. Area Income                      5000 non-null   float64  
1   Avg. Area House Age                   5000 non-null   float64  
2   Avg. Area Number of Rooms             5000 non-null   float64  
3   Avg. Area Number of Bedrooms          5000 non-null   float64  
4   Area Population                       5000 non-null   float64  
5   Price                                5000 non-null   float64  
6   Address                               5000 non-null   object  
dtypes: float64(6), object(1)  
memory usage: 273.6+ KB
```

In [5]: `df.describe()`

Out[5]:


	Avg. Area Income	Avg. Area House Age	Avg. Area Number of Rooms	Avg. Area Number of Bedrooms	Area Population	Price
count	5000.000000	5000.000000	5000.000000	5000.000000	5000.000000	5.000000e+03
mean	68583.108984	5.977222	6.987792	3.981330	36163.516039	1.232073e+06
std	10657.991214	0.991456	1.005833	1.234137	9925.650114	3.531176e+05
min	17796.631190	2.644304	3.236194	2.000000	172.610686	1.593866e+04
25%	61480.562388	5.322283	6.299250	3.140000	29403.928702	9.975771e+05
50%	68804.286404	5.970429	7.002902	4.050000	36199.406689	1.232669e+06
75%	75783.338666	6.650808	7.665871	4.490000	42861.290769	1.471210e+06
max	107701.748378	9.519088	10.759588	6.500000	69621.713378	2.469066e+06

In [6]: `df.columns`

Out[6]: Index(['Avg. Area Income', 'Avg. Area House Age', 'Avg. Area Number of Rooms', 'Avg. Area Number of Bedrooms', 'Area Population', 'Price', 'Address'], dtype='object')


```
In [7]: sns.pairplot(df)
```

```
Out[7]: <seaborn.axisgrid.PairGrid at 0x201e996a550>
```



```
In [8]: sns.distplot(df['Price'])
```

```
Out[8]: <matplotlib.axes._subplots.AxesSubplot at 0x201ebb52490>
```



```
In [9]: df1=df[['Avg. Area Income', 'Avg. Area House Age', 'Avg. Area Number of Rooms',
               'Avg. Area Number of Bedrooms', 'Area Population', 'Price']]
df1
```

```
Out[9]:
```

	Avg. Area Income	Avg. Area House Age	Avg. Area Number of Rooms	Avg. Area Number of Bedrooms	Area Population	Price
0	79545.458574	5.682861	7.009188	4.09	23086.800503	1.059034e+06
1	79248.642455	6.002900	6.730821	3.09	40173.072174	1.505891e+06
2	61287.067179	5.865890	8.512727	5.13	36882.159400	1.058988e+06
3	63345.240046	7.188236	5.586729	3.26	34310.242831	1.260617e+06
4	59982.197226	5.040555	7.839388	4.23	26354.109472	6.309435e+05
...
4995	60567.944140	7.830362	6.137356	3.46	22837.361035	1.060194e+06
4996	78491.275435	6.999135	6.576763	4.02	25616.115489	1.482618e+06
4997	63390.686886	7.250591	4.805081	2.13	33266.145490	1.030730e+06
4998	68001.331235	5.534388	7.130144	5.44	42625.620156	1.198657e+06
4999	65510.581804	5.992305	6.792336	4.07	46501.283803	1.298950e+06

5000 rows × 6 columns

```
In [10]: sns.heatmap(df1.corr())
```

```
Out[10]: <matplotlib.axes._subplots.AxesSubplot at 0x201ec109520>
```



```
In [11]: x=df1[['Avg. Area Income', 'Avg. Area House Age', 'Avg. Area Number of Rooms',  
               'Avg. Area Number of Bedrooms', 'Area Population']]  
y=df1['Price']
```

```
In [12]: from sklearn.model_selection import train_test_split  
x_train,x_test,y_train,y_test = train_test_split(x,y,test_size=0.3)
```

```
In [13]: from sklearn.linear_model import LinearRegression  
lr= LinearRegression()  
lr.fit(x_train,y_train)
```

```
Out[13]: LinearRegression()
```

```
In [14]: print(lr.intercept_)  
  
-2632503.5272272686
```


```
In [15]: coeff = pd.DataFrame(lr.coef_,x.columns,columns=["Co-efficient"])
coeff
```

Out[15]:

	Co-efficient
Avg. Area Income	21.435155
Avg. Area House Age	166308.757854
Avg. Area Number of Rooms	121233.673389
Avg. Area Number of Bedrooms	1182.722365
Area Population	15.110824

```
In [16]: prediction= lr.predict(x_test)
plt.scatter(y_test,prediction)
```

Out[16]: <matplotlib.collections.PathCollection at 0x201ed51cf40>



```
In [17]: print(lr.score(x_test,y_test))
```

0.9157296655127753

In []: