

DeepLearning.AI TensorFlow Developer

Contents

1	Introduction to TensorFlow for AI, ML, and DL	1
1.0.1	Callbacks	1
1.0.2	Upload Custom Images	1
1.0.3	ImageDataGenerator	2
2	CNN's in TensorFlow	3
2.0.1	Using OS and Splitting Data	3
2.0.2	Building a CNN with IDG	4
2.0.3	Transfer Learning: Built-in Models	4
2.0.4	Reading Images from CSVs	5
2.0.5	Multi-Class Classification	6
3	Natural Language Processing	7
3.0.1	Setup & Reading CSVs	7
3.0.2	Tokenizer	7
3.0.3	Modeling	8
3.0.4	Visualizing Clustering	8
3.0.5	Sequence Model with Pretrained Weights	9
3.0.6	Predicting Words	10
4	Sequences: Time Series and Predictions	12
4.0.1	12

1 Introduction to TensorFlow for AI, ML, and DL

1.0.1 Callbacks

We can use **callbacks** in order to stop training when we reach a certain accuracy we desire. This is to stop the loss from beginning to increase again if we start to overfit the model. [Click here](#) to see the TensorFlow Callbacks documentation.

```
1 import tensorflow as tf
2 print(tf.__version__)
3
4 class myCallback(tf.keras.callbacks.Callback):
5     def on_epoch_end(self, epoch, logs={}):
6         if(logs.get('accuracy')>0.6): # might need to use 'acc' instead
7             print("\nReached 60% accuracy so cancelling training!")
8             self.model.stop_training = True
9
10 callbacks = myCallback()
11
12 mnist = tf.keras.datasets.fashion_mnist
13 (x_train, y_train), (x_test, y_test) = mnist.load_data()
14 x_train, x_test = x_train / 255.0, x_test / 255.0
15
16 model = tf.keras.models.Sequential([
17     tf.keras.layers.Flatten(),
18     tf.keras.layers.Dense(512, activation=tf.nn.relu),
19     tf.keras.layers.Dense(10, activation=tf.nn.softmax)
20 ])
21
22 model.compile(optimizer='adam',
23               loss='sparse_categorical_crossentropy',
24               metrics=['accuracy'])
25 model.fit(x_images, y_labels, epochs=10, callbacks=[callbacks])
```

1.0.2 Upload Custom Images

We can use the below code to upload a custom image and use it on a trained model.

```
1 import numpy as np
2 from google.colab import files
3 from keras.preprocessing import image
4
5 uploaded = files.upload()
6
7 for fn in uploaded.keys():
8     # predicting images
9     path = '/content/' + fn
10    img = image.load_img(path, target_size=(300, 300))
11    x = image.img_to_array(img)
12    x = np.expand_dims(x, axis=0)
13
14    images = np.vstack([x])
15    classes = model.predict(images, batch_size=10)
16    print(classes[0])
17    if classes[0]>0.5:
18        print(fn + " is a human")
19    else:
20        print(fn + " is a horse")
```

1.0.3 ImageDataGenerator

```
1 import tensorflow as tf
2 import os
3 import zipfile
4 from os import path, getcwd, chdir
5 from tensorflow.keras.optimizers import RMSprop
6     from tensorflow.keras.preprocessing.image import ImageDataGenerator
7
8 # Import and extract zip file containing images
9 path = f"{getcwd()}/../tmp2/happy-or-sad.zip"
10 zip_ref = zipfile.ZipFile(path, 'r')
11 zip_ref.extractall("/tmp/h-or-s")
12 zip_ref.close()
13
14 def train_happy_sad_model():
15     DESIRED_ACCURACY = 0.999
16
17     class myCallback(tf.keras.callbacks.Callback):
18         def on_epoch_end(self, epoch, logs={}):
19             if(logs.get('acc')>DESIRED_ACCURACY):
20                 print('\nReached 100% accuracy so stopping training.')
21                 self.model.stop_training = True
22
23     callbacks = myCallback()
24
25     # Define and Compile the Model.
26     model = tf.keras.models.Sequential([
27         tf.keras.layers.Conv2D(64, (3,3), activation='relu', input_shape=(150,150,3)),
28         tf.keras.layers.MaxPooling2D(2,2),
29         tf.keras.layers.Conv2D(32, (3,3), activation='relu'),
30         tf.keras.layers.MaxPooling2D(2,2),
31         tf.keras.layers.Conv2D(16, (3,3), activation='relu'),
32         tf.keras.layers.MaxPooling2D(2,2),
33         tf.keras.layers.Flatten(),
34         tf.keras.layers.Dense(512),
35         tf.keras.layers.Dense(1, activation='sigmoid')
36     ])
37
38     model.compile(optimizer=RMSprop(lr=0.001),
39                 loss='binary_crossentropy',
40                 metrics=['accuracy'])
41
42     # Create an instance of an ImageDataGenerator
43     train_datagen = ImageDataGenerator(rescale=1./255)
44
45     train_generator = train_datagen.flow_from_directory(
46         '/tmp/h-or-s', # directory containing the images
47         target_size=(150,150),
48         class_mode='binary'
49     )
50
51     history = model.fit(
52         train_generator, # data generator object
53         epochs=50,
54         callbacks=[callbacks],
55         verbose=1
56     )
57
58     return history.history['acc'][-1]
```

2 CNN's in TensorFlow

2.0.1 Using OS and Splitting Data

```
1 path_cats_and_dogs = f"{getcwd()}/../tmp2/cats-and-dogs.zip"
2 shutil.rmtree('/tmp')
3
4 local_zip = path_cats_and_dogs
5 zip_ref = zipfile.ZipFile(local_zip, 'r')
6 zip_ref.extractall('/tmp')
7 zip_ref.close()
8
9 try: # Make directories for training and testing, along with class subdirectories
10     os.mkdir('/tmp/cats-v-dogs/')
11     os.mkdir('/tmp/cats-v-dogs/training/')
12     os.mkdir('/tmp/cats-v-dogs/testing/')
13     os.mkdir('/tmp/cats-v-dogs/training/cats/')
14     os.mkdir('/tmp/cats-v-dogs/testing/cats/')
15     os.mkdir('/tmp/cats-v-dogs/training/dogs/')
16     os.mkdir('/tmp/cats-v-dogs/testing/dogs/')
17 except OSError:
18     pass
19
20 def split_data(SOURCE, TRAINING, TESTING, SPLIT_SIZE):
21     """
22     a SOURCE directory containing the files
23     a TRAINING directory that a portion of the files will be copied to
24     a TESTING directory that a portion of the files will be copied to
25     a SPLIT SIZE to determine the portion
26     """
27     source_list = os.listdir(SOURCE) # get list of files
28     random.sample(source_list, len(source_list)) # shuffle the list
29     train_images = source_list[:int(len(source_list)*SPLIT_SIZE)]
30     testing_images = source_list[int(len(source_list)*SPLIT_SIZE):]
31
32     for img in train_images:
33         if os.path.getsize(SOURCE+img) != 0: # make sure not empty file
34             copyfile(SOURCE+img, TRAINING+img)
35
36     for img in testing_images:
37         if os.path.getsize(SOURCE+img) != 0: # make sure not empty file
38             copyfile(SOURCE+img, TESTING+img)
39
40     return None
41
42 CAT_SOURCE_DIR = "/tmp/PetImages/Cat/"
43 TRAINING_CATS_DIR = "/tmp/cats-v-dogs/training/cats/"
44 TESTING_CATS_DIR = "/tmp/cats-v-dogs/testing/cats/"
45 DOG_SOURCE_DIR = "/tmp/PetImages/Dog/"
46 TRAINING_DOGS_DIR = "/tmp/cats-v-dogs/training/dogs/"
47 TESTING_DOGS_DIR = "/tmp/cats-v-dogs/testing/dogs/"
48
49 split_size = .9
50 split_data(CAT_SOURCE_DIR, TRAINING_CATS_DIR, TESTING_CATS_DIR, split_size)
51 split_data(DOG_SOURCE_DIR, TRAINING_DOGS_DIR, TESTING_DOGS_DIR, split_size)
```

2.0.2 Building a CNN with IDG

```
1 model = tf.keras.models.Sequential([
2     tf.keras.layers.Conv2D(16, (3,3), activation='relu', input_shape=(150,150,3)),
3     tf.keras.layers.MaxPooling2D(2,2),
4     tf.keras.layers.Conv2D(32, (3,3), activation='relu'),
5     tf.keras.layers.MaxPooling2D(2,2),
6     tf.keras.layers.Conv2D(64, (3,3), activation='relu'),
7     tf.keras.layers.MaxPooling2D(2,2),
8     tf.keras.layers.Flatten(),
9     tf.keras.layers.Dense(512, activation='relu'),
10    tf.keras.layers.Dense(1, activation='sigmoid')
11 ])
12
13 model.compile(optimizer=RMSprop(lr=0.001), loss='binary_crossentropy',
14               metrics=['acc'])
15
16 # Feed training data into our IDG object
17 TRAINING_DIR = '/tmp/cats-v-dogs/training/'
18 train_datagen = ImageDataGenerator(rescale=1./255,
19                                     rotation_range=45,
20                                     horizontal_flip=True,
21                                     vertical_flip=True,
22                                     shear_range=0.2,
23                                     zoom_range=0.2,
24                                     fill_mode='nearest')
25
26 train_generator = train_datagen.flow_from_directory(TRAINING_DIR,
27                                                     target_size=(150,150),
28                                                     batch_size=10,
29                                                     class_mode='binary')
30
31 # Feed testing data into our IDG object
32 VALIDATION_DIR = '/tmp/cats-v-dogs/testing/'
33 validation_datagen = ImageDataGenerator(rescale=1./255)
34
35 validation_generator = validation_datagen.flow_from_directory(VALIDATION_DIR,
36                                                             target_size=(150,150),
37                                                             batch_size=10,
38                                                             class_mode='binary')
39
40 history = model.fit_generator(train_generator,
41                               epochs=2,
42                               verbose=1,
43                               validation_data=validation_generator)
```

2.0.3 Transfer Learning: Built-in Models

```
1 path_inception = f"{getcwd()}/../tmp2/"
2     inception_v3_weights_tf_dim_ordering_tf_kernels_notop.h5"
3
4 # Import the inception model
5 from tensorflow.keras.applications.inception_v3 import InceptionV3
6
7 # Create an instance of the inception model from the local pre-trained weights
8 local_weights_file = path_inception
9
10 pre_trained_model = InceptionV3(input_shape=(150,150,3), include_top=False,
11                                 weights=None)
12
13 pre_trained_model.load_weights(local_weights_file)
```

```

1 # Make all the layers in the pre-trained model non-trainable
2 for layer in pre_trained_model.layers:
3     layer.trainable = False
4
5 last_layer = pre_trained_model.get_layer('mixed7')
6 print('last layer output shape: ', last_layer.output_shape) # (None, 7, 7, 768)
7 last_output = last_layer.output
8
9 # Flatten the output layer to 1 dimension (with input from last pretrained layers)
10 x = layers.Flatten()(last_output)
11
12 x = layers.Dense(1024, activation='relu')(x)
13 x = layers.Dropout(0.2)(x)
14 x = layers.Dense(1, activation='sigmoid')(x)
15
16 model = Model(pre_trained_model.input, x)
17
18 model.compile(optimizer = RMSprop(lr=0.0001),
19               loss = 'binary_crossentropy',
20               metrics = ['acc'])

```

2.0.4 Reading Images from CSVs

```

1 def get_data(filename):
2     """
3     Read the file passed into the function. The first line contains
4     the header (so skip it). Each line contains 785 values, with
5     the first being the label and remaining being the pixel values.
6     You will need to reshape the images into 28x28.
7     """
8     with open(filename) as training_file:
9         labels = []
10        images = []
11        reader = csv.reader(training_file, delimiter = ',')
12        next(reader, None) # skip first line
13
14        for row in reader:
15            labels.append(row[0])
16            images.append(np.array(row[1:]).reshape(28,28))
17
18        labels = np.array(labels).astype(float)
19        images = np.array(images).astype(float)
20        return images, labels
21
22 path_sign_mnist_train = f"{getcwd()}/../tmp2/sign_mnist_train.csv"
23 path_sign_mnist_test = f"{getcwd()}/../tmp2/sign_mnist_test.csv"
24 training_images, training_labels = get_data(path_sign_mnist_train)
25 testing_images, testing_labels = get_data(path_sign_mnist_test)
26
27 print(training_images.shape) # (27455, 28, 28)
28 print(training_labels.shape) # (27455)
29 print(testing_images.shape) # (7172, 28, 28)
30 print(testing_labels.shape) # (7172)
31
32 # Expand dimensions (add 1 to the end)
33 training_images = np.expand_dims(training_images, axis=3) # (27455, 28, 28, 1)
34 testing_images = np.expand_dims(testing_images, axis=3) # (7172, 28, 28, 1)

```

2.0.5 Multi-Class Classification

```
1  # Create an ImageDataGenerator objects
2  train_datagen = ImageDataGenerator(
3      rescale=1./255,
4      rotation_range=45,
5      horizontal_flip=True,
6      vertical_flip=True,
7      zoom_range=0.2 )
8
9  validation_datagen = ImageDataGenerator(rescale=1./255)
10
11 # Create generators (images already loaded, not from directory)
12 train_generator = train_datagen.flow(training_images,
13                                     training_labels,
14                                     batch_size=32)
15
16 valid_generator = validation_datagen.flow(testing_images,
17                                           testing_labels,
18                                           batch_size=32)
19
20 # Define the model
21 model = tf.keras.models.Sequential([
22     tf.keras.layers.Conv2D(64, (3,3), activation='relu', input_shape=(28,28,1)),
23     tf.keras.layers.MaxPooling2D(2,2),
24     tf.keras.layers.Conv2D(128, (3,3), activation='relu'),
25     tf.keras.layers.MaxPooling2D(2,2),
26     tf.keras.layers.Flatten(),
27     tf.keras.layers.Dense(512, activation='relu'),
28     tf.keras.layers.Dense(26, activation='softmax') # 26 classes
29 ])
30
31 # Compile Model.
32 model.compile(optimizer='adam',
33              loss='sparse_categorical_crossentropy',
34              metrics=['acc'])
35
36 # Train the Model
37 history = model.fit_generator(train_generator,
38                              validation_data=valid_generator,
39                              epochs=2,
40                              verbose=1)
41
42 # Access the metrics for plotting
43 acc = history.history['acc']
44 val_acc = history.history['val_acc']
45 loss = history.history['loss']
46 val_loss = history.history['val_loss']
```

3 Natural Language Processing

3.0.1 Setup & Reading CSVs

```
1 vocab_size = 1000
2 embedding_dim = 16
3 max_length = 120
4 trunc_type = 'post'
5 pad_type = 'post'
6 oov_tok = '<OOV>'
7 training_portion = .8
8 sentences = []
9 labels = []
10 # stopwords is an array of 153 words to be removed
11
12 with open("/tmp/bbc-text.csv", 'r') as csvfile:
13     reader = csv.reader(csvfile, delimiter=',')
14     next(reader)
15     for row in reader:
16         labels.append(row[0])
17         sentence = row[1]
18         for word in stopwords:
19             token = ' ' + word + ' '
20             sentence = sentence.replace(token, '')
21             sentence = sentence.replace(' ', ' ')
22         sentences.append(sentence)
```

3.0.2 Tokenizer

```
1 train_size = int(len(sentences)*training_portion)
2
3 train_sentences = sentences[:train_size] # 1780
4 train_labels = labels[:train_size] # 1780
5
6 validation_sentences = sentences[train_size:] # 445
7 val_labels = labels[train_size:] # 445
8
9 tokenizer = Tokenizer(num_words=vocab_size, oov_token=oov_tok)
10 tokenizer.fit_on_texts(train_sentences)
11 word_index = tokenizer.word_index
12
13 train_sequences = tokenizer.texts_to_sequences(train_sentences)
14 train_padded = pad_sequences(train_sequences, padding=pad_type, maxlen=max_length)
15
16 validation_sequences = tokenizer.texts_to_sequences(validation_sentences)
17 validation_padded = pad_sequences(validation_sequences, padding=pad_type,
18                                   maxlen=max_length)
19
20 label_tokenizer = Tokenizer()
21 label_tokenizer.fit_on_texts(labels)
22
23 training_label_seq = np.array(label_tokenizer.texts_to_sequences(train_labels))
24 validation_label_seq = np.array(label_tokenizer.texts_to_sequences(val_labels))
25
```


3.0.3 Modeling

```
1 model = tf.keras.Sequential([
2     tf.keras.layers.Embedding(vocab_size, embedding_dim, input_length=max_length),
3     tf.keras.layers.GlobalAveragePooling1D(),
4     tf.keras.layers.Dense(24, activation='relu'),
5     tf.keras.layers.Dense(6, activation='softmax')
6 ])
7 model.compile(loss='sparse_categorical_crossentropy', optimizer='adam',
8               metrics=['accuracy'])
9
10 num_epochs = 30
11 history = model.fit(train_padded, training_label_seq,
12                    epochs=num_epochs,
13                    validation_data=(validation_padded, validation_label_seq),
14                    verbose=1)
15
16 def plot_graphs(history, string):
17     plt.plot(history.history[string])
18     plt.plot(history.history['val_'+string])
19     plt.xlabel("Epochs")
20     plt.ylabel(string)
21     plt.legend([string, 'val_'+string])
22     plt.show()
23
24 plot_graphs(history, "accuracy")
25 plot_graphs(history, "loss")
26
```

3.0.4 Visualizing Clustering

```
1 reverse_word_index = dict([(value, key) for (key, value) in word_index.items()])
2 e = model.layers[0]
3 weights = e.get_weights()[0]
4
5 out_v = io.open('vecs.tsv', 'w', encoding='utf-8')
6 out_m = io.open('meta.tsv', 'w', encoding='utf-8')
7 for word_num in range(1, vocab_size):
8     word = reverse_word_index[word_num]
9     embeddings = weights[word_num]
10    out_m.write(word + "\n")
11    out_v.write('\t'.join([str(x) for x in embeddings]) + "\n")
12    out_v.close()
13    out_m.close()
14
15 try:
16     from google.colab import files
17 except ImportError:
18     pass
19 else:
20     files.download('vecs.tsv')
21     files.download('meta.tsv')
22
```

Go to [TensorFlow Projector](#) and upload both the *vecs.tsv* and *meta.tsv* files.
Click *sphereize data*.

3.0.5 Sequence Model with Pretrained Weights

Note that the word vector can be downloaded [here](#).

```
1  # TOKENIZE THE TEXTS
2  sentences=[]
3  labels=[]
4  random.shuffle(corpus) # corpus contains our sentences and labels
5  for x in range(training_size):
6      sentences.append(corpus[x][0])
7      labels.append(corpus[x][1])
8
9  tokenizer = Tokenizer()
10 tokenizer.fit_on_texts(sentences)
11 word_index = tokenizer.word_index
12 vocab_size=len(word_index)
13
14 sequences = tokenizer.texts_to_sequences(sentences)
15 padded = pad_sequences(sequences, maxlen=max_length, padding=padding_type,
16                        truncating=trunc_type)
17
18 split = int(test_portion * training_size)
19
20 test_sequences = padded[0:split]
21 training_sequences = padded[split:training_size]
22 test_labels = labels[0:split]
23 training_labels = labels[split:training_size]
24
25 # LOAD THE PRETRAINED VECTORS (138532)
26 embeddings_index = {};
27 with open('/tmp/glove.6B.100d.txt') as f:
28     for line in f:
29         values = line.split();
30         word = values[0];
31         coefs = np.asarray(values[1:], dtype='float32');
32         embeddings_index[word] = coefs;
33
34 embeddings_matrix = np.zeros((vocab_size+1, embedding_dim));
35 for word, i in word_index.items():
36     embedding_vector = embeddings_index.get(word);
37     if embedding_vector is not None:
38         embeddings_matrix[i] = embedding_vector;
39
40 # CREATE THE MODEL
41 model = tf.keras.Sequential([
42     tf.keras.layers.Embedding(vocab_size+1, embedding_dim, input_length=max_length,
43                             weights=[embeddings_matrix], trainable=False),
44     tf.keras.layers.Dropout(0.2),
45     tf.keras.layers.Conv1D(64, 5, activation='relu'),
46     tf.keras.layers.MaxPooling1D(pool_size=4),
47     tf.keras.layers.LSTM(64),
48     tf.keras.layers.Dense(1, activation='sigmoid')
49 ])
50 model.compile(loss='binary_crossentropy',optimizer='adam',metrics=['accuracy'])
51
52 training_padded = np.array(training_sequences)
53 training_labels = np.array(training_labels)
54 testing_padded = np.array(test_sequences)
55 testing_labels = np.array(test_labels)
56
57 history = model.fit(training_padded, training_labels, epochs=num_epochs,
58                    validation_data=(testing_padded, testing_labels), verbose=1)
```

3.0.6 Predicting Words

[Click here](#) to see how to generate text using characters instead of words.

```
1 tokenizer = Tokenizer()
2 !wget --no-check-certificate \
3     https://storage.googleapis.com/laurencemoroney-blog.appspot.com/sonnets.txt \
4     -O /tmp/sonnets.txt
5 data = open('/tmp/sonnets.txt').read()
6
7 corpus = data.lower().split("\n")
8
9 tokenizer.fit_on_texts(corpus)
10 total_words = len(tokenizer.word_index) + 1
11
12 input_sequences = []
13 for line in corpus:
14     token_list = tokenizer.texts_to_sequences([line])[0] # [0] converts to 1D array
15     for i in range(1, len(token_list)): # loop over length of each sequence
16         n_gram_sequence = token_list[:i+1]
17         input_sequences.append(n_gram_sequence)
18
19 max_sequence_len = max([len(x) for x in input_sequences])
20 input_sequences = np.array(pad_sequences(input_sequences, maxlen=max_sequence_len,
21                                         padding='pre'))
22
23 # Use last word in sequence as label (to predict)
24 predictors, label = input_sequences[:, :-1], input_sequences[:, -1]
25
26 # One-Hot Encode our labels (each label has size 3211)
27 label = ku.to_categorical(label, num_classes=total_words)
28
29 print(input_sequences[:5])
30 # [[ 0,  0,  0,  0,  0,  0,  0,  0,  0,  0, 34, 417],
31 #  [ 0,  0,  0,  0,  0,  0,  0,  0,  0, 34, 417, 877],
32 #  [ 0,  0,  0,  0,  0,  0,  0,  0, 34, 417, 877, 166],
33 #  [ 0,  0,  0,  0,  0,  0, 34, 417, 877, 166, 213],
34 #  [ 0,  0,  0,  0,  0, 34, 417, 877, 166, 213, 517]]
```

Note that the *input_sequences* that is built from the for loop is just adding the next word of each sentence into the next line. We then use the last element of each row as the label to predict. This helps us choose which words come after certain inputs. So for row 1, [34, 417] is input and [877] is the label.

```
1 model = Sequential()
2 model.add(Embedding(total_words, 100, input_length=max_sequence_len-1))
3 model.add(Bidirectional(LSTM(120, return_sequences=True)))
4 model.add(Dropout(0.2))
5 model.add((LSTM(100, return_sequences=False)))
6 model.add(Dense(total_words/2, activation='relu',
7                 kernel_regularizer=regularizers.l2(0.01)))
8 model.add(Dense(total_words, activation='softmax'))
9 model.compile(loss='categorical_crossentropy', optimizer='adam',
10              metrics=['accuracy'])
11
12 history = model.fit(predictors, label, epochs=100, verbose=1)
```

Note that for our *input_length*, we had to subtract 1. This is because we used the last value as our label, so our longest sequence length was reduced by 1. One thing to note is that our accuracy will start very low (near 2%) but will climb steadily as we train for a long period of time (high 90%'s).

```

1 seed_text = "Help me Obi Wan Kenobi, you're my only hope"
2 next_words = 100
3
4 # Predict next 100 words in the sequence
5 for _ in range(next_words):
6     token_list = tokenizer.texts_to_sequences([seed_text])[0]
7     token_list = pad_sequences([token_list], maxlen=max_sequence_len-1, padding='pre')
8     predicted = np.argmax(model.predict(token_list), axis=1)
9     output_word = ""
10    for word, index in tokenizer.word_index.items():
11        if index == predicted:
12            output_word = word
13            break
14    seed_text += " " + output_word
15 print(seed_text)

```

4 Sequences: Time Series and Predictions

4.0.1 ...

Time series are an ordered sequence of values that are usually equally spaced over time. Time series data can be used for forecasting, imputing (previous or filling in missing data), anomalies, sound waves, etc.

Trend: time series is moving in a specific direction.

Seasonality: patterns repeat at predicted intervals.

Combination: directional trend with repeated patterns.

Neither: random values that create white noise.

Fixed Partitioning: split the time series data in only train and validation sets.

- Note that we need to include full seasons (don't split data in mid season).
- Skip creating a test set, and just retrain model on train & validation sets.

Common metrics for **evaluation** include: errors (forecast-actual), mse, rmse, mae, mape.

- We can use the keras.metrics library.

Differencing: looking at difference between data at time t and time $t-a$.

- Forecast = trailing moving average of differencing + centered moving average of $t-a$.