High-order Solution Transfer between Curved Meshes and Ill-conditioned Bézier Curve Intersection

Danny Hermes

August 9, 2018

dhermes@berkeley.edu
UC Berkeley

Outline

1. Introduction and motivation
2. Solution Transfer
3. Compensated Evaluation
4. Modified Newton's for Intersection

Introduction and motivation

Method of Characteristics

Method of Characteristics

Solve simple transport equation

$$u_t + cu_x = 0, \quad u(x,0) = u_0(x).$$

Method of Characteristics

Solve simple transport equation

$$u_t + cu_x = 0, \quad u(x,0) = u_0(x).$$

Divide physical domain

$$x(t) = x_0 + ct$$

Method of Characteristics

Solve simple transport equation

$$u_t + cu_x = 0, \quad u(x,0) = u_0(x).$$

Divide physical domain

$$x(t) = x_0 + ct$$

PDE becomes a (trivial) ODE

$$\frac{d}{dt}u(x(t),t) = 0.$$

Method of Characteristics



Lagrangian Methods

Lagrangian Methods

- Each point in the physical domain is a **particle**

Lagrangian Methods

- Each point in the physical domain is a **particle**
- Carry value (e.g. heat, pressure, density) along characteristic curve

Lagrangian Methods

- Each point in the physical domain is a **particle**
- Carry value (e.g. heat, pressure, density) along characteristic curve
- Transform PDE to family of ODEs

Lagrangian Methods

Add viscosity term to transport equation

$$u_t + cu_x - \varepsilon u_{xx} = 0.$$

Add viscosity term to transport equation

$$u_t + cu_x - \varepsilon u_{xx} = 0.$$

Same characteristics used, **but** solution no longer constant

Lagrangian Methods

Add viscosity term to transport equation

$$u_t + cu_x - \varepsilon u_{xx} = 0.$$

Same characteristics used, **but** solution no longer constant

$$\frac{d}{dt} u(x(t), t) = \varepsilon u_{xx}.$$

Remeshing and Adaptivity

- Problems caused by flow-based mesh changes

Remeshing and Adaptivity

- Problems caused by flow-based mesh changes
    - Distortion

Remeshing and Adaptivity

- Problems caused by flow-based mesh changes
    - Distortion
    - Tangling

Remeshing and Adaptivity

- Problems caused by flow-based mesh changes
  - Distortion
  - Tangling
  - Travel outside relevant physical domain

Remeshing and Adaptivity

- Problems caused by flow-based mesh changes
  - Distortion
  - Tangling
  - Travel outside relevant physical domain
- Adaptivity

Remeshing and Adaptivity

- Problems caused by flow-based mesh changes
  - Distortion
  - Tangling
  - Travel outside relevant physical domain
- Adaptivity
  - Dynamically focus computational effort

Remeshing and Adaptivity

- Problems caused by flow-based mesh changes
  - Distortion
  - Tangling
  - Travel outside relevant physical domain
- Adaptivity
  - Dynamically focus computational effort
  - Resolve sensitive features

Remeshing Example

Consider

$$u_t + \begin{bmatrix} y^2 \\ 1 \end{bmatrix} \cdot \nabla u + F(u, \nabla u) = 0$$

Remeshing Example

Consider

$$u_t + \begin{bmatrix} y^2 \\ 1 \end{bmatrix} \cdot \nabla u + F(u, \nabla u) = 0$$

with cubic characteristics

$$\begin{bmatrix} x(t) \\ y(t) \end{bmatrix} = \begin{bmatrix} x_0 \\ y_0 \end{bmatrix} + \frac{1}{3} \begin{bmatrix} (y_0 + t)^3 - y_0^3 \\ 3t \end{bmatrix}.$$

Remeshing Example



Remeshing Example



Solution Transfer

Compensated Evaluation

Modified Newton's for Intersection

Difficulties with Curved Elements



Difficulties with Curved Elements