Material Name: DuraForm™ CoCr ASTM75

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product/Trade Name: DuraForm™ CoCr ASTM75 Cobalt Chrome

Powder

Chemical Family: Metal Powder

Product Use: For use with the Sinterstation™ DM100 and DM250

Systems

Hazardous Materials Identification System (HMIS):

(Degree of hazard: 0 = low, 4 =

extreme);

Health **0*** Flammability **0**

Physical Hazards **0**

Personal Protection:

Skin, eye protection

Manufacturer:



Manufacturer Contact	3D Systems, Inc. 333 Three D Systems Circle Rock Hill, SC 29730 U.S.A.
For Information	Phone: 803.326.3900
Emergency	800.424.9300 - Chemtrec

II. COMPOSITION INFORMATION

CAS#	Component	Percent	
7440-48-4	Cobalt	60 – 65	
7440-47-3	Chromium	25 – 35	
7439-98-7	Molybdenum	3 – 7	

OSHA Classification: Irritant, Sensitizer (29 CFR 1910.1200 Appendix A)

III. HAZARDS IDENTIFICATION

Emergency Overview

Can cause sensitization by inhalation and skin contact. May cause long-term adverse effects in the aquatic environment. Use with adequate ventilation. Wash thoroughly after handling.

Potential Health Effects:

Eyes: Can cause irritation consisting of redness, swelling and pain.

Skin: Can cause irritation or other allergic reactions, including redness and/or swelling.

Inhalation: Can cause respiratory irritation.
Ingestion: Not an expected route of entry.

Chronic: Can cause an allergic skin reaction with repeated or prolonged exposure consisting of redness, swelling and/or rash

(urticaria).

Medical Conditions Aggravated by Exposure

Could irritate an existing dermatitis or respiratory condition.

IV. FIRST AID MEASURES



Material Name: DuraForm™ CoCr ASTM75

Skin contact: Immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical

attention if symptoms occur. Wash clothing before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation persists.

Inhalation: Move affected person to fresh air. In case of asphyxia, initiate artificial respiration immediately. If breathing is difficult,

give oxygen. Get medical attention immediately.


Ingestion: Ingestion is unlikely. However, if large quantities are swallowed, get medical attention.

V. FIRE FIGHTING MEASURES

Flash Point: NA Method Used: NA

Upper Flammable Limit (UFL): NA Lower Flammable Limit (LFL): NA

Auto Ignition: Not self-igniting Rate of Burning: NA



General Fire Hazards:

Hazardous Combustion Products:

Extinguishing Media:

Use water mist, dry chemical, carbon dioxide, or chemical foam. Avoid the use of a stream of

Thermal decomposition products can include CO, CO₂, organometalic compounds, and smoke.

water to control fire since dusting can occur.

Fire Fighting Equipment/Instructions: Wear full protective clothing, including helmet, self-contained positive-pressure or pressure-

demand breathing apparatus, protective clothing and facemask. Move container from area if it can be done without risk. Do not use high-volume water jet or high-pressure inert gas since pressure may cause dusting. Avoid inhalation of material or combustion by-products.

VI. ACCIDENTAL RELEASE MEASURES

Containment Procedures: Ensure adequate ventilation. Avoid formation of dust. Do not release material or contaminated water into

drains, soil or surface waters.

Clean-Up Procedures: Wear appropriate protective equipment and clothing. Avoid the generation of dusts during clean up. Clean

mechanically with non-sparking tools. Place material in an appropriate container for disposal.

Evacuation Procedures: Keep unnecessary personnel away.

Special Procedures: A slipping hazard exists when small particles are spilled.

VII. HANDLING AND STORAGE

Handling Procedures: Avoid spilling powders to prevent slip hazards. Avoid dust accumulation of this material.

Storage Procedures: Keep this material in a cool, dry place. Eliminate all sources of ignition.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

General Product Information:

CAS#	Chemical Name	ACGIH TLV	OSHA PEL	NIOSH REL
7440-48-4	Cobalt	0.02 mg/m ³ as Co	0.1 mg/m ³ as Co	0.05 mg/m ³ as Co
		BEI	(for metal dust and fume)	(for metal dust and fume)
7440-47-3	Chromium	0.5 mg/m ³	1 mg/m ³	0.5 mg/m ³
7439-98-7	Molybdenum	10 I (3 R) mg/m ³ as Mo	5 mg/m ³ as Mo	
		(insoluble compounds)	(soluble compounds)	
		0.5 R mg/m ³ as Mo		
		(soluble compounds)		

Engineering Controls

Ventilation must effectively control dusts.

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face: Wear tightly sealed goggles.

Skin: Use impervious gloves, an apron, and closed shoes.

Respiratory: If ventilation cannot effectively keep dust concentrations below established limits, appropriate certified respiratory

Material Name: DuraForm™ CoCr ASTM75

protection must be provided.

General: An eye wash fountain and safety shower are recommended.

IX. PHYSICAL AND CHEMICAL PROPERTIES

 Appearance
 Dark grey
 Odor
 Oderless

 Physical State
 Powder
 PH
 NA

 Vapour Pressure
 NA
 Flash Point
 NA

 Melting Point
 Undetermined
 Viscosity
 NA

X. CHEMICAL STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions of handling, use and transportation.

Incompatibility: None known.

Hazardous Decomposition: Thermal decomposition products can include CO, CO₂, organometalic compounds, and smoke.

Hazardous Polymerization: Will not occur.

XI. TOXICOLOGICAL INFORMATION

Acute and Chronic Toxicity

A: General Product Information: No data available.

B: Component Analysis:

Component	LD ₅₀ Oral	Irritant Effects			
		Irritant to skin and mucous membranes.			
Cobalt	6170 mg/Kg (rats)	Sensitization possible through inhalation.			
		Sensitization possible through skin contact.			

Carcinogenicity

A: General Product Information: None.

B: Component Carcinogenicity:

Component	EPA	IARC	NTP	ACGIH TLV	NIOSH	OSHA
Cobalt		2B		A3		
Chromium		3		A4		
Manganese	D					
Nickle		2B	R	A5	Ca	
Carbon Black		2B			Ca	

XII. ECOLOGICAL INFORMATION

Ecotoxicity

A: General Product Information: The aquatic toxicity of the product is unknown; however based on components, it is predicted that this material may be harmful to aquatic organisms or cause long-term adverse effects in the aquatic

environment. Prevent contamination of soil drains and surface waters.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity:
Environmental Fate: No information available for product.

XIII. DISPOSAL CONSIDERATIONS

Waste Disposal Instructions

Do not contaminate drains, soil or surface waters with the material or its container. Avoid disposal. Attempt to utilize product completely. Dispose of in compliance with all local, state, and federal regulations. Prior to disposal of unused material, 3D Systems Inc., recommends consulting and using an approved waste disposal operative to ensure regulatory compliance.



Material Name: DuraForm™ CoCr ASTM75

XIV.TRANSPORT INFORMATION

	US DOT	RID/ADR	IMDG	IATA	IMO	Canada TDG
Shipping Name			Not R	egulated		

XV. REGULATORY INFORMATION

US FEDERAL

TSCA:

All materials are listed on the TSCA Inventory or are not subject to TSCA requirements

SARA 302 EHS List (40 CFR 355 Appendix A):

None listed

SARA 313 (40 CFR 372.65):

7440-48-4 Cobalt (60 – 65%), 7440-47-3 Chromium (25 – 35%), 7439-96-5 Manganese (trace) 7440-02-0 Nickle (trace)

CERCLA (40 CFR 302.4):

Chromium (Stat Code 2) no reporting required if the particles released are

STATE RIGHT-TO-KNOW STATUS

Component	CA Prop. 65	MI	NJ	PA	MA
Cobalt	X				
Nickle	X				

greater than 100 micrometers in diameter.

Component Analysis - Inventory

Component/CAS	EC#	EEC	CAN	TSCA	NLP
Cobalt (CAS#7440-48-4)	231-158-0	EINECS	DSL	Yes	No
Chromium (CAS#7440-47-3)	231-157-5	EINECS	DSL	Yes	No
Molybdenum (CAS#7439-98-7)	231-107-2	EINECS	DSL	Yes	No

XVI. ADDITIONAL INFORMATION

MSDS Creation Date: July 2, 2008

MSDS Revision #: A MSDS Revision Date:

Reason for Revision: Updated

For more information: www.3dsystems.com

800.793.3669 (Toll-free in the US GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.) 803.326.3900 (Outside the U.S. GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.) +44 144-2282600 (Europe GMT+01:00; Mon – Fri, 08:00 a.m. - 17:00 p.m. MEZ)

DISCLAIMER OF LIABILITY: The following supersedes any related provision in your company's forms, letters, and agreements from, by or with 3D Systems Corporation. 3D Systems Corporation makes no warranty, whether expressed or implied, including warranties of merchantability or of fitness for a particular purpose for this product. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent now or hereafter in existence. Under no circumstances shall 3D Systems Corporation be liable for incidental, consequential, special, or other damages from alleged negligence, breach of warranty, strict liability or any other theory, arising out of the manufacture, use, sale, or handling of this product. In no event shall the liability of 3D Systems Corporation for any claims arising out of the manufacture, use, handling, or sale of its products exceed an amount equal to the buyer's purchase price.

© Copyright 2008 by 3D Systems, Inc. All rights reserved. Subject to change without notice; the 3D logo is a registered trademark of 3D Systems, Inc.



Material Name: DuraForm™ CoCr ASTM75

Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response,

Compensation, and Liability Act

CFR = Code of Federal Regulations

CPR = Controlled Products Regulations

DOT = Department of Transportation

DSL = Domestic Substances List

EINECS = European Inventory of Existing Commercial Chemical Substances

EPA = Environmental Protection Agency

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IDL = Ingredients Disclosure List

mg/Kg = milligrams per Kilogram

mg/L = milligrams per Liter

mg/m3 = milligrams per Cubic Meter

MSHA = Mine Safety and Health Administration

NA = Not Applicable or Not Available

NIOSH = National Institute for Occupational Safety and Health

NJTSR = New Jersey Trade Secret Registry

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

SARA = Superfund Amendments and Reauthorization Act

STEL = Short Term Exposure Limit

TDG = Transport Dangerous Goods

TSCA = Toxic Substances Control Act

WHMIS = Workplace Hazardous Materials Information System.