

Programming with Effect Handlers in Links

PLInG, Autumn 2015, University of Edinburgh

Daniel Hillerström

daniel.hillerstrom@ed.ac.uk

<http://homepages.inf.ed.ac.uk/s1467124/>

November 3, 2015

School of Informatics

The University of Edinburgh

WARNING

This talk may contain traces of jargon such as *monads*, *effects*, *algebras* and *handlers*. However the following code examples in this talk may be performed at home.

What this talk is about

Handlers for algebraic effects provide a compelling alternative to monads as a basis for effectful programming.

- **Key idea:** Separate effect signatures from their implementation.
- **“The effect”:** High-degree of modularity.

Definitions will follow later...

PART 1: Effectively, it's a problem

Programs are inherently effectful

Programs may...

- ...halt prematurely
- ...diverge
- ...be stateful (e.g. modify a global state)
- ...communicate via a network
- ...print to standard out

A pure¹ program is not much fun.

¹By pure we mean a program that has no effects.

Fundamental different approaches to effects

Imperative Repeatedly performs implicit effects on shared global state.

Functional Encapsulates effects in a computational context.

Fundamental different approaches to effects

Imperative Repeatedly performs implicit effects on shared global state.

Functional Encapsulates effects in a computational context.

This talk is oriented around *functional* programming with effects.

Effectful computations (I)

$a \rightarrow b$

Mathematical pure function

$a \rightarrow b$

C/C++ (impure) function

$a \rightarrow b$

ML (impure) function

Let's be explicit about effects

Effect annotation

An effect annotation gives a static description of the potential run-time behaviour of a computation.

Benefits

- Serves as documentation (clarity)
- Compiler can apply specific optimisations
- Possible to reason more precisely about programs

Enter the Monad

"Shall I be pure or impure?"




Figure 1: Philip Wadler aka. Lambda Man

- The Essence of Functional Programming [1]
- The Marriage of Effects and Monads [2]

Effectful computations (II)

$a \rightarrow b$

Mathematical pure function

$a \rightarrow b$

C/C++ (impure) function

$a \rightarrow b$

ML (impure) function

$a \rightarrow m b$

Haskell impure function

Effectful computations (II)

$a \rightarrow b$

Mathematical pure function

$a \rightarrow b$

C/C++ (impure) function

$a \rightarrow b$

ML (impure) function

$a \rightarrow m b$

Haskell impure function

m can be considered an effect annotation

Monads

Definition

A monad is a triple $(m, \text{return}, \text{bind})$ where

- m is a type constructor
- $\text{return} : a \rightarrow m\ a$
- $\text{bind} : m\ a \rightarrow (a \rightarrow m\ b) \rightarrow m\ b$

Great! Many monads, many effects

A couple of monads and their “effect interpretation”

IO a May perform I/O, returns a

Reader r a May read from r , returns a

Writer w a May write to w , returns a

State s a May read/write some state s , returns a

Maybe a May fail, returns a on success

Effectful computations (III)

$a \rightarrow b$

Mathematical pure function

$a \rightarrow b$

C/C++ (impure) function

$a \rightarrow b$

ML (impure) function

$a \rightarrow m_1 m_2 b$

Haskell impure function

$\not\sim$

$a \rightarrow m_2 m_1 b$

IO Monad is equivalent to a calzone pizza



Figure 2: “There’s only meat sauce inside”, they said, but you can’t really be sure.

The importance of effect ordering [3]

Two signatures²:

- $A \stackrel{\text{def}}{=} \text{WriterT String Maybe}$
 - Returns nothing on failure
- $B \stackrel{\text{def}}{=} \text{MaybeT (Writer String)}$
 - Returns a pair on failure

²Elided details about Monad Transformers

PART 2: Exit the Monad, Enter the Handler



Figure 3: Gordon Plotkin



Figure 4: John Power

Algebraic effects and computations

Definition

Algebraic effect An algebraic effect is a collection of abstract operations, e.g. $\{Op_i : a_i \rightarrow b_i\}$

Definition

Abstract computation An abstract computation is composed from abstract operations. Computations have type

Nim: A game with sticks




Set-up

- Two players: Alice and Bob; Alice always starts.
- One heap of n sticks.
- Turn-based. Each player take between 1-3 sticks.
- The one, who takes the last stick, wins.

We'll demonstrate how to encode strategic behaviour, compute game data, and cheat using handlers.

Game tree generated by mtGen with $n = 3$



References



Philip Wadler.

The essence of functional programming.

In *Proceedings of the 19th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, POPL '92, pages 1–14, New York, NY, USA, 1992. ACM.



Philip Wadler and Peter Thiemann.

The marriage of effects and monads.

ACM Trans. Comput. Log., 4(1):1–32, 2003.



Bryan O'Sullivan, John Goerzen, and Don Stewart.

Real World Haskell.

O'Reilly Media, Inc., 1st edition, 2008.



Gordon D. Plotkin and Matija Pretnar.

Handling algebraic effects.

Logical Methods in Computer Science, 9(4), 2013.



Philip Wadler, Sam Lindley, Garrett Morris, et al.

Links: Linking theory to practice for the web.