

**TUGAS PENDAHULUAN
KONSTRUKSI PERANGKAT LUNAK**

**PERTEMUAN 13
Design Pattern Implementation**



**Disusun Oleh :
Mohammad Dhimas Afrizal
2211104023
SE0601**

**Asisten Praktikum :
Naufal El Kamil Aditya Pratama Rahman
Imelda**

**Dosen Pengampu :
Yudha Islami Sulistya, S.Kom., M.Cs.**

**PROGRAM STUDI S1 SOFTWARE ENGINEERING
FAKULTAS INFORMATIKA
TELKOM UNIVERSITY PURWOKERTO
2025**

Source Code

Program.cs

```
1  using System;
2  using System.Collections.Generic;
3  using System.Threading;
4
5  namespace RefactoringGuru.DesignPatterns.Observer.Conceptual
6  {
7      public interface IObserver
8      {
9          // Receive update from subject
10         void Update(ISubject subject);
11     }
12
13     public interface ISubject
14     {
15         // Attach an observer to the subject.
16         void Attach(IObserver observer);
17
18         // Detach an observer from the subject.
19         void Detach(IObserver observer);
20
21         // Notify all observers about an event.
22         void Notify();
23     }
24
25     // The Subject owns some important state and notifies observers when the
26     // state changes.
27     public class Subject : ISubject
28     {
29         // For the sake of simplicity, the Subject's state, essential to all
30         // subscribers, is stored in this variable.
31         public int State { get; set; } = -0;
32
33         // List of subscribers. In real life, the list of subscribers can be
34         // stored more comprehensively (categorized by event type, etc.).
35         private List<IObserver> _observers = new List<IObserver>();
36
37         // The subscription management methods.
38         public void Attach(IObserver observer)
39         {
40             Console.WriteLine("Subject: Attached an observer.");
41             this._observers.Add(observer);
42         }
43
44         public void Detach(IObserver observer)
45         {
46             this._observers.Remove(observer);
47             Console.WriteLine("Subject: Detached an observer.");
48         }
49
50         // Trigger an update in each subscriber.
51         public void Notify()
52         {
53             Console.WriteLine("Subject: Notifying observers...");
54
55             foreach (var observer in _observers)
56             {
57                 observer.Update(this);
58             }
59         }
60     }
```

```

62         // can really do. Subjects commonly hold some important business logic,
63         // that triggers a notification method whenever something important is
64         // about to happen (or after it).
65         public void SomeBusinessLogic()
66         {
67             Console.WriteLine("\nSubject: I'm doing something important.");
68             this.State = new Random().Next(0, 10);
69
70             Thread.Sleep(15);
71
72             Console.WriteLine("Subject: My state has just changed to: " + this.State);
73             this.Notify();
74         }
75     }
76
77     // Concrete Observers react to the updates issued by the Subject they had
78     // been attached to.
79     class ConcreteObserverA : IObserver
80     {
81         public void Update(ISubject subject)
82         {
83             if ((subject as Subject).State < 3)
84             {
85                 Console.WriteLine("ConcreteObserverA: Reacted to the event.");
86             }
87         }
88     }
89
90     class ConcreteObserverB : IObserver
91     {
92         public void Update(ISubject subject)
93         {
94             if ((subject as Subject).State == 0 || (subject as Subject).State >= 2)
95             {
96                 Console.WriteLine("ConcreteObserverB: Reacted to the event.");
97             }
98         }
99     }
100
101     class Program
102     {
103         static void Main(string[] args)
104         {
105             // The client code.
106             var subject = new Subject();
107             var observerA = new ConcreteObserverA();
108             subject.Attach(observerA);
109
110             var observerB = new ConcreteObserverB();
111             subject.Attach(observerB);
112
113             subject.SomeBusinessLogic();
114             subject.SomeBusinessLogic();
115
116             subject.Detach(observerB);
117
118             subject.SomeBusinessLogic();
119         }
120     }
121 }

```

Output

Terminal - tpmodul13_2211104023

```

Subject: Attached an observer.
Subject: Attached an observer.

Subject: I'm doing something important.
Subject: My state has just changed to: 5
Subject: Notifying observers...
ConcreteObserverB: Reacted to the event.

Subject: I'm doing something important.
Subject: My state has just changed to: 7
Subject: Notifying observers...
ConcreteObserverB: Reacted to the event.
Subject: Detached an observer.

Subject: I'm doing something important.
Subject: My state has just changed to: 0
Subject: Notifying observers...
ConcreteObserverA: Reacted to the event.

```

Penjelasan Program

Program ini adalah **implementasi dari *Observer Design Pattern*** dalam bahasa **C#**, yang merupakan bagian dari pola desain perilaku (behavioral design pattern). Pola ini memungkinkan suatu **objek (Subject)** untuk memberi tahu **objek-objek lain (Observers)** saat terjadi perubahan **status** tanpa perlu mengetahui siapa observer tersebut. Tujuannya Untuk **memisahkan hubungan satu-ke-banyak** antara objek, sehingga ketika **satu objek berubah**, maka semua objek lain yang "mengamati" (observer) akan **diberi tahu secara otomatis**.

Struktur Program

Interface

```
public interface IObservable
{
    void Update(ISubject subject);
}

public interface ISubject
{
    void Attach(IObservable observable);
    void Detach(IObservable observable);
    void Notify();
}
```

- **IObservable:** Interface yang wajib diimplementasikan oleh semua observer. Mereka akan menerima pembaruan dari **ISubject**.
- **ISubject:** Interface yang wajib diimplementasikan oleh objek yang diamati. Memiliki metode untuk:
 - **Attach:** Menambahkan observer
 - **Detach:** Menghapus observer
 - **Notify:** Memberi tahu semua observer

Subject (yang diamati)

```
public class Subject : ISubject
{
    public int State { get; set; } = -0;

    private List<IObservable> _observers = new List<IObservable>();

    public void Attach(IObservable observable) { ... }

    public void Detach(IObservable observable) { ... }

    public void Notify() { ... }

    public void SomeBusinessLogic()
    {
        // Melakukan logika bisnis dan mengubah State
    }
}
```

```

        // Lalu memberi tahu observer
    }
}

```

- **State:** Nilai yang menjadi perhatian para observer.
- **SomeBusinessLogic():** Melakukan sesuatu (contoh: ubah nilai state menjadi acak 0–9), lalu memanggil **Notify()** untuk memberitahu semua observer.

Obseever (yang mengamati)

```

class ConcreteObserverA : IObservable
{
    public void Update(ISubject subject)
    {
        if ((subject as Subject).State < 3)
        {
            Console.WriteLine("ConcreteObserverA: Reacted to the event.");
        }
    }
}

class ConcreteObserverB : IObservable
{
    public void Update(ISubject subject)
    {
        if ((subject as Subject).State == 0 || (subject as Subject).State
        >= 2)
        {
            Console.WriteLine("ConcreteObserverB: Reacted to the event.");
        }
    }
}

```

Kedua observer ini punya **logika reaksi berbeda** tergantung nilai dari `Subject.State`.

Main Program

```
class Program
{
    static void Main(string[] args)
    {
        var subject = new Subject();

        var observerA = new ConcreteObserverA();
        subject.Attach(observerA);

        var observerB = new ConcreteObserverB();
        subject.Attach(observerB);

        subject.SomeBusinessLogic(); // Kedua observer bereaksi sesuai
kondisi

        subject.SomeBusinessLogic();

        subject.Detach(observerB); // observerB tidak akan diberi tahu
lagi

        subject.SomeBusinessLogic(); // Hanya observerA yang bereaksi
    }
}
```

Kesimpulan

Program ini adalah **contoh penerapan pola Observer**, berguna saat kamu ingin satu objek (Subject) bisa memperbarui banyak objek (Observers) saat terjadi perubahan, **tanpa ketergantungan langsung** satu sama lain. Cocok digunakan di aplikasi GUI, sistem event, atau sistem notifikasi real-time.