A Scalable Hybrid Authenticated Key Exchange for AMI using Identity-Based Cryptography

Student Name
Submission for Course
University/Institution

November 5, 2025

Abstract

The Advanced Metering Infrastructure (AMI) is a critical component of the smart grid, but its reliance on public networks exposes it to significant security threats. Many existing protocols, such as the one proposed by Hasan et al., depend on a centralized Certificate Authority (CA) for trust, creating a single point of failure and a severe scalability bottleneck for large-scale deployments. This report details the design of a novel protocol, the Hybrid IBE-Authenticated Key Exchange (IBE-AKE-AMI), which addresses this flaw by replacing the CA with an Identity-Based Signature (IBS) scheme. In this model, a device's unique identity serves as its public key, eliminating certificate management. Furthermore, this work identifies and corrects a critical, unstated security flaw in the baseline protocol: its lack of Perfect Forward Secrecy (PFS). The proposed IBE-AKE-AMI protocol integrates an ephemeral Elliptic Curve Diffie-Hellman (ECDH) exchange with the IBS authentication, successfully achieving PFS. A comparative analysis demonstrates that the proposed protocol, while introducing a computationally intensive pairing operation, reduces communication overhead by approximately 93% compared to its PKI-based counterpart.

1 Introduction

The Advanced Metering Infrastructure (AMI) is the foundational communication network for the modern smart grid, enabling real-time, bi-directional communication between utility providers and millions of consumer-side Smart Meters (SMs).[1] This network, which also includes Data Concentrator Units (DCUs) and Head-End Systems (HES), is responsible for transmitting sensitive billing data, energy consumption patterns, and critical grid control commands.[2, 3] As this data often travels over public or semi-public networks (e.g., RF mesh, cellular), a robust Authenticated Key Exchange (AKE) protocol is essential to ensure data confidentiality, integrity, and authenticity.[4]

A recent protocol proposed by Hasan et al. [5] provides a baseline for such an AKE scheme, using a traditional Public Key Infrastructure (PKI) model. In this model, a central Certificate Authority (CA) issues and manages digital certificates for every device in the network.

1.1 Problem Statement

While functional, the reliance on a CA in a massive-scale IoT environment like AMI is a well-documented architectural flaw. As identified in the `NTMC_REPORT.pdf` [6], this centralized CA model introduces two critical issues:

1. **Single Point of Failure:** A compromise or service outage of the CA can halt authentication for the entire network.
2. **Scalability Bottleneck:** The computational and logistical overhead of issuing, distributing, storing, and managing revocation lists (CRLs) for potentially billions of smart meters is operationally untenable.

Furthermore, our analysis of the baseline protocol [5] reveals a second, severe cryptographic flaw. The key agreement mechanism (specified in Table 3 of [5]) is a *static-static* Elliptic Curve Diffie-Hellman (ECDH) exchange. This means the session key is derived directly from the devices' long-term private keys. If an attacker ever compromises these long-term keys, they can retroactively decrypt *all past sessions*, a direct violation of the crucial security property of **Perfect Forward Secrecy (PFS)**.

1.2 Proposed Contribution

This report proposes a novel protocol, the **Hybrid IBE-Authenticated Key Exchange (IBE-AKE-AMI)**, which resolves these flaws. The contributions are as follows:

- **Replaces the CA** with a Private Key Generator (PKG) using an Identity-Based Signature (IBS) scheme, solving the scalability bottleneck.[6, 7]
- **Fixes the PFS Flaw** by integrating the IBS authentication with an *ephemeral* ECDH exchange, ensuring compromises of long-term keys do not affect past session keys.[8]

- **Provides a Full Analysis** of the new protocol, including security, performance, and a discussion of its own inherent drawbacks (and their mitigation).

2 Background and Literature Review

To understand the proposed protocol, we first review the foundational technologies.

2.1 Public Key Infrastructure (PKI)

Traditional PKI, used by the baseline protocol [5], relies on a trusted CA to bind an identity to a public key. Every device must store its private key and a public key certificate (signed by the CA). To authenticate, two devices exchange and verify each other's certificates. This process requires a complex and costly infrastructure for certificate management and revocation.[9]

2.2 Identity-Based Cryptography (IBC)

Proposed by Shamir in 1984 [10], Identity-Based Cryptography (IBC) is an alternative to PKI. In an IBC system [11, 12]:

- A central **Private Key Generator (PKG)** replaces the CA.
- The PKG runs a **Setup** algorithm to generate public *params* and a *master secret key* (*msk*).
- A device's public key is simply its unique identity string, ID (e.g., "SM-SN-A87F9C").
- The PKG runs an **Extract** algorithm, using the *msk*, to generate a corresponding private key sk_{ID} for the device.

This report specifically uses **Identity-Based Signatures (IBS)** [7], a component of IBC. An IBS scheme allows a device to sign a message with its sk_{ID}, and a verifier can check the signature using only the signer's public ID and the global *params*. This eliminates the need for certificates entirely.[13]

2.3 Elliptic Curve Diffie-Hellman (ECDH)

ECDH is a key agreement protocol that allows two parties to establish a shared secret over an insecure channel.[14]

1. Alice generates a private key d_A and public key $Q_A = d_A \cdot G$.
2. Bob generates a private key d_B and public key $Q_B = d_B \cdot G$.
3. They exchange Q_A and Q_B.
4. Alice computes $K = d_A \cdot Q_B = d_A \cdot (d_B \cdot G)$.
5. Bob computes $K = d_B \cdot Q_A = d_B \cdot (d_A \cdot G)$.

Both parties arrive at the same secret K. If d_A and d_B are long-term (static) keys, the protocol does not provide PFS. If they are generated fresh for each session (ephemeral), the protocol provides PFS. The baseline protocol [5] uses a static exchange, which is a critical flaw.

3 System and Threat Models

3.1 System Model

As requested, the system model for the proposed protocol consists of three main entities, replacing the CA with a PKG [11, 12, 15]:

1. **Private Key Generator (PKG):** This is the root trust anchor for the system. It runs the one-time **Setup** algorithm and the **Extract** algorithm for each device during a secure, off-line registration phase.
2. **Smart Meter (SM):** A device at the consumer premise. It has a unique public identity ID_{SM} and a corresponding private key sk_{SM} received from the PKG.
3. **Data Concentrator Unit (DCU):** A utility-owned gateway that aggregates data from many SMs. It has a unique public identity ID_{DCU} and a private key sk_{DCU}.

Figure 1 illustrates this architecture.



Figure 1: Proposed IBE-based System Model

3.2 Threat Model

To analyze the protocol, we adopt the standard **Dolev-Yao (DY) threat model.**[16, 17]

- The adversary A is an active attacker who has complete control over the communication channel (the NAN).
- A can intercept, read, modify, delay, replay, and inject any messages between the SM and DCU.[18]

- The adversary is computationally bounded and cannot break the underlying cryptographic primitives (e.g., solve the ECDH problem or forge an IBS signature).

The protocol is designed to resist the following attacks:

- **Impersonation Attack:** A should not be able to pose as a legitimate SM or DCU.[4, 19]
- **Replay Attack:** A should not be able to succeed by re-sending old, intercepted messages.[5]
- **Man-in-the-Middle (MITM) Attack:** A should not be able to sit between SM and DCU, establishing separate keys with each and relaying messages.
- **Key-Compromise Attack:** A should not be able to compute the session key.
- **PFS Violation:** A, even after compromising the long-term keys sk_{SM} and sk_{DCU}, should not be able to compute *past* session keys.[5]

4 Disadvantages of the IBE Approach (Cons)

While IBE/IBS solves the CA scalability problem [6], it is not a perfect solution and introduces its own significant risks, as requested for this analysis.

4.1 The Key Escrow Problem

The most significant "con" of any IBC system is the inherent **key escrow problem**.[20, 21] During the **Extract** phase, the PKG computes the private key sk_{ID} for *every* device in the network. This means the PKG has the ability to:

- **Passively Eavesdrop:** Decrypt any IBE-encrypted communication (if IBE were used).
- **Actively Impersonate:** Use its knowledge of sk_{ID} to forge an Identity-Based Signature for any device, allowing it to impersonate any SM or DCU at will.

This shifts the "single point of failure" from an *availability* risk (the CA) to a catastrophic *confidentiality and integrity* risk (the PKG).[20]

4.2 Mitigation: Distributed PKG

This is a well-understood problem, and the standard mitigation, as noted in the `NTMC_REPORT.pdf` [6], is to **never allow the master secret key (msk) to exist in a single location**. This is achieved using a **Distributed PKG (dPKG)** based on (t, n)-threshold cryptography.[22]

- The msk is split into n shares, held by n different servers.
- To extract a private key, a device must contact at least t of these servers (e.g., 3-out-of-5).
- Each server provides a *partial* private key. The device combines them to reconstruct its final sk_{ID}.

An attacker must compromise t independent servers to forge a key, making the system highly resilient. **Any real-world deployment of this protocol *must* use a dPKG.**

4.3 Computational Overhead

Most practical IBE/IBS schemes (like those based on Boneh-Lynn-Shacham) rely on a complex operation called a **bilinear pairing** ($e : \mathbb{G}_1 \times \mathbb{G}_2 \to \mathbb{G}_T$).[23] This operation is orders of magnitude slower than the standard ECC scalar multiplication used in ECDSA.[24, 25] This creates a performance trade-off, which is analyzed in Section 7.

5 Complete Protocol Specification

The IBE-AKE-AMI protocol consists of three phases.

5.1 Phase 1: System Setup (One-time)

Run by the PKG to generate global parameters.

1. PKG selects a pairing-friendly curve with groups $\mathbb{G}_1, \mathbb{G}_2, \mathbb{G}_T$ of prime order p and a bilinear map $e : \mathbb{G}_1 \times \mathbb{G}_2 \to \mathbb{G}_T$.
2. PKG selects a generator $P \in \mathbb{G}_2$.
3. PKG selects the master secret key $msk = s \in \mathbb{Z}_p^*$.
4. PKG computes the master public key $P_{pub} = s \cdot P \in \mathbb{G}_2$.
5. PKG defines hash functions: $H_1 : \{0,1\}^* \to \mathbb{G}_1$ and $H_2 : \{0,1\}^* \to \mathbb{Z}_p^*$.
6. PKG selects and publishes standard ECC params (e.g., curve `secp256r1`) for the ECDH part, with generator G.
7. PKG publishes $params = (e, \mathbb{G}_1, \mathbb{G}_2, \mathbb{G}_T, p, P, P_{pub}, H_1, H_2, G)$.

5.2 Phase 2: IBE-Based Registration (Offline)

This phase replaces the "Registration with CA".[5]

1. The SM authenticates to the PKG (e.g., in the factory) and provides its unique identity ID_{SM}.
2. PKG computes $Q_{ID\_SM} = H_1(ID_{SM}) \in \mathbb{G}_1$.
3. PKG uses its msk to extract the SM's private key: $sk_{SM} = s \cdot Q_{ID\_SM} \in \mathbb{G}_1$.
4. PKG securely installs sk_{SM} onto the SM.

5. This process is repeated for the DCU to get sk_{DCU}.

5.3 Phase 3: Mutual Authentication (Online)

This is the 3-message AKE protocol run over the insecure NAN. (Note: $\|$ denotes concatenation).

Step 1: SM → DCU (Message M1)

1. **Generate Ephemeral Key:** SM selects a random $d_{SM} \in \mathbb{Z}_q^*$ and computes $Q_{SM} = d_{SM} \cdot G$.
2. **Get Timestamp:** SM generates a fresh timestamp T_{SM}.
3. **Create Message:** $M_1 = (Q_{SM} \| T_{SM} \| ID_{DCU})$.
4. **Sign Message:** SM computes its IBS signature:
   - $h_1 = H_2(M_1)$
   - $sig_{SM} = h_1 \cdot sk_{SM}$
5. **Send:** SM transmits $M1 = (ID_{SM}, Q_{SM}, T_{SM}, sig_{SM})$ to the DCU.

Step 2: DCU → SM (Message M2)

1. **Verify Timestamp:** DCU checks if T_{SM} is within an acceptable window. If not, abort.
2. **Verify Signature:** DCU authenticates SM:
   - $Q_{ID\_SM} = H_1(ID_{SM})$
   - $h_1 = H_2(Q_{SM} \| T_{SM} \| ID_{DCU})$
   - **Check:** $e(sig_{SM}, P) \stackrel{?}{=} e(h_1 \cdot Q_{ID\_SM}, P_{pub})$
   - If verification fails, abort.
3. **Generate Ephemeral Key:** DCU selects a random $d_{DCU} \in \mathbb{Z}_q^*$ and computes $Q_{DCU} = d_{DCU} \cdot G$.
4. **Compute Shared Secret:** DCU computes the pre-master secret $K = d_{DCU} \cdot Q_{SM}$.
5. **Derive Keys:** DCU uses a KDF (e.g., HKDF) [26]:
   - $Info = (ID_{SM} \| ID_{DCU} \| T_{SM} \| Q_{SM} \| Q_{DCU})$
   - $(SK, K_{MAC}) = KDF(K, Info)$
6. **Sign Response:** $M_2 = (Q_{DCU} \| Q_{SM} \| T_{SM} \| ID_{SM})$
   - $h_2 = H_2(M_2)$
   - $sig_{DCU} = h_2 \cdot sk_{DCU}$
7. **Confirm Key:** $MAC_{DCU} = HMAC(K_{MAC}, \text{"DCU\_CONFIRM"})$.
8. **Send:** DCU transmits $M2 = (ID_{DCU}, Q_{DCU}, sig_{DCU}, MAC_{DCU})$ to the SM.

Step 3: SM → DCU (Message M3)

1. **Verify Signature:** SM authenticates DCU:
   - $Q_{ID\_DCU} = H_1(ID_{DCU})$
   - $h_2 = H_2(Q_{DCU} \| Q_{SM} \| T_{SM} \| ID_{SM})$
   - **Check:** $e(sig_{DCU}, P) \stackrel{?}{=} e(h_2 \cdot Q_{ID\_DCU}, P_{pub})$
   - If verification fails, abort.
2. **Compute Shared Secret:** SM computes $K = d_{SM} \cdot Q_{DCU}$.
3. **Derive Keys:** SM derives the *exact same* (SK, K_{MAC}) using the same KDF and $Info$.
4. **Verify Key Confirmation:** SM checks the DCU's MAC:
   - $MAC_{expected} = HMAC(K_{MAC}, \text{"DCU\_CONFIRM"})$
   - **Check:** $MAC_{expected} \stackrel{?}{=} MAC_{DCU}$
   - If check fails, abort.
5. **Confirm Key:** $MAC_{SM} = HMAC(K_{MAC}, \text{"SM\_CONFIRM"})$.
6. **Send:** SM transmits $M3 = (MAC_{SM})$ to the DCU.

Step 4: DCU (Final Verification)

1. **Verify Key Confirmation:** DCU checks the SM's MAC:
   - $MAC_{expected} = HMAC(K_{MAC}, \text{"SM\_CONFIRM"})$
   - **Check:** $MAC_{expected} \stackrel{?}{=} MAC_{SM}$
   - If check fails, abort.
2. **Session Established:** Both parties now possess the shared session key SK. They securely erase their ephemeral secrets d_{SM} and d_{DCU}.

6 Implementation Prototype

As requested, a basic prototype of the protocol is provided in Python. This implementation uses two key libraries:

- **Charm-Crypto** [27, 28]: A framework for rapid prototyping of advanced cryptosystems. It is used here to implement the pairing-based Identity-Based Signature (IBS) functions.[29]
- **Cryptography** [30]: The standard Python library for common cryptographic primitives. It is used here for the standard ECDH exchange (on `secp256r1`) [31, 32], HKDF, and HMAC-SHA256.

The full prototype code is shown in Listing **??**.

```python
import time
import os
# Charm-Crypto for IBE/IBS (Pairings)
from charm.toolbox.pairinggroup import PairingGroup, ZR, G1, G2
from charm.toolbox.hash_Zr import Hash as Hash_Zr
from charm.toolbox.hash_G1 import Hash as Hash_G1

# Cryptography for ECDH, KDF, HMAC
from cryptography.hazmat.primitives.asymmetric import ec
from cryptography.hazmat.primitives import hashes
from cryptography.hazmat.primitives.kdf.hkdf import HKDF
from cryptography.hazmat.primitives import hmac
from cryptography.hazmat.primitives.serialization import (
    Encoding, PublicFormat, load_pem_public_key
)
from cryptography.exceptions import InvalidSignature

# --- Helper Function for Serialization ---
def serialize(obj):
    """Simple serializer for keys and timestamps."""
    if isinstance(obj, ec.EllipticCurvePublicKey):
        return obj.public_bytes(
            Encoding.PEM, PublicFormat.SubjectPublicKeyInfo
        )
    if isinstance(obj, (int, float)):
        return str(obj).encode('utf-8')
    if isinstance(obj, str):
        return obj.encode('utf-8')
    if isinstance(obj, (bytes, bytearray)):
        return obj
    if isinstance(obj, tuple):
        # Use a non-ambiguous separator
        return b'||'.join(serialize(item) for item in obj)
    return str(obj).encode('utf-8')

# --- Core Protocol Classes ---

class PKG:
    """Implements the Private Key Generator (PKG)"""
    def __init__(self, curve_name='SS512'):
        self.group = PairingGroup(curve_name)
        self.P = self.group.random(G2) # Generator
        self.msk = self.group.random(ZR) # Master Secret
        self.P_pub = self.P * self.msk # Master Public Key

        self.params = {
            'group': self.group, 'P': self.P, 'P_pub': self.P_pub,
            'H1': lambda x: self.group.hash(x, G1), # H1: bytes -> G1
            'H2': lambda x: self.group.hash(x, ZR)  # H2: bytes -> ZR
        }
        print("PKG: Setup complete.")

    def extract(self, ID):
        """Phase 2: Extract private key for an ID"""
        print(f"PKG: Extracting key for ID: {ID}")
        Q_ID = self.params['H1'](serialize(ID))
        sk_ID = Q_ID * self.msk
        return sk_ID

class AuthenticatorDevice:
    """Base class for SM and DCU"""
    def __init__(self, ID, sk_ID, params):
        self.ID = ID
        self.sk_ID = sk_ID  # IBE private key
        self.params = params
        self.group = params['group']
        self.ephemeral_priv_key = None
        self.shared_secret_K = None
        self.SK = None
        self.K_MAC = None

    def _generate_ephemeral_key(self):
        """Generates standard ECDH key pair"""
        self.ephemeral_priv_key = ec.generate_private_key(
            ec.SECP256R1()
        )
        return self.ephemeral_priv_key.public_key()

    def _compute_shared_secret(self, peer_ephemeral_pub_key):
        """Computes K = d * Q_peer"""
        self.shared_secret_K = self.ephemeral_priv_key.exchange(
            ec.ECDH(), peer_ephemeral_pub_key
        )

    def _derive_session_keys(self, info):
        """Derives SK and K_MAC from K using HKDF"""
        hkdf = HKDF(
            algorithm=hashes.SHA256(), length=64, # 32+32
            salt=None, info=serialize(info)
        )
        key_material = hkdf.derive(self.shared_secret_K)
        self.SK = key_material[:32]
        self.K_MAC = key_material[32:]

    def ibe_sign(self, message_tuple):
        """Signs a message tuple using the IBS private key."""
        m_bytes = serialize(message_tuple)
        h = self.params['H2'](m_bytes)
        sig = self.sk_ID * h
        return sig

    def ibe_verify(self, signer_ID, message_tuple, sig):
        """Verifies an IBS signature."""
        try:
            Q_ID = self.params['H1'](serialize(signer_ID))
            m_bytes = serialize(message_tuple)
            h = self.params['H2'](m_bytes)

            # The pairing check: e(sig, P) == e(h*Q_ID, P_pub)
            left = self.group.pair_prod(sig, self.params['P'])
            right = self.group.pair_prod(Q_ID * h,
                                         self.params['P_pub'])
            return left == right
        except Exception:
```

```python
            return False

    def _compute_mac(self, data):
        h = hmac.HMAC(self.K_MAC, hashes.SHA256())
        h.update(serialize(data))
        return h.finalize()

    def _verify_mac(self, data, received_mac):
        try:
            h = hmac.HMAC(self.K_MAC, hashes.SHA256())
            h.update(serialize(data))
            h.verify(received_mac)
            return True
        except InvalidSignature:
            return False

class SmartMeter(AuthenticatorDevice):
    def step_1_initiate(self, dc_id):
        print(f"SM ({self.ID}): Initiating...")
        Q_SM_obj = self._generate_ephemeral_key()
        Q_SM_bytes = serialize(Q_SM_obj)
        self.T_SM = time.time()

        # Store for M3
        self.Q_SM_bytes = Q_SM_bytes

        self.M1_tuple = (Q_SM_bytes, self.T_SM, dc_id)
        sig_SM = self.ibe_sign(self.M1_tuple)

        M1 = (self.ID, Q_SM_bytes, self.T_SM, sig_SM)
        print(f"SM ({self.ID}): Sending M1.")
        return M1

    def step_3_complete(self, M2):
        print(f"SM ({self.ID}): Received M2.")
        (ID_DCU, Q_DCU_bytes, sig_DCU, MAC_DCU) = M2

        # Verify DCU's signature
        M2_tuple = (Q_DCU_bytes, self.Q_SM_bytes, self.T_SM, self.ID)

        if not self.ibe_verify(ID_DCU, M2_tuple, sig_DCU):
            print(f"SM ({self.ID}): *** M2 SIGNATURE FAILED ***")
            return None
        print(f"SM ({self.ID}): M2 signature verified.")

        # Compute shared secret
        Q_DCU = load_pem_public_key(Q_DCU_bytes)
        self._compute_shared_secret(Q_DCU)

        # Derive keys
        kdf_info = (self.ID, ID_DCU, self.T_SM,
                        self.Q_SM_bytes, Q_DCU_bytes)
        self._derive_session_keys(kdf_info)

        # Verify DCU's MAC
        if not self._verify_mac("DCU_CONFIRM", MAC_DCU):
            print(f"SM ({self.ID}): *** M2 MAC FAILED ***")
            return None
        print(f"SM ({self.ID}): M2 MAC verified.")

        # Send own MAC
        MAC_SM = self._compute_mac("SM_CONFIRM")
        print(f"SM ({self.ID}): Sending M3.")
        print(f"SM ({self.ID}): Session key SK = {self.SK.hex()}")
        return (MAC_SM)

class DCU(AuthenticatorDevice):
    def step_2_respond(self, M1):
        print(f"DCU ({self.ID}): Received M1.")
        (ID_SM, Q_SM_bytes, T_SM, sig_SM) = M1

        # Store for later use
        self.T_SM = T_SM
        self.Q_SM_bytes = Q_SM_bytes
        self.ID_SM = ID_SM

        if abs(time.time() - T_SM) > 10.0: # 10 sec window
            print(f"DCU ({self.ID}): *** M1 TIMESTAMP REJECTED ***")
            return None

        # Verify SM's signature
        M1_tuple = (Q_SM_bytes, T_SM, self.ID)
        if not self.ibe_verify(ID_SM, M1_tuple, sig_SM):
            print(f"DCU ({self.ID}): *** M1 SIGNATURE FAILED ***")
            return None
        print(f"DCU ({self.ID}): M1 signature verified.")

        # Generate own keys
        Q_DCU_obj = self._generate_ephemeral_key()
        Q_DCU_bytes = serialize(Q_DCU_obj)

        # Compute shared secret
        Q_SM = load_pem_public_key(Q_SM_bytes)
        self._compute_shared_secret(Q_SM)

        # Derive keys
        kdf_info = (ID_SM, self.ID, T_SM, Q_SM_bytes, Q_DCU_bytes)
        self._derive_session_keys(kdf_info)

        # Create response
        M2_tuple = (Q_DCU_bytes, Q_SM_bytes, T_SM, ID_SM)
        sig_DCU = self.ibe_sign(M2_tuple)
        MAC_DCU = self._compute_mac("DCU_CONFIRM")

        print(f"DCU ({self.ID}): Sending M2.")
        return (self.ID, Q_DCU_bytes, sig_DCU, MAC_DCU)

    def step_4_finalize(self, M3):
        print(f"DCU ({self.ID}): Received M3.")
        (MAC_SM) = M3

        if not self._verify_mac("SM_CONFIRM", MAC_SM):
            print(f"DCU ({self.ID}): *** M3 MAC FAILED ***")
            return False

        print(f"DCU ({self.ID}): M3 MAC verified.")
        print(f"DCU ({self.ID}): Session key SK = {self.SK.hex()}")
```

```
        print(f"\nDCU ({self.ID}): *** SESSION ESTABLISHED ***")
        return True

# --- Main execution block to demonstrate the protocol ---
if __name__ == "__main__":
    print("--- IBE-AKE-AMI Protocol Demonstration ---")

    # --- Phase 1 & 2: Setup and Registration ---
    pkg = PKG(curve_name='SS512')

    SM_ID = "SM-SN-A87F9C001"
    DCU_ID = "DCU-GW-B733A12F"

    sm_private_key = pkg.extract(SM_ID)
    dcu_private_key = pkg.extract(DCU_ID)

    sm = SmartMeter(SM_ID, sm_private_key, pkg.params)
    dcu = DCU(DCU_ID, dcu_private_key, pkg.params)

    # --- Phase 3: Mutual Authentication ---
    print("\n--- Phase 3: Mutual Authentication ---")

    # Step 1: SM -> DCU
    M1 = sm.step_1_initiate(DCU_ID)
    if M1 is None: quit("Protocol Failed at M1")

    #... (network transmission)...

    # Step 2: DCU -> SM
    M2 = dcu.step_2_respond(M1)
    if M2 is None: quit("Protocol Failed at M2")

    #... (network transmission)...

    # Step 3: SM -> DCU
    M3 = sm.step_3_complete(M2)
    if M3 is None: quit("Protocol Failed at M3")

    #... (network transmission)...

    # Step 4: DCU finalizes
    success = dcu.step_4_finalize(M3)
    if not success: quit("Protocol Failed at M4")

    print("\n--- Protocol Analysis ---")
    print(f"SM  SK: {sm.SK.hex()}")
    print(f"DCU SK: {dcu.SK.hex()}")
    assert sm.SK == dcu.SK
    print("Result: Session keys match. Protocol successful.")
```

7 Comparative Analysis

We now compare the proposed IBE-AKE-AMI protocol against the baseline PKI-based protocol from Hasan et al..[5]

7.1 Security Features Comparison

The most significant difference is the correction of the PFS flaw. The proposed protocol achieves true Perfect Forward Secrecy by using ephemeral keys for the ECDH exchange, a feature the baseline protocol [5] claims but does not correctly implement. The trade-off is the introduction of the key escrow problem, which is a known risk of all IBE-based systems [20, 21] and **must** be mitigated with a dPKG.[6]

A full comparison of security features is provided in Table 1.

7.2 Cost Comparison (Communication & Computational)

The shift from PKI to IBS introduces a major performance trade-off: it dramatically reduces communication overhead at the cost of higher computational latency during setup.

7.2.1 Communication Cost

This is the primary advantage of the IBE-AKE protocol. The baseline PKI protocol requires each party to transmit a large X.509 certificate, which can be 2-4 KB in size.[33, 34] Our protocol eliminates this, replacing the certificate with a small, public ID string.

Furthermore, an Identity-Based Signature (e.g., BLS) is often smaller than a standard ECDSA signature. For a 128-bit security level:

- **ECDSA Signature** (baseline): 64 bytes.[25, 35]
- **IBS Signature (BLS)** (proposed): 48 bytes.[25]

As shown in Table 2, this results in a communication overhead reduction of approximately **93.1%**, a massive saving for a low-bandwidth AMI network.

7.2.2 Computational Cost

This is the trade-off. The IBS **verify** operation, which requires bilinear pairings, is significantly more computationally expensive than an ECDSA verification.

- **ECDSA Verify** (baseline): Very fast. Benchmarks range from 0.079 ms [25] to 8.53 ms [36] depending on the curve and platform.
- **IBS Verify (Pairing)** (proposed): Very slow. Benchmarks for a pairing operation are in the range of 2.7 ms to 4.4 ms.[24, 25] The verification requires two such operations.

Therefore, the initial session setup (M2 and M3 verification steps) will be slower. However, for an AMI network, a one-time setup latency of a few milliseconds is an acceptable price to pay for a persistent 93% reduction in bandwidth consumption.

8 Conclusion

This report has detailed the design, specification, and analysis of a novel hybrid authenticated key exchange protocol, IBE-AKE-AMI. The design was motivated by the critical flaws identified in the baseline protocol

Table 1: Comparative Analysis of Security Features

Feature	**Baseline Protocol (Hasan et al. [5])**	**Proposed IBE-AKE-AMI**	**Justification**
Mutual Authentication	Yes	Yes	Both protocols signatures (ECD ify identity.
Session Key Secrecy	Yes	Yes	Both rely on th ECDH problem.
Perfect Forward Secrecy	**No** (Critical Flaw)	**Yes** (Improvement)	Baseline uses st posed protocol us protecting past s
Resists Replay Attacks	Yes	Yes	Both use timest protocol adds a key confirmation
Scalability Bottleneck	**Yes** (CA-based)	**No** (PKG is offline)	The CA is a b tificate issuance/ PKG is only ne registration.
Key Escrow Risk	**No**	**Yes (Inherent)**	The CA does not The PKG *genera* all private keys.[2
Risk Mitigation	N/A	**Yes (dPKG)**	The key escrow "con" that is plementing a threshold PKG.[6

Table 2: Communication Cost Comparison (Authentication)

Parameter	**Baseline (PKI) [5]**	**Proposed (IBE-AKE)**
Certificate ($Cert$)	~2048 bytes	0 bytes
Identity (ID)	0 bytes	~32 bytes
ECDH Public Key (Q)	33 bytes	33 bytes
Signature (sig)	64 bytes (ECDSA)	48 bytes (IBS/BLS)
Timestamp (T)	4 bytes	4 bytes
MAC	~32 bytes	32 bytes
M1	~2085 bytes	**117 bytes**
M2	~2145 bytes	**145 bytes**
M3	~64 bytes	**32 bytes**
Total Overhead	**~4294 bytes**	**~294 bytes**
Reduction	**~93.1%**	

[5, 6], namely its reliance on a centralized CA and its lack of Perfect Forward Secrecy.

The proposed IBE-AKE-AMI protocol successfully addresses both issues.

1. It replaces the CA with an Identity-Based Signature scheme, solving the scalability bottleneck and reducing communication overhead by over 93%.

2. It integrates an ephemeral ECDH exchange with the IBS authentication, achieving true Perfect Forward Secrecy.

The analysis also highlights the primary drawback of this approach: the inherent key escrow problem.[20, 21] This risk is significant but can be effectively mitigated by implementing the PKG as a (t, n)-threshold distributed system.[6]

Given this, the IBE-AKE-AMI protocol is a demonstrably superior solution for securing large-scale AMI networks, provided this mandatory mitigation is in place. It makes a favorable trade-off, accepting a minor increase in computational latency during setup for a massive and permanent reduction in network bandwidth.

References

[1] V. C. Gungor et al., "A survey on smart grid potential applications and communication requirements," *IEEE Trans. Ind. Inform.*, 2012.

[2] M. Benmalek, Y. Challal, and A. Derhab, "Authentication for Smart Grid AMI systems: Threat models, Solutions, and Challenges," *ResearchGate*, 2019. [4]

[3] L. Zhang, S. Tang, and H. Luo, "Elliptic Curve Cryptography-Based Authentication with Identity Protection for Smart Grids," *PLoS ONE*, 2016. [37]

[4] M. N. Yousaf, et al., "Attacks on Authentication and Authorization Models in Smart Grid," *ResearchGate*, 2019. [13]

[5] M. K. Hasan, et al., "A hybrid key agreement scheme utilized elliptic curve Diffie-Hellman for IoT based advanced metering environment," *Earth Science Informatics*, 2024. [1, 38]

[6] NTMC Eval 2 Report - Group 8, "Gaps, Drawbacks, and Proposed Solutions," *Internal Document*, 2024. [1]

[7] G. Sharma and S. Kalra, "A survey on identity-based cryptography and its applications," *Comparative research on... PKI and IBE*, 2017. [36]

[8] F. M. J. Al-Rbaie, et al., "A Hybrid Key Exchange Protocol Based on ECDH and IBE for IoT," *MDPI Electronics*, 2024. [39, 40]

[9] M. Malone, "Everything you ever wanted to know about PKI," *Smallstep Blog*, 2019. [6]

[10] A. Shamir, "Identity-based cryptosystems and signature schemes," *Advances in Cryptology*, 1984.

[11] D. Boneh, "An Overview of Identity Based Encryption," *Stanford University*, 2023. [8]

[12] D. Boneh and M. K. Franklin, "Identity-based encryption from the Weil pairing," *Advances in Cryptology—CRYPTO 2001*, 2001. [41]

[13] E. Kiltz, "Identity-Based Signatures," *Ruhr-University Bochum*, 2010. [11]

[14] T. Perrin, "The Double Ratchet Algorithm (work in progress)," *Signal*, 2016. [32]

[15] D. Appenzeller et al., "Identity-Based Encryption (IBE) Architecture," *RFC 5408*, 2009. [42]

[16] D. Dolev and A. C. Yao, "On the Security of Public Key Protocols," *IEEE Transactions on Information Theory*, 1983. [43]

[17] Wikipedia, "Dolev–Yao model," *Wikipedia, The Free Encyclopedia*, 2024. [23]

[18] B. R. Preneel, "The Dolev-Yao model," *Cornell University*, 2005. [24]

[19] M. A. R. Chaudhry et al., "A Secure and Lightweight Authentication Scheme for Smart Meter Impersonation Attack," *MDPI Sensors*, 2024. [25]

[20] M. A. Khan, "Analyzing the Key Escrow Problem in Identity Based Cryptography," *ResearchGate*, 2024. [3]

[21] H. Abelson, et al., "The Risks of Key Recovery, Key Escrow, and Trusted Third-Party Encryption," *Schneier on Security*, 1998. [44]

[22] D. Boneh, "Identity Based Encryption," *Stanford University*, 2014. [45]

[23] C. Costello, "Pairing for Beginners," *IACR ePrint*, 2016.

[24] H. Mohsen, "How to estimate the computation overhead of ECDSA?" *Cryptography Stack Exchange*, 2020. [21]

[25] IETF, "BLS Signatures," *draft-irtf-cfrg-bls-signature-05*, 2020. [22]

[26] H. Krawczyk and P. Eronen, "HMAC-based Extract-and-Expand Key Derivation Function (HKDF)," *RFC 5869*, 2010. [32]

[27] "Charm: A Framework for Rapidly Prototyping Cryptosystems," *JHU Information Security Institute*, GitHub Repository. [26]

[28] J. A. Akinyele, et al., "Charm: an extensible Python-based framework for rapidly prototyping cryptographic systems," *NDSS*, 2017. [46]

[29] "Identity-based signatures (IBSig)," *Charm-Crypto Documentation*. [9]

[30] "Cryptography," *Python Cryptographic Authority*, 2024. [47]

[31] "Elliptic curve cryptography," *Cryptography.io Documentation*, 2024. [48]

[32] "Generate Keypair Using ECDH in Python," *SSOJet*, 2024. [28, 29]

[33] "Identity-Based Cryptography vs. PKI," *Thales CPL Blog*, 2023. [33]

[34] G. Ferrari, et al., "On the Performance of Identity-Based Cryptography," *Medium*, 2010.

[35] "What is the size of a digital signature?" *Cryptography Stack Exchange*, 2020. [34]

[36] "Signatures: RSA compared to ECDSA," *Cryptography Stack Exchange*, 2010. [49]