

```

In [1]: from pathlib import Path
import os
import sqlite3

import s3fs
import pandas as pd

current_dir = Path(os.getcwd()).absolute()
results_dir = current_dir.joinpath('results')
kv_data_dir = results_dir.joinpath('kvdb')
kv_data_dir.mkdir(parents=True, exist_ok=True)

def read_cluster_csv(file_path, endpoint_url='https://storage.budsc.midwest
s3 = s3fs.S3FileSystem(
    anon=True,
    client_kwargs={
        'endpoint_url': endpoint_url
    }
)
return pd.read_csv(s3.open(file_path, mode='rb'))

```

```

In [2]: def create_measurements_table(conn):
sql = """
CREATE TABLE IF NOT EXISTS measurements (
    visit_id integer NOT NULL,
    person_id text NOT NULL,
    quantity text,
    reading real,
    FOREIGN KEY (visit_id) REFERENCES visits (visit_id),
    FOREIGN KEY (person_id) REFERENCES people (people_id)
);
"""

c = conn.cursor()
c.execute(sql)

def load_measurements_table(conn):
create_measurements_table(conn)
df_m = read_cluster_csv('data/external/tidynomicon/measurements.csv')
measurements = df_m.values
c = conn.cursor()
c.execute('DELETE FROM measurements;') # Delete data if exists
c.executemany('INSERT INTO measurements VALUES (?,?,?,?)', measurements

```

```
In [3]: def create_people_table(conn):
        sql = """
        CREATE TABLE IF NOT EXISTS people (
            people_id text NOT NULL,
            personal_name text,
            family_name text
        );
        """

        c = conn.cursor()
        c.execute(sql)

    def load_people_table(conn):
        create_people_table(conn)
        df = read_cluster_csv('data/external/tidynomicon/person.csv')
        people = df.values
        c = conn.cursor()
        c.execute('DELETE FROM people;') # Delete data if exists
        c.executemany('INSERT INTO people VALUES (?, ?, ?)', people)
```

```
In [4]: def create_sites_table(conn):
        sql = """
        CREATE TABLE IF NOT EXISTS sites (
            site_id text PRIMARY KEY,
            latitude double NOT NULL,
            longitude double NOT NULL
        );
        """

        c = conn.cursor()
        c.execute(sql)

    def load_sites_table(conn):
        create_sites_table(conn)
        df_s = read_cluster_csv('data/external/tidynomicon/site.csv')
        sites = df_s.values
        c = conn.cursor()
        c.execute('DELETE FROM sites;') # Delete data if exists
        c.executemany('INSERT INTO sites VALUES (?, ?, ?)', sites)
```

```
In [5]: def create_visits_table(conn):
        sql = """
        CREATE TABLE IF NOT EXISTS visits (
            visit_id integer PRIMARY KEY,
            site_id text NOT NULL,
            visit_date text,
            FOREIGN KEY (site_id) REFERENCES sites (site_id)
        );
        """

        c = conn.cursor()
        c.execute(sql)

    def load_visits_table(conn):
        create_visits_table(conn)
        df_v = read_cluster_csv('data/external/tidynomicon/visited.csv')
        visits = df_v.values
        c = conn.cursor()
        c.execute('DELETE FROM visits;') # Delete data if exists
        c.executemany('INSERT INTO visits VALUES (?, ?, ?)', visits)
```

```
In [6]: db_path = results_dir.joinpath('patient-info.db')
        conn = sqlite3.connect(str(db_path))
```

```
        load_people_table(conn)
        load_sites_table(conn)
        load_visits_table(conn)
        load_measurements_table(conn)

        sql = """SELECT * FROM visits;"""

        c = conn.cursor()
        c.execute(sql)

        result = c.fetchall

        print(result)
        conn.commit()
        conn.close()
```

<built-in method fetchall of sqlite3.Cursor object at 0x7f63c19dadcd>

```
In [ ]:
```