

(1) Implement the following:

(a) Design an employee class for reading and displaying the employee information, the getInfo() and displayInfo() methods will be used respectively. Where getInfo() will be private method.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class employee
```

```
{
```

```
    char name[20];
```

```
    int age;
```

```
    float basic_sal;
```

```
    void getInfo()
```

```
    {
```

```
        cout<<endl<<"Enter name: ";
```

```
        cin>>name;
```

```
        cout<<endl<<"Enter age: ";
```

```
        cin>>age;
```

```
        cout<<endl<<"Enter basic salary: ";
```

```
        cin>>basic_sal;
```

```
    }
```

```
    public: void
```

```
    displayInfo()
```

```
    {
```

```
        getInfo();
```

```
        cout<<endl<<"\tEMPLOYEE INFORMATION\n";
```

```
        cout<<"\t-----";
```

```
        cout<<endl<<" Name: "<<name;
```

```
        cout<<endl<<" Age: "<<age;
```

```
        cout<<endl<<" Basic Salary: "<<basic_sal;
```

```
        cout<<endl<<" Gross Salary: "<<basic_sal + (0.6*basic_sal) +  
(0.4*basic_sal);
```

```
    }
```

};

```
void main()
{
    clrscr();
    employee e;

    e.displayInfo();
    getch();
}
```

Output:

Enter name: Dhiraj

Enter age: 33

Enter basic salary: 8000

EMPLOYEE INFORMATION

Name: Dhiraj

Age: 33

Basic Salary: 8000

Gross Salary: 16000

(b) Design the class student containing getData() and displayData() as two of its methods which will be used for reading and displaying the student information respectively. Where getData() will be private method.

#include<iostream.h>

#include<conio.h>

```
class student
{
```

```
char name[20];
int age; float
percentage; void
getData()
{
    cout<<endl<<"Enter name: ";
    cin>>name; cout<<endl<<"Enter
age: "; cin>>age;
    cout<<endl<<"Enter percentage: ";
    cin>>percentage;
}

public: void
displayData()
{
    getData();
    cout<<endl<<"\tSTUDENT INFORMATION\n";
    cout<<"\t-----";
    cout<<endl<<" Name: "<<name;
    cout<<endl<<" Age: "<<age; cout<<endl<<"
Percentage: "<<percentage;
}
};

void main()
{
    clrscr();
    student s;

    s.displayData();
    getch();
}
```

Output:

Enter name: Dhiraj

Enter age: 33

Enter percentage: 73

STUDENT INFORMATION

Name: Dhiraj

Age: 33

Percentage: 73

(c) Design the class Demo which will contain the following methods: readNo() ,factorial() for calculating the factorial of a number, reverseNo() will reverse the given number, isPalindrome() will check the given number is palindrome, isArmstrong() which will calculate the given number is armStrong or not.Where readNo() will be private method.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class Demo
```

```
{
```

```
int n,nn;
```

```
void readNo()
```

```
{
```

```
cout<<"\nEnter a number: ";
```

```
cin>>n;
```

```
}
```

```
public: int
```

```
factorial()
```

```
{
```

```
readNo();
```

```
int f=1;
```

```
while(n>0)
{
    f=f*n;
n--;
}
return f;
}
```

```
int reverseNo()
{
    readNo();
int d,num=0;
nn=n;
while(n>0)
{
    d=n%10;
num=num*10+d;   n=n/10;
}
return num;
}
```

```
int isPalindrome()
{
    int revnum=reverseNo();
if(nn==revnum)
    return 1;
else
    return 0;
}
```

```
int isArmstrong()
{
    readNo();
int nn=n,sum=0,d;
```

```
while(n>0)
{
    d=n%10;
    sum=sum+(d*d*d);    n=n/10;
}
```

```
if(nn==sum)
    return 1;
else
    return 0;
}
};
```

```
void main()
{
    clrscr();
    Demo d;
    int res;
    cout<<endl<<"To find out Factorial of Input Number\n";
    cout<<"-----";
    res=d.factorial();
    cout<<endl<<"Factorial= "<<res;
    cout<<endl<<"\nTo find out the reverse of Input Number\n";
    cout<<"-----";
    res=d.reverseNo();
    cout<<endl<<"Reverse = "<<res;

    cout<<endl<<"\nTo check whether input number is palindrome\n";
    cout<<"-----";
    if(d.isPalindrome())
        cout<<"\nNumber is palindrome";
    else
        cout<<"\nNumber is not palindrome";
```

```
cout<<endl<<"\nTo check whether input number is Armstrong\n";  
cout<<"-----";
```

```
if(d.isArmstrong())  
    cout<<"\nNumber is armstrong";  
else  
    cout<<"\nNumber is not armstrong";  
getch();  
}
```

Output:

To find out Factorial of Input Number

Enter a number: 5

Factorial= 120

To find out the reverse of Input Number

Enter a number: 1234

Reverse = 4321

To check whether input number is palindrome

Enter a number: 12321

Number is palindrome

To check whether input number is Armstrong

Enter a number: 154

Number is not Armstrong

(d) Write a program to demonstrate function definition outside class and accessing class members in function definition.

```
#include<iostream.h> #include<conio.h>
```

```
class Student
```

```
{
    int roll_no;
    char name [30];
    float percentage;
public:
    void getdata ();
    void show ();
};
void Student:: getdata ()
{
    cout <<"Enter Roll No:
";    cin >> roll_no;
    cout << endl <<"Enter name:
";    cin >> name;
    cout << endl <<"Enter Percentage:
";    cin >> percentage;
}
void Student:: show ()
{
    cout << endl <<"Roll No: " << roll_no;
    cout << endl <<"Name: " << name;    cout <<
endl <<"Percentage: " <<percentage;
}
```

```
void main()
{
    clrscr();
    Student studObj;
    studObj.getdata();
    studObj.show(); getch();
}
```

Output:

Enter Roll No: 101

Enter name: Dhiraj

Enter percentage: 78

Roll No: 101

Name: Dhiraj

Percentage: 78

(2) Implement the following

(a) Write a friend function for adding the two complex numbers, using a single class.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class complex
```

```
{
```

```
    float n,m;
```

```
public:
```

```
    void getData()
```

```
    {
```

```
        cout<<"\nEnter real number: ";
```

```
    cin>>n;
```

```
        cout<<"\nEnter imaginary number: ";
```

```
    cin>>m;
```

```
    }
```

```
    void showData()
```

```
    {
```

```
        cout<< n <<" + j"<< m ;
```

```
    }
```

```
    friend complex sum(complex, complex);
```

```
};
```

```
complex sum(complex c1, complex c2)
```

```
{
```

```
    complex c3;
```

```
    c3.n=c1.n+c2.n;
```

```
c3.m=c1.m+c2.m; return
```

```
c3;
```

```
}
```

```
void main()
```

```
{
```

```
clrscr(); complex obj1,
```

```
obj2, obj3;
```

```
cout<<"\nEnter Data for 1st Complex Number \n";
```

```
cout<<"-----";
```

```
obj1.getData();
```

```
cout<<"\nEnter Data for 2nd Complex Number \n";
```

```
cout<<"-----";
```

```
obj2.getData();
```

```
obj3=sum(obj1,obj2);
```

```
cout<<"\nComplex Number1: ";
```

```
obj1.showData();
```

```
cout<<"\nComplex Number2: ";
```

```
obj2.showData(); cout<<"\nComplex
```

```
Number3: ";
```

```
obj3.showData();
```

```
getch();
```

```
}
```

Output:

Enter Data for 1st Complex Number

Enter real number: 1.2

Enter imaginary number: 2.4

Enter Data for 2nd Complex Number

Enter real number: 4.5

Enter imaginary number: 6.4

Complex Number1: $1.2 + j2.4$

Complex Number2: $4.5 + j6.4$

Complex Number3: $5.7 + j8.8$

(b) Write a friend function for adding the two different distances and display its sum, using two classes.

```
#include<iostream.h>
#include<conio.h> class
distance2;
class distance1
{ int
feet; int
inch;

public: void
getData()
{
cout<<"\nEnter feet: ";
cin>>feet; cout<<"\nEnter
inches: "; cin>>inch;
}

void showData()
{
cout<< feet <<"-" <<inch<<"\n";
}

friend void sum(distance1, distance2);
};

class distance2
{
int feet,inch;
```

```
public: void
getData()
{
    cout<<"\nEnter feet: ";
    cin>>feet; cout<<"\nEnter
inches: "; cin>>inch;
}

void showData()
{
    cout<< feet<<"-"<<inch <<"\n" ;
}
friend void sum(distance1, distance2);
};

void sum(distance1 d1, distance2 d2)
{
    int f=d1.feet+d2.feet;
    int i=d1.inch+d2.inch;

    if(i>=12)
    {
        i=i-12;
f++;
    }
    cout<< f<<"-"<<i <<"\n" ;
}

void main()
{
    clrscr(); distance1 obj1; distance2 obj2;
    cout<<"\nEnter Data for 1st Distance \n";
    cout<<"-----";
```

```
obj1.getData(); cout<<"\nEnter Data for  
2nd Distance \n"; cout<<"-----  
-----"; obj2.getData();
```

```
cout<<"\nDistance1: ";  
obj1.showData();
```

```
cout<<"\nDistance2: ";  
obj2.showData();
```

```
cout<<"\nDistance3: ";  
sum(obj1,obj2); getch();  
}
```

Output:

Enter Data for 1st Distance

Enter feet: 12

Enter inches: 7

Enter Data for 2nd Distance

Enter feet: 2

Enter inches: 8

Distance1: 12'-7"

Distance2: 2'-8"

Distance3: 15'-3"

(c) Write a friend function for adding the two matrix from two different classes and display its sum.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class matrix2;
```

```
class matrix1
```

```
{
```

```
int a[3][3];
```

```
public:
```

```
void getData()
```

```
{
```

```
for(int i=0;i<3;i++)
```

```
{
```

```
for(int j=0;j<3;j++)
```

```
cin>>a[i][j];
```

```
}
```

```
}
```

```
void showData()
```

```
{
```

```
for(int i=0;i<3;i++)
```

```
{
```

```
for(int j=0;j<3;j++)
```

```
cout<<a[i][j]<<" ";
```

```
cout<<endl;
```

```
}
```

```
}
```

```
friend void sum(matrix1, matrix2);
```

```
};
```

```
class matrix2
```

```
{ int
a[3][3];
public:
    void getData()
    {
        for(int i=0;i<3;i++)
        {
            for(int j=0;j<3;j++)
                cin>>a[i][j];
        }
    }

    void showData()
    {
        for(int i=0;i<3;i++)
        {
            for(int j=0;j<3;j++)
                cout<<a[i][j]<<" ";
            cout<<endl;
        }
    }

    friend void sum(matrix1, matrix2);
};

void sum(matrix1 m1, matrix2 m2)
{
    int a[3][3];
    for(int i=0;i<3;i++)
    {
        for(int j=0;j<3;j++)
        {
            a[i][j]=m1.a[i][j] + m2.a[i][j];
            cout<<a[i][j]<<" ";
        }
    }
}
```

```
        }
        cout<<endl;
    }
}

void main()
{
    clrscr(); matrix1 obj1; matrix2 obj2;
    cout<<"\nEnter Data for 1st Matrix \n";
    cout<<"-----\n";
    obj1.getData(); cout<<"\nEnter Data for
    2nd Matrix \n"; cout<<"-----
    ---\n"; obj2.getData();

    cout<<"\nMatrix1: \n";
    obj1.showData();

    cout<<"\nMatrix2: \n";
    obj2.showData();

    cout<<"\nMatrix3: \n";

    sum(obj1,obj2);

    getch();
}
```

Output:

```
Enter Data for 1st Matrix
----- 1
2 3
4 5 6
7 8 9
Enter Data for 2nd Matrix
----- 1
2 3
```


4 5 6

7 8 9

Matrix1:

1 2 3

4 5 6

7 8 9

Matrix2:

1 2 3

4 5 6

7 8 9

Matrix3:

2 4 6

8 10 12

14 16 18

(3) Implement the following:

(a) Design a class Complex for adding the two complex numbers and also show the use of constructor.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class complex
```

```
{
```

```
    float n,m;
```

```
public: complex()
```

```
{
```

```
    n=0;
```

```
    m=0;
```

```
}
```

```
complex(int a, int b)
```

```
{
    n=a;
    m=b;
}
void showData()
{
    cout<< n <<" + j"<< m ;
}

complex sum(complex c1)
{
    complex c3;
    c3.n=n+c1.n;
    c3.m=m+c1.m; return
    c3;
}
};

void main()
{
    clrscr();
    complex obj1(3,4);
    complex obj2(4,5);
    complex obj3;

    obj3=obj1.sum(obj2);
    cout<<"\nComplex Number1: ";
    obj1.showData();

    cout<<"\nComplex Number2: ";
    obj2.showData(); cout<<"\nComplex
    Number3: "; obj3.showData();
    getch();
}
```

Output:

Complex Number1: $3 + j4$

Complex Number2: $4 + j5$ Complex Number3: $7 + j9$

(b) Design a class Geometry containing the methods area() and volume() and also overload the area() function .

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class geometry
```

```
{ int l,b;
```

```
public: int
```

```
area(int x)
```

```
{
```

```
l=b=x;
```

```
return(l*b);
```

```
}
```

```
int area(int x, int y)
```

```
{ l=x; b=y;
```

```
return(l*b);
```

```
}
```

```
int volume(int x)
```

```
{
```

```
l=x;
```

```
return(l*l*l);
```

```
}
```

```
};
```

```
void main()
```

```
{
```

```
clrscr();
```

```
geometry g;
```

```
cout<<"\nArea of square= "<<g.area(10);
cout<<"\nArea of rectangle= "<<g.area(10,15);
cout<<"\nVolume of cube= "<<g.volume(6);
getch();
}
```

Output:

Area of square= 100
Area of rectangle= 150
Volume of cube= 216

(c) Design a class Static Demo to show the implementation of static variable and static function.

```
#include<iostream.h>
#include<conio.h> #include<stdio.h>
class student
{
    int roll_no;
    char name[30];
    float percent;
    static int c;
public:
    void get()
    {
        cout<<"\nEnter Name:"; gets(name);
        cout<<"\nEnter percentage:"; cin>>percent;
        roll_no=++c;
    }
    void show()
    {
        cout<<"\nRoll No:"<<roll_no; cout<<"\nName:"<<name;
        cout<<"\nPercentage:"<<percent;
        cout<<"\n\n\tTotal number of students admitted:"<<c;
    }
}
```

```
int student::c;
```

```
void main()
{ clrscr(); student s1,s2; s1.get();
  s2.get(); cout<<"\n Object 1
  Data";
  cout<<"\n*****";
  s1.show(); cout<<"\nObject 2
  Data";
  cout<<"\n*****";
  s2.show();
  getch();
}
```

Output:

Enter Name: DhirajSagar

Enter percentage: 78

Enter Name: Rakesh Sagar

Enter percentage: 96

Object 1 Data

Roll No: 1

Name: DhirajSagar

Percentage: 78

Total number of students admitted: 2

Object 2 Data

Roll No: 2

Name: Rakesh Sagar

Percentage: 96

Total number of students admitted: 2

```
#include<iostream.h>
#include<conio.h> #include<stdio.h>
class student
{
    int
    roll_no;
    char name[30];
    float percent;
    static int c;

    public:
        void get()
        {
            cout<<"\nEnter Name:";
            gets(name);
            cout<<"\nEnter percentage:";   cin>>percent;
            roll_no=++c;
        }
        void show()
        {
            cout<<"\nRoll No:"<<roll_no;   cout<<"\nName:"<<name;
            cout<<"\nPercentage:"<<percent;
        }
        static void show_count()
        {
            cout<<"\n\n\tTotal number of students admitted:"<<c;
        }
};

int student::c;
void main()
{ clrscr(); student
  s1,s2,s3;
  s1.get(); s2.get();
  s3.get();
  cout<<"\n
```

```
Object 1 Data";
cout<<"\n*****
*****",
s1.show();
cout<<"\n\nObject 2 Data";
cout<<"\n*****
*****",
s2.show();
cout<<"\n\nObject 3 Data";
cout<<"\n*****
*****",
s3.show();
student::show_count();
getch();
}
```

Output:

```
Enter Name: Dhiraj
Enter percentage: 77
Enter Name: Rakesh
Enter percentage: 88
Enter Name: Tarun
Enter percentage: 87
```

Object 1 Data

Roll No: 1

Name: Dhiraj

Percentage: 77

Object 2 Data

Roll No: 2

Name: Rakesh

Percentage: 88

Object 3 Data

Roll No: 3

Name: Tarun

Percentage: 87

Total number of students admitted: 3

(4) Implement the following

(a) Overload the operator unary(-) for demonstrating operator overloading.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class abc
```

```
{
```

```
int a,b,c;
```

```
public:
```

```
void get()
```

```
{
```

```
cout<<"\nEnter three numbers: ";
```

```
cin>>a>>b>>c;
```

```
}
```

```
void show()
```

```
{
```

```
cout<<"\n\nA= "<<a<<"\tB= "<<b<<"\tC= "<<c;
```

```
}
```



```
void operator -()
{
    a= -a;
b= -b;
    c= -c;
}

};

void main()
{
clrscr();
abc a1;
    a1.get();
    cout<<"\n\n Original contents";
    a1.show();
    -a1;
    cout<<"\n\n After Negation";
    a1.show();
    getch();
}
```

Output:

Enter three numbers: 5

-6

7

Original contents

A= 5 B= -6 C= 7

After Negation

A= -5 B= 6 C= -7

(b) Overload the operator + for adding the timings of two clocks, And also pass objects as an argument.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class time
```

```
{
```

```
    int hrs,min,sec;
```

```
public:
```

```
    void get()
```

```
    {
```

```
        cout<<"\n\tEnter time (in hrs:minutes:seconds form): ";
```

```
        cin>>hrs>>min>>sec;
```

```
    }
```

```
    void show()
```

```
    {
```

```
        cout<<"\n"<<hrs<<":"<<min<<":"<<sec;
```

```
    }
```

```
time operator +(time t2)
```

```
{
```

```
    time t3;    t3.sec=sec + t2.sec;
```

```
    t3.min=min + t2.min + (t3.sec/60);
```

```
    t3.sec=t3.sec%60;    t3.hrs=hrs +
```

```
    t2.hrs + (t3.min/60);
```

```
    t3.min=t3.min%60;
```

```
    return t3;
```

```
}
```

```
};
```

```
void main()
```

```
{    clrscr();
```

```
time t1,t2,t3;
```

```
t1.get();
```

```
t2.get();
```

```
t1.show();
t2.show();
t3=t1 + t2;
t3.show();
    getch();
}
```

Output:

```
Enter time (in hrs:minutes:seconds form): 10 30 40
Enter time (in hrs:minutes:seconds form): 5 40 30
10:30:40           // time 1
5:40:30            // time2
16:11:10           // time1 + time2
```

(c) Overload the + for concatenating the two strings. For e.g "c" + "++" =
c++

```
#include<iostream.h>
#include<conio.h>
#include<string.h>
```

```
class string
{
    char str[60];
```

```
public:
    void get()
    {
        cout<<"\n\tEnter a string: ";
        cin>>str;
    }
```

```
void show()
{
    cout<<"\n"<<str;
```

```
string operator +(string s2)
{
    string s3;
    strcpy(s3.str,str);
    strcat(s3.str,s2.str);    return
    s3;
}
};
```

```
void main()
{    clrscr();
string s1,s2,s3;
s1.get();    s2.get();
cout<<"\nString 1";
s1.show();
cout<<"\nString 2";
    s2.show();
    cout<<"\nAfter concatenation String 3";
s3=s1 + s2;    s3.show();
    getch();
}
```

Output:

Enter a string: Dhiraj

Enter a string: Sagar

String 1

Dhiraj

String 2

Sagar

After concatenation String 3

SanjeelaSagar

(5) Implement the following

(a) Design a class for single level inheritance using public and private type derivation.

(1) Using public type derivation:

```
#include<iostream.h>
#include<conio.h>  class
base
{
int n;

public:
    void get()
    {
        cout<<"\nEnter value for n:";
        cin>>n;
    }

    void show()
    {
        cout<<"\n\t\tN="<<n;
    }
};

class derived:public base
{
int b;
public:
    void get()
    {
        base::get();
```

```
        cout<<"\nEnter value for b: ";
        cin>>b;
    }

};

void main()
{
    clrscr();
    derived d1;
    d1.get();
    d1.show();

    getch();
}
```

Output:

```
Enter value for n:5
Enter value for b: 7
    N=5
```

(2) Using private type derivation:

```
#include<iostream.h>
#include<conio.h>

class base
{
int n;

public:
    void get()
    {
        cout<<"\nEnter value for n:";
        cin>>n;
    }
}
```

```
void show()
{
    cout<<"\n\t\tN="<<n;
}

};

class derived:private base
{
int b;
public:
    void get()
    {
        base::get();
        cout<<"\nEnter value for b: ";
        cin>>b;
    }
    void display()
    {
        show();
    }
};

void main()
{
    clrscr();
    derived d1;
    d1.get();
    // d1.show(); not accessible as its scope is private
    d1.display();
    getch();
}
```

Output:

Enter value for n:5

Enter value for b: 6

(b) Design a class for multiple inheritance.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class internal
{
int n;

public:
    void get()
    {
        cout<<"\nEnter n: ";
cin>>n;
    }
    int n_return()
    {
        return n;
    }

    void show()
    {
        cout<<"\n\nInternal marks: "<<n;
    }
};

class external
{
int m;
public:
    void get()
    {
```



```
        cout<<"\nEnter m: ";
cin>>m;
    }

    int m_return()
    {
        return m;
    }

    void show()
    {
        cout<<"\nM: "<<m;
    }
};

class final:public internal, public external
{
    float tot;
public:

    void get()
    {
        internal::get();
        external::get();
    }
    void show()
    {
        tot=internal::n_return()+external::m_return();
        cout<<"\nTotal: "<<tot;
    }
};

void main()
{
    clrscr();
    final t;
```

```
t.get();  
t.show();
```

```
getch();  
}
```

Output:

Enter n: 5

Enter m: 4

Total: 9

(c) Implement the hierarchical inheritance.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class person
```

```
{
```

```
    char name[30];
```

```
    int age;
```

```
public:
```

```
    void getdata()
```

```
    {
```

```
        cout<<"\nEnter name and age: ";
```

```
        cin>>name>>age;
```

```
    }
```

```
    void showdata()
```

```
    {
```

```
        cout<<"\nName: "<<name;
```

```
        cout<<"\nAge: "<<age;
```

```
    }
```

```
};
```

```
class student:public person
```

```
{
```

```
int marks;
public:
    void get()
    {
        getdata();
    }
    cout<<"\nEnter marks: ";
    cin>>marks;
}

    void show()
    {
        showdata();
    }
    cout<<"\nMarks: "<<marks;
}

};
class employee:public person
{
    char design[30];
public:
    void get()
    {
        getdata();
        cout<<"\nEnter designation: ";
        cin>>design;
    }
    void show()
    {
        showdata();
        cout<<"\nDesignation: "<<design;
    }
};

void main()
{
    clrscr();    student s;
    employee e;    cout<<"\nEnter
student's data";
```

```
s.get();  
cout<<"\n\nEnter employee's data";  
e.get();  
cout<<"\n\nstudent's Data";  
s.show();    cout<<"\n\nEmployee's  
Data";    e.show();  
  
    getch();  
}
```

Output:

Enter student's data

Enter name and age: Dhiraj

33

Enter marks: 72

Enter employee's data

Enter name and age: Rakesh

35

Enter designation: Manager

student's Data Name:

Dhiraj

Age: 33

Marks: 72

Employee's Data

Name: Rakesh

Age: 35

Designation: Manager

(6) Implement the following

(a) Implement the concept of method overriding.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class employee
```

```
{
```

```
    int emp_code,age;
```

```
    char name[30], qualification[30];
```

```
public:
```

```
    void get()
```

```
    {
```

```
        cout<<"\nEnter employee id: ";
```

```
        cin>>emp_code;
```

```
        cout<<"\nEnter employee name: ";
```

```
        cin>>name;
```

```
        cout<<"\nEnter employee age: ";
```

```
        cin>>age;
```

```
        cout<<"\nEnter employee qualification: ";
```

```
        cin>>qualification;
```

```
    }
```

```
    void show()
```

```
    {
```

```
        cout<<"\n\nEmployee id: "<<emp_code;
```

```
        cout<<"\tName: "<<name;
```

```
        cout<<"\nAge: "<<age<<"\t\tQualification: "<<qualification;
```

```
    }
```

```
};
```

```
class contract_employee: public employee
```

```
{
```

```
    int contract_id;
```

```
public:
```

```
    void get()
```

```
    {
```

```
        cout<<"\nEnter contract_id: ";
```

```
        cin>>contract_id;
```

```
    }
```

```
void show()
{
    cout<<"\nContract ID: "<<contract_id;
}

};

void main()
{
    clrscr();
    contract_employee ce;
    ce.get();
    ce.show();
    getch();
}
```

Output:

Enter contract_id: 101

Contract ID: 101

(b) Show the use of virtual function

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
class base
{
public: virtual void
display()
{
    cout<<"\nDisplay of base class called";
}
};
```

```
class derived:public base
```

```
{
```

```
public: void  
display()  
{  
    cout<<"\nDisplay of derived class called";  
}  
};
```

```
void main()  
{ clrscr();  
base *b;  
derived d;  
b=&d; b->display();  
getch();  
}
```

Output:

Display of derived class called

(c) Show the implementation of abstract class.

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
// Using abstract methods and classes. class
```

```
Figure
```

```
{  
    public:  
    double dim1; double  
    dim2; Figure(double a,  
    double b)  
    {  
        dim1 = a;  
        dim2 = b;  
    }  
    // pure virtual function  
    virtual double area()=0;  
};
```

```
class Rectangle:public Figure
{
public:

    Rectangle(double a, double b):Figure(a,b)
    {
    }
// implement area for rectangle
double area()
{
    cout<<"\nInside Area for Rectangle:";
    return dim1 * dim2;
}
};
```

```
class Triangle:public Figure
{
public:

    Triangle(double a, double b):Figure(a,b)
    {
    }

// implement area for right triangle

double area()
{
    cout<<"\nInside Area for Triangle:";
    return dim1 * dim2 / 2;
}
};

void main()
```



```
{ clrscr();  
Rectangle r(9, 5);  
Triangle t(10, 8);
```

```
cout<< r.area();
```

```
cout<< t.area();  
getch();  
}
```

Output:

Inside Area for Rectangle:45

Inside Area for Triangle:40

(7) Implement the following

(a) String operations for string length , string concatenation

```
#include<iostream>
```

```
#include<string>
```

```
using namespace std;
```

```
void main()
```

```
{
```

```
    string str1="Sanjeela";
```

```
    string str2="Sagar";
```

```
    cout<<endl<<"Length of "<<str1<<": "<<str1.length();
```

```
    string str3=str1+str2;
```

```
    cout<<endl<<str3;
```

```
}
```

Output:

Length of Sanjeela: 8

SanjeelaSagar

(b) String operations for string reverse, string comparison,

```
#include<iostream>
#include<string>
#include<algorithm>

using namespace std;

void main()
{
    string str="Hello, Its going to reverse";
    reverse(str.begin(), str.end()); cout<<str;

    string s1="Sanjeela";
    string s2="Sagar";

    if(s1<s2)
        cout<<endl<<s1<<" comes before "<<s2;
    else
        cout<<endl<<s2<<" comes before "<<s1;
}
```

Output:

esrever ot gniog stl ,olleH
Sagar comes before Dhiraj

(c) Console formatting functions.

Example 1:

Without using iomanip setw() method.

```
#include<iostream.h> #include<conio.h>
void main()
{ clrscr(); char s[10];
  cout<<"Enter your name: ";
  cin>>s; cout<<endl<<s;
  getch();
}
```

Output:

Enter your name: SanjeelaSagar

SanjeelaSagar

With using iomanip setw() method.

```
#include<iostream.h>
#include<conio.h> #include<iomanip.h>
void main()
{ clrscr(); char s[10];
  cout<<"Enter your name: ";
  cin>>setw(10)>>s;
  cout<<endl<<s;
  getch();
}
```

Output:

Enter your name: SanjeelaSagar SanjeelaS

Example 2:

```
#include <iostream.h>
#include<conio.h>
```

```
void main()
{
  clrscr();
  char c[] = "DhirajSagar";
  cout.write(c, 13).put("\n"); // put('\n') is used in place of endl
  char ch[] = "A"; cout<<"ch = "; cout.write(ch,1)<<endl; //
  writes one byte of ch. char s[] = "ABCDEFGHIIJC" ;
  cout.write(s, 5)<<endl; // writes 5 bytes from string s
```

```
char name[15]; cout<< "Enter a name: "; cin.read(name
,15); // reads 15 bytes from name
cout.write(name,15)<<endl; // writes 15 bytes from Name
getch();
}
```

Output:

DhirajSaga

ch=A ABCDE

Enter a name: DhirajRakesh Sagar

DhirajRakesh

(8) Implement the following:

(a) Show the implementation of exception handling

```
#include<iostream.h> void
```

```
main()
```

```
{
```

```
    float percent;
```

```
    cout<<"Enter your percentage: ";
```

```
    cin>>percent;
```

```
    try
```

```
    {
```

```
        if(percent<0 || percent>100)
```

```
            throw(percent);
```

```
    else
```

```
        cout<<endl<<"Your percentage: "<<percent;
```

```
    }catch(int p)
```

```
    {
```

```
        cout<<endl<<"Invalid percentage: "<<p;
```

```
    } }
```

Output:

Enter percentage: 150

Invalid percentage: 150

(b) Show the implementation for exception handling for strings

```
#include<iostream>
```

```
#include<string>
```

```
using namespace std;
```

```
void main()
{ string
s;

    cout<<"Enter the name of your course: ";
    cin>>s;

    try
    {
        if(s=="B.Sc - IT" || s=="BMS" || s=="B.Com")
            cout<<endl<<"Your have chosen Course: "<<s;
    else
        throw(s);
    }catch(string ss)
    {
        cout<<endl<<"Oh!!!!!!!!!! you have chosen the course that we
don't provide: "<<ss;
    }
}
```

Output:

1st Run:

Enter the name of your course: MCA

Oh!!!!!!!!!! you have chosen the course that we don't provide: MCA

2nd Run:

Enter the name of your course: BMS

You have chosen Course: BMS

(9) Show the implementation

(a) Design a class FileDemo, open a file in read mode and display the total number of words and lines in the file.

```
#include<iostream.h>
#include<conio.h>
#include<fstream.h>

void main()
{
    clrscr();

    ifstream fread("WordLineCount.txt");
    int wc=1,lc=1;
    char c;
    while(fread)
    {
        fread.get(c);
        if(c==' ' || c=='\n')
            wc++; if(c=='\n')
                lc++;
    }
    fread.close(); cout<<"\n Total no. of words in
the file: "<<wc; cout<<"\n Total no. of lines in
the file: "<<lc; getch();
}
```

Output:

Contents of the file

----- This
is the first line of the file.
This is the second line of the file. This
is the third line of the file.
Total no. of words in the file: 24
Total no. of lines in the file: 3

(b) Design a class to handle multiple files and file operations

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
#include<fstream.h>
```

```
void main()
```

```
{
```

```
clrscr();
```

```
ofstream fwrite("Alphabets.txt");
```

```
fwrite<<"ABCDEFGHIJKLMNOPQRSTUVWXYZ";
```

```
fwrite.close();
```

```
ifstream fread("Alphabets.txt");
```

```
ofstream fwrite1("Vowels.txt");
```

```
ofstream fwrite2("Consonants.txt");
```

```
char c;
```

```
while(fread)
```

```
{
```

```
fread.get(c);
```

```
if(c=='A' || c=='E' || c=='I' || c=='O' || c=='U')
```

```
    fwrite1<<c;
```

```
else
```

```
    fwrite2<<c;
```

```
}
```

```
fread.close();
```

```
fwrite1.close();
```

```
fwrite2.close();
```

```
fread.open("Alphabets.txt");
```

```
ifstream fread1("Vowels.txt");
```

```
ifstream fread2("Consonants.txt");
```

```
cout<<"\n\nContents of Alphabets File\n"; cout<<"-----\n";
while(fread)
{
    fread.get(c);
    cout<<c;
}

fread.close();

cout<<"\n\nContents of Vowels File\n"; cout<<"-----\n";
while(fread1)
{
    fread1.get(c);
    cout<<c;
}

fread1.close();
cout<<"\n\nContents of Consonants File\n"; cout<<"-----\n";
while(fread2)
{
    fread2.get(c);
    cout<<c;
}

fread2.close();
getch();
}
```

Output:

Contents of Alphabets File

Contents of Vowels File

AEIOU

Contents of Consonants File

BCDFGHJKLMNPQRSTVWXYZ

(c) Design a editor for appending and editing the files

```
#include<iostream.h>
```

```
#include<conio.h> #include<fstream.h>
```

```
class student
```

```
{
```

```
    char
```

```
name[30];    int
```

```
age;    float
```

```
percent;
```

```
public:
```

```
void getdata()
```

```
{
```

```
    cout<<endl<<"Enter name: ";
```

```
    cin>>name;    cout<<endl<<"Enter
```

```
age: ";    cin>>age;
```

```
    cout<<endl<<"Enter percentage: ";
```

```
    cin>>percent;
```

```
}
```

```
void showdata()
```

```
{
```

```
    cout<<endl<<name;
```

```
    cout<<"\t\t"<< age;
```

```
    cout<<"\t\t"<<percent;
```

```
}  
};
```

```
void main()
```

```
{
```

```
clrscr();
```

```
student st;
```

```
fstream freadwrite("Student.txt", ios::ate | ios::in | ios::out);
```

```
freadwrite.seekg(0,ios::beg);
```

```
cout<<endl<<"Current contents of file";
```

```
while(freadwrite.read((char*)&st,sizeof(st)))
```

```
    st.showdata();
```

```
    freadwrite.clear();
```

```
    cout<<endl<<"Enter details for one more student";
```

```
st.getdata();
```

```
    char c;
```

```
cin.get(c);
```

```
    freadwrite.write((char*)&st, sizeof(st)); freadwrite.seekg(0);
```

```
    cout<<endl<<"After addition of one more student";
```

```
    cout<<endl<<"Name \t\t Age \t\t Percentage";
```

```
while(freadwrite.read((char*)&st, sizeof(st)))
```

```
{
```

```
    st.showdata();
```

```
}
```

```
int n = freadwrite.tellg() / sizeof(st);
```

```
cout<<endl<<"Total no. of student record: "<<n;
```

```
cout<<endl<<"Enter student number to be updated: ";
```

```
int num; cin>>num;
```

```
cin.get(c);
```

```
int l=(num-1) * sizeof(st);
```

```
if(freadwrite.eof())
```

```
    freadwrite.clear();
```

```
    freadwrite.seekp(l);
```

```
    cout<<endl<<"Enter new values for the student";
```

```
        st.getdata();
```

```
cin.get(c);
```

```
    freadwrite.write((char*)&st, sizeof(st))<<flush;
```

```
freadwrite.seekg(0);
```

```
cout<<endl<<"After updation contents are";
```

```
cout<<endl<<"Name \t\t Age \t\t Percentage";
```

```
while(freadwrite.read((char*)&st, sizeof(st)))
```

```
{
```

```
    st.showdata();
```

```
}
```

```
freadwrite.close();
```

```
getch();
```

```
}
```

Output:

Current contents of file

Name	Age	Percentage
Dhiraj	33	78
Rakesh	34	82
Sagar	22	67

Enter details for one more student

Enter name: Kashyap

Enter age: 19

Enter percentage: 89

After addition of one more student

Name	Age	Percentage
Dhiraj	33	78
Rakesh	34	82
Sagar	22	67
Kashyap	19	89

Total no. of student record: 4

Enter student number to be updated: 4

Enter new values for the student

Enter name: Kashyap

Enter age: 20

Enter percentage: 80

After updation contents are

Name	Age	Percentage
Dhiraj	33	78
Rakesh	34	82
Sagar	22	67
Kashyap	20	80

(10) Show the implementation for the following **(a)** Show the implementation of template class library for swap function.

```
#include<iostream.h>
```

```
#include<conio.h> template<class
```

```
A>
```

```
void swap(A &a, A &b)
```

```
{
    A t=a;
    a=b; b=t;
};
void main()
{ clrscr();
  int n,m;
  float f1,f2;
  char c,d;
  cout<<endl<<"Enter two integers: ";
  cin>>n>>m;
  cout<<endl<<"Enter two floats: ";
  cin>>f1>>f2;
  cout<<endl<<"Enter two characters: ";
  cin>>c>>d;
  cout<<endl<<"Integers before swapping\n";
  cout<<"-----";
  cout<<endl<<"N= "<<n<<"\tM= "<<m;
  swap(n,m);
  cout<<endl<<"\nIntegers after swapping\n";
  cout<<"-----";
  cout<<endl<<"N= "<<n<<"\tM= "<<m;

  cout<<endl<<"\nFloats before swapping\n";
  cout<<"-----";
  cout<<endl<<"F1= "<<f1<<"\tF2= "<<f2; swap(f1,f2);

  cout<<endl<<"\nFloats after swapping\n"; cout<<"-----
";
  cout<<endl<<"F1= "<<f1<<"\tF2= "<<f2;

  cout<<endl<<"\nCharacters before swapping\n";
  cout<<"-----";
  cout<<endl<<"C= "<<c<<"\tD= "<<d;
```

```
swap(c,d);
cout<<endl<<"\nCharacters after swapping\n";
cout<<"-----";
cout<<endl<<"C= "<<c<<"\tD= "<<d;

getch();
}
```

Output:

```
Enter two integers: 10    20
Enter two floats: 10.5   11.5
Enter two characters: c   d
Integers before swapping
-----
N= 10  M= 20
Integers after swapping
-----
N= 20  M= 10
Floats before swapping
----- F1=
10.5    F2= 11.5
Floats after swapping
----- F1=
11.5    F2= 10.5
Characters before swapping
----- C=
c   D= d
Characters after swapping
-----
C= d   D= c
```

(b) Design the template class library for sorting ascending to descending and vice-versa

```
#include<iostream.h>
```

```
#include<conio.h>
```

```
template<class A>
void sort_asc(A *a, int n)
{ int
i,j; A
t;
for(i=0;i<n-1;i++)
{
for(j=i+1;j<n;j++)
{
if(a[i]>a[j])
{
t=a[i];
a[i]=a[j];
a[j]=t;
}
}
}
};
```

```
void main()
{ clrscr();
int a[10],i;
float f[10];
char c[10];
```

```
cout<<endl<<"Enter 10 integers\n";
for(i=0;i<10;i++) cin>>a[i];
cout<<endl<<"Enter 10 floats\n";
for(i=0;i<10;i++)
cin>>f[i];
```

```
cout<<endl<<"Enter 10 characters\n";
```

```
for(i=0;i<10;i++)
```

```
cin>>c[i];
```

```
cout<<endl<<"Integers before sorting\n";
```

```
for(i=0;i<10;i++)
```

```
    cout<<a[i]<<"\t";
```

```
sort_asc(a,10);
```

```
cout<<endl<<"Integers after sorting\n";
```

```
for(i=0;i<10;i++)
```

```
    cout<<a[i]<<"\t";
```

```
cout<<endl<<"Floats before sorting\n";
```

```
for(i=0;i<10;i++)
```

```
    cout<<f[i]<<"\t";
```

```
sort_asc(f,10);
```

```
cout<<endl<<"Floats after sorting\n";
```

```
for(i=0;i<10;i++)
```

```
    cout<<f[i]<<"\t";
```

```
cout<<endl<<"Characters before sorting\n";
```

```
for(i=0;i<10;i++)
```

```
    cout<<c[i]<<"\t";
```

```
sort_asc(c,10);
```

```
cout<<endl<<"Characters after sorting\n"; for(i=0;i<10;i++)
```

```
    cout<<c[i]<<"\t";
```

```
getch();
```

```
}
```


Output:

Enter 10 integers

10 9 8 7 6 5 4 3 2 1

Enter 10 floats

10.9 9.8 8.7 7.6 6.5 5.4 4.3 3.2 2.1 1.1

Enter 10 characters

z x c v b n m a s d

Integers before sorting

10 9 8 7 6 5 4 3 2 1

Integers after sorting

1 2 3 4 5 6 7 8 9 10

Floats before sorting

10.9 9.8 8.7 7.6 6.5 5.4 4.3 3.2 2.1 1.1

Floats after sorting

1.1 2.1 3.2 4.3 5.4 6.5 7.6 8.7 9.8 10.9

Characters before sorting

z x c v b n m a s d

Characters after sorting

a b c d m n s v x z

(c) Design the template class library for concatenating two strings

```
// string::operator+=
```

```
#include <iostream>
```

```
#include <string> using
```

```
namespace std;
```

```
template<class A>
```

```
void str_cat(A &a, A &b)
```

```
{ a=a + "  
";  
a=a+ b;  
};  
void main ()  
{  
    string name ("Sanjeela"); string  
Surname ("Sagar");  
cout<<endl<<"First Name: "<<name;  
cout<<endl<<"Surname: "<<Surname;  
str_cat(name,Surname);  
    cout << endl<< "Full Name: "<<name;  
}
```

Output:

First Name: Dhiraj

Surname: Sagar

Full Name: DhirajSagar
