

Name:	DHIR VIJAY SURTI
Roll No:	57
Class/Sem:	SE/IV
<b>Experiment No.:</b>	2
Title:	Selection Sort
<b>Date of Performance:</b>	
<b>Date of Submission:</b>	
Marks:	
Sign of Faculty:	

# Vidyavardhini's College of Engineering and Technology

### Department of Artificial Intelligence & Data Science

### **Experiment No. 2**

Title: Selection Sort

Aim: To implement Selection Comparative analysis for large values of 'n'

Objective: To introduce the methods of designing and analyzing algorithms

#### Theory:

Selection sort is a sorting algorithm, specifically an in-place comparison sort. Selection sort is noted for its simplicity, and it has performance advantages over more complicated algorithms in certain situations, particularly where auxiliary memory is limited.

The algorithm divides the input list into two parts: the sub list of items already sorted, which is built up from left to right at the front (left) of the list, and the sub list of items remaining to be sorted that occupy the rest of the list. Initially, the sorted sub list is empty and the unsorted sub list is the entire input list. The algorithm proceeds by finding the smallest (or largest, depending on sorting order) element in the unsorted sub list, exchanging it with the leftmost unsorted element (putting it in sorted order), and moving the sublist boundaries one element to the right.

#### **Example:**

arr[] = 64 25 12 22 11

// Find the minimum element in arr[0...4] // and place it at beginning

11 25 12 22 64

// Find the minimum element in arr[1...4] // and place it at beginning of arr[1...4]

11 12 25 22 64

// Find the minimum element in arr[2...4] // and place it at beginning of arr[2...4]

11 12 **22** 25 64

// Find the minimum element in arr[3...4] // and place it at beginning of arr[3...4]



### 11 12 22 **25** 64

### Algorithm and Complexity:

Alg.: SELECTION-SORT(A)	-20	100
( <del>7</del> )	cost	Times
$n \leftarrow length[A]$	c <sub>1</sub>	1
for $j \leftarrow 1$ to $n - 1$		n-1
do smallest ← j		n-1
for $\underline{i} \leftarrow j + 1$ to n		$\sum_{j=1}^{n-1} (n-j+1)$
$\approx$ n2/2 comparisons, do if A[i] <a[smallest]< td=""><td><math display="block">\sum_{j=1}^{n-1} (n-j)</math></td></a[smallest]<>		$\sum_{j=1}^{n-1} (n-j)$
then smallest $\leftarrow \underline{i}$		$\sum_{j=1}^{n-1} (n-j)$
$\approx$ n exchanges, exchange A[j] $\leftrightarrow$ A[smallest]	c <sub>7</sub>	n-1

### **Implementation:**


```
// C program for implementation of selection sort
#include <stdio.h>
void swap(int* xp, int* yp)
{
    int temp = *xp;
        *xp = *yp;
        *yp = temp;
}
void selectionSort(int arr[], int n)
{
    int i, j, min_idx;
    // One by one move boundary of unsorted subarray
    for (i = 0; i < n - 1; i++) {
        // Find the minimum element in unsorted array</pre>
```



```
min_idx = i;
                for (j = i + 1; j < n; j++)
                        if (arr[j] < arr[min_idx])</pre>
                                min_idx = j;
                // Swap the found minimum element with the first
                // element
                swap(&arr[min_idx], &arr[i]);
        }
}
/* Function to print an array */
void printArray(int arr[], int size)
{
        int i;
        for (i = 0; i < size; i++)
                printf("%d ", arr[i]);
        printf("\n");
}
// Driver program to test above functions
int main()
{
        int arr[] = { 64, 25, 12, 22, 11 };
        int n = sizeof(arr) / sizeof(arr[0]);
        selectionSort(arr, n);
        printf("Sorted array: \n");
        printArray(arr, n);
        return 0;
}
```



Output:



**Conclusion:** The implementation of selection sort demonstrated its effectiveness in sorting elements by repeatedly selecting the minimum element from the unsorted portion and placing it at the beginning. This experiment underscores selection sort's simplicity and efficiency for small datasets, offering insights into its practical application in sorting algorithms.