RAJALAKSHMI ENGINEERING COLLEGE

Dhishanth G 251801063-2025-AIDS D2

| | |
|---|---|
| **Started on** | Friday, 4 September 2026, 6:22 PM |
| **State** | Finished |
| **Completed on** | Friday, 4 September 2026, 6:23 PM |
| **Time taken** | 24 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

**Problem Statement**

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Div
Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

**Answer:** (penalty regime: 0 %)

```c
#include <stdio.h>

// Divide and Conquer: find the first occurrence of 0
int firstZero(int arr[], int low, int high)
{
    if (low > high)
        return -1;

    int mid = low + (high - low) / 2;

    if (arr[mid] == 0)
    {
        // Check whether this is the first zero
        if (mid == 0 || arr[mid - 1] == 1)
            return mid;

        return firstZero(arr, low, mid - 1);
    }
    else
    {
        return firstZero(arr, mid + 1, high);
    }
}

int main()
{
    int m;
    scanf("%d", &m);

    int arr[m];

    for (int i = 0; i < m; i++)
        scanf("%d", &arr[i]);

    int index = firstZero(arr, 0, m - 1);

    if (index == -1)
        printf("0");
    else
        printf("%d", m - index);

    return 0;
}
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 5<br>1<br>1<br>1<br>0<br>0 | 2 | 2 | ✔ |
| ✔ | 10<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1 | 0 | 0 | ✔ |
| ✔ | 8<br>0<br>0<br>0<br>0<br>0<br>0<br>0<br>0 | 8 | 8 | ✔ |
| ✔ | 17<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>1<br>0<br>0 | 2 | 2 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Dhishanth G 251801063-2025-AIDS D2

| | |
|---|---|
| **Started on** | Friday, 4 September 2026, 6:23 PM |
| **State** | Finished |
| **Completed on** | Friday, 4 September 2026, 6:25 PM |
| **Time taken** | 1 min 38 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element alw exists in the array.

**Example 1:**

```
Input: nums = [3,2,3]
Output: 3
```

**Example 2:**

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

**Constraints:**

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

**For example:**

| Input | Result |
|---|---|
| 3<br>3 2 3 | 3 |
| 7<br>2 2 1 1 1 2 2 | 2 |

**Answer:** (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int a[n];

    for(int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    for(int i = 0; i < n; i++)
    {
        int count = 0;

        for(int j = 0; j < n; j++)
        {
            if(a[i] == a[j])
                count++;
        }

        if(count > n / 2)
        {
            printf("%d", a[i]);
            break;
        }
    }

    return 0;
}
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 3<br>3 2 3 | 3 | 3 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Dhishanth G 251801063-2025-AIDS D2

| | |
|---|---|
| **Started on** | Friday, 4 September 2026, 6:25 PM |
| **State** | Finished |
| **Completed on** | Friday, 4 September 2026, 6:26 PM |
| **Time taken** | 1 min 36 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

**Problem Statement:**

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and algorithm to find floor of x.

**Input Format**

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

**Output Format**

First Line Contains Integer – Floor value for x

**Answer:** (penalty regime: 0 %)

```c
#include <stdio.h>

int floorValue(int a[], int low, int high, int x)
{
    if (low > high)
        return -1;

    int mid = (low + high) / 2;

    if (a[mid] == x)
        return a[mid];

    if (a[mid] > x)
        return floorValue(a, low, mid - 1, x);

    if (mid == high || a[mid + 1] > x)
        return a[mid];

    return floorValue(a, mid + 1, high, x);
}

int main()
{
    int n, x;

    scanf("%d", &n);

    int a[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    scanf("%d", &x);

    printf("%d", floorValue(a, 0, n - 1, x));

    return 0;
}
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 6<br>1<br>2<br>8<br>10<br>12<br>19<br>5 | 2 | 2 | ✔ |

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 5<br>10<br>22<br>85<br>108<br>129<br>100 | 85 | 85 | ✔ |
| ✔ | 7<br>3<br>5<br>7<br>9<br>11<br>13<br>15<br>10 | 9 | 9 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Dhishanth G 251801063-2025-AIDS D2

| | |
|---|---|
| **Started on** | Friday, 4 September 2026, 6:27 PM |
| **State** | Finished |
| **Completed on** | Friday, 4 September 2026, 6:28 PM |
| **Time taken** | 1 min 8 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

**Problem Statement:**

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to c
there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwis
"No".

Note: Write a Divide and Conquer Solution

**Input Format**

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

**Output Format**

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

**Answer:** (penalty regime: 0 %)

```c
#include <stdio.h>

int findPair(int a[], int left, int right, int x)
{
    if (left >= right)
        return 0;

    int sum = a[left] + a[right];

    if (sum == x)
    {
        printf("%d\n", a[left]);
        printf("%d\n", a[right]);
        return 1;
    }

    if (sum < x)
        return findPair(a, left + 1, right, x);
    else
        return findPair(a, left, right - 1, x);
}

int main()
{
    int n, x;

    scanf("%d", &n);

    int a[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    scanf("%d", &x);

    if (!findPair(a, 0, n - 1, x))
        printf("No");

    return 0;
}
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 4<br>2<br>4<br>8<br>10<br>14 | 4<br>10 | 4<br>10 | ✔ |

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 5<br>2<br>4<br>6<br>8<br>10<br>100 | No | No | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Dhishanth G 251801063-2025-AIDS D2

| | |
|---|---|
| **Started on** | Friday, 4 September 2026, 6:29 PM |
| **State** | Finished |
| **Completed on** | Friday, 4 September 2026, 6:29 PM |
| **Time taken** | 46 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

Write a Program to Implement the Quick Sort Algorithm

Input Format:
The first line contains the no of elements in the list-n
The next n lines contain the elements.

Output:
Sorted list of elements

**For example:**

| Input | Result |
|---|---|
| 5<br>67 34 12 98 78 | 12 34 67 78 98 |

**Answer:**

```c
#include <stdio.h>

void quickSort(int a[], int low, int high)
{
    if (low < high)
    {
        int pivot = a[high];
        int i = low - 1;

        for (int j = low; j < high; j++)
        {
            if (a[j] < pivot)
            {
                i++;

                int temp = a[i];
                a[i] = a[j];
                a[j] = temp;
            }
        }

        int temp = a[i + 1];
        a[i + 1] = a[high];
        a[high] = temp;

        int p = i + 1;

        quickSort(a, low, p - 1);
        quickSort(a, p + 1, high);
    }
}

int main()
{
    int n;
    scanf("%d", &n);

    int a[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &a[i]);

    quickSort(a, 0, n - 1);

    for (int i = 0; i < n; i++)
        printf("%d ", a[i]);

    return 0;
}
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 5<br>67 34 12 98 78 | 12 34 67 78 98 | 12 34 67 78 98 | ✔ |
| ✔ | 10<br>1 56 78 90 32 56 11 10 90 114 | 1 10 11 32 56 56 78 90 90 114 | 1 10 11 32 56 56 78 90 90 114 | ✔ |
| ✔ | 12<br>9 8 7 6 5 4 3 2 1 10 11 90 | 1 2 3 4 5 6 7 8 9 10 11 90 | 1 2 3 4 5 6 7 8 9 10 11 90 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course