Ideation Phase
Brainstorm & Idea Prioritization Template

Date	03 October 2026
Team ID	SWTID-2026-7991
Project Name	Script-Controlled ACL – Restrict Record Access Based on Field Value
Maximum Marks	4 Marks

Brainstorm & Idea Prioritization Template:

Brainstorming for this project focuses on the ServiceNow Script-Controlled ACL workflow: creating the EEE user and bb1–bb4 roles, creating the u_institution_details table, configuring READ, CREATE, WRITE and DELETE ACLs, and verifying each permission.

Step-1: Team Gathering, Collaboration and Select the Problem Statement

Selected problem statement:

How might we configure and verify ServiceNow ACLs so that the EEE user can access the required Institution Details records and operations according to bb1, bb2, bb3 and bb4 roles, while unauthorized access is denied?

Stakeholder / user perspectives:

- ServiceNow administrator / security administrator
- EEE user with bb1 role for READ access
- User with bb1 + bb2 roles for CREATE access
- User with bb1 + bb2 + bb3 roles for WRITE access
- User with bb1 + bb2 + bb3 + bb4 roles for DELETE access
- User without the required role

Step-2: Brainstorm, Idea Listing and Grouping

Ideas generated from the actual ACL configuration and verification workflow:

Idea Group	Idea	Purpose
User & Role Setup	Create the EEE user and custom roles bb1, bb2, bb3 and bb4.	Establishes the roles required for staged access control.
Institution Details Table	Create u_institution_details with Student Roll Number, Student Name, Faculty Name, Branch, Email, Phone Number and Description.	Provides the records and fields protected by the ACLs.
Script-Controlled READ	Use an Advanced READ ACL with bb1, Branch = EEE and a script that allows admin and bb1 users.	Restricts record visibility while retaining administrator access.
CREATE Permission	Create a record CREATE ACL requiring bb2.	Separates record creation from READ permission.
WRITE Permission	Create a record WRITE ACL requiring bb3.	Separates editing permission from creation and reading.
DELETE Permission	Create a record DELETE ACL requiring bb4.	Restricts deletion to users with the required role.
Impersonation Testing	Impersonate EEE users and Admin and open u_institution_details.list/LIST.	Tests the ACL behavior as actual users.
Negative Verification	Verify users without the required role cannot view protected records.	Confirms the deny behavior.
Role Combination Testing	Verify bb1+bb2, bb1+bb2+bb3 and bb1+bb2+bb3+bb4 combinations.	Confirms progressive permissions for create, edit and delete.
Outcome Documentation	Record verification results and the final ACL outcome.	Makes the completed configuration easier to review.

Ideation Phase
Brainstorm & Idea Prioritization Template

Step-3: Idea Prioritization

Ideas are prioritized using the template's Importance–Feasibility view. Importance reflects the security and user impact of the ACL requirement; feasibility reflects how directly the idea fits the existing ServiceNow configuration workflow.

Idea	Importance	Feasibility	Priority
Script-controlled READ with Branch = EEE	High	High	P1
Role-specific bb1–bb4 permissions	High	High	P1
Separate CREATE / WRITE / DELETE ACLs	High	High	P1
Impersonation and negative verification	High	High	P1
u_institution_details table and required fields	High	High	P1
Role-combination testing	High	High	P1
Outcome documentation	Medium	High	P2

Selected concept:

A layered ServiceNow ACL configuration using the EEE Branch condition for READ, script validation for administrator/bb1 access, and role-specific bb2, bb3 and bb4 permissions for CREATE, WRITE and DELETE, followed by impersonation-based verification.

Prioritized implementation flow

1	
2	
3	
4	
5	
6	
7	
8	