Project Design Phase-II
Solution Requirements (Functional & Non-functional)

Date	03 0ctober2026
Team ID	**SWTID-2026-7991**
Project Name	Script-Controlled ACL – Restrict Record Access Based on Field Value
Maximum Marks	4 Marks

Functional Requirements:

Following are the functional requirements of the proposed Script-Controlled ACL solution.

FR No.	Functional Requirement (Epic)	Sub Requirement (Story / Sub-Task)
FR-1	User and Role Setup	Create the EEE User and create custom roles bb1, bb2, bb3 and bb4; assign the roles to the EEE User.
FR-2	Institution Details Table	Create u_institution_details and add Student Roll Number, Student Name, Faculty Name, Branch, Email, Phone Number and Description fields.
FR-3	READ ACL	Create an active Advanced record READ ACL using bb1 and the data condition Branch is EEE; allow admin full access through the supplied script.
FR-4	CREATE ACL	Create an active record CREATE ACL for u_institution_details requiring bb2; verify the EEE user with bb1 + bb2 can create records.
FR-5	WRITE ACL	Create an active record WRITE ACL requiring bb3; verify the user with bb1 + bb2 + bb3 can view and edit EEE branch records.
FR-6	DELETE ACL	Create an active record DELETE ACL requiring bb4; verify the user with bb1 + bb2 + bb3 + bb4 can delete EEE branch records.
FR-7	Access Verification	Impersonate EEE users and Admin, open u_institution_details.list/LIST, and verify allowed and denied access for each configured operation.

Non-functional Requirements:

Following are the non-functional requirements relevant to the ACL lab solution.

NFR No.	Non-Functional Requirement	Description
NFR-1	**Usability**	ACL configuration and verification should be clear enough to test through ServiceNow navigation and user impersonation.
NFR-2	**Security**	Record-level access must protect sensitive data by enforcing role- and field-based READ, CREATE, WRITE and DELETE permissions.
NFR-3	**Reliability**	Configured ACL rules should consistently enforce the defined access behavior when users perform the corresponding operations.
NFR-4	**Performance**	ACL checks should support record access decisions as part of normal list and form operations in the lab.
NFR-5	**Availability**	The configured access-control behavior should remain available when the relevant ServiceNow table and ACL records are active.
NFR-6	**Scalability**	Separate roles and operation-specific ACLs provide a structure that can be extended with additional users, records or access rules.