

Installing and Configuring the Hortonworks ODBC driver on Mac OS X

David Hoyle
28 April 2013

Summary

This document describes how to install and configure the Hortonworks ODBC driver on Mac OS X. After you install and configure the ODBC driver, you can access Hortonworks sandbox data using Microsoft Excel.

In this procedure, we will use Microsoft Excel 2011 to access Hortonworks sandbox data. You should also be able to access sandbox data using other versions of Excel. The process may not be identical in other versions of Excel, but it should be similar.

Prerequisites:

- Mac running OS X
- Hortonworks Sandbox 1.2 (installed and running)
- Excel 2011

Overview

To install and configure the Hortonworks ODBC driver on Mac OS X:

1. Download and install the Hortonworks ODBC driver for Mac OS X.
2. Download and install the iODBC Driver Manager for Mac OS X.
3. Configure the Hortonworks ODBC driver
4. Open Excel and test the connection to the Hortonworks sandbox.

Step 1 – Download and Install the Hortonworks ODBC Driver for Mac OS X

1. Open a web browser and navigate to <http://hortonworks.com/download/>. Click the **Add-Ons** link at the bottom of the Hortonworks Data Platform 1.2 box.

Downloads

Learn why Hortonworks Data Platform is the fastest growing Hadoop distribution and is used in production on the largest clusters on the planet.

Latest Releases:

Hortonworks Data Platform 1.2

1.2.3.1 | [Docs](#) | [Release Notes](#) | [Technical Specs](#)

- Complete Hadoop Distribution
- Run a cluster in your own environment
- Automated and Manual install options
- RHEL, CentOS, and SLES

[Download + Install »](#)

Looking for a Connector or ODBC driver? Browse [Add-Ons](#)

Hortonworks Sandbox

[VM](#) | [Technical Specs](#)

- Self-contained, downloadable VM
- Pre-installed Hadoop cluster, no setup required
- End-user tools for data access & query
- Built-in tutorials and videos

[Download + Install »](#)

[Checkout the release blog announcement here.](#)

Early Access:

[NEW! HADOOP 2.0](#)

[NEW! HDP FOR WINDOWS](#)

2. On the Add-Ons page, scroll down to Hortonworks Hive ODBC Driver (Windows + Mac) and select **Mac OS X (dmg)**.

Talend Open Studio for Big Data is a powerful and versatile open source data integration tool. Talend provides data managers, operators, and analysts a graphical tool that abstracts the underlying Hadoop complexities and dramatically improves the efficiency of job design through an easy-to-use Eclipse development environment.

Download (tar.gz) »

Documentation »

Teradata Connector for Hadoop

The **Teradata Connector for Hadoop** is the fastest and most scalable way to transfer data between Teradata Database and Apache Hadoop. Jointly developed by Teradata and Hortonworks, the Connector plugs into the Hortonworks Data Platform and offers wire-speed, fully parallel data transfers between Teradata and Apache Hive, HBase, HCatalog or HDFS. The connector lets you move more data faster, freeing up more time for critical data processing.

Download (tar.gz) »

Documentation »

Hortonworks Hive ODBC Driver (Windows + Mac)

The **Hortonworks Hive ODBC Driver** allows you to connect popular Business Intelligence (BI) tools to query, analyze and visualize data stored within the Hortonworks Data Platform.

Windows 32-bit (msi) »

Windows 64-bit (msi) »

Mac OS X (dmg) »

Hortonworks Hive ODBC Driver (Linux)

The **Hortonworks Hive ODBC Driver** allows you to connect popular Business Intelligence (BI) tools to query, analyze and visualize data stored within the Hortonworks Data Platform.

CentOS 6 (tar.gz) »

CentOS 5 (tar.gz) »

SUSE 11 (tar.gz) »

3. Review the Hortonworks license, then click **Accept Agreement**.

Hortonworks

Learn Hadoop Try Hadoop Install Hadoop Follow [+] Logout / Profile

Enterprise Hadoop Products Hadoop Training Community Partners Resources About Us Blog Search...

Thank You: Hortonworks

Thank you for downloading the Hortonworks Hive ODBC Driver. This driver allows you to connect popular Business Intelligence (BI) tools to query, analyze and visualize data stored within the Hortonworks Data Platform.

While you are waiting for the download to complete, we have some resources to assist you during the installation process:

- News: Hortonworks Brings New Features to the Hadoop Ecosystem
- Knowledgebase
- User Forums
- Hadoop Training Courses

Please agree to the below EULA to download this file:


HORTONWORKS LICENSE AGREEMENT

PLEASE READ THIS AGREEMENT CAREFULLY BEFORE YOU AGREE TO THESE TERMS. IF YOU ARE ACTING ON BEHALF OF AN ENTITY, THEN YOU REPRESENT THAT YOU HAVE THE AUTHORITY TO ENTER INTO THIS AGREEMENT ON BEHALF OF THAT ENTITY. IF YOU DO NOT AGREE TO THESE TERMS, YOU SHOULD NOT AGREE TO THE TERMS OF THIS AGREEMENT OR USE THE SOFTWARE.


This Hortonworks License Agreement ("Agreement") is made by Hortonworks, Inc. with its principal place of business at 455 West Maude Ave., Suite 200, Sunnyvale, California 94085 and you ("Customer"). The effective date ("Effective Date") is the date you accept this Agreement.

Cancel **Accept Agreement**


4. A confirmation message appears. Click **OK** to open the file with the Disk Image Mounter.




5. When the download is complete, the driver package appears in a new window. Double-click (or right-click with the mouse) the driver package, then select **Open**.




6. To start the installation, click **Continue** on the ODBC Driver Installer Welcome screen.




7. Review the license agreement, then click **Continue**.




8. Click **Agree** on the pop-up message to agree to the license terms.




9. Click **Install** to accept the default installation folder.



10. A progress indicator appears while the driver is being installed.



11. When the installation is complete, the Driver Installer displays a confirmation message. Click **Close** to close the installer.



Now that you have installed the Hortonworks ODBC driver for Mac OS X, the next step is to install the iODBC Driver Manager for Mac OS X.

Step 2 – Download and Install the iODBC Driver Manager for Mac OS X

1. Open a web browser and navigate to:

<http://www.iodbc.org/dataspace/iodbc/wiki/iODBC/Downloads>

Scroll down to the Mac OS X section and select the applicable installer package.

Note: In this tutorial, we successfully installed the latest available version of the iODBC driver for Mac OS X (10.5 Leopard, 10.6 Snow Leopard) on a MacBook Pro running OS X 10.8.3.

Stable (v3.52.7)

The sources for the iODBC Driver Manager are available as a tarball, [libiodbc-3.52.7.tar.gz](#) or from [SourceForge](#). You can also view the [ChangeLog](#).

Source

File	Download
IODBC Source tarball	libiodbc-3.52.7.tar.gz
Linux source RPM	libiodbc-3.52.7-1.src.rpm

Mac OS X

This package contains iODBC as a Framework plus the graphical ODBC configuration administrator and bindings for Microsoft Office:

Mac OS X (10.5 Leopard, 10.6 Snow Leopard) [iodbc-sdk-3.52.7-macosx-10.5.dmg](#)
Mac OS X (10.4 Tiger) [iodbc-sdk-3.52.7-macosx-10.4.dmg](#)

This package contains a bug-fix for the version of iODBC provided by Apple, installing in /usr; this is recommend for compiling interfaces such as Perl DBD::ODBC, the [Ruby ODBC bridge](#) and [PHP](#):


Mac OS X (10.5 Leopard, 10.6 Snow Leopard) [iodbc-usr-sdk.zip](#)

Packages for Linux Distributions

Ubuntu and Debian GNU/Linux have [packages](#) for iodbc:

```
bash# apt-cache search iodbc
```


2. Click **Save File** on the confirmation pop-up message.



Stable (v3.52.7)

The sources for the iODBC Driver Manager are:

Source

File	Download
iODBC Source tarball	libiodbc-3.52.7.tar.gz
Linux source RPM	libiodbc-3.52.7-1.src.rpm

Mac OS X

This package contains iODBC as a Framework plus the graphical ODBC configuration administrator and bindings for Microsoft Office:

Mac OS X (10.5 Leopard, 10.6 Snow Leopard) [iodbc-sdk-3.52.7-macosx-10.5.dmg](#)

Mac OS X (10.4 Tiger) [iodbc-sdk-3.52.7-macosx-10.4.dmg](#)

This package contains a bug-fix for the version of iODBC provided by Apple, installing in /usr; this is recommend for compiling interfaces such as DBD::ODBC, the Ruby ODBC bridge and PHP:


Mac OS X (10.5 Leopard, 10.6 Snow Leopard) [iodbc-usr-sdk.zip](#)

Packages for Linux Distributions

Ubuntu and Debian GNU/Linux have packages for iodbc:

```
bash# apt-cache search iodbc
libiodbc2 - iODBC Driver Manager
libiodbc2-dev - iODBC Driver Manager (development files)
```

3. When the installer file download is complete, double-click the file, then select **Open**.



Stable (v3.52.7)

The sources for the iODBC Driver Manager are:

Source

File	Download
iODBC Source tarball	libiodbc-3.52.7.tar.gz
Linux source RPM	libiodbc-3.52.7-1.src.rpm

Mac OS X

This package contains iODBC as a Framework plus the graphical ODBC configuration administrator and bindings for Microsoft Office:

Mac OS X (10.5 Leopard, 10.6 Snow Leopard) [iodbc-sdk-3.52.7-macosx-10.5.dmg](#)

Mac OS X (10.4 Tiger) [iodbc-sdk-3.52.7-macosx-10.4.dmg](#)

This package contains a bug-fix for the version of iODBC provided by Apple, installing in /usr; this is recommend for compiling interfaces such as DBD::ODBC, the Ruby ODBC bridge and PHP:


Mac OS X (10.5 Leopard, 10.6 Snow Leopard) [iodbc-usr-sdk.zip](#)

Packages for Linux Distributions


Ubuntu and Debian GNU/Linux have packages for iodbc:

```
bash# apt-cache search iodbc
libiodbc2 - iODBC Driver Manager
```


- The driver package appears in a new window. Double-click the driver package, then select **Open**.




- To start the installation, click **Continue** on the ODBC Driver Installer Welcome screen.




6. Review the Read Me information, then click **Continue**.




7. Review the license agreement, then click **Continue**.




8. Click **Agree** on the pop-up message to agree to the license terms.



9. Click **Install** to accept the default installation folder.



10. When the installation is complete, the Driver Installer displays a confirmation message. Click **Close** to close the installer.



Now that you have installed the iODBC Driver Manager for Mac OS X, the next step is to configure the Hortonworks ODBC .ini files.

Step 3 – Configure the Hortonworks ODBC Driver

Overview

To configure the Hortonworks ODBC driver:

1. Enable the Finder to view hidden files.
2. Configure the Hortonworks ODBC .ini files.
3. Set the DYLD_LIBRARY_PATH environmental variable.

Procedure

In this procedure we will edit hidden files that start with a period and are not usually visible with Finder. We will run two Terminal commands to make these files visible with Finder. These commands are case-sensitive.

1. Open Finder (or click an empty portion of the desktop) to display the Finder menu at the top of the screen. Select **Go > Utilities > Terminal**, then click **Open** to open a Terminal window.
2. In the Terminal window, type in the following command, then press the Enter key:

```
defaults write com.apple.Finder AppleShowAllFiles TRUE
```


3. In order for the changes to take effect, you must restart the Finder. To restart the Finder, type the following command in the Terminal window, then press the Enter key.

```
killall Finder
```

You can now view hidden files using the Finder. If you would like to reset Finder later to hide hidden files, use the following Terminal commands to hide hidden files and restart the Finder:

```
defaults write com.apple.Finder AppleShowAllFiles FALSE  
killall Finder
```

4. Use **Go > Go to Folder** or the Finder to navigate to the `/usr/lib/hive/lib/native/hiveodbc/Setup` directory. The Setup directory contains the following sample files:
 - `odbc.ini` and `odbcinst.ini` – sample DSN setup files
 - `hortonworks.hiveodbc.ini` – sample Hortonworks driver configuration file
5. Copy the `hortonworks.hiveodbc.ini` to the Home directory and rename the file as `.hortonworks.hiveodbc.ini` (insert a period at the beginning of the file name).
6. In the Home directory, open the `.hortonworks.hiveodbc.ini` file with TextEdit in plain text mode. Confirm that the line containing the `ODBCInstLib` setting for the iODBC driver manager is uncommented (does not have a `#` symbol at the beginning of the line). The path should be set to the location of the `libiodbcinst.dylib` file by default.



```
[Driver]

## - Note that this default DriverManagerEncoding of UTF-32 is for iODBC.
## - SimbaDM can be used with UTF-8 or UTF-16.
## The DriverUnicodeEncoding setting will cause SimbaDM to run in UTF-8 when set to 2 or UTF-16
when set to 1.

DriverManagerEncoding=UTF-32
DSILogging=0
ErrorMessagesPath=/usr/lib/hive/lib/native/hiveodbc/ErrorMessage/

## - Uncomment the ODBCInstLib corresponding to the Driver Manager being used.
## - Note that the path to your ODBC Driver Manager must be specified in DYLD_LIBRARY_PATH.


# iODBC
ODBCInstLib=/usr/lib/libiodbcinst.dylib

# SimbaDM
#ODBCInstLib=libodbcinst.dylib
#ODBCInstLib=libodbcinst.a(odbcinst.dylib)
```

7. Review the contents of the Home directory. If there are no .odbc.ini or .odbcinst.ini files in the Home directory, copy the odbc.ini and .odbcinst.ini files from the /usr/lib/hive/lib/native/hiveodbc/Setup folder to the Home directory.

Rename the files to .odbc.ini and .odbcinst.ini (insert a period at the beginning of the file name).

Use TextEdit in plain text mode to edit the configuration settings in the .odbc.ini file. The host settings should be set to the IP address of the sandbox. PORT should be set to 10000 (the default listening port). HS2AuthMech should be set to 2, and Username should be set to the sandbox user name (in this case, the default user name "sandbox").

A screenshot of a text editor window titled ".odbc.ini". The window contains the following text:

```
[ODBC]
; Specify any global ODBC configuration here such as ODBC tracing.
[ODBC Data Sources]
Sample Hortonworks Hive DSN = Hortonworks Hive ODBC Driver

[Sample Hortonworks Hive DSN]
; Description: DSN Description.
; This key is not necessary and is only to give a description of the data source.
Description      = Hortonworks Hive ODBC Driver DSN
; Driver: The location where the ODBC driver is installed to.
Driver           = /usr/lib/hive/lib/native/universal/libhortonworkshiveodbc.dylib
; The DriverUnicodeEncoding setting is only used for SimbaDM
; When set to 1, SimbaDM runs in UTF-16 mode.
; When set to 2, SimbaDM runs in UTF-8 mode.
DriverUnicodeEncoding=2
; Values for HOST, PORT, HS2HostFQDN, and HS2KrbServiceName should be set here.
; They can also be specified on the connection string.
HOST             = 192.168.56.101
PORT             = 10000
Schema           = default
FastSQLPrepare   = 0
UseNativeQuery   = 0
HiveServerType   = 2
HS2AuthMech      = 2
HS2HostFQDN      = 192.168.56.101
HS2KrbServiceName = [Hive Server 2 SASL service name]
UserName         = sandbox
```

8. If there is already an .odbc.ini or .odbcinst.ini file in the Home directory, copy the relevant settings from the odbc.ini and .odbcinst.ini sample files in the /usr/lib/hive/lib/native/hiveodbc/Setup folder to the files in the Home directory. Configure the settings as described in the previous step.
9. Finally, add the /usr/lib/hive/lib/native/universal directory to the DYLD_LIBRARY_PATH environment variable. Open a Terminal window and type the following command, then press the Enter key:

```
Launchctl setenv DYLD_LIBRARY_PATH /usr/lib/hive/lib/native/universal
```

This command will set the DYLD_LIBRARY_PATH variable only for the current session – you will need to run the command again each time you log in. To permanently set the DYLD_LIBRARY_PATH environmental variable, navigate to the /etc folder and add the following line to the launchd.conf file:

```
setenv DYLD_LIBRARY_PATH /usr/lib/hive/lib/native/universal
```


If there is no launchd.conf file in the /etc folder, you can use TextEdit to create a launchd.txt file, then rename it to launchd.conf.

Note: You may need to be logged in as an administrator to edit files in the /etc folder.


Now that you have configured the Hortonworks ODBC driver, the next step is to open Excel and test the connection to the Hortonworks sandbox.

Step 4 – Open Excel and Test the Connection to the Hortonworks Sandbox


1. Open a new Excel workbook, then select **Data > Get External Data > New Database Query**.
2. On the iODBC Data Source Chooser window, select the Hortonworks ODBC data source, then click **Test**.



3. On the Login pop-up, type "sandbox" in the Username box, then click **Ok**.




4. It may take several seconds for the connection to be established. After the connection is established, a confirmation message appears. Click **OK** to close the message.



Now that you have configured the Hortonworks ODBC driver, you can use Excel to access data in the Hortonworks sandbox.


5. Open a new Excel workbook, then select **Data > Get External Data > New Database Query**.
6. On the iODBC Data Source Chooser window, select the Hortonworks ODBC data source, then click **OK**.
7. On the Login pop-up, type "sandbox" in the Username box, then click **Ok**. The Microsoft Query window and the Tables pop-up box appear.




8. In the Tables pop-up box, select a table, then click **Add Table**. The table will appear in the top section of the Microsoft Query window. It may take several seconds for the table to appear.

Notes


- The tables listed in the pop-up have been previously created in the Sandbox with a **Create new table** command using either HCatalog or Beeswax (**Beeswax > Tables**).
- In this tutorial, we selected the omniture table previously created in the "Loading Data into the Hortonworks Sandbox" tutorial, but you can select any available table.



9. To preview the table data, select the table in the Field drop-down, then click **Test**. The data will appear in the lower section of the Microsoft Query window. It may take several seconds for the data to appear.



10. To import the data into Excel, click **Return Data** at the bottom right of the Microsoft Query Window, then click **OK** on the Returning Data to Microsoft Excel pop-up box.



11. The table data appears in the Excel workbook.

Column1	Column2	Column3	Column4	Column5	Column6	Column7
ts	ip	url	swid	city	country	state
2012-03-15	99.122.210.2	http://www.7AAB8415-E	homestead	usa	fl	
2012-03-15	69.76.12.213	http://www.8D0E437E-9	coeur d alen	usa	id	
2012-03-15	167.240.15.94	http://www.E3FEB462-C	queensbury	usa	ny	
2012-03-15	167.240.15.94	http://www.E3FEB462-C	queensbury	usa	ny	
2012-03-15	98.234.107.7	http://www.49E0D2E-1	sunnyvale	usa	ca	
2012-03-15	75.85.165.38	http://www.F6F8B460-4	san diego	usa	ca	
2012-03-15	171.53.206.17	http://www.AC4D6E52-2	charlottesville	usa	va	
2012-03-15	197.96.62.161	http://www.56C1008E-6	parrish	usa	fl	
2012-03-15	1129.119.158	http://www.CCSF240A-9	dallas	usa	tx	
2012-03-15	196.241.99.50	http://www.303AADFF-4	capitol heigh	usa	md	
2012-03-15	196.241.99.50	http://www.303AADFF-4	capitol heigh	usa	md	
2012-03-15	124.187.64.39	http://www.66D56071-E	new brunsw	usa	nj	
2012-03-15	98.184.170.4	http://www.04721673-E	tulsa	usa	ok	
2012-03-15	175.135.144.6	http://www.1FC431962-D	rockford	usa	mi	
2012-03-15	167.191.202.2	http://www.A2DB48C4-3	marietta	usa	ga	
2012-03-15	171.53.206.17	http://www.AC4D6E52-2	charlottesville	usa	va	
2012-03-15	169.142.74.25	http://www.8A6915CB-2	ridley park	usa	pa	
2012-03-15	150.15.125.29	http://www.31550A54-1	houston	usa	tx	
2012-03-15	150.15.125.29	http://www.31550A54-1	houston	usa	tx	
2012-03-15	1173.196.5.72	http://www.3487FA7C-B	los angeles	usa	ca	
2012-03-15	206.28.62.19	http://www.AA2E3ECS-6	harold	usa	ky	
2012-03-15	124.253.61.96	http://www.C6A93018-3	las vegas	usa	nv	
2012-03-15	168.33.16.193	http://www.1E81310F-3	hancock	usa	md	
2012-03-15	169.230.197.2	http://www.31978DC6-C	los angeles	usa	ca	
2012-03-15	124.4.226.156	http://www.26A31713-6	san jose	usa	ca	
2012-03-15	171.236.197.3	http://www.9D1A8CAC-3	salem	usa	or	
2012-03-15	1134.84.139.1	http://www.EA1B84CE-3	minneapolis	usa	mn	
2012-03-15	24.167.239.2	http://www.AD3A6D9A-4	south milwa	usa	wi	
2012-03-15	1174.55.131.1	http://www.77D0D0AA-4	clarks summi	usa	pa	
2012-03-15	171.200.5.78	http://www.D0FE7D26-F	milford	usa	de	
2012-03-15	174.240.132.6	http://www.632959CD-0	sidell	usa	la	
2012-03-15	167.6.176.68	http://www.5A084276-B	denver	usa	co	
2012-03-15	174.190.188.1	http://www.CEB1C0DA-4	atlanta	usa	ga	
2012-03-15	1216.96.254.1	http://www.6AD578C4-5	knoxville	usa	tn	
2012-03-15	108.18.57.30	http://www.F4D4F5ED-6	alexandria	usa	va	
2012-03-15	1152.14.218.1	http://www.A37386D5-F	raleigh	usa	nc	
2012-03-15	176.89.18.233	http://www.12CBA6D0-C	bridgeport	usa	vt	
2012-03-15	124.27.26.169	http://www.5D0F56A0-4	austin	usa	tx	