

Pipes

```
sri_dhruthi@Dhruthi: ~  
GNU nano 8.7.1 pipe.c *  
#include <stdio.h>  
#include <unistd.h>  
#include <string.h>  
  
int main()  
{  
    int fd[2];  
    char message[] = "Hello from Parent";  
    char buffer[100];  
  
    pipe(fd);  
  
    if (fork() == 0)  
    {  
        // Child process  
        close(fd[1]);  
  
        read(fd[0], buffer, sizeof(buffer));  
  
        printf("Received: %s\n", buffer);  
  
        close(fd[0]);  
    }  
    else  
    {  
        // Parent process  
        close(fd[0]);  
  
        write(fd[1], message, strlen(message) + 1);  
  
        printf("Message sent\n");  
  
        close(fd[1]);  
    }  
  
    return 0;  
}
```

```
sri_dhruthi@Dhruthi:~$ nano pipe.c  
sri_dhruthi@Dhruthi:~$ gcc pipe.c -o pipe  
sri_dhruthi@Dhruthi:~$ ./pipe  
Message sent  
Received: Hello from Parent  
sri_dhruthi@Dhruthi:~$ |
```

Pipe reader

```
sri_dhruthi@Dhruthi: ~  
GNU nano 8.7.1 pipe_reader.c *  
#include <stdio.h>  
#include <unistd.h>  
  
int main()  
{  
    int fd[2];  
    char buffer[100];  
  
    pipe(fd);  
  
    if (fork() == 0)  
    {  
        close(fd[1]);  
  
        read(fd[0], buffer, sizeof(buffer));  
  
        printf("Received: %s\n", buffer);  
  
        close(fd[0]);  
    }  
    else  
    {  
        close(fd[0]);  
  
        write(fd[1], "Hello from Writer", 18);  
  
        close(fd[1]);  
    }  
  
    return 0;  
}
```

```
sri_dhruthi@Dhruthi:~$ nano pipe_reader.c  
sri_dhruthi@Dhruthi:~$ gcc pipe_reader.c -o pipe_reader  
sri_dhruthi@Dhruthi:~$ ./pipe_reader  
Received: Hello from Writer
```