

Database Assignment 1

Roll No.: 243514

Name: Dhruva Rakesh B

Date: 26-03-24

Note : Use Emp, dept and salgrade table

1. To list all records with sal > 2000 and comm>200

```
mysql> select * from emp where sal > 2000 and comm > 200;
Empty set (0.00 sec)
```

2. To list all record with job='Clerk' or sal>2000

```
mysql> select * from emp
-> where job = 'clerk' or sal > 2000;
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7369	SMITH	CLERK	7902	1980-12-17	800.00	NULL	20
7566	JONES	MANAGER	7839	1981-04-02	2975.00	NULL	20
7698	BLAKE	MANAGER	7839	1981-05-01	2850.00	NULL	30
7782	CLARK	MANAGER	7839	1981-06-09	2450.00	NULL	10
7788	SCOTT	ANALYST	7566	1982-12-09	3000.00	NULL	20
7839	KING	PRESIDENT	NULL	1981-11-17	5000.00	NULL	10
7876	ADAMS	CLERK	7788	1983-01-12	1100.00	NULL	20
7900	JAMES	CLERK	7698	1981-12-03	950.00	NULL	30
7902	FORD	ANALYST	7566	1981-12-03	3000.00	NULL	20
7934	MILLER	CLERK	7782	1982-01-23	1300.00	NULL	10

```
10 rows in set (0.01 sec)
```

3. To list all the record with sal=1250 or 1100 or 2850

```
mysql> select * from emp
-> where sal in (1250,1100,2850);
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7521	WARD	SALESMAN	7698	1981-02-22	1250.00	500.00	30
7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
7698	BLAKE	MANAGER	7839	1981-05-01	2850.00	NULL	30
7876	ADAMS	CLERK	7788	1983-01-12	1100.00	NULL	20

```
4 rows in set (0.01 sec)
```

4. To list all employees with sal>1250 and

```
mysql> select * from emp
-> where sal between 1250 and 2850;
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7499	ALLEN	SALESMAN	7698	1981-02-20	1600.00	300.00	30
7521	WARD	SALESMAN	7698	1981-02-22	1250.00	500.00	30
7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
7698	BLAKE	MANAGER	7839	1981-05-01	2850.00	NULL	30
7782	CLARK	MANAGER	7839	1981-06-09	2450.00	NULL	10
7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30
7934	MILLER	CLERK	7782	1982-01-23	1300.00	NULL	10

```
7 rows in set (0.00 sec)
```

5. To list all employees with name ends with AS

```
mysql> select * from emp where ename regexp '.*AS&';
Empty set (0.02 sec)
```

6. To list all employees with job starts with C and ends with K

```
mysql> select * from emp where job regexp '^C.*K$';
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7369	SMITH	CLERK	7902	1980-12-17	800.00	NULL	20
7876	ADAMS	CLERK	7788	1983-01-12	1100.00	NULL	20
7900	JAMES	CLERK	7698	1981-12-03	950.00	NULL	30
7934	MILLER	CLERK	7782	1982-01-23	1300.00	NULL	10

```
4 rows in set (0.00 sec)
```

7. To list all employees with job contains L at third position and M at third last position

```
mysql> select * from emp where job regexp '^..L.*M..$';
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7499	ALLEN	SALESMAN	7698	1981-02-20	1600.00	300.00	30
7521	WARD	SALESMAN	7698	1981-02-22	1250.00	500.00	30
7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30

4 rows in set (0.00 sec)

8. To list all the record with sal not equal to 1250 or 1100 or 2850

```
mysql> select * from emp where sal not in (1250,1100,2850);
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7369	SMITH	CLERK	7902	1980-12-17	800.00	NULL	20
7499	ALLEN	SALESMAN	7698	1981-02-20	1600.00	300.00	30
7566	JONES	MANAGER	7839	1981-04-02	2975.00	NULL	20
7782	CLARK	MANAGER	7839	1981-06-09	2450.00	NULL	10
7788	SCOTT	ANALYST	7566	1982-12-09	3000.00	NULL	20
7839	KING	PRESIDENT	NULL	1981-11-17	5000.00	NULL	10
7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30
7900	JAMES	CLERK	7698	1981-12-03	950.00	NULL	30
7902	FORD	ANALYST	7566	1981-12-03	3000.00	NULL	20
7934	MILLER	CLERK	7782	1982-01-23	1300.00	NULL	10

10 rows in set (0.00 sec)

9. To list all employees with salnot >1250 and <2850

```
mysql> select * from emp where sal not between 1250 and 2850;
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7369	SMITH	CLERK	7902	1980-12-17	800.00	NULL	20
7566	JONES	MANAGER	7839	1981-04-02	2975.00	NULL	20
7788	SCOTT	ANALYST	7566	1982-12-09	3000.00	NULL	20
7839	KING	PRESIDENT	NULL	1981-11-17	5000.00	NULL	10
7876	ADAMS	CLERK	7788	1983-01-12	1100.00	NULL	20
7900	JAMES	CLERK	7698	1981-12-03	950.00	NULL	30
7902	FORD	ANALYST	7566	1981-12-03	3000.00	NULL	20

7 rows in set (0.00 sec)

10. To list all employees with job starts with C , E at 3rd position and ends with K


```
mysql> select * from emp where job regexp '^C.E.*K$';
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7369	SMITH	CLERK	7902	1980-12-17	800.00	NULL	20
7876	ADAMS	CLERK	7788	1983-01-12	1100.00	NULL	20
7900	JAMES	CLERK	7698	1981-12-03	950.00	NULL	30
7934	MILLER	CLERK	7782	1982-01-23	1300.00	NULL	10

```
4 rows in set (0.00 sec)
```

11. To list all rows with comm is null

```
mysql> select * from emp where comm is NULL;
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7369	SMITH	CLERK	7902	1980-12-17	800.00	NULL	20
7566	JONES	MANAGER	7839	1981-04-02	2975.00	NULL	20
7698	BLAKE	MANAGER	7839	1981-05-01	2850.00	NULL	30
7782	CLARK	MANAGER	7839	1981-06-09	2450.00	NULL	10
7788	SCOTT	ANALYST	7566	1982-12-09	3000.00	NULL	20
7839	KING	PRESIDENT	NULL	1981-11-17	5000.00	NULL	10
7876	ADAMS	CLERK	7788	1983-01-12	1100.00	NULL	20
7900	JAMES	CLERK	7698	1981-12-03	950.00	NULL	30
7902	FORD	ANALYST	7566	1981-12-03	3000.00	NULL	20
7934	MILLER	CLERK	7782	1982-01-23	1300.00	NULL	10

```
10 rows in set (0.00 sec)
```

12. To list all employees with sal is null and name starts with 'S'

```
mysql> select * from emp where sal is null and ename regexp '^S';
```

```
Empty set (0.00 sec)
```

13. To list all employees with job contains 5 characters

```
mysql> select * from emp where job regexp '^.....$';
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7369	SMITH	CLERK	7902	1980-12-17	800.00	NULL	20
7876	ADAMS	CLERK	7788	1983-01-12	1100.00	NULL	20
7900	JAMES	CLERK	7698	1981-12-03	950.00	NULL	30
7934	MILLER	CLERK	7782	1982-01-23	1300.00	NULL	10

```
4 rows in set (0.00 sec)
```

14. To list all employees with name contain 'A' at 1 position and job Contains 5 characters

```
mysql> select * from emp where ename regexp '^A' and job regexp '^.....$';
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7876	ADAMS	CLERK	7788	1983-01-12	1100.00	NULL	20

```
1 row in set (0.00 sec)
```

Q2. Solve the following

1. Retrieve the details (Name, Salary and dept no) of the emp who are working in department code 20, 30 and 40.

```
mysql> select ename,sal,deptno from emp where deptno in (20,30,40);
```

ename	sal	deptno
SMITH	800.00	20
ALLEN	1600.00	30
WARD	1250.00	30
JONES	2975.00	20
MARTIN	1250.00	30
BLAKE	2850.00	30
SCOTT	3000.00	20
TURNER	1500.00	30
ADAMS	1100.00	20
JAMES	950.00	30
FORD	3000.00	20

```
11 rows in set (0.00 sec)
```

2. Display the total salary of all employees . Total salary will be calculated as $sal + comm + sal * 0.10$

```
mysql> select (sal+ifnull(comm,0)+(sal*0.1)) as 'total salary' from emp;
+-----+
| total salary |
+-----+
|      880.000 |
|     2060.000 |
|     1875.000 |
|     3272.500 |
|     2775.000 |
|     3135.000 |
|     2695.000 |
|     3300.000 |
|     5500.000 |
|     1650.000 |
|     1210.000 |
|     1045.000 |
|     3300.000 |
|     1430.000 |
+-----+
14 rows in set (0.00 sec)
```

3. List the Name and job of the emp who have joined before 1 jan 1986 and whose salary range is between 1200 and 2500. Display the columns with user defined Column headers.

```
mysql> select ename as 'Name', job from emp where hiredate < '1986-01-01'
-> and sal between 1200 and 2500;
+-----+-----+
| Name | job |
+-----+-----+
| ALLEN | SALESMAN |
| WARD  | SALESMAN |
| MARTIN | SALESMAN |
| CLARK | MANAGER |
| TURNER | SALESMAN |
| MILLER | CLERK |
+-----+-----+
6 rows in set (0.00 sec)
```

4. List the empno, name, and department number of the emp works under manager with id 7698

```
mysql> select empno,ename,deptno from emp where mgr = 7698;
```

empno	ename	deptno
7499	ALLEN	30
7521	WARD	30
7654	MARTIN	30
7844	TURNER	30
7900	JAMES	30

```
5 rows in set (0.00 sec)
```

5. List the name, job, and salary of the emp who are working in departments 10 and 30.

```
mysql> select ename,job,sal from emp where deptno in (10,30);
```

ename	job	sal
ALLEN	SALESMAN	1600.00
WARD	SALESMAN	1250.00
MARTIN	SALESMAN	1250.00
BLAKE	MANAGER	2850.00
CLARK	MANAGER	2450.00
KING	PRESIDENT	5000.00
TURNER	SALESMAN	1500.00
JAMES	CLERK	950.00
MILLER	CLERK	1300.00

```
9 rows in set (0.00 sec)
```

6. Display name concatenated with dept code separated by comma and space. Name the column as 'Emp info'.

```
mysql> select concat(ename,concat(', ',deptno)) as 'Emp info' from emp;
```

Emp info
SMITH, 20
ALLEN, 30
WARD, 30
JONES, 20
MARTIN, 30
BLAKE, 30
CLARK, 10
SCOTT, 20
KING, 10
TURNER, 30
ADAMS, 20
JAMES, 30
FORD, 20
MILLER, 10

```
14 rows in set (0.00 sec)
```

7. Display the emp details who do not have manager.

```
mysql> select * from emp where mgr is null;
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7839	KING	PRESIDENT	NULL	1981-11-17	5000.00	NULL	10

```
1 row in set (0.00 sec)
```

8. Write a query which will display name, department no and date of joining of all employee who were joined January 1, 1981 and March 31, 1983. Sort it based on date of joining (ascending)


```
mysql> select ename,deptno,hiredate from emp where hiredate between
-> '1981-01-01' and '1983-03-01' order by hiredate;
```

ename	deptno	hiredate
ALLEN	30	1981-02-20
WARD	30	1981-02-22
JONES	20	1981-04-02
BLAKE	30	1981-05-01
CLARK	10	1981-06-09
TURNER	30	1981-09-08
MARTIN	30	1981-09-28
KING	10	1981-11-17
JAMES	30	1981-12-03
FORD	20	1981-12-03
MILLER	10	1982-01-23
SCOTT	20	1982-12-09
ADAMS	20	1983-01-12

13 rows in set (0.00 sec)

9. Display the employee details where the job contains word 'AGE' anywhere in the Job

```
mysql> select * from emp where job regexp '.*AGE.*';
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7566	JONES	MANAGER	7839	1981-04-02	2975.00	NULL	20
7698	BLAKE	MANAGER	7839	1981-05-01	2850.00	NULL	30
7782	CLARK	MANAGER	7839	1981-06-09	2450.00	NULL	10

3 rows in set (0.00 sec)

10. List the details of the employee , whose names start with 'A' and end with 'S' or whose names contains N as the second or third character, and ending with either 'N' or 'S'.

```
mysql> select * from emp where ename regexp '^A.*S$|^..?N.*[NS]$';
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7566	JONES	MANAGER	7839	1981-04-02	2975.00	NULL	20
7876	ADAMS	CLERK	7788	1983-01-12	1100.00	NULL	20

2 rows in set (0.00 sec)

11. List the names of the emp having '_' character in their name.

```
mysql> select ename from emp where ename regexp '[_]';
Empty set (0.00 sec)
```

```
mysql> select ename from emp where ename like '%\_%';
+-----+
| ename  |
+-----+
| uih_jhj |
+-----+
1 row in set (0.00 sec)
```

```
mysql> select ename from emp where ename regexp '_';
+-----+
| ename  |
+-----+
| uih_jhj |
+-----+
1 row in set (0.00 sec)
```

Single Row functions

1. To list all employees and their email, to generate email use 2 to 5 characters from ename Concat it with 2 to 4 characters in job and then concat it with '@mycompany.com'

```
mysql> select ename,concat(substring(ename,2,5),substring(job,2,4),'@mycompany.com'
) as email from emp;
+-----+-----+
| ename  | email                                     |
+-----+-----+
| SMITH  | MITHLERK@mycompany.com                 |
| ALLEN  | LLENALLES@mycompany.com                 |
| WARD   | ARDALES@mycompany.com                   |
| JONES  | ONESANAG@mycompany.com                  |
| MARTIN | ARTINALLES@mycompany.com                |
| BLAKE  | LAKEANAG@mycompany.com                  |
| CLARK  | LARKANAG@mycompany.com                  |
| SCOTT  | COTTNALLY@mycompany.com                 |
| KING   | INGRESI@mycompany.com                   |
| TURNER | URNERALES@mycompany.com                 |
| ADAMS  | DAMSLERK@mycompany.com                  |
| JAMES  | AMESLERK@mycompany.com                  |
| FORD   | ORDNALY@mycompany.com                   |
| MILLER | ILLERLERK@mycompany.com                 |
+-----+-----+
14 rows in set (0.00 sec)
```

2. List all employees who joined in September.

```
mysql> select * from emp where hiredate regexp '-09-';
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30

2 rows in set (0.00 sec)

3. List the empno, name, and department number of the emp who have experience of 18 or more years and sort them based on their experience.

```
mysql> select empno,ename,deptno,floor(datediff(curdate(),hiredate)/365) exp from emp having exp>=18 order by exp;
```

empno	ename	deptno	exp
7788	SCOTT	20	41
7876	ADAMS	20	41
8	u1h_jhj	30	42
7654	MARTIN	30	42
7698	BLAKE	30	42
7782	CLARK	10	42
7839	KING	10	42
7844	TURNER	30	42
7900	JAMES	30	42
7902	FORD	20	42
7934	MILLER	10	42
7369	SMITH	20	43
7499	ALLEN	30	43
7521	WARD	30	43
7566	JONES	20	43

15 rows in set (0.00 sec)

Activate Windows
Go to Settings to activate Windows.

4. Display the employee details who joined on 3rd of any month or any year.

```
mysql> select * from emp where hiredate like '%-%-03';
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
7900	JAMES	CLERK	7698	1981-12-03	950.00	NULL	30
7902	FORD	ANALYST	7566	1981-12-03	3000.00	NULL	20

2 rows in set (0.00 sec)

5. display all employees who joined between years 1981 to 1983.


```
mysql> select * from emp where hiredate between '1981-01-01' and '1983-12-31';
```

EMPNO	ENAME	JOB	MGR	HIREDATE	SAL	COMM	DEPTNO
8	uih_jhj	clerk	5670	1981-05-06	543.00	43.00	30
7499	ALLEN	SALESMAN	7698	1981-02-20	1600.00	300.00	30
7521	WARD	SALESMAN	7698	1981-02-22	1250.00	500.00	30
7566	JONES	MANAGER	7839	1981-04-02	2975.00	NULL	20
7654	MARTIN	SALESMAN	7698	1981-09-28	1250.00	1400.00	30
7698	BLAKE	MANAGER	7839	1981-05-01	2850.00	NULL	30
7782	CLARK	MANAGER	7839	1981-06-09	2450.00	NULL	10
7788	SCOTT	ANALYST	7566	1982-12-09	3000.00	NULL	20
7839	KING	PRESIDENT	NULL	1981-11-17	5000.00	NULL	10
7844	TURNER	SALESMAN	7698	1981-09-08	1500.00	0.00	30
7876	ADAMS	CLERK	7788	1983-01-12	1100.00	NULL	20
7900	JAMES	CLERK	7698	1981-12-03	950.00	NULL	30
7902	FORD	ANALYST	7566	1981-12-03	3000.00	NULL	20
7934	MILLER	CLERK	7782	1982-01-23	1300.00	NULL	10

```
14 rows in set (0.00 sec)
```

Group functions

6. Display the Highest, Lowest, Total & Average salary of all employee. Label the columns Maximum, Minimum, Total and Average respectively for each Department. Also round the result to the nearest whole number.

```
mysql> select round(max(sal)) Maximum,round(min(sal)) Minimum,round(sum(sal)) Total,round(avg(sal)) Average from emp group by deptno;
```

Maximum	Minimum	Total	Average
2850	543	9943	1420
3000	800	10875	2175
5000	1300	8750	2917

```
3 rows in set (0.00 sec)
```

7. Display Department no and number of managers working in that department. Label the column as 'Total Number of Managers' for each department.


```
mysql> select deptno,count(distinct mgr) 'Total Number of Managers' from emp group by deptno;
+-----+-----+
| deptno | Total Number of Managers |
+-----+-----+
|      10 |                2 |
|      20 |                4 |
|      30 |                3 |
+-----+-----+
3 rows in set (0.00 sec)
```

8. Get the Department number, and sum of Salary of all non managers where the sum is greater than 20000

```
mysql> select deptno,sum(sal) from emp where job!='manager' group by deptno having sum(sal)>20000;
Empty set (0.00 sec)
```