

Restaurent Assignment MongoDB

Roll no.: 243514

Name: Dhruva Rakesh B

Date: 03/04/2024

1. Write a MongoDB query to display all the documents in the collection restaurants

```
db.restaurent.find()
```

2. Write a MongoDB query to display the fields restaurant_id, name, borough and cuisine for all the documents in the collection restaurant.

```
db.restaurent.find({}, {restaurant_id:1, name:1, borough:1, cuisine:1})
```

3. Write a MongoDB query to display the fields restaurant_id, name, borough and cuisine, but exclude the field _id for all the documents in the collection restaurant.

```
db.restaurent.find({}, {restaurant_id:1, name:1, borough:1, cuisine:1, _id:0})
```

4. Write a MongoDB query to display the fields restaurant_id, name, borough and zip code, but exclude the field _id for all the documents in the collection restaurant.

```
db.restaurent.find({}, {restaurant_id:1, name:1, borough:1, 'address.zipcode':1, _id:0})
```

5. Write a MongoDB query to display all the restaurant which is in the borough Bronx

```
db.restaurent.find({borough: 'Bronx'})
```

6. Write a MongoDB query to display the first 5 restaurant which is in the borough Bronx.

```
db.restaurent.find({borough: 'Bronx'}).limit(5)
```

7. Write a MongoDB query to display the next 5 restaurants after skipping first 5 which are in the borough Bronx.

```
db.restaurent.find({borough: 'Bronx'}).limit(5).skip(5)
```

8. Write a MongoDB query to find the restaurants who achieved a score more than 90.

```
db.restaurent.find({'grades.score': {$gt: 90}})
```

9. Write a MongoDB query to find the restaurants that achieved a score, more than 80 but less than 100.

```
db.restaurent.find({'grades.score':{$gt:80,$lt:100}})
```

10. Write a MongoDB query to find the restaurants which locate in latitude value less than -95.754168.

```
db.restaurent.find({'address.coord.1':{$lt:-95.754168}})
```

11. Write a MongoDB query to find the restaurants that do not prepare any cuisine of 'American' and their grade score more than 70 and latitude less than -65.754168.

```
db.restaurent.find({'cuisine':{'$nin':['American']}},{'grades.score':{$gt:70},{'address.coord.0':{$lt:-65.754168}})
```

12. Write a MongoDB query to find the restaurants which do not prepare any cuisine of 'American' and achieved a score more than 70 and located in the longitude less than 65.754168.

```
db.restaurent.find({'cuisine':{'$nin':['American']}},{'grades.score':{$gt:70},{'address.coord.1':{$lt:65.754168}})
```

13. Write a MongoDB query to find the restaurants which do not prepare any cuisine of 'American' and achieved a grade point 'A' not belongs to the borough Brooklyn. The document must be displayed according to the cuisine in descending order.

```
db.restaurent.find({'cuisine':{'$nin':['American']}},{'grades.grade':'A',{'borough':{'$nin':['Brooklyn']}}}).sort({'cuisine':-1})
```

14. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which contain 'Wil' as first three letters for its name.

```
db.restaurent.find({'name:/^Wil./},{restaurant_id:1,name:1,borough:1,cuisine:1})
```

15. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which contain 'ces' as last three letters for its name.

```
db.restaurent.find({'name:/.*ces$/},{restaurant_id:1,name:1,borough:1,cuisine:1})
```

16. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which contain 'Reg' as three letters somewhere in its name.

```
db.restaurent.find({name:/. *Reg.* /},{restaurant_id:1,name:1,borough:1,cuisine:1})
```

17. Write a MongoDB query to find the restaurants which belong to the borough Bronx and prepared either American or Chinese dish.

```
db.restaurent.find({borough:'Bronx',cuisine:{$in:['American','Chinese']}})
```

18. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which belong to the borough Staten Island or Queens or Bronx or Brooklyn.

```
db.restaurent.find({borough:{$in:['Staten Island','Queens','Bronx','Brooklyn']},{restaurant_id:1,name:1,borough:1,cuisine:1})
```

19. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which are not belonging to the borough Staten Island or Queens or Bronx or Brooklyn.

```
db.restaurent.find({borough:{$nin:['Staten Island','Queens','Bronx','Brooklyn']},{restaurant_id:1,name:1,borough:1,cuisine:1})
```

20. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which achieved a score which is not more than 10.

```
db.restaurent.find({'grades.score':{$lte:10}},{restaurant_id:1,name:1,borough:1,cuisine:1})
```

21. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which prepared dish except 'American' and 'Chinees' or restaurant's name begins with letter 'Wil'.

```
db.restaurent.find({cuisine:{$nin:['American','Chinese']},name:/^Wil.* /},{restaurant_id:1,name:1,borough:1,cuisine:1})
```

22. Write a MongoDB query to find the restaurant Id, name, and grades for those restaurants which achieved a grade of "A" and scored 11 on an ISODate "2014-08-11T00:00:00Z" among many of survey dates

```
db.restaurent.find({'grades.grade':'A','grades.score':11,'grades.1.date':ISODate('2014-08-11T00:00:00.000Z')},{restaurant_id:1,name:1,grades:1})
```

23. Write a MongoDB query to find the restaurant Id, name and grades for those restaurants where the 2nd element of grades array contains a grade of "A" and score 9 on an ISODate "2014-08-11T00:00:00Z".

```
db.restaurent.find({'grades.1.grade':'A','grades.1.score':9,'grades.1.date': ISODate('2014-08-11T00:00:00.000Z')},{restaurant_id:1,name:1,grades:1})
```

24. Write a MongoDB query to find the restaurant Id, name, address and geographical location for those restaurants where 2nd element of coord array contains a value which is more than 42 and upto 52

```
db.restaurent.find({'address.coord.1':{'$gt:42,$lt:52'}},{restaurant_id:1,name:1,address:1})
```

25. Write a MongoDB query to arrange the name of the restaurants in ascending order along with all the columns.

```
db.restaurent.find({}).sort({name:1})
```

26. Write a MongoDB query to arrange the name of the restaurants in descending along with all the columns.

```
db.restaurent.find({}).sort({name:-1})
```

27. Write a MongoDB query to arranged the name of the cuisine in ascending order and for that same cuisine borough should be in descending order.

```
db.restaurent.find({}).sort({cuisine:1},{borough:-1})
```

28. Write a MongoDB query to know whether all the addresses contains the street or not.

```
db.restaurent.find({'address.street':{'$in:[null],$exists:true'}})
```

```
db.restaurent.find({'address.street':null})
```

29. Write a MongoDB query which will select all documents in the restaurants collection where the coord field value is Double.

```
db.restaurent.find({'address.coord':{'$type':'double'}})
```

30. Write a MongoDB query which will select the restaurant Id, name and grades for those restaurants which returns 0 as a remainder after dividing the score by 7.

```
db.restaurent.find({'grades.score':{'$mod':[7,0]}},{restaurant_id:1,name:1,grades:1})
```

31. Write a MongoDB query to find the restaurant name, borough, longitude and attitude and cuisine for those restaurants which contains 'mon' as three letters somewhere in its name.

```
db.restaurent.find({name:/.*mon.*/{},{name:1,borough:1,'address.coord':1,cuisine:1})
```

32. Write a MongoDB query to find the restaurant name, borough, longitude and latitude and cuisine for those restaurants which contain 'Mad' as first three letters of its name.

```
db.restaurent.find({name:/^Mad.*/{},{name:1,borough:1,'address.coord':1,cuisine:1})
```