Archi Query Screenshots

A few examples from local testing on v2.0.0rc2 with Gemini 2.5 Flash

Query 1

You

what is couchDB

Agent Activity 1m 18s

617 prompt + 540 completion = 1,157 tokens

archi

CouchDB is a **distributed, JSON document-oriented database** designed for high availability, scalability, and ease of use. Key features include:

1. **Document-Centric Storage**: Stores data as JSON documents (e.g., `{ "name": "Alice", "email": "alice@example.com" }`).
2. **Replication**: Built-in replication for data synchronization across multiple nodes.
3. **Conflict-Free Updates**: Resolves conflicts during replication using a "last writer wins" or custom logic.
4. **RESTful API**: Accessible via HTTP, making it easy to integrate with web applications.
5. **Offline Operation**: Supports offline data storage with eventual synchronization.

It is commonly used in scenarios requiring decentralized data management, such as mobile backends, IoT, or collaborative applications. Would you like details about its architecture, use cases, or how it compares to other databases?

CMS Comp Ops · gemini/gemini-3-flash-preview

Query 2

Chat

Chat

You

couchDB WMAgent draining

Agent Activity 2m 19s

archi

The term **"CouchDB WMAgent draining"** is not a standard or widely documented phrase, but based on context, it likely refers to a scenario involving **CouchDB** (a NoSQL database) and a **Workflow Management Agent (WMAgent)**, possibly in a distributed computing or data processing environment (e.g., HPC, LHC, or custom workflows). Here's how to interpret and address it:

Possible Interpretations

1. **Draining in CouchDB**
   - **Draining** in CouchDB typically refers to a process where a node (server) is gracefully shut down, ensuring data is replicated or moved before termination. This is part of **horizontal scaling** or **failover** mechanisms.
2. **WMAgent Interaction**
   - **WMAgent** could be a custom or third-party tool (e.g., a workflow scheduler, data aggregator, or monitoring agent) that interacts with CouchDB.
   - "Draining" might imply the WMAgent is **terminating connections**, **stopping data ingestion**, or **shutting down gracefully** while ensuring data consistency.

Troubleshooting Steps

1. **Check Logs**
   - Look for **CouchDB logs** (`/var/log/couchdb/`) or **WMAgent logs** for errors during draining.
   - Search for terms like `drain` , `shutdown` , `replication` , or `conflict` .
2. **Verify Configurations**
   - Ensure **CouchDB replication settings** are correct (e.g., `replica_timeout` , `auto_compaction`).
   - Check if the WMAgent is configured to **pause writes** or **trigger replication** before draining

Failed to retrieve from documents with qwen3:8b.

Query 3

You

What are the steps to handle a transfer failure?

Agent Activity (2 tools) 21.2s

archi

{'type': 'text', 'text': 'To handle a transfer failure, follow these steps:\n\n### **1. Detect the Transfer Failure**\n* **Alert-Driven**: Look for `RucioTransferFailureSpike` alerts, which trigger when a site-pair failure', 'extras': {'signature': 'Cl8Bvj72+ywh7QTaw/OLu3thDBEQKg4k3UjQn5AzlUTCuAwxtBtky4vVf/
ymHsed7NKzDw9RhTXpRNjDNeLWQo+PtAysf3n7o2YhCm2epaMVjfFGdPcxNkK0oiByJB9WcwqoAgG+Pvb7Ozfn1WuW2YxxB4PzQszkVyU
+IE+JukrfLxL34uxhz9IXbnrYq9IEMUKx4gi8Ywi0rkuQL97MGyJ1Z9py+Crq0mSjchF78e6HkoiADwQBSeIJUVTIOrhk2gpJVFfVABajnd6yu2j4X
O/
AYVfCyWHV1hVXYmpWiW7gdK6NvDb7uD7NMEKIOLKa+3Ee6rXomIS9wCug5yssSiFZnmtaLOZJZyBG3whimpNMZNI4T6oKuP0IoXgsOuNC
fyILFGUt2QvgglrLH5bCqLOXnuI85jxQhWZfZ/N9pLoyD26EGEDIM9+
+FBaiPsK4SamGMvuwb4q7c4jVDAOdSUwq0BW80R2PryX7t5ZgVaOoftWHO5z1dKZAXw4/
XcUk8hSjvL8DWwcLM23aYfoq1zpEbiOXBYbAH4/H/
OviR0tnAqDhqLsTZUfEujwIFMUdudLay37DQ2QRaiVT6gSAdA9chBinPmFBstUiNQGecXY4PgJNMtKYtUpcgpqdpY/
FPmfquLw/njRcAfts7TZ4/74Ib+yp+i0cILSdFwrYbMvRUOPTSE4ltBfScV3/QibdVx+dfRIKkPOspeA=='},
'index': 0} rate exceeds 20% for 15 minutes. The alert provides the source RSE, destination RSE, failure rate, and file count.

- **Proactive Monitoring**: Check the Rucio ConMon dashboard (https://monit-grafana.cern.ch/rucio-conmon/) for:
  - Transfer queues growing without draining (files accumulating in `SUBMITTING` state).
  - Rules stuck in `REPLICATING` state for over 24 hours.
  - Sites with unusually low incoming transfer rates.
- **Workflow-Driven**: If a workflow is stuck in the `Acquired` state and MSTransferor logs show a rule in `STUCK` state, use `rucio rule-info <rule-id>` to confirm.

2. Characterize the Failure: Get the Error Message

- **FTS WebUI (recommended)**: Go to https://fts3.cern.ch/ftsmon/, filter by source and destination storage, and click on a failed transfer to see full error details.
- **Rucio CLI**:
  - `rucio list-requests --src-rse=<SOURCE_RSE> --dst-rse=<DEST_RSE> --state=FAILED | head`

Correct answer but thought signature leakage.

Query 4

You

Who is the current shift operator on duty?

Agent Activity 6.1s

archi

{'type': 'text', 'text': 'I cannot provide you with the real-time information about who the current shift operator on duty is. My knowledge base contains historical data and documentation, not live operational schedules. \n\nTo find out who is currently on shift, you would', 'extras': {'signature': 'CmUBvj72+3gAQsQ88/
uoExDYOyZF4tyFMjJsvK071ZrpgjqciKjtx3kZs6hgzofAjtDCe0yrYPxYKHFYkddTAwZKKCsuvARPriw0l4NvqphVntuOA29R56tISOcE2AA
ikTQ3z6Y8i6Fyz3mKKSVdl/32pGx3p1ba589×9gRtavBBWjDiNJA4nTT35cMQ/
X+c3d02fqr7XAlEPK+P1eFMV3gK6+TlliDIUgAJ0GoLEQDBSeE7UfGOEYwRwD51+mQJyrgzMkB4SZZZd6Qz+6jCOjMnzVHDLCp6tJyeh
PMG+6Brn7Tw81bNNEJBa/0JPkcTSr71OBaVyjEThrVmooQT3LY0QMiXiPTH29LWKvUzkArG53El0tWjNGEBv9PyQJnUD+iRXFJVKeono
HbxqPwRuVtbMDXBMvrudOt+/
Lt0uV7lvO5sge1aLFMw17RUW9hYxHBiC9y51jNyKsnu8FGnUG1mDDKYRubVJN9S1zvAsZB5tzjhXxyBEVyQ6H5+iE8zB0nWltWlQqy0OL
'index': 0} typically need to check:

- **CMS shift schedules**: These are usually available through internal calendars or dedicated shift management systems.
- **CMS Operations communication channels**: Such as a dedicated chat, mailing list, or a shift handover document for the current day.

CMS Comp Ops · gemini/gemini-3-flash-preview

Acknowledges when knowledge is outside its database.