```
> clang-7 -pthread -lm -o main main.c
> ./main

 1. Insert to Queue (EnQueue)
 2. delete from the Queue (DeQueue)
 3. Display the content
 Enter the option :1
Enter the element
1

 1. Insert to Queue (EnQueue)
 2. delete from the Queue (DeQueue)
 3. Display the content
 Enter the option :1
Enter the element
2

 1. Insert to Queue (EnQueue)
 2. delete from the Queue (DeQueue)
 3. Display the content
 Enter the option :1
Enter the element
3

 1. Insert to Queue (EnQueue)
 2. delete from the Queue (DeQueue)
 3. Display the content
 Enter the option :3

Queue contents:123
 1. Insert to Queue (EnQueue)
 2. delete from the Queue (DeQueue)
 3. Display the content
 Enter the option ;2
Removed element from the queue 1
 1. Insert to Queue (EnQueue)
```

```
2. delete from the Queue (DeQueue)
3. Display the content
Enter the option :3

Queue contents:123
1. Insert to Queue (EnQueue)
2. delete from the Queue (DeQueue)
3. Display the content
Enter the option :2
Removed element from the queue 1
1. Insert to Queue (EnQueue)
2. delete from the Queue (DeQueue)
3. Display the content
Enter the option :2
Removed element from the queue 2
1. Insert to Queue (EnQueue)
2. delete from the Queue (DeQueue)
3. Display the content
Enter the option :2
Removed element from the queue 3
1. Insert to Queue (EnQueue)
2. delete from the Queue (DeQueue)
3. Display the content
Enter the option :2
Queue is empty

1. Insert to Queue (EnQueue)
2. delete from the Queue (DeQueue)
3. Display the content
Enter the option :3
Queue is empty

1. Insert to Queue (EnQueue)
2. delete from the Queue (DeQueue)
3. Display the content
Enter the option :
```