
 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Computer Networks (01CT0503)	Aim: Simulate star topology and check the connectivity between devices.	
Experiment No: 03	Date: 22-08-2024	Enrolment No: 92200133029


Aim: Simulate star topology and check the connectivity between devices.

Step – 1: Take PC and Switches.



Step – 2 : Connect PC and Switches via cables.



 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Computer Networks (01CT0503)	Aim: Simulate star topology and check the connectivity between devices.	
Experiment No: 03	Date: 22-08-2024	Enrolment No: 92200133029

Step – 3 : Give the IP address to all PCs.

PC0

Physical Config **Desktop** Programming Attributes

IP Configuration

Interface FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IPv4 Address 10.0.0.1

Subnet Mask 255.0.0.0

Default Gateway 0.0.0.0

DNS Server 0.0.0.0

IPv6 Configuration

☐ Automatic ☒ Static

PC1

Physical Config **Desktop** Programming Attributes

IP Configuration

Interface FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IPv4 Address 10.0.0.2


Subnet Mask 255.0.0.0

Default Gateway 0.0.0.0

DNS Server 0.0.0.0

IPv6 Configuration

☐ Automatic ☒ Static

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Computer Networks (01CT0503)	Aim: Simulate star topology and check the connectivity between devices.	
Experiment No: 03	Date: 22-08-2024	Enrolment No: 92200133029

PC2

Physical Config **Desktop** Programming Attributes

IP Configuration

Interface FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IPv4 Address 10.0.0.3

Subnet Mask 255.0.0.0

Default Gateway 0.0.0.0

DNS Server 0.0.0.0

IPv6 Configuration

☐ Automatic ☒ Static

IPv6 Address

Link Local Address FE80::20D:BDFF:FE71:CDCA

Default Gateway

DNS Server

802.1X

PC3

Physical Config **Desktop** Programming Attributes

IP Configuration

Interface FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IPv4 Address 10.0.0.4

Subnet Mask 255.0.0.0

Default Gateway 0.0.0.0

DNS Server 0.0.0.0

IPv6 Configuration


☐ Automatic ☒ Static

IPv6 Address

Link Local Address FE80::200:CFF:FE4A:6330

Default Gateway

DNS Server

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Computer Networks (01CT0503)	Aim: Simulate star topology and check the connectivity between devices.	
Experiment No: 03	Date: 22-08-2024	Enrolment No: 92200133029

PC4

Physical Config **Desktop** Programming Attributes

IP Configuration

Interface FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IPv4 Address 10.0.0.5

Subnet Mask 255.0.0.0

Default Gateway 0.0.0.0

DNS Server 0.0.0.0

IPv6 Configuration

☐ Automatic ☒ Static

IPv6 Address

Link Local Address FE80::202:4AFF:FE27:A854

PC5

Physical Config **Desktop** Programming Attributes

IP Configuration

Interface FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IPv4 Address 10.0.0.6

Subnet Mask 255.0.0.0

Default Gateway 0.0.0.0


DNS Server 0.0.0.0

IPv6 Configuration

☐ Automatic ☒ Static

IPv6 Address

Link Local Address FE80::201:96FF:FEE7:17A4

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Computer Networks (01CT0503)	Aim: Simulate star topology and check the connectivity between devices.	
Experiment No: 03	Date: 22-08-2024	Enrolment No: 92200133029

Step – 4 : Check connections in command prompt.

PC0

Physical Config Desktop Programming Attributes

Command Prompt

```

Cisco Packet Tracer PC Command Line 1.0
C:\>ping 10.0.0.4

Pinging 10.0.0.4 with 32 bytes of data:

Reply from 10.0.0.4: bytes=32 time=3ms TTL=128
Reply from 10.0.0.4: bytes=32 time<1ms TTL=128
Reply from 10.0.0.4: bytes=32 time<1ms TTL=128
Reply from 10.0.0.4: bytes=32 time<1ms TTL=128

Ping statistics for 10.0.0.4:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 3ms, Average = 0ms
  
```


```

C:\>ping 10.0.0.2

Pinging 10.0.0.2 with 32 bytes of data:

Reply from 10.0.0.2: bytes=32 time=1ms TTL=128
Reply from 10.0.0.2: bytes=32 time<1ms TTL=128
Reply from 10.0.0.2: bytes=32 time<1ms TTL=128
Reply from 10.0.0.2: bytes=32 time<1ms TTL=128

Ping statistics for 10.0.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms
  
```

 Marwadi University Marwadi Chandarana Group	Marwadi University Faculty of Engineering and Technology Department of Information and Communication Technology	
Subject: Computer Networks (01CT0503)	Aim: Simulate star topology and check the connectivity between devices.	
Experiment No: 03	Date: 22-08-2024	Enrolment No: 92200133029

Conclusion:

In Packet Tracer, simulation of a Star topology, I connected several devices to a central switch, which made it easier to manage and troubleshoot the network. To check if the devices were connected properly, I used the ping command, which helps test if one device can reach another. By sending ping requests, I confirmed that all devices were successfully linked to the switch and could communicate with each other. This exercise showed how a Star topology makes network management simple and ensures stable connections between devices.