

Blockchain Technology

D2

19BCE248

Practical 5

AIM: Implementing Smart Contract for your respective Term Paper topic

Topic: Smart Parking System

Code:

```
pragma solidity ^0.5.0;
contract SmartParking{
    struct Parking{
        bool isParked;
        uint price;
        bool isSpecial;
    }
    struct Person{
        bool isGuest;
        bool isAuthenticated;
    }

    Parking[] public parking;
    Person[] public person;

    function addPerson(bool isGuest,bool isAuthenticated) public {
        person.push(Person(isGuest,isAuthenticated));
    }

    function addParking(bool isParked,uint price,bool isSpecial) public {
        parking.push(Parking(isParked,price,isSpecial));
    }

    function getVacantPlace(bool isGuest) public view returns(uint){
        for(uint i=0;i<parking.length;i++){
            if(!parking[i].isParked ){
                if(isGuest && !parking[i].isSpecial){
                    return i;
                }else if(!isGuest && parking[i].isSpecial){
                    return i;
                }
            }
        }
        return 1000;
    }
}
```

```

    function allocateParking(bool isGuest, bool isAuthenticated) public
returns(bool){
    require(isAuthenticated);
    uint slotIndex=getVacantPlace(isGuest);
    if(slotIndex==1000){
        return false;
    }
    parking[slotIndex].isParked=true;
}
}

```

Here we have implemented a very basic level of smart contract which covers most of the concept of solidity and to get familiar with the syntax as well as the remix environment.

There are mainly two stakeholders:

- 1) Person (Consumer)
 - isGuest : Tells information about whether the particular person is daily visitor or guest.
 - isAuthenticated: A very essential part to see whether he/she has a valid existential or are bind with some inappropriate activities which could further lead some problem to owner.
- 2) Parking (Supplier)
 - isParked: Occupied/Vacant
 - price: amount of parking slot
 - isSpecial: Already reserved for daily customer or for the owners or pre-booked.

Similarly we have three functions namely:

- 1) addPerson : Called whenever a new person arrives at entry gate
- 2) addParking : Pre-defined at the time of construction
- 3) getVacantPlace : According to current snapshot return index of vacant places
- 4) allocateParking : getVacantPlace check for authenticity and allocate parking if all the requirements fulfilled.

Output:

Parking:

- 1) false,35,false
- 2) false,35,false
- 3) false,35,false
- 4) false,50,true
- 5) false,50,true

allocateParking:

1) true,true

transaction hash	0xe607bac5a1481076c27e193319ffc8fdb70eedea0ce1ff8ba30ff43531334165 🔗
from	0x5B38Da6a701c568545dCfcB03FcB875f56beddC4 🔗
to	SmartParking.allocateParking(bool,bool) 0x0fC5025C764cE34df352757e82f7B5c4Df39A836 🔗
gas	56495 gas 🔗
transaction cost	49126 gas 🔗
execution cost	49126 gas 🔗
input	0x532...00001 🔗

2) true,true

status	true Transaction mined and execution succeed
transaction hash	0x92834b2fe2da16921eccb5997fea8acfda1f62d41975196a868ace02940656ad 🔗
from	0x5B38Da6a701c568545dCfcB03FcB875f56beddC4 🔗
to	SmartParking.allocateParking(bool,bool) 0x0fC5025C764cE34df352757e82f7B5c4Df39A836 🔗

3) true,true


Will again allocate

4) true,true

decoded output	{ "0": "bool: false" }
----------------	------------------------------

Deny

5) false,false

	[vm] from: 0x5B3...eddC4 to: SmartParking.allocateParking(bool,bool) 0x0fC...9A836 value: 0 wei data: 0x532...00000 logs: 0 hash: 0x36b...14ff7 transact to SmartParking.allocateParking errored: VM error: revert.
---	---

Error due to not authenticate person