

Linux module : 5 – assignment

Que: Schedule tasks using cron or at.

Ans: A time-based job scheduler that can run commands or scripts at specific times or intervals. You can use the crontab command to create, edit, and view cron jobs:

- **Create a cron job:** Use the crontab -e command to open the crontab file in a text editor. Add a new line with the task you want to schedule. The line should include five fields that specify the time and day of the task, followed by the command to run.
- **Edit a cron job:** Use the crontab -e command again to open the crontab file.
- **View cron jobs:** Use the crontab -l command to see a list of all your scheduled cron jobs.
- **Remove cron jobs:** Use the crontab -r command to delete all cron jobs for the current user.

Que: use yum to install, update, and remove software packages.

Ans:

- **Install a package:** Use the command `sudo yum install <pckg-name>`
- **Update a package:** Use the command `sudo yum update <pckg-name>`
- **Remove a package:** Use the command `sudo yum remove <pckg-name>`

Que: install all httpd packages.

Ans: done in lab.

Que: Open kickstart configuration graphically.

Ans:

1. Select the Main Menu Button on the Panel
2. Select System Tools
3. Select Kickstart

Que: Configure new kickstart file.

Ans:

- Create a Kickstart file.
- Make the Kickstart file available on removable media, a hard drive or a network location.
- Create boot media, which will be used to begin the installation.
- Make the installation source available.
- Start the Kickstart installation.

Que: Show full configuration of new kickstart file.

Ans:

- To show the configuration of a new kickstart file in Linux, you can use the ksvalidator command line utility to verify that the file is valid. You can replace /path/to/kickstart.ks with the path to the kickstart file you want to verify.
- A kickstart configuration file contains all the information required to perform an automated installation. Here are some ways to create a kickstart file:

- ❖ **Use the Kickstart Configurator:** Available from Red Hat
- ❖ **Copy a kickstart configuration:** From another system
- ❖ **Write the file manually:** You can use a text editor like Gedit or vim on Linux systems, or Notepad on Windows systems

Que: Validate new kickstart file.

Ans:

- To validate a Kickstart file in Linux, you can use the ksvalidator command line utility:
 1. Run ksvalidator /path/to/kickstart.ks
 2. Replace /path/to/kickstart.ks with the path to the Kickstart file you want to verify
- The ksvalidator tool checks for: Correct syntax and Deprecated options.
- However, it doesn't guarantee that the installation will be successful.

Que: All http on firewall.

Ans:

- ❖ To allow all incoming HTTP connections on a Linux firewall, you can use the following commands:
 - iptables: `sudo iptables -A INPUT -p tcp --dport 80 -m conntrack --ctstate NEW,ESTABLISHED -j ACCEPT`
 - firewall-cmd: `sudo firewall-cmd --permanent --zone=public --add-service=http`

- ❖ You can also use the `firewall-cmd` command to allow HTTPS traffic by running `sudo firewall-cmd --permanent --zone=public --add-service=https`.
- ❖ To save the `firewalld` rules, you can run `sudo firewall-cmd --reload`.

Que: Reload firewall.

Ans: To reload a firewall in Linux, you can use the command line tool `firewall-cmd --reload`:

- **`firewall-cmd --reload`:** Reloads firewall rules and keeps state information. The current permanent configuration becomes the new runtime configuration.
- **`firewall-cmd --complete-reload`:** Reloads the firewall completely, including `netfilter` kernel modules. This will likely terminate active connections because state information is lost.

Que: start and restart http.

Ans: To start and restart the Hyper Text Transfer Protocol (HTTP) server, in Linux, you can use the terminal to run the following commands:

- ❖ **Start:** To start `httpd`, you can use the `systemctl start httpd` command.
- ❖ **Restart:** To restart `httpd`, you can run the command `sudo systemctl restart httpd`.

Que: install new foundation using new kickstart file.

Ans: done in lab.

