

# Security Scan Report

Target: /fake/target

Scan Date: August 26, 2026 at 21:48 UTC

Scan ID: d178974c-830a-4e99-853f-bae357aa7f00

0 CRITICAL

1 HIGH

0 MEDIUM

2 LOW

# Executive Summary

Security scan of '/fake/target' identified 4 raw findings, reduced to 3 unique issues after deduplication. ■ 1 HIGH-severity issue(s) should be prioritized for remediation within the next 48 hours. 2 LOW-priority issue(s) have been logged for backlog tracking.

## Scan Statistics

| Metric              | Value |
|---------------------|-------|
| Total Raw Findings  | 4     |
| After Deduplication | 3     |
| Critical Findings   | 0     |
| High Findings       | 1     |
| Medium Findings     | 0     |
| Low Findings        | 2     |
| Scan Duration       | 0.0s  |

# Detailed Findings

## [HIGH] #1: Sql Injection in users.py:42

|                    |                        |
|--------------------|------------------------|
| Risk Score         | 0.5488                 |
| Affected Location  | app/routes/users.py:42 |
| Vulnerability Type | SQL_INJECTION          |
| CWE ID             | CWE-89                 |
| Detected By        | semgrep                |

**Explanation**  
SQL Injection occurs when user-controlled input is directly interpolated into SQL queries, allowing an attacker to alter query logic. Found in users.py.

**Code or HTTP Excerpt**

```
42 | query = f"SELECT * FROM users WHERE id = {user_id}"
```

**Business Impact**  
An attacker could read, modify, or delete user accounts and personal data, potentially exfiltrating the entire database including credentials and PII.

**Fix Recommendation**  
**Best Fix:** Use parameterized/prepared queries instead of string concatenation. Pass user input as bind parameters, not as part of the query string.

---

## [LOW] #2: Xss in render.py:15

|                    |                        |
|--------------------|------------------------|
| Risk Score         | 0.3478                 |
| Affected Location  | app/utils/render.py:15 |
| Vulnerability Type | XSS                    |
| CWE ID             | CWE-79                 |
| Detected By        | semgrep                |

**Explanation**  
Cross-Site Scripting (XSS) allows attackers to inject malicious scripts into web pages viewed by other users. Found in render.py.

**Business Impact**  
An attacker could steal session tokens from user accounts and personal data, redirect users to phishing pages, or perform actions as the victim.

**Fix Recommendation**  
**Best Fix:** Apply context-aware output encoding before rendering user content. Use your framework's built-in auto-escaping.

---

### [LOW] #3: Hardcoded Secret in settings.py:8

|                    |                      |
|--------------------|----------------------|
| Risk Score         | 0.3168               |
| Affected Location  | config/settings.py:8 |
| Vulnerability Type | HARDCODED_SECRET     |
| Detected By        | semgrep              |

#### Explanation

Hardcoded credentials, API keys, or tokens in source code can be extracted by anyone with repository access. Found in settings.py.

#### Business Impact

The exposed credentials could grant unauthorized access to user credentials and passwords, enabling data theft or service abuse.

#### Fix Recommendation

**Best Fix:** Move the password to an environment variable. Use `os.environ.get('DB_PASSWORD')` instead of the literal string. Rotate the exposed password immediately.

---

# Appendix

## Deduplication Statistics

Total raw findings: 4 | After deduplication: 3 | Reduction: 25%

## Scan Metadata

|                  |                                      |
|------------------|--------------------------------------|
| Scan ID          | d178974c-830a-4e99-853f-bae357aa7f00 |
| Target           | /fake/target                         |
| Timestamp        | 2026-08-26T21:48:29.455817+00:00     |
| Duration         | 0.0s                                 |
| Scanners Used    | semgrep                              |
| Scanner Versions | semgrep=unknown                      |

## Raw Findings Data (JSON)

```
[
  {
    "id": "f0690813-19e3-4c00-829f-a81046bd20d2",
    "title": "Sql Injection in users.py:42",
    "file": "app/routes/users.py",
    "line_start": 42,
    "line_end": null,
    "severity": "HIGH",
    "vuln_type": "SQL_INJECTION",
    "description": "SQL injection via string concatenation",
    "rule_id": "python.lang.security.sqli",
    "confidence": 0.9,
    "cwe_id": "CWE-89",
    "cvss_score": null,
    "code_snippet": "query = f\"SELECT * FROM users WHERE id = {user_id}\"",
    "sources": [
      "semgrep"
    ],
    "risk_score": 0.5488,
    "risk_category": "HIGH",
    "category_source": "vuln_floor",
    "category_reason": "minimum floor for SQL_INJECTION",
    "llm_explanation": "SQL Injection occurs when user-controlled input is directly interpolated into SQL queries",
    "fix_suggestion": "Use parameterized/prepared queries instead of string concatenation. Pass user input as a parameter.",
    "business_impact": "An attacker could read, modify, or delete user accounts and personal data, potentially leading to data breaches or account hijacking.",
    "attack_path": "UNKNOWN: deterministic fallback has no runtime proof.",
    "next_test": "Run one authorized, read-only validation test and stop if it changes state or exposes read-only data.",
    "raw": {}
  },
  {
    "id": "72d69a39-4f85-4cba-9a12-f57267465e06",
    "title": "Xss in render.py:15",
    "file": "app/utils/render.py",
    "line_start": 15,
    "line_end": null,
    "severity": "MEDIUM",
    "vuln_type": "XSS",
    "description": "Unescaped user input in template",
    "rule_id": "python.flask.security.xss",
  }
]
```

```

    "confidence": 0.7,
    "cwe_id": "CWE-79",
    "cvss_score": null,
    "code_snippet": null,
    "sources": [
        "semgrep"
    ],
    "risk_score": 0.3478,
    "risk_category": "LOW",
    "category_source": "score",
    "category_reason": "score-threshold",
    "llm_explanation": "Cross-Site Scripting (XSS) allows attackers to inject malicious scripts into web pages.",
    "fix_suggestion": "Apply context-aware output encoding before rendering user content. Use your framework's built-in escaping functions.",
    "business_impact": "An attacker could steal session tokens from user accounts and personal data, redirecting them to malicious sites.",
    "attack_path": "UNKNOWN: deterministic fallback has no runtime proof.",
    "next_test": "Run one authorized, read-only validation test and stop if it changes state or exposes read-only data.",
    "raw": {}
},
{
    "id": "48d20751-7f24-44bf-83b9-edbcbb434ed4",
    "title": "Hardcoded Secret in settings.py:8",
    "file": "config/settings.py",
    "line_start": 8,
    "line_end": null,
    "severity": "LOW",
    "vuln_type": "HARDCODED_SECRET",
    "description": "Hardcoded password detected",
    "rule_id": "python.lang.security.hardcoded-password",
    "confidence": 0.4,
    "cwe_id": null,
    "cvss_score": null,
    "code_snippet": null,
    "sources": [
        "semgrep"
    ],
    "risk_score": 0.3168,
    "risk_category": "LOW",
    "category_source": "score",
    "category_reason": "score-threshold",
    "llm_explanation": "Hardcoded credentials, API keys, or tokens in source code can be extracted by anyone with access to the code repository.",
    "fix_suggestion": "Move the password to an environment variable. Use os.environ.get('DB_PASSWORD') instead of a hardcoded string.",
    "business_impact": "The exposed credentials could grant unauthorized access to user credentials and passwords.",
    "attack_path": "UNKNOWN: deterministic fallback has no runtime proof.",
    "next_test": "Run one authorized, read-only validation test and stop if it changes state or exposes read-only data.",
    "raw": {}
}
]

```