Protocol-Based Attacks

Dr. Pinaki Sankar Chatterjee

Definition:

Protocol-based attacks exploit weaknesses or flaws in the design, implementation, or usage of network protocols. These attacks target the communication protocols that govern how data is transmitted and received over a network.

Common Types of Protocol-Based Attacks

- Man-in-the-Middle (MitM) Attack

-The attacker intercepts communication between two parties, potentially altering or eavesdropping on the data.

-Exploits weaknesses in protocols that lack proper encryption or authentication (e.g., unsecured HTTP, some wireless protocols).

- Replay Attack

-An attacker captures valid data transmissions and retransmits them to produce an unauthorized effect.

-Common in authentication protocols lacking freshness mechanisms like timestamps or nonces.

- TCP SYN Flood (Denial of Service)

-Exploits the TCP three-way handshake by sending numerous SYN requests but never completing the handshake.

-Consumes server resources and can cause denial of service.

- DNS Spoofing/Poisoning

-The attacker corrupts DNS cache or responses, redirecting users to malicious sites.

-Exploits weaknesses in the DNS protocol's validation.

- SMURF Attack

-Uses ICMP echo requests (ping) sent to broadcast addresses with the victim’s IP spoofed as the source.

-Causes a flood of replies to the victim, overwhelming their network.

- ARP Spoofing/Poisoning

-Manipulates Address Resolution Protocol (ARP) tables to associate the attacker’s MAC address with a legitimate IP address.

-Facilitates MitM or denial of service.

- DHCP Starvation Attack

-Attacker floods DHCP server with fake requests.

-Exhausts IP address pool.

-Denies legitimate clients access to network.

- IP Spoofing

-The attacker sends IP packets with a forged source IP address.

-Often used to bypass IP-based authentication or to launch DoS attacks.

- ICMP Attacks (Ping of Death, Smurf Attack)

-Abuse Internet Control Message Protocol (ICMP) for DoS.

-Smurf Attack: Broadcasts ping requests with spoofed IP, causing many hosts to reply to a victim, overwhelming it.

Why Are Protocol-Based Attacks Effective?

- Protocols are fundamental to network communication, often implemented with backward compatibility or performance prioritization.
- Some protocols were designed without security in mind.
- Flaws or design weaknesses can be leveraged before patches or security measures are applied.

How to Defend Against Protocol-Based Attacks

- Use secure, updated protocols (e.g., TLS instead of SSL, SSH instead of Telnet).
- Implement network monitoring and intrusion detection systems.
- Apply proper network segmentation and filtering (firewalls, ACLs).
- Use anti-spoofing techniques (e.g., ingress/egress filtering).

Cont..

- Regularly update and patch systems and protocol implementations.
- Employ strong authentication and encryption where possible.