

# GENAI ASSIGNMENT

6th Semester, Academic Year 2026

Date:27-01-2026

Name: Dhruv Thakur	SRN:PES2UG23CS175	Section C
--------------------	-------------------	-----------

## OUTPUT TABLE:

Task	Model	Classification (Success/Failure)	Observation (What actually happened?)	Why did this happen? (Architectural Reason)
Generation	BERT	Failure	Could not generate a meaningful continuation; produced errors or incoherent text.	BERT is an encoder-only model and is not trained for autoregressive next-token generation.
	RoBERTa	Failure	Similar to BERT, output was nonsensical or the pipeline failed to generate proper text.	RoBERTa is also encoder-only and lacks a decoder for sequence generation.
	BART	Success	Generated a fluent continuation of the prompt.	BART has an encoder-decoder architecture trained for sequence-to-sequence generation.
Fill-Mask	BERT	Success	Correctly predicted words like "create", "generate".	BERT is trained using Masked Language Modeling (MLM).
	RoBERTa	Success	Predicted highly accurate and confident masked tokens.	RoBERTa is an optimized encoder trained extensively on MLM.
	BART	Partial Success	Filled the mask but predictions were less direct or varied.	BART is trained with denoising autoencoding, not pure MLM.
QA	BERT	Partial Success	Extracted relevant phrase such as "hallucinations, bias, and deepfakes" with low confidence.	Base BERT is not fine-tuned for question answering tasks like SQuAD.
	RoBERTa	Partial Success	Returned similar or slightly better span selection than BERT.	Strong encoder, but still not specifically trained for QA.
	BART	Partial Success	Sometimes produced the correct answer span, sometimes incomplete.	Encoder-decoder can map question-context pairs, but without QA fine-tuning performance is unstable.

## GITHUB LINK:

[https://github.com/dhruvv154/PES2UG23CS175\\_Genai\\_Lab/tree/main/UNIT-1](https://github.com/dhruvv154/PES2UG23CS175_Genai_Lab/tree/main/UNIT-1)