# CENTAFLEX-D Variant Series

Standard Types, Different from DIN 6281 / Flanges to SAE J620

## SPECIALIZED VARIANT CONFIGURATIONS

While the standard CENTAFLEX-D configurations strictly conform to DIN 6281 frameworks, complex industrial packaging setups often demand dimensional deviations to accommodate non-standard shaft extensions, specific spatial limits, or modified housing geometries. This supplemental portfolio variant catalog details extended dimensional structures and custom inertia profiles across sizes 160 up to 560, while retaining native integration capability for standard **SAE J620** engine flywheels.

## EXTENDED APPLICATION CAPABILITIES

- **Non-DIN Dimensional Adaptability:** Custom values for lengths ($L_2$) and clearance profiles ($C_3$) allow robust retrofitting into legacy plants or highly custom heavy-duty packaging environments.
- **Broad Flywheel Sizing Spectrum:** Seamlessly bridges compact $8"$ setups all the way to massive heavy-duty $24"$ engine flywheels.
- **High-Inertia Attenuation:** Features optimized mass distribution metrics ($J$) across primary and secondary coupling halves, allowing precision torsional vibration calculation adjustment for variable speed industrial machines.

## STANDARD BAUFORMEN ABWEICHEND VON DIN 6281

*Extended dimensional matrix and tailored technical metrics for alternative CENTAFLEX-D coupling assemblies.*

| size Grösse | SAE J620 | $C_3$ [mm] | $L_2$ [mm] | $d_2$ [mm] | | $N_2$ [mm] | $d_3$ [mm] | S ±1 | $d_4$ +3 | T +3 | weight [kg] | Mass moment of inertia J [kgm²] | | Order Code Bestellnummer |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | min | max | | | | | | | primary | secondary | |
| 160 | 8" | 73 | 55 | - | 60 | 90 | 160 | 4 | - | - | 7,2 | 0,0319 | 0,0098 | CF-D-160-*-8-73-** |
| 160 | 8" | 110 | 92 | - | 60 | 90 | 160 | 4 | - | - | 8,8 | 0,0319 | 0,0112 | CF-D-160-*-8-110-** |
| 160 | 10" | 110 | 92 | - | 60 | 90 | 160 | 4 | - | - | 10,3 | 0,0621 | 0,0112 | CF-D-160-*-10-110-** |
| 160 | 11½" | 96 | 92 | - | 60 | 90 | 160 | 4 | 300 | 10 | 12,8 | 0,0724 | 0,0112 | CF-D-160-*-11-96-** |
| 198 | 10" | 97 | 82 | - | 75 | 115 | 198 | 4 | 225 | 2 | 14,1 | 0,0681 | 0,0272 | CF-D-198-*-10-97-** |
| 198 | 11½" | 131 | 106 | - | 75 | 115 | 198 | 4 | - | - | 17,6 | 0,1251 | 0,0295 | CF-D-198-*-11-131-** |
| 198 | 14" | 117 | 106 | - | 75 | 115 | 198 | 4 | 345 | 6 | 25,6 | 0,3716 | 0,0295 | CF-D-198-*-14-117-** |
| 220 | 11½" | 147 | 122 | - | 85 | 124 | 220 | 4 | - | - | 22,0 | 0,1328 | 0,0545 | CF-D-220-*-11-147-** |
| 220 | 14" | 133 | 122 | - | 85 | 124 | 220 | 4 | 345 | 6 | 29,9 | 0,3746 | 0,0545 | CF-D-220-*-14-133-** |
| 275 | 11½" | 167 | 142 | - | 100 | 145 | 275 | 4 | - | - | 35,2 | 0,1743 | 0,1550 | CF-D-275-*-11-167-** |
| 275 | 14" | 153 | 142 | - | 100 | 145 | 275 | 4 | 345 | 6 | 34,4 | 0,4044 | 0,1550 | CF-D-275-*-14-153-** |
| 275 | 16" | 143 | 142 | - | 100 | 145 | 275 | 4 | 450 | 15 | 47,6 | 0,6850 | 0,1550 | CF-D-275-*-16-143-** |
| 350 | 11½" | 167 | 150 | 65 | 130 | 192 | 350 | 4 | - | - | 57,0 | 0,2377 | 0,4391 | CF-D-350-*-11-167-** |
| 350 | 14" | 153 | 150 | 65 | 130 | 192 | 350 | 4 | 396 | 15 | 65,5 | 0,6640 | 0,4391 | CF-D-350-*-14-153-** |
| 350 | 16" | 143 | 150 | 65 | 130 | 192 | 350 | 4 | 450 | 25 | 69,0 | 0,7455 | 0,4391 | CF-D-350-*-16-143-** |
| 350 | 18" | 120 | 90 | 65 | 120 | 192 | 350 | 4 | - | - | 67,0 | 1,5006 | 0,4371 | CF-D-350-*-18-120-** |
| 350 | 18" | 180 | 150 | 65 | 130 | 192 | 350 | 4 | - | - | 77,0 | 1,5006 | 0,4910 | CF-D-350-*-18-180-** |
| 425 | 16" | 210 | 180 | 85 | 155 | 240 | 425 | 5 | 427 | 10 | 112,7 | 1,1523 | 1,3104 | CF-D-425-*-16-210-** |
| 425 | 18" | 210 | 180 | 85 | 155 | 240 | 425 | 5 | 427 | 10 | 115,6 | 1,3678 | 1,3104 | CF-D-425-*-18-210-** |
| 425 | 21" | 214 | 180 | 85 | 155 | 240 | 425 | 5 | 427 | 10 | 129,6 | 2,5506 | 1,3104 | CF-D-425-*-21-214-** |
| 425 | 24" | 214 | 180 | 85 | 155 | 240 | 425 | 5 | 427 | 10 | 135,9 | 3,3279 | 1,3104 | CF-D-425-*-24-214-** |
| 560 | 24" | 290 | 240 | 120 | 220 | 330 | 560 | 6 | 550 | 20 | 275,5 | 6,0572 | 5,0808 | CF-D-560-*-24-290-** |

* indicate shorehardness here. / Shorehärte, hier einsetzen.

** state finished bore dia $d_2$ here. / Fertigbohrung für $d_2$ hier einsetzen.

**Engineering Note:** Variant couplings allow highly optimized parameter combinations. For complex multi-bearing machinery lines, a dedicated Torsional Vibration Analysis (TVA) is strongly recommended to finalize rubber element selection.

Procurement, Retrofitting & Custom Engineering Support (India):
For dimensional confirmations, variable shorehardness element options ($^*$), or complete drop-in retrofitting replacements, please contact:
**Jinharsh Industrial Solutions Private Limited**
Email: crm@jinharsh.com | Web: www.jinharsh.com