

CENTAFLEX-A Highly Flexible Couplings


Technical Data Matrix for Sizes 1 to 28 | Highly Elastic Industrial Couplings

PRODUCT OVERVIEW & TORSIONAL ELASTICITY

The **CENTAFLEX-A** series represents the industry standard for highly flexible, multi-directional elastic couplings. Engineered with a segmented precompressed rubber element design, it excels at dampening severe torsional oscillations, tuning natural resonances, and neutralizing parallel, axial, and angular misalignments across complex industrial drive chains.

KEY PERFORMANCE ADVANTAGES

- Precompressed Rubber Design:** The specialized element geometry maintains exceptional durability under extreme compression vectors, extending service life.
- Dynamic Tuning Flexibility:** Available in variable rubber qualities (50 Shore A and 60 Shore A) to isolate critical system natural frequencies cleanly.
- Versatile Application Spectrum:** Extensively specified for main pump packages, generator assemblies, marine propulsion lines, and heavy compressor modules.



CENTAFLEX-
A SERIES
ELEMENT

TECHNICAL DATA (SIZES 1 – 28)

Size	Rubber quality [Shore A]	Nominal torque T_KN [kNm]	Maximum torque T_Kmax [kNm]	Continuous vibratory torque T_KW [kNm]	Permissible power loss P_KV [W]	Dynamic torsional stiffness C_Tdyn [kNm/rad]	Relative damping ψ	Speed n_max [min-1]	Axial displacement		Radial displacement		Angular displacement	
									Permissible ΔK_a [mm]	Stiffness C_a [kN/mm]	Permissible ΔK_r [mm]	Stiffness C_r [kN/mm]	Permissible ΔK_w [°]	Stiffness C_w [kNm/°]
1	50 60	0,010	0,025	0,005	6	0,09 0,14	0,60 0,78	10000	2	0,0266 0,0380	1,5	0,105 0,150	3	0,00021 0,00030
2	50 60	0,020	0,060	0,010	10	0,18 0,29	0,60 0,78	8000	3	0,0154 0,0220	1,5	0,105 0,150	3	0,00021 0,00030
4	50 60	0,050	0,125	0,020	15	0,55 0,85	0,60 0,78	7000	3	0,0525 0,0750	1,5	0,350 0,500	3	0,00168 0,00240
8	50 60	0,100	0,280	0,040	25	0,90 1,50	0,80 1,00	6500	4	0,0525 0,0750	2	0,350 0,500	3	0,00252 0,00360
12	50 60	0,140	0,360	0,050	30	2,70 4,40	0,80 1,00	6500	4	0,1750 0,2500	2	0,700 1,000	2	0,00630 0,00900
16	50 60	0,200	0,560	0,080	40	2,00 3,40	0,80 1,00	6000	5	0,1550 0,3200	2	0,300 0,600	3	0,01750 0,01900
22	50 60	0,275	0,750	0,100	50	6,10 9,00	0,80 1,00	6000	5	0,3100 0,5000	2	0,850 1,500	2	0,02100 0,02400
25	50 60	0,315	0,875	0,125	68	2,80 4,50	0,80 1,00	5000	5	0,2100 0,3950	2	0,400 0,800	3	0,01900 0,02100
28	50 60	0,420	1,200	0,150	75	7,50 12,00	0,80 1,00	5000	5	0,4000 0,7000	2	1,000 1,800	2	0,02400 0,02800

* Values for 70 and 75 Shore A rubber quality variants are readily available on request.
** At 60 Shore A rubber quality ratings.
Engineering Advisory: Detailed calculations regarding continuous temperature power loss and resonance limits should always be coupled with a comprehensive torsional vibration analysis prior to deployment.

Procurement, Shore Selection & Vibration Analysis Support (India):

For dynamic torsional vibration analysis (TVA), custom 70/75 Shore element requests, or rapid quote processing, please contact:
Jinharsh Industrial Solutions Private Limited
Email: crm@jinharsh.com | Web: www.jinharsh.com