

CENTAFLEX-A TYPE 0-S

HIGHLY FLEXIBLE COUPLING ELEMENTS & SPECIALIZED DIMENSIONAL SPECIFICATIONS

Description: The CENTAFLEX-A Type 0-S design represents a specialized variant engineered with modified anchoring dimensions and tailored variable structural parameters (T_x profiles). Optimized for intricate multi-shaft connection frameworks, it enables exact resonance tuning and reliable transmission safety across heavy-duty compressor setups and industrial engine lines.

KEY PERFORMANCE ADVANTAGES

- **Optimized Structural Adaptation:** Features specialized dimension variants ($\$P_2$, R_2 , T_2 , T_x) tailored specifically to receive close-fit cylindrical components and custom adapter hubs.
- **High-Fidelity Torsional Isolation:** Maximizes systemic protection against continuous vibratory stress spikes and natural resonance build-ups.
- **Durable Single-Mass Geometry:** Built using elite precompressed rubber compounds to maintain high-capacity execution criteria under demanding operating vectors.

DIMENSIONAL SPECIFICATIONS (SIZES 1 - 600)

Below is the official documented matrix for the **CENTAFLEX-A Type 0-S** series configuration blueprint:

Size	Dimensions [mm]														Mass Moments [kgm²]		Mass [kg]		
	A	d ₃	E	G	N ₁	P ₂	R ₂	S	T ₂	T _x	X ₁	X ₄	X ₅	T _K	Y	J ₁	J ₂	m ₁	m ₂
1	24	56	22	11	30	5	6.2	2	10.5	10	-	-	-	44	2x180°	0.00004	0.00002	0.06	0.05
2	24	85	20	10	40	14.2	8.2	4	13.5	14	4	-	3	68	2x180°	0.00011	0.00012	0.1	0.11
4	28	100	24	12	45	18.5	8.2	4	13.5	14	4	-	3	80	3x120°	0.00023	0.00020	0.15	0.15
8	32	120	28	14	60	20.5	10.2	4	16.5	17.1	4	10	3	100	3x120°	0.0007	0.0005	0.29	0.25
12	32	122	28	14	60	20.5	10.2	4	16.5	17.1	4	10	3	100	4x90°	0.0010	0.0005	0.32	0.32
16	42	150	36	18	70	25.2	12.2	6	18.3	19.1	5	13.5	5	125	3x120°	0.0019	0.0014	0.5	0.5
22	42	150	36	18	70	25.2	12.2	6	18.3	19.1	5	13.5	5	125	4x90°	0.0026	0.0016	0.6	0.6
25	46	170	40	20	85	26	14.2	6	22	22	5	14	5	140	3x120°	0.0036	0.0025	0.8	0.6
28	46	170	40	20	85	26	14.2	6	22	22.5	5	14	5	140	4x90°	0.0046	0.0030	0.9	0.6
30	58	200	50	25	100	33.5	16.2	8	24.5	25	5	18	5	165	3x120°	0.0083	0.0060	1.3	1.1
50	58	200	50	25	100	33.5	16.2	8	24.5	25.1	5	18	5	165	4x90°	0.0106	0.0072	1.7	1.2
80	65	205	61	30.5	100	34.5	16.5	4	24.5	25.1	5	18	5	165	4x90°	0.0119	0.0092	1.7	1.6
90	70	260	62	31	125	46	20.2	8	31	32	8	22.5	5	215	3x120°	0.0294	0.0213	2.7	2.3
140	70	260	62	31	125	46	20.2	8	31	32.1	8	22.5	5	215	4x90°	0.0368	0.0251	3.4	2.6
200	80	300	72	36	145	45.5	20.2	8	32	32.1	8	22.5	5	250	4x90°	0.0596	0.0471	4.2	3.7
250	85	340	77	22.5/54.5	160	60	20.2	8	*	32.1	10	-	8	280	4x90°	0.091	0.086	5	5.5
400	105	370	95	28.5/66.5	170	71	24.2	10	*	45	10	-	8	300	4x90°	0.204	0.154	9.6	8.2
600	125	470	110	33/77	200	87	24.2	15	*	53	10	-	9	380	4x90°	0.569	0.363	16.5	13.3

* Engineering value metrics available on request. Dimensions subject to strict production tolerances.

PROCUREMENT, SIZING SELECTION & ENGINEERING SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited

Authorized India Partner: CENTA Power Transmission | Regal
Rexnord

Email: crm@jinharsh.com

Web: www.jinharsh.com