

CENTAFLEX-A TYPE 0

HIGHLY FLEXIBLE COUPLING ELEMENTS & DIMENSIONAL SPECIFICATIONS

Description: The CENTAFLEX-A Type 0 design features a bare highly flexible elastomeric element configuration designed for direct adaptation into specialized flywheel hubs, custom flanges, and compact spacer assemblies. It delivers industry-leading torsional damping performance alongside extreme multi-directional misalignment handling capacity while maintaining minimal structural envelope dimensions.

KEY PERFORMANCE ADVANTAGES

- Ultra-Compact Envelope:** Designed without external bulky hub additions to allow seamless, space-saving drop-in positioning in tight coaxial drive-train profiles.
- Excellent Misalignment Mitigation:** Isolates heavy axial, radial, and angular misalignments, shielding critical main pump assemblies, gearboxes, and generator components.
- Zero-Backlash Characteristics:** Provides uniform, smooth torque progression profiles ideal for continuous dynamic indexing and alternating industrial load segments.

DIMENSIONAL SPECIFICATIONS (SIZES 1 - 800)

Below is the complete engineering dimension blueprint data for the **CENTAFLEX-A Type 0** configuration sequence:

Size	Dimensions [mm]																			Mass Moments [kgm²]		Mass [kg]	
	A	d ₃	E	G	N ₁	P ₁	P ₂	R ₁	R ₂	S	T ₁	T ₂	X ₁	X ₂	X ₃	X ₄	X ₅	T _K	Y	J ₁	J ₂	m ₁	m ₂
1	24	56	22	11	30	18	5	6.2	6.2	2	10.5	10.5	-	-	-	-	-	44	2x180°	0.00002	0.00002	0.04	0.05
2	24	85	20	10	40	12	14.2	8.2	8.2	4	13.5	13.5	4	9	3	-	3	68	2x180°	0.00009	0.00002	0.08	0.11
4	28	100	24	12	45	17	18.5	8.2	8.2	4	13.5	13.5	4	9	3	-	3	80	3x120°	0.00020	0.00020	0.13	0.15
8	32	120	28	14	60	20.5	20.5	10.2	10.2	4	16.5	16.5	4	12	4	10	3	100	3x120°	0.0006	0.0005	0.25	0.25
12	32	122	28	14	60	20.5	20.5	10.2	10.2	4	16.5	16.5	4	12	4	10	3	100	4x90°	0.0007	0.0005	0.28	0.32
16	42	150	36	18	70	23.5	25.2	12.2	12.2	6	18.1	18.3	5	18	6	13.5	5	125	3x120°	0.0015	0.0014	0.4	0.5
22	42	150	36	18	70	23.5	25.2	12.2	12.2	6	18.1	18.3	5	18	6	13.5	5	125	4x90°	0.0019	0.0016	0.5	0.6
25	46	170	40	20	85	26	26	14.2	14.2	6	21.1	22	5	18	5	14	5	140	3x120°	0.0027	0.0025	0.6	0.6
28	46	170	40	20	85	26	26	14.2	14.2	6	21.1	22	5	18	5	14	5	140	4x90°	0.0034	0.0030	0.7	0.8
30	58	200	50	25	100	34.5	33.5	16.2	16.2	8	24.1	24.5	5	20	6	18	5	165	3x120°	0.0065	0.0060	1.0	1.1
50	58	200	50	25	100	34.5	33.5	16.2	16.2	8	24.1	24.5	5	20	6	18	5	165	4x90°	0.0081	0.0072	1.3	1.2
80	65	205	61	30.5	100	34.5	34.5	16.5	16.5	4	24.1	24.5	5	20	6	18	5	165	4x90°	0.0095	0.0092	1.4	1.6
90	70	260	62	31	125	45	46	20.2	20.2	8	30.5	31	8	25	5	22.5	5	215	3x120°	0.0237	0.0213	2.2	2.3
140	70	260	62	31	125	45	46	20.2	20.2	8	30.5	31	8	25	5	22.5	5	215	4x90°	0.0286	0.0251	2.7	2.6
200	80	300	72	36	145	44	45.5	20.2	20.2	8	32	32	8	25	5	22.5	5	250	4x90°	0.0481	0.0471	3.4	3.7
250	85	340	77	22.5/54.5	160	60	60	20.2	20.2	8	30.5	*	10	30	8	-	8	280	4x90°	0.081	0.086	4.5	5.5
400	105	370	95	28.5/66.5	170	67	71	24.2	20.2	10	42.5	*	10	40	8	-	8	300	4x90°	0.155	0.154	7.5	8.2
600	125	470	110	33/77	200	84	87	27.2	24.2	15	50	*	10	60	9	-	9	380	4x90°	0.464	0.363	13.8	13.3
800	145	545	128	29/64/99	230	112	103	22.2	22.2	17	45	*	10	45	9	-	9	370/470	4x90°	0.586	0.637	20.1	24.1

* Spec values available on request. Dimensions subject to manufacturing tolerances.

PROCUREMENT, SIZING SELECTION & ENGINEERING SUPPORT (INDIA)

Jinharsh Industrial Solutions Private Limited
Authorized India Partner: CENTA Power Transmission | Regal
Rexnord

Email: crm@jinharsh.com
Web: www.jinharsh.com